

---

# **Basilica Documentation**

*Release 0.2.5*

**Michael Lucy, Jorge Silva**

**Apr 08, 2019**



---

## Contents

---

<b>1</b>	<b>Quickstart</b>	<b>1</b>
1.1	Install the python client . . . . .	1
1.2	Embed some sentences . . . . .	1
1.3	Get an API key . . . . .	2
1.4	What next? . . . . .	2
<b>2</b>	<b>Basilica Python Client</b>	<b>3</b>



### 1.1 Install the python client

First, install the Python client.

```
$ pip install basilica
```

### 1.2 Embed some sentences

Let's embed some sentences to make sure the client is working.

```
import basilica
sentences = [
    "This is a sentence!",
    "This is a similar sentence!",
    "I don't think this sentence is very similar at all...",
]
with basilica.Connection('SLOW_DEMO_KEY') as c:
    embeddings = list(c.embed_sentences(sentences))
print(embeddings)
```

```
[[0.8556405305862427, ...], ...]
```

Let's also make sure these embeddings make sense, by checking that the cosine distance between the two similar sentences is smaller:

```
from scipy import spatial
print(spatial.distance.cosine(embeddings[0], embeddings[1]))
print(spatial.distance.cosine(embeddings[0], embeddings[2]))
```

```
0.024854343247535327
0.25084750542635814
```

Great!

## 1.3 Get an API key

The example above uses the slow demo key. You can get an API key of your own by signing up at <https://www.basilica.ai/accounts/register> . (If you already have an account, you can view your API keys at <https://www.basilica.ai/api-keys> .)

## 1.4 What next?

- Read the documentation for the python client: *Basilica Python Client*
- See an in-depth tutorial on training an image model: [How To Train An Image Model With Basilica](#)

---

## Basilica Python Client

---

```
class basilica.Connection(auth_key, server='https://api.basilica.ai', retries=2, back-  
off_factor=0.1, status_forcelist=500)
```

A connection to basilica.ai that can be used to generate embeddings.

### Parameters

- **auth\_key** (*str*) – Your auth key. You can view your auth keys at [https://basilica.ai/auth\\_keys](https://basilica.ai/auth_keys).
- **server** (*str*) – What URL to use to connect to the server.
- **retries** (*int*) – Number of times to retry failed connections and requests.
- **backoff\_factor** (*float*) – See `urllib3.util.retry.Retry.backoff_factor`.
- **status\_forcelist** (*Tuple[int]*) – What HTTP response codes trigger a retry.

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:  
...     print(c.embed_sentence('A sentence.'))  
[0.6246702671051025, ..., -0.03025037609040737]
```

```
embed_image(image, model='generic', version='default', opts={}, timeout=10)
```

Generate the embedding for a JPEG image. The image should be passed as a byte string.

### Parameters

- **image** (*str*) – The image to embed.
- **model** (*str*) – What model to use (i.e. the kind of image being embedded).
- **version** (*str*) – What version of that model to use.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.

- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** An embedding.

**Return type** List[float]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     with open('img.jpg', 'rb') as f:
...         print(c.embed_image(f.read()))
[0.6246702671051025, ...]
```

**embed\_image\_file** (*image\_file*, *model*='generic', *version*='default', *opts*={}, *timeout*=10)

Generate the embedding for a JPEG image file. The file name should be passed as a path that can be understood by *open*.

#### Parameters

- **image\_file** (*str*) – Path to the image to embed.
- **model** (*str*) – What model to use (i.e. the kind of image being embedded).
- **version** (*str*) – What version of that model to use.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.
- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** An embedding.

**Return type** List[float]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     print(c.embed_image_file('img.jpg'))
[0.6246702671051025, ...]
```



**embed\_image\_files** (*image\_files*, *model*='generic', *version*='default', *batch\_size*=32, *opts*={}, *timeout*=30)

Generate embeddings for JPEG image files. The file names should be passed as paths that can be understood by *open*.

#### Parameters

- **image\_files** (*Iterable[str]*) – An iterable (such as a list) of paths to the images to embed.
- **model** (*str*) – What model to use (i.e. the kind of image being embedded).
- **version** (*str*) – What version of that model to use.
- **batch\_size** (*int*) – How many instances to send to the server at a time.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.
- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** A generator of embeddings.

**Return type** Generator[List[float]]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     for embedding in c.embed_image_files(['img1.jpg', 'img2.jpg']):
...         print(embedding)
[0.6246702671051025, ...]
[-0.03025037609040737, ...]
```

**embed\_images** (*images*, *model*='generic', *version*='default', *batch\_size*=32, *opts*={}, *timeout*=30)

Generate embeddings for JPEG images. Images should be passed as byte strings, and will be sent to the server in batches to be embedded.

#### Parameters

- **images** (*Iterable[str]*) – An iterable (such as a list) of the images to embed.
- **model** (*str*) – What model to use (i.e. the kind of image being embedded).
- **version** (*str*) – What version of that model to use.
- **batch\_size** (*int*) – How many instances to send to the server at a time.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.

- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** A generator of embeddings.

**Return type** Generator[List[float]]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     images = []
...     for filename in ['img1.jpg', 'img2.jpg']:
...         with open(filename, 'rb') as f:
...             images.append(f.read())
...     for embedding in c.embed_images(images):
...         print(embedding)
[0.6246702671051025, ...]
[-0.03025037609040737, ...]
```

**embed\_sentence** (*sentence*, *model*='english', *version*='default', *opts*={}, *timeout*=5)

Generate the embedding for a sentence.

#### Parameters

- **sentence** (*str*) – The sentence to embed.
- **model** (*str*) – What model to use (i.e. the kind of sentence being embedded).
  - **generic**: Generic English text embedding (the default.)
  - **reddit**: Text embedding specialized for English Reddit posts.
  - **twitter**: Text embedding specialized for English tweets.
  - **email**: Text embedding specialized for English emails.
  - **product-reviews**: Text embedding specialized for English product reviews.
- **version** (*str*) – What version of that model to use.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.
- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.

- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** An embedding.

**Return type** List[float]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     print(c.embed_sentence('This is a sentence.'))
[0.6246702671051025, ...]
```

**embed\_sentences** (*sentences*, *model='english'*, *version='default'*, *batch\_size=64*, *opts={}*, *timeout=15*)

Generate embeddings for sentences.

#### Parameters

- **sentences** (*Iterable[str]*) – An iterable (such as a list) of sentences to embed.
- **model** (*str*) – What model to use (i.e. the kind of sentence being embedded).
  - **generic**: Generic English text embedding (the default.)
  - **reddit**: Text embedding specialized for English Reddit posts.
  - **twitter**: Text embedding specialized for English tweets.
  - **email**: Text embedding specialized for English emails.
  - **product-reviews**: Text embedding specialized for English product reviews.
- **version** (*str*) – What version of that model to use.
- **batch\_size** (*int*) – How many instances to send to the server at a time.
- **opts** (*Dict[str, Any]*) – Options specific to the model/version you chose.
- **opts["dimensions"]** (*int*) – Number of dimensions to return. PCA will be used to reduce the number of dimensions with minimal information loss.
- **opts["normalize\_l2"]** (*bool*) – Whether or not each instance should be scaled to have unit L2 norm. (This is sometimes useful for instance retrieval tasks.) Defaults to False.
- **opts["normalize\_mean"]** (*bool*) – Whether or not to normalize each feature in the embedding to have mean 0 across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **opts["normalize\_variance"]** (*bool*) – Whether or not to normalize each feature in the embedding to have unit variance across our sample dataset. Defaults to True when *dimensions* is set, or False otherwise.
- **timeout** (*int*) – HTTP timeout for request.

**Returns** A generator of embeddings.

**Return type** Generator[List[float]]

```
>>> with basilica.Connection('SLOW_DEMO_KEY') as c:
...     for embedding in c.embed_sentences(['Sentence one.', 'Sentence two.']):
...         print(embedding)
```

(continues on next page)

(continued from previous page)

```
[0.6246702671051025, ...]  
[-0.03025037609040737, ...]
```

## C

`Connection` (*class in basilica*), 3

## E

`embed_image()` (*basilica.Connection method*), 3

`embed_image_file()` (*basilica.Connection method*), 4

`embed_image_files()` (*basilica.Connection method*), 4

`embed_images()` (*basilica.Connection method*), 5

`embed_sentence()` (*basilica.Connection method*), 6

`embed_sentences()` (*basilica.Connection method*), 7