
certbot-dns-dnsmadeeasy Documentation

Release 0

Certbot Project

Jun 10, 2019

Contents:

| | | |
|----------|---|-----------|
| 1 | Named Arguments | 3 |
| 2 | Credentials | 5 |
| 3 | Examples | 7 |
| 4 | API Documentation | 9 |
| 4.1 | certbot_dns_dnsmadeeasy.dns_dnsmadeeasy | 9 |
| 5 | Indices and tables | 11 |
| | Python Module Index | 13 |
| | Index | 15 |

The `dns_dnsmadeeasy` plugin automates the process of completing a `dns-01` challenge (`DNS01`) by creating, and subsequently removing, TXT records using the DNS Made Easy API.

CHAPTER 1

Named Arguments

| | |
|--|--|
| <code>--dns-dnsmadeeasy-credentials</code> | DNS Made Easy <i>credentials</i> INI file. (Required) |
| <code>--dns-dnsmadeeasy-propagation-seconds</code> | The number of seconds to wait for DNS to propagate before asking the ACME server to verify the DNS record. (Default: 60) |

Credentials

Use of this plugin requires a configuration file containing DNS Made Easy API credentials, obtained from your DNS Made Easy account page.

Listing 1: Example credentials file:

```
# DNS Made Easy API credentials used by Certbot
dns_dnsmadeeasy_api_key = 1c1a3c91-4770-4ce7-96f4-54c0eb0e457a
dns_dnsmadeeasy_secret_key = c9b5625f-9834-4ff8-baba-4ed5f32cae55
```

The path to this file can be provided interactively or using the `--dns-dnsmadeeasy-credentials` command-line argument. Certbot records the path to this file for use during renewal, but does not store the file's contents.

Caution: You should protect these API credentials as you would the password to your DNS Made Easy account. Users who can read this file can use these credentials to issue arbitrary API calls on your behalf. Users who can cause Certbot to run using these credentials can complete a `dns-01` challenge to acquire new certificates or revoke existing certificates for associated domains, even if those domains aren't being managed by this server.

Certbot will emit a warning if it detects that the credentials file can be accessed by other users on your system. The warning reads "Unsafe permissions on credentials configuration file", followed by the path to the credentials file. This warning will be emitted each time Certbot uses the credentials file, including for renewal, and cannot be silenced except by addressing the issue (e.g., by using a command like `chmod 600` to restrict access to the file).

Examples

Listing 1: To acquire a certificate for `example.com`

```
certbot certonly \  
  --dns-dnsmadeeasy \  
  --dns-dnsmadeeasy-credentials ~/.secrets/certbot/dnsmadeeasy.ini \  
  -d example.com
```

Listing 2: To acquire a single certificate for both `example.com` and `www.example.com`

```
certbot certonly \  
  --dns-dnsmadeeasy \  
  --dns-dnsmadeeasy-credentials ~/.secrets/certbot/dnsmadeeasy.ini \  
  -d example.com \  
  -d www.example.com
```

Listing 3: To acquire a certificate for `example.com`, waiting 2 minutes for DNS propagation

```
certbot certonly \  
  --dns-dnsmadeeasy \  
  --dns-dnsmadeeasy-credentials ~/.secrets/certbot/dnsmadeeasy.ini \  
  --dns-dnsmadeeasy-propagation-seconds 120 \  
  -d example.com
```


4.1 certbot_dns_dnsmadeeasy.dns_dnsmadeeasy

DNS Authenticator for DNS Made Easy DNS.

class `certbot_dns_dnsmadeeasy.dns_dnsmadeeasy.Authenticator` (**args*, ***kwargs*)
Bases: `certbot.plugins.dns_common.DNSAuthenticator`

DNS Authenticator for DNS Made Easy

This Authenticator uses the DNS Made Easy API to fulfill a dns-01 challenge.

classmethod `add_parser_arguments` (*add*)
Add plugin arguments to the CLI argument parser.

NOTE: If some of your flags interact with others, you can use `cli.report_config_interaction` to register this to ensure values are correctly saved/overridable during renewal.

Parameters `add` (*callable*) – Function that proxies calls to `argparse.ArgumentParser.add_argument` prepending options with unique plugin name prefix.

`_setup_credentials` ()
Establish credentials, prompting if necessary.

`_perform` (*domain*, *validation_name*, *validation*)
Performs a dns-01 challenge by creating a DNS TXT record.

Parameters

- **domain** (*str*) – The domain being validated.
- **validation_domain_name** (*str*) – The validation record domain name.
- **validation** (*str*) – The validation record content.

Raises `errors.PluginError` – If the challenge cannot be performed

`__cleanup` (*domain, validation_name, validation*)

Deletes the DNS TXT record which would have been created by `__perform_achall`.

Fails gracefully if no such record exists.

Parameters

- **`domain`** (*str*) – The domain being validated.
- **`validation_domain_name`** (*str*) – The validation record domain name.
- **`validation`** (*str*) – The validation record content.

`class` `certbot_dns_dnsmadeeasy.dns_dnsmadeeasy._DNSMadeEasyLexiconClient` (*api_key, secret_key, ttl*)

Bases: `certbot.plugins.dns_common_lexicon.LexiconClient`

Encapsulates all communication with the DNS Made Easy via Lexicon.

CHAPTER 5

Indices and tables

- `genindex`
- `modindex`
- `search`

C

certbot_dns_dnsmadeeasy, 1
certbot_dns_dnsmadeeasy.dns_dnsmadeeasy,
9

Symbols

`_DNSMadeEasyLexiconClient` (class in `certbot_dns_dnsmadeeasy.dns_dnsmadeeasy`), 10

`_cleanup()` (`certbot_dns_dnsmadeeasy.dns_dnsmadeeasy.Authenticator` method), 9

`_perform()` (`certbot_dns_dnsmadeeasy.dns_dnsmadeeasy.Authenticator` method), 9

`_setup_credentials()` (`certbot_dns_dnsmadeeasy.dns_dnsmadeeasy.Authenticator` method), 9

A

`add_parser_arguments()` (`certbot_dns_dnsmadeeasy.dns_dnsmadeeasy.Authenticator` class method), 9

`Authenticator` (class in `certbot_dns_dnsmadeeasy.dns_dnsmadeeasy`), 9

C

`certbot_dns_dnsmadeeasy` (module), 1

`certbot_dns_dnsmadeeasy.dns_dnsmadeeasy` (module), 9