

---

# **Dask Cloud Provider Documentation**

*Release 0.1.0+5.g461fb59*

**Dask Cloud Provider Developers**

**Oct 23, 2019**



---

## Contents

---

<b>1</b>	<b>AWS</b>	<b>3</b>
1.1	Fargate/ECS . . . . .	3
1.1.1	GPU Support . . . . .	3
	<b>Index</b>	<b>9</b>



*Native Cloud integration for Dask.*

This library creates Dask clusters on a given cloud provider with no set up other than having credentials. Currently, it only supports AWS.

```
$ pip install dask-cloudprovider
```

Below are the different modules for creating clusters on various cloud providers.



In order to create clusters on AWS you need to set your access key, secret key and region. The simplest way is to use the aws command line tool.

```
$ pip install awscli
$ aws configure
```

## 1.1 Fargate/ECS

The `FargateCluster` will create a new Fargate ECS cluster by default along with all the IAM roles, security groups, and so on that it needs to function.

```
from dask_cloudprovider import FargateCluster
cluster = FargateCluster()
```

All AWS resources created by `FargateCluster` should be removed on garbage collection. If the process is killed harshly this will not happen.

You can also create Dask clusters using EC2 based ECS clusters using `ECSCluster`.

Creating the ECS cluster is out of scope for this library but you can pass in the ARN of an existing one like this:

```
from dask_cloudprovider import ECSCluster
cluster = ECSCluster(cluster_arn="arn:aws:ecs:<region>:<acctid>:cluster/<clustername>
↪")
```

All the other required resources such as roles, task definitions, tasks, etc will be created automatically like in `FargateCluster`.

### 1.1.1 GPU Support

There is also support in `ECSCluster` for GPU aware Dask clusters. To do this you need to create an ECS cluster with GPU capable instances (from the p3 or p3dn families) and specify the number of GPUs each worker task should

have.

```
from dask_cloudprovider import ECSCluster
cluster = ECSCluster(
    cluster_arn="arn:aws:ecs:<region>:<acctid>:cluster/<gpuclustername>",
    worker_gpu=1)
```

## API

<code>ECSCluster([fargate_scheduler, ...])</code>	Deploy a Dask cluster using ECS
<code>FargateCluster(**kwargs)</code>	Deploy a Dask cluster using Fargate on ECS

```
class dask_cloudprovider.ECSCluster (fargate_scheduler=False, fargate_workers=False,
                                     image=None, scheduler_cpu=None, scheduler_mem=None,
                                     scheduler_timeout=None, worker_cpu=None, worker_mem=None,
                                     worker_gpu=None, n_workers=None, cluster_arn=None,
                                     cluster_name_template=None, execution_role_arn=None,
                                     task_role_arn=None, task_role_policies=None,
                                     cloudwatch_logs_group=None, cloudwatch_logs_stream_prefix=None,
                                     cloudwatch_logs_default_retention=None, vpc=None,
                                     subnets=None, security_groups=None, environment=None,
                                     tags=None, find_address_timeout=None, skip_cleanup=None,
                                     aws_access_key_id=None, aws_secret_access_key=None,
                                     region_name=None, **kwargs)
```

### Deploy a Dask cluster using ECS

This creates a dask scheduler and workers on an ECS cluster. If you do not configure a cluster one will be created for you with sensible defaults.

#### Parameters

**fargate\_scheduler: bool (optional)** Select whether or not to use fargate for the scheduler.

Defaults to `False`. You must provide an existing cluster.

**fargate\_workers: bool (optional)** Select whether or not to use fargate for the workers.

Defaults to `False`. You must provide an existing cluster.

**image: str (optional)** The docker image to use for the scheduler and worker tasks.

Defaults to `daskdev/dask:latest` or `rapidsai/rapidsai:latest` if `worker_gpu` is set.

**scheduler\_cpu: int (optional)** The amount of CPU to request for the scheduler in milli-cpu (1/1024).

Defaults to 1024 (one vCPU).

**scheduler\_mem: int (optional)** The amount of memory to request for the scheduler in MB.

Defaults to 4096 (4GB).

**scheduler\_timeout: str (optional)** The scheduler task will exit after this amount of time if there are no clients connected.



Defaults to 5 minutes.

**worker\_cpu: int (optional)** The amount of CPU to request for worker tasks in milli-cpu (1/1024).

Defaults to 4096 (four vCPUs).

**worker\_mem: int (optional)** The amount of memory to request for worker tasks in MB.

Defaults to 16384 (16GB).

**worker\_gpu: int (optional)** The number of GPUs to expose to the worker.

To provide GPUs to workers you need to use a GPU ready docker image that has `dask-cuda` installed and GPU nodes available in your ECS cluster. Fargate is not supported at this time.

Defaults to *None*, no GPUs.

**n\_workers: int (optional)** Number of workers to start on cluster creation.

Defaults to *None*.

**cluster\_arn: str (optional if fargate is true)** The ARN of an existing ECS cluster to use for launching tasks.

Defaults to *None* which results in a new cluster being created for you.

**cluster\_name\_template: str (optional)** A template to use for the cluster name if `cluster_arn` is set to *None*.

Defaults to `'dask-{uuid}'`

**execution\_role\_arn: str (optional)** The ARN of an existing IAM role to use for ECS execution.

This ARN must have `sts:AssumeRole` allowed for `ecs-tasks.amazonaws.com` and allow the following permissions:

- `ecr:GetAuthorizationToken`
- `ecr:BatchCheckLayerAvailability`
- `ecr:GetDownloadUrlForLayer`
- `ecr:GetRepositoryPolicy`
- `ecr:DescribeRepositories`
- `ecr:ListImages`
- `ecr:DescribeImages`
- `ecr:BatchGetImage`
- `logs:*`
- `ec2:AuthorizeSecurityGroupIngress`
- `ec2:Describe*`
- `elasticloadbalancing:DeregisterInstancesFromLoadBalancer`
- `elasticloadbalancing:DeregisterTargets`
- `elasticloadbalancing:Describe*`
- `elasticloadbalancing:RegisterInstancesWithLoadBalancer`

- `elasticloadbalancing:RegisterTargets`

Defaults to `None` (one will be created for you).

**task\_role\_arn: str (optional)** The ARN for an existing IAM role for tasks to assume. This defines which AWS resources the dask workers can access directly. Useful if you need to read from S3 or a database without passing credentials around.

Defaults to `None` (one will be created with S3 read permission only).

**task\_role\_policies: List[str] (optional)** If you do not specify a `task_role_arn` you may want to list some IAM Policy ARNs to be attached to the role that will be created for you.

E.g if you need your workers to read from S3 you could add `arn:aws:iam::aws:policy/AmazonS3ReadOnlyAccess`.

Default `None` (no policies will be attached to the role)

**cloudwatch\_logs\_group: str (optional)** The name of an existing cloudwatch log group to place logs into.

Default `None` (one will be created called `dask-ecs`)

**cloudwatch\_logs\_stream\_prefix: str (optional)** Prefix for log streams.

Defaults to the cluster name.

**cloudwatch\_logs\_default\_retention: int (optional)** Retention for logs in days. For use when log group is auto created.

Defaults to 30.

**vpc: str (optional)** The ID of the VPC you wish to launch your cluster in.

Defaults to `None` (your default VPC will be used).

**subnets: List[str] (optional)** A list of subnets to use when running your task.

Defaults to `None`. (all subnets available in your VPC will be used)

**security\_groups: List[str] (optional)** A list of security group IDs to use when launching tasks.

Defaults to `None` (one will be created which allows all traffic between tasks and access to ports 8786 and 8787 from anywhere).

**environment: dict (optional)** Extra environment variables to pass to the scheduler and worker tasks.

Useful for setting `EXTRA_APT_PACKAGES`, `EXTRA_CONDA_PACKAGES` and `EXTRA_PIP_PACKAGES` if you're using the default image.

Defaults to `None`.

**tags: dict (optional)** Tags to apply to all resources created automatically.

Defaults to `None`. Tags will always include `{"createdBy": "dask-cloudprovider"}`

**find\_address\_timeout: int** Configurable timeout in seconds for finding the task IP from the cloudwatch logs.

Defaults to 60 seconds.

**skip\_cleanup: bool (optional)** Skip cleaning up of stale resources. Useful if you have lots of resources and this operation takes a while.

Default `False`.

**\*\*kwargs: dict** Additional keyword arguments to pass to `SpecCluster`.

**Attributes**

- asynchronous**
- dashboard\_link**
- observed**
- plan**
- requested**
- scheduler\_address**
- tags**

**Methods**

<code>adapt(self, \*args[, minimum, maximum])</code>	Turn on adaptivity
<code>logs(self)</code>	Return logs for the scheduler and workers
<code>new_worker_spec(self)</code>	Return name and spec for the next worker
<code>scale(self[, n, memory, cores])</code>	Scale cluster to n workers
<code>scale_up(self[, n, memory, cores])</code>	Scale cluster to n workers

<b>close</b>	
<b>scale_down</b>	
<b>sync</b>	

**logs** (*self*)

Return logs for the scheduler and workers

**Parameters**

- scheduler** [boolean] Whether or not to collect logs for the scheduler
- workers** [boolean or Iterable[str], optional] A list of worker addresses to select. Defaults to all workers if *True* or no workers if *False*

**Returns**

**logs: Dict[str]** A dictionary of logs, with one item for the scheduler and one for each worker

**class** `dask_cloudprovider.FargateCluster` (**\*\*kwargs**)

Deploy a Dask cluster using Fargate on ECS

This creates a dask scheduler and workers on a Fargate powered ECS cluster. If you do not configure a cluster one will be created for you with sensible defaults.

**Parameters**

**kwargs: dict** Keyword arguments to be passed to `ECSCluster`.

**Attributes**

- asynchronous**
- dashboard\_link**
- observed**

**plan**  
**requested**  
**scheduler\_address**  
**tags**

### Methods

<code>adapt(self, \*args[, minimum, maximum])</code>	Turn on adaptivity
<code>logs(self)</code>	Return logs for the scheduler and workers
<code>new_worker_spec(self)</code>	Return name and spec for the next worker
<code>scale(self[, n, memory, cores])</code>	Scale cluster to n workers
<code>scale_up(self[, n, memory, cores])</code>	Scale cluster to n workers

<b>close</b>	
<b>scale_down</b>	
<b>sync</b>	

## E

ECSCluster (*class in dask\_cloudprovider*), 4

## F

FargateCluster (*class in dask\_cloudprovider*), 7

## L

logs () (*dask\_cloudprovider.ECSCluster method*), 7