
django-debug-toolbar-force Documentation

Release 0.1

Artur Barseghyan <artur.barseghyan@gmail.com>

May 23, 2019

Contents

1	Prerequisites	3
2	Documentation	5
3	Installation	7
4	Usage	9
5	Testing	11
6	License	13
7	Support	15
8	Author	17
9	Docs	19
9.1	Release history and notes	19
9.1.1	0.1.3	19
9.1.2	0.1.2	19
9.1.3	0.1.1	20
9.1.4	0.1	20
9.2	debug_toolbar_force package	20
9.2.1	Subpackages	20
9.2.2	Submodules	20
9.2.3	debug_toolbar_force.apps module	20
9.2.4	debug_toolbar_force.conf module	20
9.2.5	debug_toolbar_force.defaults module	20
9.2.6	debug_toolbar_force.middleware module	20
9.2.7	debug_toolbar_force.settings module	21
9.2.8	Module contents	21
10	Indices and tables	23
	Python Module Index	25

Show `django-debug-toolbar` in non- or partial-HTML views.

CHAPTER 1

Prerequisites

- Python 2.7, 3.4, 3.5, 3.6
- Django 1.8, 1.9, 1.10, 1.11 and 2.0
- django-debug-toolbar 1.5 (may work on earlier versions as well, although not guaranteed).

CHAPTER 2

Documentation

Documentation is available on [Read the Docs](#).

- (1) Install latest stable version from PyPI:

```
pip install django-debug-toolbar-force
```

or latest stable version from GitHub:

```
pip install https://github.com/barseghyanartur/django-debug-toolbar-force/archive/  
↪stable.tar.gz
```

or latest stable version from BitBucket:

```
pip install https://bitbucket.org/barseghyanartur/django-debug-toolbar-force/get/  
↪stable.tar.gz
```

- (2) Add `debug_toolbar_force.middleware.ForceDebugToolbarMiddleware` to `MIDDLEWARE` (or `MIDDLEWARE_CLASSES` for older versions of Django) of the your projects' Django settings (you would typically do that in your dev settings only).

```
MIDDLEWARE += (  
    'debug_toolbar.middleware.DebugToolbarMiddleware',  
    'debug_toolbar_force.middleware.ForceDebugToolbarMiddleware',  
)
```


CHAPTER 4

Usage

In your browser, visit a non-HTML view and append `?debug-toolbar` at the end.

```
GET http://localhost:8000/foo/json-view/?debug-toolbar
```


CHAPTER 5

Testing

Simply type:

```
./runtests.py
```

or use tox:

```
tox
```

or use tox to check specific env:

```
tox -e py35
```


CHAPTER 6

License

GPL 2.0/LGPL 2.1

CHAPTER 7

Support

For any issues contact me at the e-mail given in the *Author* section.

CHAPTER 8

Author

Artur Barseghyan <artur.barseghyan@gmail.com>

Contents:

9.1 Release history and notes

Sequence based identifiers are used for versioning (schema follows below):

```
major.minor[.revision]
```

- It's always safe to upgrade within the same minor version (for example, from 0.3 to 0.3.4).
- Minor version changes might be backwards incompatible. Read the release notes carefully before upgrading (for example, when upgrading from 0.3.4 to 0.4).
- All backwards incompatible changes are mentioned in this document.

9.1.1 0.1.3

2017-12-30

- Django 2.0 support.

9.1.2 0.1.2

2017-04-14

- Django 1.11 support.

9.1.3 0.1.1

2016-12-21

- Minor fixes.

9.1.4 0.1

2016-11-29

- Initial release.

9.2 debug_toolbar_force package

9.2.1 Subpackages

9.2.2 Submodules

9.2.3 debug_toolbar_force.apps module

```
class debug_toolbar_force.apps.Config(app_name, app_module)
    Bases: django.apps.config.AppConfig

    Config.

    label = 'debug_toolbar_force'
    name = 'debug_toolbar_force'
```

9.2.4 debug_toolbar_force.conf module

```
debug_toolbar_force.conf.get_setting(setting, override=None)
    Get setting.

    Get a setting from debug_toolbar_force conf module, falling back to the default.

    If override is not None, it will be used instead of the setting.
```

Parameters

- **setting** – String with setting name
- **override** – Value to use when no setting is available. Defaults to None.

Returns Setting value.

9.2.5 debug_toolbar_force.defaults module

9.2.6 debug_toolbar_force.middleware module

```
class debug_toolbar_force.middleware.ForceDebugToolbarMiddleware
    Bases: object

    The django-debug-toolbar for views that do not return HTML.
```


process_request (*request*)

Process request.

If `GET_PARAM_NAME_NON AJAX` is present in `request.GET`, set `request.is_ajax` to `False`.

process_response (*request, response*)

Process response.

If `GET_PARAM_NAME_FORCE` is present in `request.GET` wrap response in `<html><body>{{ response }}</body></html>`.

9.2.7 debug_toolbar_force.settings module

9.2.8 Module contents

CHAPTER 10

Indices and tables

- `genindex`
- `modindex`
- `search`

d

- `debug_toolbar_force`, 21
- `debug_toolbar_force.apps`, 20
- `debug_toolbar_force.conf`, 20
- `debug_toolbar_force.defaults`, 20
- `debug_toolbar_force.middleware`, 20
- `debug_toolbar_force.settings`, 21

C

`Config` (class in `debug_toolbar_force.apps`), 20

D

`debug_toolbar_force` (module), 21
`debug_toolbar_force.apps` (module), 20
`debug_toolbar_force.conf` (module), 20
`debug_toolbar_force.defaults` (module), 20
`debug_toolbar_force.middleware` (module), 20
`debug_toolbar_force.settings` (module), 21

F

`ForceDebugToolbarMiddleware` (class in `debug_toolbar_force.middleware`), 20

G

`get_setting()` (in module `debug_toolbar_force.conf`), 20

L

`label` (`debug_toolbar_force.apps.Config` attribute), 20

N

`name` (`debug_toolbar_force.apps.Config` attribute), 20

P

`process_request()` (`debug_toolbar_force.middleware.ForceDebugToolbarMiddleware` method), 20
`process_response()` (`debug_toolbar_force.middleware.ForceDebugToolbarMiddleware` method), 21