
Nemo*arethusapluginDocumentation*

Release

Thibault Clérice

June 22, 2016

1	Arethusa for CapiTainS Nemo	1
1.1	Contributors	1

Arethusa for CapiTainS Nemo

This repository contains a plugin for embedding Arethusa in [Flask Capitains Nemo](#). It was produced during the Perseids Tufts Hackathon in May 2016.

The version of the Arethusa code which is used here can be found at https://github.com/alpheios-project/arethusa/tree/nemo_arethusa_widget It is currently using commit 924f384.

1.1 Contributors

- Bridget Almas (@balmas)
- Frederik Baumgardt (@fbaumgardt)
- Thibault Clérice (@ponteineptique)
- Elijah Cooke (@elijahjcooke)

Index :

1.1.1 Arethusa for Nemo API

class `nemo_arethusa_plugin.Arethusa` (*queryinterface*, *args, **kwargs)
 Arethusa plugin for Nemo

Note: This class inherits some routes from the base [AnnotationsApiPlugin](#)

Parameters `queryinterface` (*flask_nemo.query.proto.QueryPrototype*) –
 QueryInterface to use to retrieve annotations

Variables

- **interface** – QueryInterface used to retrieve annotations
- **HAS_AUGMENT_RENDER** – (True) Adds a stack of render

The overall plugins contains three new routes (on top of AnnotationsAPIPlugin) :

- `/arethusa.deps.json` which feeds informations about Arethusa assets dependencies
- `/arethusa-assets/<filename>` which is a self implemented assets route.
- `/arethusa.config.json` which is the config for the widget

It contains two new templates :

- a `arethusa::text.html` template which overrides the original when there is treebank available
- a `arethusa::widget.tree.json` template which provides the configuration for the widget

It contains a render functions which will use the `arethusa::text.html` instead of `main::text.html` if there is a treebank found within the `QueryInterface`

`Arethusa.render (**kwargs)`

Render function stack.

If the template called is the `main::text.html`, it checks annotations from its query interface and replace it by `arethusa::text.html` if there is a treebank annotation

Parameters `kwargs` – Dictionary of named arguments

Returns Dictionary of named arguments

`Arethusa.r_arethusa_assets (filename)`

Routes for assets

Parameters `filename` – Filename in data/assets to retrieve

Returns Content of the file

`Arethusa.r_arethusa_dependencies ()`

Return the json config of dependencies asked by arethusa

Returns Json with dependencies

`Arethusa.r_arethusa_config ()`

Config JSON route for Arethusa : defines the layout and other resources

Returns {"template"}

1.1.2 Text Template and It's Macro

The `arethusa::text.html` contains few macro to ensure reusability of the concept by other resources :

`tb_macro()`

Contains the container for the Arethusa Widget

`tabs(text, treebank)`

Creates a Bootstrap tab interface where the first tab is the text, the second would be the treebank

Blocks and extensions

- The template extends `main::container.html` and feeds blocks `additinalscript` and `article`.
- It imports from `main::text.html` : `show_passage`, `header_passage`, `default_footer`, and `nav`

A

Arethusa (class in nemo_arethusa_plugin), 1

R

r_arethusa_assets() (nemo_arethusa_plugin.Arethusa method), 2

r_arethusa_config() (nemo_arethusa_plugin.Arethusa method), 2

r_arethusa_dependencies() (nemo_arethusa_plugin.Arethusa method), 2

render() (nemo_arethusa_plugin.Arethusa method), 2