
pythreejs Documentation

Release 2.0.2

PyThreejs Development Team

Nov 09, 2018

1	Quickstart	3
2	Contents	5
2.1	Installation	5
2.2	Upgrading to 1.x	5
2.3	Introduction	6
2.4	Examples	7
2.5	API Reference	23
2.6	Extending pythreejs	175
2.7	Developer install	179
	Python Module Index	181

Version: 2.0.2

pythreejs is a [Jupyter widgets](#) based [notebook](#) extension that allows Jupyter to leverage the WebGL capabilities of modern browsers by creating bindings to the javascript library [three.js](#).

By being based on top of the jupyter-widgets infrastructure, it allows for eased integration with other interactive tools for notebooks.

CHAPTER 1

Quickstart

To get started with pythreejs, install with pip:

```
pip install pythreejs
```

If you are using a notebook version older than 5.3, or if your kernel is in another environment than the notebook server, you will also need to register the front-end extensions.

For the notebook front-end:

```
jupyter nbextension install [--sys-prefix | --user | --system] --py pythreejs  
jupyter nbextension enable [--sys-prefix | --user | --system] --py pythreejs
```

For jupyterlab:

```
jupyter labextension install jupyter-threejs
```

Note: If you are installing an older version of pythreejs, you might have to add a version specifier for the labextension to match the Python package, e.g. *jupyter-threejs@1.0.0*.

2.1 Installation

The simplest way to install pythreejs is via pip:

```
pip install pythreejs
```

or via conda:

```
conda install pythreejs
```

With jupyter notebook version ≥ 5.3 , this should also install and enable the relevant front-end extensions. If for some reason this did not happen (e.g. if the notebook server is in a different environment than the kernel), you can install / configure the front-end extensions manually. If you are using classic notebook (as opposed to Jupyterlab), run:

```
jupyter nbextension install [--sys-prefix / --user / --system] --py pythreejs
jupyter nbextension enable [--sys-prefix / --user / --system] --py pythreejs
```

with the appropriate flag. If you are using Jupyterlab, install the extension with:

```
jupyter labextension install jupyter-threejs
```

2.2 Upgrading to 1.x

If you are upgrading to version 1.x from a version prior to 1.0, there are certain backwards-incompatible changes that you should note:

- `Plain[Buffer]Geometry` was renamed to `[Buffer]Geometry`. This was done in order to be more consistent with the names used in three.js. The base classes for geometry are now called `Base[Buffer]Geometry`. This also avoids the confusion with `Plane[Buffer]Geometry`.

- `LambertMaterial` -> `MeshLambertMaterial`, and other similar material class renames were done. Again, this was to more closely match the names used in three.js itself.

2.3 Introduction

The pythreejs API attempts to mimic the three.js API as closely as possible, so any resource on its API should also be helpful for understanding pythreejs. See for example the [official three.js documentation](#).

The major difference between the two is the render loop. As we normally do not want to call back to the kernel for every rendered frame, some helper classes have been created to allow for user interaction with the scene with minimal overhead:

2.3.1 Renderer classes

While the `WebGLRenderer` class mimics its three.js counterpart in only rendering frames on demand (one frame per call to its `render()` method), the `Renderer` class sets up an interactive render loop allowing for *Interactive controls* and *Animation views*. Similarly, a *Preview* widget allows for a quick visualization of various threejs objects.

2.3.2 Interactive controls

These are classes for managing user interaction with the WebGL canvas, and translating that into actions. One example is the *OrbitControls* class, which allows the user to control the camera by zooming, panning, and orbital rotation around a target. Another example is the *Picker* widget, which allows for getting the objects and surface coordinates underneath the mouse cursor.

To use controls, pass them to the renderer, e.g.:

```
Renderer (controls=[OrbitControls(...), ...], ...)
```

2.3.3 Animation views

The view widgets for the *AnimationAction* class gives interactive controls to the user for controlling a *threejs animation*.

Other notable deviations from the threejs API are listed below:

- Buffers are based on [numpy arrays](#), with their inbuilt knowledge of shape and dtype. As such, most threejs APIs that take a buffer are slightly modified (fewer options need to be specified explicitly).
- The generative geometry objects (e.g. *SphereGeometry* and *BoxBufferGeometry*) do not sync their vertices or similar data by default. To gain access to the generated data, convert them to either the *Geometry* or *BufferGeometry* type with the *from_geometry()* factory method.
- Methods are often not mirrored to the Python side. However, they can be executed with the *exec_three_obj_method()* method. Consider contributing to make methods directly available. Possibly, these can be auto-generated as well.

2.4 Examples

This section contains several examples generated from Jupyter notebooks. The widgets have been embedded into the page.

2.4.1 Geometry types

```
In [1]: from pythreejs import *
        from IPython.display import display
        from math import pi
```

```
In [2]: # Reduce repo churn for examples with embedded state:
        from pythreejs._example_helper import use_example_model_ids
        use_example_model_ids()
```

```
In [3]: BoxGeometry(
        width=5,
        height=10,
        depth=15,
        widthSegments=5,
        heightSegments=10,
        depthSegments=15)
```

```
Preview(child=BoxGeometry(depth=15.0, depthSegments=15, height=10.0, heightSegments=10, width=5.0, w
```

```
In [4]: BoxBufferGeometry(
        width=5,
        height=10,
        depth=15,
        widthSegments=5,
        heightSegments=10,
        depthSegments=15)
```

```
Preview(child=BoxBufferGeometry(depth=15.0, depthSegments=15, height=10.0, heightSegments=10, width=
```

```
In [5]: CircleGeometry(
        radius=10,
        segments=10,
        thetaStart=0.25,
        thetaLength=5.0)
```

```
Preview(child=CircleGeometry(radius=10.0, segments=10, thetaLength=5.0, thetaStart=0.25), shadowMap=
```

```
In [6]: CircleBufferGeometry(
        radius=10,
        segments=10,
        thetaStart=0.25,
        thetaLength=5.0)
```

```
Preview(child=CircleBufferGeometry(radius=10.0, segments=10, thetaLength=5.0, thetaStart=0.25), shad
```

```
In [7]: CylinderGeometry(
        radiusTop=5,
        radiusBottom=10,
        height=15,
        radialSegments=6,
        heightSegments=10,
        openEnded=False,
        thetaStart=0,
        thetaLength=2.0*pi)
```

```
Preview(child=CylinderGeometry(height=15.0, heightSegments=10, radiusBottom=10.0, radiusTop=5.0), sha
```

```
In [8]: CylinderBufferGeometry(
        radiusTop=5,
        radiusBottom=10,
        height=15,
        radialSegments=6,
        heightSegments=10,
        openEnded=False,
        thetaStart=0,
        thetaLength=2.0*pi)
```

```
Preview(child=CylinderBufferGeometry(height=15.0, heightSegments=10, radiusBottom=10.0, radiusTop=5.0))
```

```
In [9]: DodecahedronGeometry(radius=10, detail=0, _flat=True)
```

```
Preview(child=DodecahedronGeometry(radius=10.0), shadowMap=WebGLShadowMap())
```

```
In [ ]: # TODO:
        # EdgesGeometry(...)
```

```
In [ ]: # TODO:
        # ExtrudeGeometry(...)
```

```
In [10]: IcosahedronGeometry(radius=10, _flat=True)
```

```
Preview(child=IcosahedronGeometry(radius=10.0), shadowMap=WebGLShadowMap())
```

```
In [11]: LatheBufferGeometry(
        points=[
            [ 0, -10, 0 ],
            [ 10, -5, 0 ],
            [ 5, 5, 0 ],
            [ 0, 10, 0 ]
        ],
        segments=16,
        phiStart=0.0,
        phiLength=2.0*pi, _flat=True)
```

```
Preview(child=LatheBufferGeometry(points=[[0, -10, 0], [10, -5, 0], [5, 5, 0], [0, 10, 0]], segments=16))
```

```
In [12]: OctahedronGeometry(radius=10, detail=0, _flat=True)
```

```
Preview(child=OctahedronGeometry(radius=10.0), shadowMap=WebGLShadowMap())
```

```
In [13]: ParametricGeometry(
        func="""function(u,v,out) {
            var x = 5 * (0.5 - u);
            var y = 5 * (0.5 - v);
            out.set(10 * x, 10 * y, x*x - y*y);
        }""",
        slices=5,
        stacks=10, _flat=True)
```

```
Preview(child=ParametricGeometry(func='function(u,v,out) { \n            var x = 5 * (0.5 - u);\n
```

```
In [14]: PlaneGeometry(
        width=10,
        height=15,
        widthSegments=5,
        heightSegments=10)
```

```
Preview(child=PlaneGeometry(height=15.0, heightSegments=10, width=10.0, widthSegments=5), shadowMap=WebGLShadowMap())
```

```
In [15]: PlaneBufferGeometry(
        width=10,
        height=15,
```

```

        widthSegments=5,
        heightSegments=10)
Preview(child=PlaneBufferGeometry(height=15.0, heightSegments=10, width=10.0, widthSegments=5), shadowMap=WebGLShadowMap())
In [ ]: # TODO
        # PolyhedronGeometry(...)
In [16]: # TODO: issues when radius is 0...
        RingGeometry(
            innerRadius=10,
            outerRadius=25,
            thetaSegments=8,
            phiSegments=12,
            thetaStart=0,
            thetaLength=6.283185307179586)
Preview(child=RingGeometry(innerRadius=10.0, outerRadius=25.0, phiSegments=12), shadowMap=WebGLShadowMap())
In [17]: # TODO: issues when radius is 0...
        RingBufferGeometry(
            innerRadius=10,
            outerRadius=25,
            thetaSegments=8,
            phiSegments=12,
            thetaStart=0,
            thetaLength=6.283185307179586)
Preview(child=RingBufferGeometry(innerRadius=10.0, outerRadius=25.0, phiSegments=12), shadowMap=WebGLShadowMap())
In [ ]: # TODO
        # ShapeGeometry(...)
In [18]: SphereGeometry(
        radius=20,
        widthSegments=8,
        heightSegments=6,
        phiStart=0,
        phiLength=1.5*pi,
        thetaStart=0,
        thetaLength=2.0*pi/3.0)
Preview(child=SphereGeometry(phiLength=4.71238898038469, radius=20.0, thetaLength=2.0943951023931953), shadowMap=WebGLShadowMap())
In [19]: SphereBufferGeometry(
        radius=20,
        widthSegments=8,
        heightSegments=6,
        phiStart=0,
        phiLength=1.5*pi,
        thetaStart=0,
        thetaLength=2.0*pi/3.0)
Preview(child=SphereBufferGeometry(phiLength=4.71238898038469, radius=20.0, thetaLength=2.0943951023931953), shadowMap=WebGLShadowMap())
In [20]: TetrahedronGeometry(radius=10, detail=1, _flat=True)
Preview(child=TetrahedronGeometry(detail=1, radius=10.0), shadowMap=WebGLShadowMap())
In [ ]: # TODO: font loading
        # TextGeometry(...)
In [21]: TorusGeometry(
        radius=20,
        tube=5,
        radialSegments=20,

```

```
tubularSegments=6,  
arc=1.5*pi)
```

```
Preview(child=TorusGeometry(arc=4.71238898038469, radialSegments=20, radius=20.0, tube=5.0), shadowMap=WebGLShadowMap())
```

```
In [22]: TorusBufferGeometry(radius=100)
```

```
Preview(child=TorusBufferGeometry(radius=100.0), shadowMap=WebGLShadowMap())
```

```
In [23]: TorusKnotGeometry(  
    radius=20,  
    tube=5,  
    tubularSegments=64,  
    radialSegments=8,  
    p=2,  
    q=3)
```

```
Preview(child=TorusKnotGeometry(radius=20.0, tube=5.0), shadowMap=WebGLShadowMap())
```

```
In [24]: TorusKnotBufferGeometry(  
    radius=20,  
    tube=5,  
    tubularSegments=64,  
    radialSegments=8,  
    p=2,  
    q=3)
```

```
Preview(child=TorusKnotBufferGeometry(radius=20.0, tube=5.0), shadowMap=WebGLShadowMap())
```

```
In [ ]: # TODO: handling THREE.Curve  
TubeGeometry(  
    path=None,  
    segments=64,  
    radius=1,  
    radiusSegments=8,  
    close=False)
```

```
In [25]: WireframeGeometry(geometry=TorusBufferGeometry(  
    radius=20,  
    tube=5,  
    radialSegments=6,  
    tubularSegments=20,  
    arc=2.0*pi  
))
```

```
Preview(child=WireframeGeometry(geometry=TorusBufferGeometry(radialSegments=6, radius=20.0, tube=5.0), shadowMap=WebGLShadowMap()))
```

```
In [ ]:
```

2.4.2 Animation

```
In [1]: from pythreejs import *  
import ipywidgets  
from IPython.display import display
```

```
In [2]: # Reduce repo churn for examples with embedded state:  
from pythreejs._example_helper import use_example_model_ids  
use_example_model_ids()
```

```
In [3]: view_width = 600  
view_height = 400
```

Let's first set up a basic scene with a cube and a sphere,

```
In [4]: sphere = Mesh(
    SphereBufferGeometry(1, 32, 16),
    MeshStandardMaterial(color='red')
)
```

```
In [5]: cube = Mesh(
    BoxBufferGeometry(1, 1, 1),
    MeshPhysicalMaterial(color='green'),
    position=[2, 0, 4]
)
```

as well as lighting and camera:

```
In [6]: camera = PerspectiveCamera(position=[10, 6, 10], aspect=view_width/view_height)
key_light = DirectionalLight(position=[0, 10, 10])
ambient_light = AmbientLight()
```

Keyframe animation

The three.js animation system is built as a [keyframe](#) system. We'll demonstrate this by animating the position and rotation of our camera.

First, we set up the keyframes for the position and the rotation separately:

```
In [7]: positon_track = VectorKeyframeTrack(name='.position',
    times=[0, 2, 5],
    values=[10, 6, 10,
            6.3, 3.78, 6.3,
            -2.98, 0.84, 9.2,
            ])
rotation_track = QuaternionKeyframeTrack(name='.quaternion',
    times=[0, 2, 5],
    values=[-0.184, 0.375, 0.0762, 0.905,
            -0.184, 0.375, 0.0762, 0.905,
            -0.0430, -0.156, -0.00681, 0.987,
            ])
```

Next, we create an animation clip combining the two tracks, and finally an animation action to control the animation. See the three.js docs for more details on the different responsibilities of the different classes.

```
In [8]: camera_clip = AnimationClip(tracks=[positon_track, rotation_track])
camera_action = AnimationAction(AnimationMixer(camera), camera_clip, camera)
```

Now, let's see it in action:

```
In [9]: scene = Scene(children=[sphere, cube, camera, key_light, ambient_light])
controller = OrbitControls(controlling=camera)
renderer = Renderer(camera=camera, scene=scene, controls=[controller],
    width=view_width, height=view_height)
```

```
In [10]: renderer
```

```
Renderer(camera=PerspectiveCamera(aspect=1.5, position=(10.0, 6.0, 10.0), projectionMatrix=(1.429671
```

```
In [11]: camera_action
```

```
AnimationAction(clip=AnimationClip(duration=5.0, tracks=(VectorKeyframeTrack(name='.position', times=
```

Let's add another animation clip, this time animating the color of the sphere's material:

```
In [12]: color_track = ColorKeyframeTrack(name='.material.color',
    times=[0, 1], values=[1, 0, 0, 0, 0, 1]) # red to blue
```

```
color_clip = AnimationClip(tracks=[color_track], duration=1.5)
color_action = AnimationAction(AnimationMixer(sphere), color_clip, sphere)
```

```
In [13]: color_action
```

```
AnimationAction(clip=AnimationClip(duration=1.5, tracks=(ColorKeyframeTrack(name='.material.color', t
```

Note how the two animation clips can freely be combined since they affect different properties. It's also worth noting that the color animation can be combined with manual camera control, while the camera animation cannot. When animating the camera, you might want to consider disabling the manual controls.

Animating rotation

When animating the camera rotation above, we used the camera's quaternion. This is the most robust method for animating free-form rotations. For example, the animation above was created by first moving the camera manually, and then reading out its position and quaternion properties at the wanted views. If you want more intuitive axes control, it is possible to animate the rotation sub-attributes instead, as shown below.

```
In [14]: f = """
function f(origu, origv, out) {
    // scale u and v to the ranges I want: [0, 2*pi]
    var u = 2*Math.PI*origu;
    var v = 2*Math.PI*origv;

    var x = Math.sin(u);
    var y = Math.cos(v);
    var z = Math.cos(u+v);

    out.set(x,y,z)
}
"""
surf_g = ParametricGeometry(func=f, slices=16, stacks=16);

surf1 = Mesh(geometry=surf_g,
              material=MeshLambertMaterial(color='green', side='FrontSide'))
surf2 = Mesh(geometry=surf_g,
              material=MeshLambertMaterial(color='yellow', side='BackSide'))
surf = Group(children=[surf1, surf2])

camera2 = PerspectiveCamera( position=[10, 6, 10], aspect=view_width/view_height)
scene2 = Scene(children=[surf, camera2,
                        DirectionalLight(position=[3, 5, 1], intensity=0.6),
                        AmbientLight(intensity=0.5)])
renderer2 = Renderer(camera=camera2, scene=scene2,
                    controls=[OrbitControls(controlling=camera2)],
                    width=view_width, height=view_height)

display(renderer2)

Renderer(camera=PerspectiveCamera(aspect=1.5, position=(10.0, 6.0, 10.0), quaternion=(0.0, 0.0, 0.0, 2.0)))

In [15]: spin_track = NumberKeyframeTrack(name='.rotation[y]', times=[0, 2], values=[0, 6.28])
spin_clip = AnimationClip(tracks=[spin_track])
spin_action = AnimationAction(AnimationMixer(surf), spin_clip, surf)
spin_action
```

```
AnimationAction(clip=AnimationClip(tracks=(NumberKeyframeTrack(name='.rotation[y]', times=array([0, 2
```

Note that we are spinning the object itself, and that we are therefore free to manipulate the camera at will.

Morph targets

Set up a simple sphere geometry, and add a morph target that is an oblong pill shape:

```
In [16]: # This lets three.js create the geometry, then syncs back vertex positions etc.
# For this reason, you should allow for the sync to complete before executing
# the next cell.
```

```
morph = BufferGeometry.from_geometry(SphereBufferGeometry(1, 32, 16))
```

```
In [17]: import numpy as np
```

```
# Set up morph targets:
vertices = np.array(morph.attributes['position'].array)
for i in range(len(vertices)):
    if vertices[i, 0] > 0:
        vertices[i, 0] += 1
morph.morphAttributes = {'position': [
    BufferAttribute(vertices),
]}

morphMesh = Mesh(morph, MeshPhongMaterial(
    color='#ff3333', shininess=150, morphTargets=True))
```

Set up animation for going back and forth between the sphere and pill shape:

```
In [18]: pill_track = NumberKeyframeTrack(
    name='.morphTargetInfluences[0]', times=[0, 1.5, 3], values=[0, 2.5, 0])
pill_clip = AnimationClip(tracks=[pill_track])
pill_action = AnimationAction(AnimationMixer(morphMesh), pill_clip, morphMesh)
```

```
In [19]: camera3 = PerspectiveCamera( position=[5, 3, 5], aspect=view_width/view_height)
scene3 = Scene(children=[morphMesh, camera3,
    DirectionalLight(position=[3, 5, 1], intensity=0.6),
    AmbientLight(intensity=0.5)])
renderer3 = Renderer(camera=camera3, scene=scene3,
    controls=[OrbitControls(controlling=camera3)],
    width=view_width, height=view_height)
display(renderer3, pill_action)
```

```
Renderer(camera=PerspectiveCamera(aspect=1.5, position=(5.0, 3.0, 5.0), quaternion=(0.0, 0.0, 0.0, 1.0))
AnimationAction(clip=AnimationClip(duration=3.0, tracks=(NumberKeyframeTrack(name='.morphTargetInfluences[0]', times=[0, 1.5, 3], values=[0, 2.5, 0]),))
```

Skeletal animation

First, set up a skinned mesh with some bones:

```
In [20]: import numpy as np
```

```
N_BONES = 3

ref_cylinder = CylinderBufferGeometry(5, 5, 50, 5, N_BONES * 5, True)
cylinder = BufferGeometry.from_geometry(ref_cylinder)
```

```
In [21]: skinIndices = []
skinWeights = []
vertices = cylinder.attributes['position'].array
boneHeight = ref_cylinder.height / (N_BONES - 1)
for i in range(vertices.shape[0]):

    y = vertices[i, 1] + 0.5 * ref_cylinder.height
```

```
skinIndex = y // boneHeight
skinWeight = ( y % boneHeight ) / boneHeight

# Ease between each bone
skinIndices.append([skinIndex, skinIndex + 1, 0, 0 ])
skinWeights.append([1 - skinWeight, skinWeight, 0, 0 ])

cylinder.attributes = dict(
    cylinder.attributes,
    skinIndex=BufferAttribute(skinIndices),
    skinWeight=BufferAttribute(skinWeights),
)

shoulder = Bone(position=(0, -25, 0))
elbow = Bone(position=(0, 25, 0))
hand = Bone(position=(0, 25, 0))

shoulder.add(elbow)
elbow.add(hand)
bones = [shoulder, elbow, hand]
skeleton = Skeleton(bones)

mesh = SkinnedMesh(cylinder, MeshPhongMaterial(side='DoubleSide', skinning=True))
mesh.add(bones[0])
mesh.skeleton = skeleton
```

In [22]: helper = SkeletonHelper(mesh)

Next, set up some simple rotation animations for the bones:

In [23]: # Rotate on x and z axes:

```
bend_tracks = [
    NumberKeyframeTrack(
        name='.bones[1].rotation[x]',
        times=[0, 0.5, 1.5, 2],
        values=[0, 0.3, -0.3, 0]),
    NumberKeyframeTrack(
        name='.bones[1].rotation[z]',
        times=[0, 0.5, 1.5, 2],
        values=[0, 0.3, -0.3, 0]),
    NumberKeyframeTrack(
        name='.bones[2].rotation[x]',
        times=[0, 0.5, 1.5, 2],
        values=[0, -0.3, 0.3, 0]),
    NumberKeyframeTrack(
        name='.bones[2].rotation[z]',
        times=[0, 0.5, 1.5, 2],
        values=[0, -0.3, 0.3, 0]),
]
bend_clip = AnimationClip(tracks=bend_tracks)
bend_action = AnimationAction(AnimationMixer(mesh), bend_clip, mesh)
```

Rotate on y axis:

```
wring_tracks = [
    NumberKeyframeTrack(name='.bones[1].rotation[y]', times=[0, 0.5, 1.5, 2], values=[0, 0.7, -0.7, 0]),
    NumberKeyframeTrack(name='.bones[2].rotation[y]', times=[0, 0.5, 1.5, 2], values=[0, 0.7, -0.7, 0]),
]
wring_clip = AnimationClip(tracks=wring_tracks)
```

```
wring_action = AnimationAction(AnimationMixer(mesh), wring_clip, mesh)
In [24]: camera4 = PerspectiveCamera( position=[40, 24, 40], aspect=view_width/view_height)
scene4 = Scene(children=[mesh, helper, camera4,
                        DirectionalLight(position=[3, 5, 1], intensity=0.6),
                        AmbientLight(intensity=0.5)])
renderer4 = Renderer(camera=camera4, scene=scene4,
                    controls=[OrbitControls(controlling=camera4)],
                    width=view_width, height=view_height)
display(renderer4)
Renderer(camera=PerspectiveCamera(aspect=1.5, position=(40.0, 24.0, 40.0), quaternion=(0.0, 0.0, 0.0, 1.0)), scene=scene4)
In [25]: bend_action
AnimationAction(clip=AnimationClip(duration=2.0, tracks=(NumberKeyframeTrack(name='.bones[1].rotation', keyframes=[(0, 0), (1, 1.5708)], interpolation='LINEAR'),)), wring_action)
In [26]: wring_action
AnimationAction(clip=AnimationClip(duration=2.0, tracks=(NumberKeyframeTrack(name='.bones[1].rotation', keyframes=[(0, 0), (1, 1.5708)], interpolation='LINEAR'),)), wring_action)
In [ ]:
```

2.4.3 Textures

```
In [1]: from pythreejs import *
from IPython.display import display
from math import pi

In [2]: # Reduce repo churn for examples with embedded state:
from pythreejs._example_helper import use_example_model_ids
use_example_model_ids()

In [3]: checker_tex = ImageTexture(imageUri='img/checkerboard.png')
earth_tex = ImageTexture(imageUri='img/earth.jpg')

In [4]: checker_tex
Preview(child=ImageTexture(imageUri='img/checkerboard.png', repeat=(1.0, 1.0), version=1), shadowMap=WebGLShadowMap)
In [5]: earth_tex
Preview(child=ImageTexture(imageUri='img/earth.jpg', repeat=(1.0, 1.0), version=1), shadowMap=WebGLShadowMap)
In [6]: #
# Create checkerboard pattern
#

# tex dims need to be power of two.
arr_w = 256
arr_h = 256

import numpy as np

def gen_checkers(width, height, n_checkers_x, n_checkers_y):
    array = np.ones((width, height, 3), dtype='float32')

    # width in texels of each checker
    checker_w = width / n_checkers_x
    checker_h = height / n_checkers_y

    for y in range(arr_h):
        for x in range(arr_w):
```

```

        color_key = int(x / checker_w) + int(y / checker_h)
        if color_key % 2 == 0:
            array[x, y, :] = [ 0, 0, 0 ]
        else:
            array[x, y, :] = [ 1, 1, 1 ]
    return array

```

```

data_tex = DataTexture(
    data=gen_checkers(arr_w, arr_h, 4, 4),
    format="RGBFormat",
    type="FloatType",
)

```

In [7]: data_tex

```

Preview(child=DataTexture(data=array([[0., 0., 0.],
    [0., 0., 0.],
    [0., 0., 0.],
    ...

```

In [8]: data_tex.data = gen_checkers(arr_w, arr_h, 12, 20)

In []:

2.4.4 Renderer properties

```

In [1]: from pythreejs import *
        from IPython.display import display
        import ipywidgets

```

```

In [2]: # Reduce repo churn for examples with embedded state:
        from pythreejs._example_helper import use_example_model_ids
        use_example_model_ids()

```

Transparent background

To have the render view use a transparent background, there are three steps you need to do: 1. Ensure that the background property of the Scene object is set to None. 2. Ensure that alpha=True is passed to the constructor of the Renderer object. This ensures that an alpha channel is used by the renderer. 3. Ensure that the clearOpacity property of the Renderer object is set to 0. For more details about this, see below.

```

In [3]: ball = Mesh(geometry=SphereGeometry(),
                    material=MeshLambertMaterial(color='red'))
        key_light = DirectionalLight(color='white', position=[3, 5, 1], intensity=0.5)

        c = PerspectiveCamera(position=[0, 5, 5], up=[0, 1, 0], children=[key_light])

        scene = Scene(children=[ball, c, AmbientLight(color='#777777')], background=None)

        renderer = Renderer(camera=c,
                             scene=scene,
                             alpha=True,
                             clearOpacity=0,
                             controls=[OrbitControls(controlling=c)])

        display(renderer)

```

```

Renderer(camera=PerspectiveCamera(children=(DirectionalLight(color='white', intensity=0.5, position=

```

The use of clear color/opacity is explained in more detailed in the docs of three.js, but in short: - If `autoClear` is true the renderer output is cleared on each rendered frame. - If `autoClearColor` is true the background color is cleared on each frame. - When the background color is cleared, it is reset to `Renderer.clearColor`, with an opacity of `Renderer.clearOpacity`.

```
In [4]: # Let's set up some controls for the clear color/opacity:
```

```
opacity = ipywidgets.FloatSlider(min=0., max=1.)
ipywidgets.jslink((opacity, 'value'), (renderer, 'clearOpacity'))

color = ipywidgets.ColorPicker()
ipywidgets.jslink((color, 'value'), (renderer, 'clearColor'))

display(ipywidgets.HBox(children=[
    ipywidgets.Label('Clear color:'), color, ipywidgets.Label('Clear opacity:'), opacity]))
HBox(children=(Label(value='Clear color:'), ColorPicker(value='black'), Label(value='Clear opacity:')))
```

Scene background

If we set the background property of the scene, it will be filled in on top of whatever clear color is there, basically making the clear color ineffective.

```
In [5]: scene_background = ipywidgets.ColorPicker()
        _background_link = None
```

```
def toggle_scene_background(change):
    global _background_link
    if change['new']:
        _background_link = ipywidgets.jslink((scene_background, 'value'), (scene, 'background'))
    else:
        _background_link.close()
        _background_link = None
        scene.background = None
```

```
scene_background_toggle = ipywidgets.ToggleButton(False, description='Scene Color')
scene_background_toggle.observe(toggle_scene_background, 'value')
```

```
display(ipywidgets.HBox(children=[
    ipywidgets.Label('Scene background color:'), scene_background, scene_background_toggle]))
```

```
HBox(children=(Label(value='Scene background color:'), ColorPicker(value='black'), ToggleButton(value='Scene Color')))
```

```
In [ ]:
```

2.4.5 Thick line geometry

Three.js has some example code for thick lines via an instance-based geometry. Since WebGL does not guarantee support for line thickness greater than 1 for GL lines, pythreejs includes these objects by default.

```
In [1]: from pythreejs import *
        from IPython.display import display
        from ipywidgets import VBox, HBox, Checkbox, jslink
        import numpy as np
```

```
In [2]: # Reduce repo churn for examples with embedded state:
        from pythreejs._example_helper import use_example_model_ids
        use_example_model_ids()
```

First, let's set up a normal GL line for comparison. Depending on your OS/browser combination, this might not respect the `linewidth` argument. E.g. most browsers on Windows does not support linewidth greater than 1, due to lack of support in the ANGLE library that most browsers rely on.

```
In [3]: g1 = BufferGeometry(
    attributes={
        'position': BufferAttribute(np.array([
            [0, 0, 0], [1, 1, 1],
            [2, 2, 2], [4, 4, 4]
        ], dtype=np.float32), normalized=False),
        'color': BufferAttribute(np.array([
            [1, 0, 0], [1, 0, 0],
            [0, 1, 0], [0, 0, 1]
        ], dtype=np.float32), normalized=False),
    },
)
m1 = LineBasicMaterial(vertexColors='VertexColors', linewidth=10)
line1 = LineSegments(g1, m1)
line1
```

```
Preview(child=LineSegments(geometry=BufferGeometry(attributes={'position': BufferAttribute(array=array
```

Next, we'll set up two variants of the instance geometry based lines. One with a single color, and one with vertex colors.

```
In [4]: g2 = LineSegmentsGeometry(
    positions=[
        [[0, 0, 0], [1, 1, 1]],
        [[2, 2, 2], [4, 4, 4]]
    ],
)
m2 = LineMaterial(linewidth=10, color='cyan')
line2 = LineSegments2(g2, m2)
line2
```

```
Preview(child=LineSegments2(geometry=LineSegmentsGeometry(positions=array([[0., 0., 0.],
[1., 1., 1.]...)
```

```
In [5]: g3 = LineSegmentsGeometry(
    positions=[
        [[0, 0, 0], [1, 1, 1]],
        [[2, 2, 2], [4, 4, 4]]
    ],
    colors=[
        [[1, 0, 0], [1, 0, 0]],
        [[0, 1, 0], [0, 0, 1]]
    ],
)
m3 = LineMaterial(linewidth=10, vertexColors='VertexColors')
line3 = LineSegments2(g3, m3)
line3
```

```
Preview(child=LineSegments2(geometry=LineSegmentsGeometry(colors=array([[1., 0., 0.],
[1., 0., 0.]],
...))
```

Finally, let's set up a simple scene and renderer, and add some checkboxes so we can toggle the visibility of the different lines.

```
In [6]: view_width = 600
    view_height = 400
    camera = PerspectiveCamera(position=[10, 0, 0], aspect=view_width/view_height)
```

```
key_light = DirectionalLight(position=[0, 10, 10])
ambient_light = AmbientLight()
```

```
In [7]: scene = Scene(children=[line1, line2, line3, camera, key_light, ambient_light])
        controller = OrbitControls(controlling=camera, screenSpacePanning=False)
        renderer = Renderer(camera=camera, scene=scene, controls=[controller],
                             width=view_width, height=view_height)
```

```
In [8]: chks = [
        Checkbox(True, description='GL line'),
        Checkbox(True, description='Fat line (single color)'),
        Checkbox(True, description='Fat line (vertex colors)'),
    ]
    jslink((chks[0], 'value'), (line1, 'visible'))
    jslink((chks[1], 'value'), (line2, 'visible'))
    jslink((chks[2], 'value'), (line3, 'visible'))
    VBox([renderer, HBox(chks)])
```

```
VBox(children=(Renderer(camera=PerspectiveCamera(aspect=1.5, position=(10.0, 0.0, 0.0), projectionMat
```

For reference, the code below shows how you would recreate the line geometry and material from the kernel. The only significant difference is that you need to declare the render view resolution on material creation, while the included `LineMaterial` automatically sets this.

```
In [9]: # The line segment points and colors.
        # Each array of six is one instance/segment [x1, y1, z1, x2, y2, z2]
        posInstBuffer = InstancedInterleavedBuffer( np.array([
            [0, 0, 0, 1, 1, 1],
            [2, 2, 2, 4, 4, 4]
        ], dtype=np.float32))
        colInstBuffer = InstancedInterleavedBuffer( np.array([
            [1, 0, 0, 1, 0, 0],
            [0, 1, 0, 0, 0, 1]
        ], dtype=np.float32))

        # This uses InstancedBufferGeometry, so that the geometry is reused for each line segment
        lineGeo = InstancedBufferGeometry(attributes={
            # Helper line geometry (2x4 grid), that is instanced
            'position': BufferAttribute(np.array([
                [ 1,  2,  0], [1,  2,  0],
                [-1,  1,  0], [1,  1,  0],
                [-1,  0,  0], [1,  0,  0],
                [-1, -1,  0], [1, -1,  0]
            ], dtype=np.float32)),
            'uv': BufferAttribute(np.array([
                [-1,  2], [1,  2],
                [-1,  1], [1,  1],
                [-1, -1], [1, -1],
                [-1, -2], [1, -2]
            ], dtype=np.float32)),
            'index': BufferAttribute(np.array([
                0, 2, 1,
                2, 3, 1,
                2, 4, 3,
                4, 5, 3,
                4, 6, 5,
                6, 7, 5
            ], dtype=np.uint8)),
            # The line segments are split into start/end for each instance:
            'instanceStart': InterleavedBufferAttribute(posInstBuffer, 3, 0),
            'instanceEnd': InterleavedBufferAttribute(posInstBuffer, 3, 3),
```

```
        'instanceColorStart': InterleavedBufferAttribute(colInstBuffer, 3, 0),
        'instanceColorEnd': InterleavedBufferAttribute(colInstBuffer, 3, 3),
    })
```

In [10]: # The line material shader:

```
lineMat = ShaderMaterial(
    vertexShader=''
    #include <common>
    #include <color_pars_vertex>
    #include <fog_pars_vertex>
    #include <logdepthbuf_pars_vertex>
    #include <clipping_planes_pars_vertex>

    uniform float linewidth;
    uniform vec2 resolution;

    attribute vec3 instanceStart;
    attribute vec3 instanceEnd;

    attribute vec3 instanceColorStart;
    attribute vec3 instanceColorEnd;

    varying vec2 vUv;

    void trimSegment( const in vec4 start, inout vec4 end ) {

        // trim end segment so it terminates between the camera plane and the near plane

        // conservative estimate of the near plane
        float a = projectionMatrix[ 2 ][ 2 ]; // 3rd entry in 3th column
        float b = projectionMatrix[ 3 ][ 2 ]; // 3rd entry in 4th column
        float nearEstimate = - 0.5 * b / a;

        float alpha = ( nearEstimate - start.z ) / ( end.z - start.z );

        end.xyz = mix( start.xyz, end.xyz, alpha );

    }

    void main() {

        #ifdef USE_COLOR

            vColor.xyz = ( position.y < 0.5 ) ? instanceColorStart : instanceColorEnd;

        #endif

        float aspect = resolution.x / resolution.y;

        vUv = uv;

        // camera space
        vec4 start = modelViewMatrix * vec4( instanceStart, 1.0 );
        vec4 end = modelViewMatrix * vec4( instanceEnd, 1.0 );

        // special case for perspective projection, and segments that terminate either in, or be
        // clearly the gpu firmware has a way of addressing this issue when projecting into ndc
        // but we need to perform ndc-space calculations in the shader, so we must address this
        // perhaps there is a more elegant solution -- WestLangley
```



```
bool perspective = ( projectionMatrix[ 2 ][ 3 ] == - 1.0 ); // 4th entry in the 3rd column

if ( perspective ) {

    if ( start.z < 0.0 && end.z >= 0.0 ) {

        trimSegment( start, end );

    } else if ( end.z < 0.0 && start.z >= 0.0 ) {

        trimSegment( end, start );

    }

}

// clip space
vec4 clipStart = projectionMatrix * start;
vec4 clipEnd = projectionMatrix * end;

// ndc space
vec2 ndcStart = clipStart.xy / clipStart.w;
vec2 ndcEnd = clipEnd.xy / clipEnd.w;

// direction
vec2 dir = ndcEnd - ndcStart;

// account for clip-space aspect ratio
dir.x *= aspect;
dir = normalize( dir );

// perpendicular to dir
vec2 offset = vec2( dir.y, - dir.x );

// undo aspect ratio adjustment
dir.x /= aspect;
offset.x /= aspect;

// sign flip
if ( position.x < 0.0 ) offset *= - 1.0;

// endcaps
if ( position.y < 0.0 ) {

    offset += - dir;

} else if ( position.y > 1.0 ) {

    offset += dir;

}

// adjust for linewidth
offset *= linewidth;

// adjust for clip-space to screen-space conversion // maybe resolution should be based
offset /= resolution.y;
```

```
// select end
vec4 clip = ( position.y < 0.5 ) ? clipStart : clipEnd;

// back to clip space
offset *= clip.w;

clip.xy += offset;

gl_Position = clip;

vec4 mvPosition = ( position.y < 0.5 ) ? start : end; // this is an approximation

#include <logdepthbuf_vertex>
#include <clipping_planes_vertex>
#include <fog_vertex>
}
'''
    fragmentShader='''
uniform vec3 diffuse;
uniform float opacity;

varying float vLineDistance;

#include <common>
#include <color_pars_fragment>
#include <fog_pars_fragment>
#include <logdepthbuf_pars_fragment>
#include <clipping_planes_pars_fragment>

varying vec2 vUv;

void main() {

    #include <clipping_planes_fragment>

    if ( abs( vUv.y ) > 1.0 ) {

        float a = vUv.x;
        float b = ( vUv.y > 0.0 ) ? vUv.y - 1.0 : vUv.y + 1.0;
        float len2 = a * a + b * b;

        if ( len2 > 1.0 ) discard;

    }

    vec4 diffuseColor = vec4( diffuse, opacity );

    #include <logdepthbuf_fragment>
    #include <color_fragment>

    gl_FragColor = vec4( diffuseColor.rgb, diffuseColor.a );

    #include <premultiplied_alpha_fragment>
    #include <tonemapping_fragment>
    #include <encodings_fragment>
    #include <fog_fragment>

}
```

```

'''
    vertexColors='VertexColors',
    uniforms=dict(
        linewidth={'value': 10.0},
        resolution={'value': (100., 100.)},
        **UniformsLib['common']
    )
)

```

```
In [11]: Mesh(lineGeo, lineMat)
```

```
Preview(child=Mesh(geometry=InstancedBufferGeometry(attributes={'position': BufferAttribute(array=ar
```

```
In [ ]:
```

2.5 API Reference

The pythreejs API attempts to mimic [the three.js API](#) as closely as possible. This API reference therefore does not attempt to explain the purpose of any forwarded objects or attributes, but can still be useful for:

- The trait signatures of various properties.
- Classes, properties and methods custom to pythreejs.
- Variations from the three.js API, e.g. for *BufferAttribute*.

2.5.1 `_base`

Preview

```

class pythreejs.Preview(child, **kwargs)
    Bases: pythreejs._base.renderable.RenderableWidget

    child = Instance()
        a ThreeWidget

```

RenderableWidget

```

class pythreejs.RenderableWidget(**kwargs)
    Bases: ipywidgets.widgets.domwidget.DOMWidget

    autoClear = Bool(True)
        A boolean (True, False) trait.

    autoClearColor = Bool(True)
        A boolean (True, False) trait.

    autoClearDepth = Bool(True)
        A boolean (True, False) trait.

    autoClearStencil = Bool(True)
        A boolean (True, False) trait.

    clearColor = Unicode('#000000')
        A trait for unicode strings.

    clearOpacity = CFloat(1.0)
        A casting version of the float trait.

```

clippingPlanes = List()
An instance of a Python list.

freeze()

gammaFactor = CFloat(2.0)
A casting version of the float trait.

gammaInput = Bool(False)
A boolean (True, False) trait.

gammaOutput = Bool(False)
A boolean (True, False) trait.

localClippingEnabled = Bool(False)
A boolean (True, False) trait.

log(msg)
A trait whose value must be an instance of a specified class.
The value can also be an instance of a subclass of the specified class.
Subclasses can declare default classes by overriding the class attribute

maxMorphNormals = CInt(4)
A casting version of the int trait.

maxMorphTargets = CInt(8)
A casting version of the int trait.

physicallyCorrectLights = Bool(False)
A boolean (True, False) trait.

send_msg(message_type, payload=None)

shadowMap = Instance()
A trait whose value must be an instance of a specified class.
The value can also be an instance of a subclass of the specified class.
Subclasses can declare default classes by overriding the class attribute

sortObject = Bool(True)
A boolean (True, False) trait.

toneMapping = Enum('LinearToneMapping')
An enum whose value must be in a given sequence.

toneMappingExposure = CFloat(1.0)
A casting version of the float trait.

toneMappingWhitePoint = CFloat(1.0)
A casting version of the float trait.

ThreeWidget

```
class pythreejs.ThreeWidget(**kwargs)
    Bases: ipywidgets.widgets.widget.Widget
    Base widget type for all pythreejs widgets
    exec_three_obj_method(method_name, *args, **kwargs)
        Execute a method on the three object.
```

Excute the method specified by *method_name* on the three object, with arguments *args*. *kwargs* is currently ignored.

2.5.2 animation

tracks

BooleanKeyframeTrack

```
class pythreejs.BooleanKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

BooleanKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/BooleanKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/BooleanKeyframeTrack>

ColorKeyframeTrack

```
class pythreejs.ColorKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

ColorKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/ColorKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/ColorKeyframeTrack>

NumberKeyframeTrack

```
class pythreejs.NumberKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

NumberKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/NumberKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/NumberKeyframeTrack>

QuaternionKeyframeTrack

```
class pythreejs.QuaternionKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

QuaternionKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/QuaternionKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/QuaternionKeyframeTrack>

StringKeyframeTrack

```
class pythreejs.StringKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

StringKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/StringKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/StringKeyframeTrack>

VectorKeyframeTrack

```
class pythreejs.VectorKeyframeTrack (name="", times=None, values=None, interpolation="InterpolateLinear")
```

VectorKeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/tracks/VectorKeyframeTrack>

Inherits *KeyframeTrack*.

Three.js docs: <https://threejs.org/docs/#api/animation/tracks/VectorKeyframeTrack>

AnimationAction

```
class pythreejs.AnimationAction (mixer=None, clip=None, localRoot=None)
```

AnimationAction is a three widget that also has its own view.

The view offers animation action controls.

This widget has some manual overrides on the Python side.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/AnimationAction>

mixer

```
Instance(AnimationMixer, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

clip

```
Instance(AnimationClip, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

localRoot

```
Instance(ThreeWidget, allow_none=True).tag(sync=True, **widget_serialization)
```

clampWhenFinished

```
Bool(False, allow_none=False).tag(sync=True)
```

enabled

```
Bool(True, allow_none=False).tag(sync=True)
```

loop

```
Enum(LoopModes, "LoopRepeat", allow_none=False).tag(sync=True)
```

paused

```
Bool(False, allow_none=False).tag(sync=True)
```

reiterations

```
CInt(float('inf'), allow_none=False).tag(sync=True)
```

time

```
CFloat(0, allow_none=False).tag(sync=True)
```

timeScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

weight

```
CFloat(1, allow_none=False).tag(sync=True)
```

zeroSlopeAtEnd

```
Bool(True, allow_none=False).tag(sync=True)
```

zeroSlopeAtStart

```
Bool(True, allow_none=False).tag(sync=True)
```

pause()

play()

reiterations = Union(int)
an int or a float

stop()

AnimationClip

class pythreejs.**AnimationClip** (*name=None, duration=-1, tracks=[]*)
 AnimationClip

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/AnimationClip>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/AnimationClip>

name

```
Unicode(None, allow_none=True).tag(sync=True)
```

duration

```
CFloat(-1, allow_none=False).tag(sync=True)
```

tracks

```
Tuple().tag(sync=True, **widget_serialization)
```

duration = CFloat(-1)
 a float

name = Unicode(None)
 a unicode string

tracks = Tuple()
 a tuple of any type

AnimationMixer

class pythreejs.**AnimationMixer** (*rootObject=None, time=0, timeScale=1*)
 AnimationMixer

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/AnimationMixer>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/AnimationMixer>

rootObject

```
Instance(ThreeWidget, allow_none=True).tag(sync=True, **widget_serialization)
```

time

```
CFloat(0, allow_none=False).tag(sync=True)
```

timeScale


```
CFloat(1, allow_none=False).tag(sync=True)
```

rootObject = Instance()

a ThreeWidget or None

time = CFloat(0)

a float

timeScale = CFloat(1)

a float

AnimationObjectGroup

class pythreejs.**AnimationObjectGroup**

AnimationObjectGroup

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/AnimationObjectGroup>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/AnimationObjectGroup>

AnimationUtils

class pythreejs.**AnimationUtils**

AnimationUtils

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/AnimationUtils>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/AnimationUtils>

KeyframeTrack

class pythreejs.**KeyframeTrack** (*name=""*, *times=None*, *values=None*, *interpolation="InterpolateLinear"*)

KeyframeTrack

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/KeyframeTrack>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/KeyframeTrack>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

times

```
WebGLDataUnion().tag(sync=True)
```

values

```
WebGLDataUnion().tag(sync=True)
```

interpolation

```
Enum(InterpolationModes, "InterpolateLinear", allow_none=False).tag(sync=True)
```

```
interpolation = Enum('InterpolateLinear')  
any of ['InterpolateDiscrete', 'InterpolateLinear', 'InterpolateSmooth']
```

```
name = Unicode('')  
a unicode string
```

```
times = WebGLDataUnion()  
a numpy array or a NDArrayBase
```

```
values = WebGLDataUnion()  
a numpy array or a NDArrayBase
```

PropertyBinding

```
class pythreejs.PropertyBinding  
PropertyBinding
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/PropertyBinding>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/PropertyBinding>

PropertyMixer

```
class pythreejs.PropertyMixer  
PropertyMixer
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/animation/PropertyMixer>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/animation/PropertyMixer>

2.5.3 audio

AudioAnalyser

```
class pythreejs.AudioAnalyser  
AudioAnalyser
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/audio/AudioAnalyser>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/audio/AudioAnalyser>

AudioListener

class pythreejs.**AudioListener**
AudioListener

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/audio/AudioListener>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/audio/AudioListener>

Audio

class pythreejs.**Audio**
Audio

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/audio/Audio>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/audio/Audio>

PositionalAudio

class pythreejs.**PositionalAudio**
PositionalAudio

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/audio/PositionalAudio>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/audio/PositionalAudio>

2.5.4 cameras

ArrayCamera

class pythreejs.**ArrayCamera** (*fov=50, aspect=1, near=0.1, far=2000*)
ArrayCamera

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/ArrayCamera>

Inherits *PerspectiveCamera*.

Three.js docs: <https://threejs.org/docs/#api/cameras/ArrayCamera>

type

```
Unicode("ArrayCamera", allow_none=False).tag(sync=True)
```

type = Unicode('ArrayCamera')
a unicode string

Camera

class pythreejs.Camera

Camera

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/Camera>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/cameras/Camera>

matrixWorldInverse

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).
↳tag(sync=True)
```

projectionMatrix

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).
↳tag(sync=True)
```

type

```
Unicode("Camera", allow_none=False).tag(sync=True)
```

matrixWorldInverse = **Matrix4**((1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1))
a tuple of any type

projectionMatrix = **Matrix4**((1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1))
a tuple of any type

type = **Unicode**('Camera')
a unicode string

CombinedCamera

class pythreejs.CombinedCamera (*width=0, height=0, fov=50, near=0.1, far=2000, orthoNear=0.1, orthoFar=2000*)

CombinedCamera

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Camera*.

Three.js docs: <https://threejs.org/docs/#api/cameras/CombinedCamera>

fov

```
CFloat(50, allow_none=False).tag(sync=True)
```

zoom

```
CFloat(1, allow_none=False).tag(sync=True)
```

near

```
CFloat(0.1, allow_none=False).tag(sync=True)
```

far

```
CFloat(2000, allow_none=False).tag(sync=True)
```

orthoNear

```
CFloat(0.1, allow_none=False).tag(sync=True)
```

orthoFar

```
CFloat(2000, allow_none=False).tag(sync=True)
```

width

```
CFloat(0, allow_none=False).tag(sync=True)
```

height

```
CFloat(0, allow_none=False).tag(sync=True)
```

mode

```
Enum(['perspective', 'orthographic'], "perspective", allow_none=False).  
→tag(sync=True)
```

impersonate

```
Bool(True, allow_none=False).tag(sync=True)
```

type

```
Unicode("CombinedCamera", allow_none=False).tag(sync=True)
```

```
far = CFloat(2000)  
a float
```

```
fov = CFloat(50)  
a float
```

```
height = CFloat(0)  
a float
```

```
impersonate = Bool(True)  
a boolean
```

```

mode = Enum('perspective')
    any of ['perspective', 'orthographic']

near = CFloat(0.1)
    a float

orthoFar = CFloat(2000)
    a float

orthoNear = CFloat(0.1)
    a float

type = Unicode('CombinedCamera')
    a unicode string

width = CFloat(0)
    a float

zoom = CFloat(1)
    a float

```

CubeCamera

```

class pythreejs.CubeCamera
    CubeCamera

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/CubeCamera>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/cameras/CubeCamera>

type

```
Unicode("CubeCamera", allow_none=False).tag(sync=True)
```

```

type = Unicode('CubeCamera')
    a unicode string

```

OrthographicCamera

```

class pythreejs.OrthographicCamera (left=0, right=0, top=0, bottom=0, near=0.1, far=2000)
    OrthographicCamera

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/OrthographicCamera>

Inherits *Camera*.

Three.js docs: <https://threejs.org/docs/#api/cameras/OrthographicCamera>

zoom

```
CFloat(1, allow_none=False).tag(sync=True)
```

left

```
CFloat(0, allow_none=False).tag(sync=True)
```

right

```
CFloat(0, allow_none=False).tag(sync=True)
```

top

```
CFloat(0, allow_none=False).tag(sync=True)
```

bottom

```
CFloat(0, allow_none=False).tag(sync=True)
```

near

```
CFloat(0.1, allow_none=False).tag(sync=True)
```

far

```
CFloat(2000, allow_none=False).tag(sync=True)
```

type

```
Unicode("OrthographicCamera", allow_none=False).tag(sync=True)
```

bottom = CFloat(0)

a float

far = CFloat(2000)

a float

left = CFloat(0)

a float

near = CFloat(0.1)

a float

right = CFloat(0)

a float

top = CFloat(0)

a float

type = Unicode('OrthographicCamera')

a unicode string

zoom = CFloat(1)

a float

PerspectiveCamera

class pythreejs.**PerspectiveCamera** (*fov=50, aspect=1, near=0.1, far=2000*)
PerspectiveCamera

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/PerspectiveCamera>

Inherits *Camera*.

Three.js docs: <https://threejs.org/docs/#api/cameras/PerspectiveCamera>

fov

```
CFloat(50, allow_none=False).tag(sync=True)
```

zoom

```
CFloat(1, allow_none=False).tag(sync=True)
```

near

```
CFloat(0.1, allow_none=False).tag(sync=True)
```

far

```
CFloat(2000, allow_none=False).tag(sync=True)
```

focus

```
CFloat(10, allow_none=False).tag(sync=True)
```

aspect

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("PerspectiveCamera", allow_none=False).tag(sync=True)
```

aspect = CFloat(1)
a float

far = CFloat(2000)
a float

focus = CFloat(10)
a float

fov = CFloat(50)
a float

near = CFloat(0.1)
a float


```

type = Unicode('PerspectiveCamera')
    a unicode string

zoom = CFloat(1)
    a float

```

StereoCamera

```

class pythreejs.StereoCamera
    StereoCamera

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/cameras/StereoCamera>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/cameras/StereoCamera>

aspect

```
CFloat(1, allow_none=False).tag(sync=True)
```

eyeSep

```
CFloat(0.064, allow_none=False).tag(sync=True)
```

cameraL

```
Instance(PerspectiveCamera, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

cameraR

```
Instance(PerspectiveCamera, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

```

aspect = CFloat(1)
    a float

```

```

cameraL = Instance()
    a PerspectiveCamera or None

```

```

cameraR = Instance()
    a PerspectiveCamera or None

```

```

eyeSep = CFloat(0.064)
    a float

```

2.5.5 controls

Controls

```

class pythreejs.Controls
    Controls

```

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/controls/Controls>

controlling

```
Instance(Object3D, allow_none=False).tag(sync=True, **widget_serialization)
```

```
controlling = Instance()  
    an Object3D
```

FlyControls

```
class pythreejs.FlyControls (controlling=None)  
    FlyControls
```

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Controls*.

Three.js docs: <https://threejs.org/docs/#api/controls/FlyControls>

moveVector

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

rotationVector

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

movementSpeed

```
CFloat(1, allow_none=False).tag(sync=True)
```

rollSpeed

```
CFloat(0.05, allow_none=False).tag(sync=True)
```

syncRate

```
CFloat(1, allow_none=False).tag(sync=True)
```

```
moveVector = Vector3((0, 0, 0))  
    a tuple of any type
```

```
movementSpeed = CFloat(1)  
    a float
```

```
rollSpeed = CFloat(0.05)  
    a float
```

```
rotationVector = Vector3((0, 0, 0))  
    a tuple of any type
```

```
syncRate = CFloat(1)  
    a float
```

OrbitControls

class `pythreejs.OrbitControls` (*controlling=None*)
This widget has some manual overrides on the Python side.

Inherits `Controls`.

Three.js docs: <https://threejs.org/docs/#api/controls/OrbitControls>

autoRotate

```
Bool(False, allow_none=False).tag(sync=True)
```

autoRotateSpeed

```
CFloat(2, allow_none=False).tag(sync=True)
```

dampingFactor

```
CFloat(0.25, allow_none=False).tag(sync=True)
```

enabled

```
Bool(True, allow_none=False).tag(sync=True)
```

enableDamping

```
Bool(False, allow_none=False).tag(sync=True)
```

enableKeys

```
Bool(True, allow_none=False).tag(sync=True)
```

enablePan

```
Bool(True, allow_none=False).tag(sync=True)
```

enableRotate

```
Bool(True, allow_none=False).tag(sync=True)
```

enableZoom

```
Bool(True, allow_none=False).tag(sync=True)
```

keyPanSpeed

```
CFloat(7, allow_none=False).tag(sync=True)
```

maxAzimuthAngle

```
CFloat(float('inf'), allow_none=False).tag(sync=True)
```

maxDistance

```
CFloat(float('inf'), allow_none=False).tag(sync=True)
```

maxPolarAngle

```
CFloat(3.141592653589793, allow_none=False).tag(sync=True)
```

maxZoom

```
CFloat(float('inf'), allow_none=False).tag(sync=True)
```

minAzimuthAngle

```
CFloat(-float('inf'), allow_none=False).tag(sync=True)
```

minDistance

```
CFloat(0, allow_none=False).tag(sync=True)
```

minPolarAngle

```
CFloat(0, allow_none=False).tag(sync=True)
```

minZoom

```
CFloat(0, allow_none=False).tag(sync=True)
```

panSpeed

```
CFloat(1, allow_none=False).tag(sync=True)
```

rotateSpeed

```
CFloat(1, allow_none=False).tag(sync=True)
```

screenSpacePanning

```
Bool(True, allow_none=False).tag(sync=True)
```

zoomSpeed

```
CFloat(1, allow_none=False).tag(sync=True)
```

target

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

reset()

Reset the controlled object to its initial state.

Picker

class pythreejs.**Picker** (*controlling=None*)

Picker

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Controls*.

Three.js docs: <https://threejs.org/docs/#api/controls/Picker>

event

The DOM MouseEvent type to trigger the pick

```
Unicode("click", allow_none=False).tag(sync=True)
```

all

Wether to send info on all object intersections beneath the picked point, or only the first one. See *picked*.

```
Bool(False, allow_none=False).tag(sync=True)
```

distance

The distance from the camera of the picked point (null if no object picked)

```
CFloat(None, allow_none=True).tag(sync=True)
```

point

The coordinates of the picked point (all zero if no object picked)

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

face

The vertex indices of the picked face (all zero if no face picked)

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

faceNormal

The normal vector of the picked face (all zero if no face picked)

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

faceVertices

The three vertices that make up the picked face, as vectors (empty if no face picked)

```
List(trait=List()).tag(sync=True)
```

faceIndex

The index of the face picked (null if no face picked)

```
CInt(None, allow_none=True).tag(sync=True)
```

modifiers

The keyboard modifiers held at the pick event in the following order: [SHIFT, CTRL, ALT, META]

```
List().tag(sync=True)
```

object

The picked object (null if no object picked)

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

picked

The other fields on the picker will always be for the first object intersection. If `all` is set true, this field will be an array containing the same information for all intersections.

```
List().tag(sync=True)
```

uv

The UV coordinate picked (all zero if invalid pick)

```
Vector2(default_value=[0, 0]).tag(sync=True)
```

indices

The vertex indices of the picked face (empty if no face picked)

```
List().tag(sync=True)
```

all = Bool(False)

a boolean

distance = CFloat(None)

a float

event = Unicode('click')

a unicode string

face = Vector3((0, 0, 0))

a tuple of any type

faceIndex = CInt(None)

an int

faceNormal = Vector3((0, 0, 0))

a tuple of any type

faceVertices = `List()`
a list with values that are: a list

indices = `List()`
a list of any type

modifiers = `List()`
a list of any type

object = `Instance()`
an `Object3D` or `None`

picked = `List()`
a list of any type

point = `Vector3((0, 0, 0))`
a tuple of any type

uv = `Vector2((0, 0))`
a tuple of any type

TrackballControls

class `pythreejs.TrackballControls` (*controlling=None*)
`TrackballControls`

Autogenerated by `generate-wrappers.js` This class is a custom class for `pythreejs`, with no direct corresponding class in `three.js`.

Inherits `Controls`.

Three.js docs: <https://threejs.org/docs/#api/controls/TrackballControls>

enabled

```
Bool(True, allow_none=False).tag(sync=True)
```

minDistance

```
CFloat(0, allow_none=False).tag(sync=True)
```

maxDistance

```
CFloat(float('inf'), allow_none=False).tag(sync=True)
```

rotateSpeed

```
CFloat(1, allow_none=False).tag(sync=True)
```

zoomSpeed

```
CFloat(1.2, allow_none=False).tag(sync=True)
```

panSpeed

```
CFloat(0.3, allow_none=False).tag(sync=True)
```

staticMoving

```
Bool(False, allow_none=False).tag(sync=True)
```

dynamicDampingFactor

```
CFloat(0.2, allow_none=False).tag(sync=True)
```

noRotate

```
Bool(False, allow_none=False).tag(sync=True)
```

noZoom

```
Bool(False, allow_none=False).tag(sync=True)
```

noPan

```
Bool(False, allow_none=False).tag(sync=True)
```

noRoll

```
Bool(False, allow_none=False).tag(sync=True)
```

target

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

dynamicDampingFactor = CFloat(0.2)

a float

enabled = Bool(True)

a boolean

maxDistance = CFloat(inf)

a float

minDistance = CFloat(0)

a float

noPan = Bool(False)

a boolean

noRoll = Bool(False)

a boolean

noRotate = Bool(False)

a boolean


```

noZoom = Bool(False)
    a boolean

panSpeed = CFloat(0.3)
    a float

rotateSpeed = CFloat(1)
    a float

staticMoving = Bool(False)
    a boolean

target = Vector3((0, 0, 0))
    a tuple of any type

zoomSpeed = CFloat(1.2)
    a float

```

2.5.6 core

BaseBufferGeometry

```

class pythreejs.BaseBufferGeometry
    BaseBufferGeometry

```

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/BaseBufferGeometry>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

type

```
Unicode("BaseBufferGeometry", allow_none=False).tag(sync=True)
```

```

name = Unicode('')
    a unicode string

```

```

type = Unicode('BaseBufferGeometry')
    a unicode string

```

BaseGeometry

```

class pythreejs.BaseGeometry
    BaseGeometry

```

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/BaseGeometry>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

type

```
Unicode("BaseGeometry", allow_none=False).tag(sync=True)
```

name = Unicode('')
a unicode string

type = Unicode('BaseGeometry')
a unicode string

BufferAttribute

class pythreejs.**BufferAttribute** (*array=None, normalized=False*)

This widget has some manual overrides on the Python side.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/BufferAttribute>

array

```
WebGLDataUnion().tag(sync=True)
```

dynamic

```
Bool(False, allow_none=False).tag(sync=True)
```

needsUpdate

```
Bool(False, allow_none=False).tag(sync=True)
```

normalized

```
Bool(False, allow_none=False).tag(sync=True)
```

version

```
CInt(-1, allow_none=False).tag(sync=True)
```

BufferGeometry

class pythreejs.**BufferGeometry**

This widget has some manual overrides on the Python side.

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/core/BufferGeometry>

index

```
Union([
    Instance(BufferAttribute, allow_none=True),
    Instance(InterleavedBufferAttribute, allow_none=True)
]).tag(sync=True, **widget_serialization)
```

attributes

```
Dict(Union([
    Instance(BufferAttribute),
    Instance(InterleavedBufferAttribute)
])).tag(sync=True, **widget_serialization)
```

morphAttributes

```
Dict(TypedTuple(Union([
    Instance(BufferAttribute),
    Instance(InterleavedBufferAttribute)
]))).tag(sync=True, **widget_serialization)
```

userData

```
Dict(default_value={}, allow_none=False).tag(sync=True)
```

MaxIndex

```
CInt(65535, allow_none=False).tag(sync=True)
```

_ref_geometry

```
Union([
    Instance(BaseGeometry, allow_none=True),
    Instance(BaseBufferGeometry, allow_none=True)
]).tag(sync=True, **widget_serialization)
```

_store_ref

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("BufferGeometry", allow_none=False).tag(sync=True)
```

classmethod from_geometry (geometry, store_ref=False)

Creates a PlainBufferGeometry of another geometry.

store_ref determines if the reference is stored after initialization. If it is, it will be used for future embedding.

validate

Clock

class pythreejs.**Clock**
Clock

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/Clock>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/Clock>

DirectGeometry

class pythreejs.**DirectGeometry**
DirectGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/DirectGeometry>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/DirectGeometry>

EventDispatcher

class pythreejs.**EventDispatcher**
EventDispatcher

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/EventDispatcher>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/EventDispatcher>

Geometry

class pythreejs.**Geometry**
This widget has some manual overrides on the Python side.

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/core/Geometry>

vertices

```
List(trait=List()).tag(sync=True)
```

colors

```
List(trait=Unicode(), default_value=["#ffffff"]).tag(sync=True)
```

faces

```
TypedTuple(trait=Face3()).tag(sync=True)
```

faceVertexUvs

```
List().tag(sync=True)
```

lineDistances

```
List().tag(sync=True)
```

morphTargets

```
List().tag(sync=True)
```

morphNormals

```
List().tag(sync=True)
```

skinWeights

```
List(trait=List()).tag(sync=True)
```

skinIndices

```
List(trait=List()).tag(sync=True)
```

_ref_geometry

```
Instance(BaseGeometry, allow_none=True).tag(sync=True, **widget_serialization)
```

_store_ref

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("Geometry", allow_none=False).tag(sync=True)
```

classmethod from_geometry (*geometry*, *store_ref=False*)

Creates a PlainGeometry of another geometry.

store_ref determines if the reference is stored after initialization. If it is, it will be used for future embedding.

NOTE: The PlainGeometry will copy the arrays from the source geometry. To avoid this, use PlainBufferGeometry.

InstancedBufferAttribute

class pythreejs.**InstancedBufferAttribute** (*array=None, meshPerAttribute=1*)
 InstancedBufferAttribute

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/InstancedBufferAttribute>

Inherits *BufferAttribute*.

Three.js docs: <https://threejs.org/docs/#api/core/InstancedBufferAttribute>

meshPerAttribute

```
CInt(1, allow_none=False).tag(sync=True)
```

meshPerAttribute = CInt(1)
 an int

InstancedBufferGeometry

class pythreejs.**InstancedBufferGeometry**
 InstancedBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/InstancedBufferGeometry>

Inherits *BufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/core/InstancedBufferGeometry>

maxInstancedCount

```
CInt(None, allow_none=True).tag(sync=True)
```

type

```
Unicode("InstancedBufferGeometry", allow_none=False).tag(sync=True)
```

maxInstancedCount = CInt(None)
 an int

type = Unicode('InstancedBufferGeometry')
 a unicode string

InstancedInterleavedBuffer

class pythreejs.**InstancedInterleavedBuffer** (*array=None, meshPerAttribute=1*)
 InstancedInterleavedBuffer

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/InstancedInterleavedBuffer>

Inherits *InterleavedBuffer*.

Three.js docs: <https://threejs.org/docs/#api/core/InstancedInterleavedBuffer>

meshPerAttribute

```
CInt(1, allow_none=False).tag(sync=True)
```

```
meshPerAttribute = CInt(1)
    an int
```

InterleavedBufferAttribute

```
class pythreejs.InterleavedBufferAttribute (data=None, itemSize=0, offset=0, normalized=False)
```

InterleavedBufferAttribute

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/InterleavedBufferAttribute>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/InterleavedBufferAttribute>

data

```
Instance(InterleavedBuffer, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

itemSize

```
CInt(0, allow_none=False).tag(sync=True)
```

offset

```
CInt(0, allow_none=False).tag(sync=True)
```

normalized

```
Bool(False, allow_none=False).tag(sync=True)
```

```
data = Instance()
    an InterleavedBuffer or None
```

```
itemSize = CInt(0)
    an int
```

```
normalized = Bool(False)
    a boolean
```

```
offset = CInt(0)
    an int
```

InterleavedBuffer

```
class pythreejs.InterleavedBuffer (array=None)
```

InterleavedBuffer

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/InterleavedBuffer>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/InterleavedBuffer>

array

```
WebGLDataUnion().tag(sync=True)
```

dynamic

```
Bool(False, allow_none=False).tag(sync=True)
```

version

```
CInt(0, allow_none=False).tag(sync=True)
```

needsUpdate

```
Bool(False, allow_none=False).tag(sync=True)
```

array = `WebGLDataUnion()`
a numpy array or a `NDArrayBase`

dynamic = `Bool(False)`
a boolean

needsUpdate = `Bool(False)`
a boolean

version = `CInt(0)`
an int

Layers

class `pythreejs.Layers`

Layers

Autogenerated by `generate-wrappers.js` See <https://threejs.org/docs/#api/core/Layers>

Inherits `ThreeWidget`.

Three.js docs: <https://threejs.org/docs/#api/core/Layers>

Object3D

class `pythreejs.Object3D`

This widget has some manual overrides on the Python side.

Inherits `ThreeWidget`.

Three.js docs: <https://threejs.org/docs/#api/core/Object3D>

name

```
Unicode("", allow_none=False).tag(sync=True)
```


type

```
Unicode("Object3D", allow_none=False).tag(sync=True)
```

children

```
Tuple().tag(sync=True, **widget_serialization)
```

up

```
Vector3(default_value=[0, 1, 0]).tag(sync=True)
```

position

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

rotation

```
Euler(default_value=[0, 0, 0, "XYZ"]).tag(sync=True)
```

quaternion

```
Vector4(default_value=[0, 0, 0, 1]).tag(sync=True)
```

scale

```
Vector3(default_value=[1, 1, 1]).tag(sync=True)
```

modelViewMatrix

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).  
↪tag(sync=True)
```

normalMatrix

```
Matrix3(default_value=[1, 0, 0, 0, 1, 0, 0, 0, 1]).tag(sync=True)
```

matrix

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).  
↪tag(sync=True)
```

matrixWorld

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).  
↪tag(sync=True)
```

matrixAutoUpdate

```
Bool(True, allow_none=False).tag(sync=True)
```

matrixWorldNeedsUpdate

```
Bool(False, allow_none=False).tag(sync=True)
```

visible

```
Bool(True, allow_none=False).tag(sync=True)
```

castShadow

```
Bool(False, allow_none=False).tag(sync=True)
```

receiveShadow

```
Bool(False, allow_none=False).tag(sync=True)
```

frustumCulled

```
Bool(True, allow_none=False).tag(sync=True)
```

renderOrder

```
CInt(0, allow_none=False).tag(sync=True)
```

add (*children*)

lookAt (*vector*)

remove (*children*)

rotateX (*rad*)

rotateY (*rad*)

rotateZ (*rad*)

setRotationFromMatrix (*m*)

m is a 3 by 3 matrix, as a list of rows. The columns of this matrix are the vectors x, y, and z

Raycaster

```
class pythreejs.Raycaster (origin=[0, 0, 0], direction=[0, 0, 0], near=0, far=1000000, )  
    Raycaster
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/core/Raycaster>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/core/Raycaster>

origin

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

direction

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

near

```
CFloat(0, allow_none=False).tag(sync=True)
```

far

```
CFloat(1000000, allow_none=False).tag(sync=True)
```

ray

```
Instance(Ray, allow_none=True).tag(sync=True, **widget_serialization)
```

linePrecision

```
CFloat(1, allow_none=False).tag(sync=True)
```

direction = Vector3((0, 0, 0))
a tuple of any type

far = CFloat(1000000)
a float

linePrecision = CFloat(1)
a float

near = CFloat(0)
a float

origin = Vector3((0, 0, 0))
a tuple of any type

ray = Instance()
a Ray or None

2.5.7 extras

core

CurvePath

```
class pythreejs.CurvePath
    CurvePath
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/CurvePath>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/CurvePath>

Curve

class pythreejs.**Curve**
Curve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/Curve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/Curve>

Font

class pythreejs.**Font**
Font

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/Font>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/Font>

Path

class pythreejs.**Path**
Path

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/Path>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/Path>

ShapePath

class pythreejs.**ShapePath**
ShapePath

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/ShapePath>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/ShapePath>

Shape

class pythreejs.**Shape**
Shape

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/core/Shape>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/core/Shape>

curves

ArcCurve

class pythreejs.**ArcCurve**

ArcCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/ArcCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/ArcCurve>

CatmullRomCurve3

class pythreejs.**CatmullRomCurve3**

CatmullRomCurve3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/CatmullRomCurve3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/CatmullRomCurve3>

CubicBezierCurve3

class pythreejs.**CubicBezierCurve3**

CubicBezierCurve3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/CubicBezierCurve3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/CubicBezierCurve3>

CubicBezierCurve

class pythreejs.**CubicBezierCurve**

CubicBezierCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/CubicBezierCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/CubicBezierCurve>

EllipseCurve

class pythreejs.**EllipseCurve**

EllipseCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/EllipseCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/EllipseCurve>

LineCurve3

class pythreejs.**LineCurve3**
LineCurve3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/LineCurve3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/LineCurve3>

LineCurve

class pythreejs.**LineCurve**
LineCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/LineCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/LineCurve>

QuadraticBezierCurve3

class pythreejs.**QuadraticBezierCurve3**
QuadraticBezierCurve3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/QuadraticBezierCurve3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/QuadraticBezierCurve3>

QuadraticBezierCurve

class pythreejs.**QuadraticBezierCurve**
QuadraticBezierCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/QuadraticBezierCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/QuadraticBezierCurve>

SplineCurve

class pythreejs.**SplineCurve**
SplineCurve

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/curves/SplineCurve>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/curves/SplineCurve>

objects

ImmediateRenderObject

class pythreejs.**ImmediateRenderObject**

ImmediateRenderObject

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/extras/objects/ImmediateRenderObject>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/extras/objects/ImmediateRenderObject>

2.5.8 geometries

BoxBufferGeometry

class pythreejs.**BoxBufferGeometry** (*width=1, height=1, depth=1, widthSegments=1, heightSegments=1, depthSegments=1*)

BoxBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/BoxGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/BoxGeometry>

width

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

depth

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

depthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("BoxBufferGeometry", allow_none=False).tag(sync=True)
```

depth = CFloat(1)
a float

depthSegments = CInt(1)
an int

height = CFloat(1)
a float

heightSegments = CInt(1)
an int

type = Unicode('BoxBufferGeometry')
a unicode string

width = CFloat(1)
a float

widthSegments = CInt(1)
an int

BoxGeometry

class pythreejs.**BoxGeometry** (*width=1, height=1, depth=1, widthSegments=1, heightSegments=1, depthSegments=1*)

BoxGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/BoxGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/BoxGeometry>

width

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

depth

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments


```
CInt(1, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

depthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("BoxGeometry", allow_none=False).tag(sync=True)
```

depth = CFloat(1)

a float

depthSegments = CInt(1)

an int

height = CFloat(1)

a float

heightSegments = CInt(1)

an int

type = Unicode('BoxGeometry')

a unicode string

width = CFloat(1)

a float

widthSegments = CInt(1)

an int

BoxLineGeometry

class pythreejs.BoxLineGeometry(*width=1, height=1, depth=1, widthSegments=1, heightSegments=1, depthSegments=1*)

BoxLineGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/BoxGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/BoxGeometry>

width

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

depth

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

depthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("BoxLineGeometry", allow_none=False).tag(sync=True)
```

depth = CFloat(1)
a float

depthSegments = CInt(1)
an int

height = CFloat(1)
a float

heightSegments = CInt(1)
an int

type = Unicode('BoxLineGeometry')
a unicode string

width = CFloat(1)
a float

widthSegments = CInt(1)
an int

CircleBufferGeometry

```
class pythreejs.CircleBufferGeometry(radius=1, segments=8, thetaStart=0, thetaLength=6.283185307179586)
```

CircleBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/CircleGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/CircleGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

segments

```
CInt(8, allow_none=False, min=3).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("CircleBufferGeometry", allow_none=False).tag(sync=True)
```

radius = CFloat(1)

a float

segments = CInt(8)

an int

thetaLength = CFloat(6.283185307179586)

a float

thetaStart = CFloat(0)

a float

type = Unicode('CircleBufferGeometry')

a unicode string

CircleGeometry

```
class pythreejs.CircleGeometry(radius=1, segments=8, thetaStart=0, thetaLength=6.283185307179586)
```

CircleGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/CircleGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/CircleGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

segments

```
CInt(8, allow_none=False, min=3).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("CircleGeometry", allow_none=False).tag(sync=True)
```

radius = CFloat(1)
a float

segments = CInt(8)
an int

thetaLength = CFloat(6.283185307179586)
a float

thetaStart = CFloat(0)
a float

type = Unicode('CircleGeometry')
a unicode string

ConeGeometry

```
class pythreejs.ConeGeometry(radius=20, height=100, radialSegments=8, height-
                             Segments=1, openEnded=False, thetaStart=0, thetaL-
                             ength=6.283185307179586)
```

ConeGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/ConeGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/ConeGeometry>

radius

```
CFloat(20, allow_none=False).tag(sync=True)
```

height

```
CFloat(100, allow_none=False).tag(sync=True)
```

radialSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

openEnded

```
Bool(False, allow_none=False).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("ConeGeometry", allow_none=False).tag(sync=True)
```

height = CFloat(100)
a float

heightSegments = CInt(1)
an int

openEnded = Bool(False)
a boolean

radialSegments = CInt(8)
an int

radius = CFloat(20)
a float

thetaLength = CFloat(6.283185307179586)
a float

thetaStart = CFloat(0)
a float

type = Unicode('ConeGeometry')
a unicode string

CylinderBufferGeometry

```
class pythreejs.CylinderBufferGeometry(radiusTop=1, radiusBottom=1, height=1,
radiusSegments=8, heightSegments=1,
openEnded=False, thetaStart=0, thetaLength=6.283185307179586)
```

CylinderBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/CylinderGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/CylinderGeometry>

radiusTop

```
CFloat(1, allow_none=False).tag(sync=True)
```

radiusBottom

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

radiusSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

openEnded

```
Bool(False, allow_none=False).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("CylinderBufferGeometry", allow_none=False).tag(sync=True)
```

height = CFloat(1)
a float

heightSegments = CInt(1)
an int

openEnded = Bool(False)
a boolean

```

radiusBottom = CFloat(1)
    a float
radiusSegments = CInt(8)
    an int
radiusTop = CFloat(1)
    a float
thetaLength = CFloat(6.283185307179586)
    a float
thetaStart = CFloat(0)
    a float
type = Unicode('CylinderBufferGeometry')
    a unicode string

```

CylinderGeometry

```

class pythreejs.CylinderGeometry (radiusTop=1, radiusBottom=1, height=1, radiusSegments=8,
    heightSegments=1, openEnded=False, thetaStart=0, thetaLength=6.283185307179586)

```

CylinderGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/CylinderGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/CylinderGeometry>

radiusTop

```
CFloat(1, allow_none=False).tag(sync=True)
```

radiusBottom

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

radiusSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

openEnded

```
Bool(False, allow_none=False).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("CylinderGeometry", allow_none=False).tag(sync=True)
```

height = CFloat(1)

a float

heightSegments = CInt(1)

an int

openEnded = Bool(False)

a boolean

radiusBottom = CFloat(1)

a float

radiusSegments = CInt(8)

an int

radiusTop = CFloat(1)

a float

thetaLength = CFloat(6.283185307179586)

a float

thetaStart = CFloat(0)

a float

type = Unicode('CylinderGeometry')

a unicode string

DodecahedronGeometry

class pythreejs.DodecahedronGeometry (*radius=1, detail=0*)

DodecahedronGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/DodecahedronGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/DodecahedronGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```


detail

```
CInt(0, allow_none=False).tag(sync=True)
```

type

```
Unicode("DodecahedronGeometry", allow_none=False).tag(sync=True)
```

detail = **CInt**(0)

an int

radius = **CFloat**(1)

a float

type = **Unicode**('DodecahedronGeometry')

a unicode string

EdgesGeometry

class pythreejs.**EdgesGeometry**

EdgesGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/EdgesGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/EdgesGeometry>

type

```
Unicode("EdgesGeometry", allow_none=False).tag(sync=True)
```

type = **Unicode**('EdgesGeometry')

a unicode string

ExtrudeGeometry

class pythreejs.**ExtrudeGeometry**

ExtrudeGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/ExtrudeGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/ExtrudeGeometry>

type

```
Unicode("ExtrudeGeometry", allow_none=False).tag(sync=True)
```

type = **Unicode**('ExtrudeGeometry')

a unicode string

IcosahedronGeometry

class pythreejs.IcosahedronGeometry (*radius=1, detail=0*)
IcosahedronGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/IcosahedronGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/IcosahedronGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

detail

```
CInt(0, allow_none=False).tag(sync=True)
```

type

```
Unicode("IcosahedronGeometry", allow_none=False).tag(sync=True)
```

detail = CInt(0)
an int

radius = CFloat(1)
a float

type = Unicode('IcosahedronGeometry')
a unicode string

LatheBufferGeometry

class pythreejs.LatheBufferGeometry (*points=[], segments=12, phiStart=0, phiLength=6.283185307179586*)
LatheBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/LatheGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/LatheGeometry>

points

```
List(trait=List()).tag(sync=True)
```

segments

```
CInt(12, allow_none=False).tag(sync=True)
```

phiStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

phiLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("LatheBufferGeometry", allow_none=False).tag(sync=True)
```

phiLength = CFloat(6.283185307179586)

a float

phiStart = CFloat(0)

a float

points = List()

a list with values that are: a list

segments = CInt(12)

an int

type = Unicode('LatheBufferGeometry')

a unicode string

LatheGeometry

```
class pythreejs.LatheGeometry (points=[], segments=12, phiStart=0,
                               phiLength=6.283185307179586)
```

LatheGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/LatheGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/LatheGeometry>

points

```
List(trait=List()).tag(sync=True)
```

segments

```
CInt(12, allow_none=False).tag(sync=True)
```

phiStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

phiLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("LatheGeometry", allow_none=False).tag(sync=True)
```

phiLength = CFloat(6.283185307179586)
a float

phiStart = CFloat(0)
a float

points = List()
a list with values that are: a list

segments = CInt(12)
an int

type = Unicode('LatheGeometry')
a unicode string

LineGeometry

class pythreejs.LineGeometry
LineGeometry

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *LineSegmentsGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/LineGeometry>

positions

```
WebGLDataUnion(dtype="float32", shape_constraint=shape_constraints(None, 3)).  
↪tag(sync=True)
```

colors

```
WebGLDataUnion(None, dtype="float32", shape_constraint=shape_constraints(None,  
↪ 3), allow_none=True).tag(sync=True)
```

type

```
Unicode("LineGeometry", allow_none=False).tag(sync=True)
```

colors = WebGLDataUnion(None)
a numpy array or a NDArrayBase

positions = WebGLDataUnion()
a numpy array or a NDArrayBase

type = Unicode('LineGeometry')
a unicode string

LineSegmentsGeometry

class pythreejs.**LineSegmentsGeometry**
LineSegmentsGeometry

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/LineSegmentsGeometry>

positions

```
WebGLDataUnion(dtype="float32", shape_constraint=shape_constraints(None, 2, ↵
↵3)).tag(sync=True)
```

colors

```
WebGLDataUnion(None, dtype="float32", shape_constraint=shape_constraints(None,
↵ 2, 3), allow_none=True).tag(sync=True)
```

type

```
Unicode("LineSegmentsGeometry", allow_none=False).tag(sync=True)
```

colors = **WebGLDataUnion(None)**
a numpy array or a NDArrayBase

positions = **WebGLDataUnion()**
a numpy array or a NDArrayBase

type = **Unicode('LineSegmentsGeometry')**
a unicode string

OctahedronGeometry

class pythreejs.**OctahedronGeometry**(radius=1, detail=0)
OctahedronGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/OctahedronGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/OctahedronGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

detail

```
CInt(0, allow_none=False).tag(sync=True)
```

type

```
Unicode("OctahedronGeometry", allow_none=False).tag(sync=True)
```

detail = CInt(0)
an int

radius = CFloat(1)
a float

type = Unicode('OctahedronGeometry')
a unicode string

ParametricGeometry

class pythreejs.**ParametricGeometry** (*func*, *slices=3*, *stacks=3*)
ParametricGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/ParametricGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/ParametricGeometry>

func

```
Unicode('function(u, v, vec) { }').tag(sync=True)
```

slices

```
CInt(3, allow_none=False).tag(sync=True)
```

stacks

```
CInt(3, allow_none=False).tag(sync=True)
```

type

```
Unicode("ParametricGeometry", allow_none=False).tag(sync=True)
```

func = Unicode('function(u, v, vec) { }')
a unicode string

slices = CInt(3)
an int

stacks = CInt(3)
an int

type = Unicode('ParametricGeometry')
a unicode string

PlaneBufferGeometry

```
class pythreejs.PlaneBufferGeometry (width=1, height=1, widthSegments=1, heightSegments=1)
```

PlaneBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/PlaneGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/PlaneGeometry>

width

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("PlaneBufferGeometry", allow_none=False).tag(sync=True)
```

height = CFloat(1)

a float

heightSegments = CInt(1)

an int

type = Unicode('PlaneBufferGeometry')

a unicode string

width = CFloat(1)

a float

widthSegments = CInt(1)

an int

PlaneGeometry

```
class pythreejs.PlaneGeometry (width=1, height=1, widthSegments=1, heightSegments=1)
```

PlaneGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/PlaneGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/PlaneGeometry>

width

```
CFloat(1, allow_none=False).tag(sync=True)
```

height

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("PlaneGeometry", allow_none=False).tag(sync=True)
```

height = CFloat(1)

a float

heightSegments = CInt(1)

an int

type = Unicode('PlaneGeometry')

a unicode string

width = CFloat(1)

a float

widthSegments = CInt(1)

an int

PolyhedronGeometry

class pythreejs.PolyhedronGeometry (vertices=[], faces=[], radius=1, detail=0)

PolyhedronGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/PolyhedronGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/PolyhedronGeometry>

vertices

```
List().tag(sync=True)
```

indices


```
List().tag(sync=True)
```

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

detail

```
CFloat(0, allow_none=False).tag(sync=True)
```

faces

```
List().tag(sync=True)
```

type

```
Unicode("PolyhedronGeometry", allow_none=False).tag(sync=True)
```

detail = CFloat(0)
a float

faces = List()
a list of any type

indices = List()
a list of any type

radius = CFloat(1)
a float

type = Unicode('PolyhedronGeometry')
a unicode string

vertices = List()
a list of any type

RingBufferGeometry

```
class pythreejs.RingBufferGeometry (innerRadius=0.5, outerRadius=1, thetaSegments=8, phiSegments=8, thetaStart=0, thetaLength=6.283185307179586)
```

RingBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/RingGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/RingGeometry>

innerRadius

```
CFloat(0.5, allow_none=False).tag(sync=True)
```

outerRadius

```
CFloat(1, allow_none=False).tag(sync=True)
```

thetaSegments

```
CInt(8, allow_none=False, min=3).tag(sync=True)
```

phiSegments

```
CInt(8, allow_none=False, min=1).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("RingBufferGeometry", allow_none=False).tag(sync=True)
```

innerRadius = CFloat(0.5)

a float

outerRadius = CFloat(1)

a float

phiSegments = CInt(8)

an int

thetaLength = CFloat(6.283185307179586)

a float

thetaSegments = CInt(8)

an int

thetaStart = CFloat(0)

a float

type = Unicode('RingBufferGeometry')

a unicode string

RingGeometry

```
class pythreejs.RingGeometry(innerRadius=0.5, outerRadius=1, thetaSegments=8, phiSegments=8, thetaStart=0, thetaLength=6.283185307179586)
```

RingGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/RingGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/RingGeometry>

innerRadius

```
CFloat(0.5, allow_none=False).tag(sync=True)
```

outerRadius

```
CFloat(1, allow_none=False).tag(sync=True)
```

thetaSegments

```
CInt(8, allow_none=False, min=3).tag(sync=True)
```

phiSegments

```
CInt(8, allow_none=False, min=1).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("RingGeometry", allow_none=False).tag(sync=True)
```

innerRadius = **CFloat(0.5)**
a float

outerRadius = **CFloat(1)**
a float

phiSegments = **CInt(8)**
an int

thetaLength = **CFloat(6.283185307179586)**
a float

thetaSegments = **CInt(8)**
an int

thetaStart = **CFloat(0)**
a float

type = **Unicode('RingGeometry')**
a unicode string

ShapeGeometry

class pythreejs.**ShapeGeometry** (*shapes=[]*)
 ShapeGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/ShapeGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/ShapeGeometry>

shapes

```
Tuple().tag(sync=True, **widget_serialization)
```

curveSegments

```
CInt(12, allow_none=False).tag(sync=True)
```

material

```
CInt(0, allow_none=False).tag(sync=True)
```

type

```
Unicode("ShapeGeometry", allow_none=False).tag(sync=True)
```

curveSegments = CInt(12)
 an int

material = CInt(0)
 an int

shapes = Tuple()
 a tuple of any type

type = Unicode('ShapeGeometry')
 a unicode string

SphereBufferGeometry

class pythreejs.**SphereBufferGeometry** (*radius=1, widthSegments=8, heightSegments=6, phiStart=0, phiLength=6.283185307179586, thetaStart=0, thetaLength=3.141592653589793*)

SphereBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/SphereGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/SphereGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(6, allow_none=False).tag(sync=True)
```

phiStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

phiLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(3.141592653589793, allow_none=False).tag(sync=True)
```

type

```
Unicode("SphereBufferGeometry", allow_none=False).tag(sync=True)
```

```
heightSegments = CInt(6)
```

```
an int
```

```
phiLength = CFloat(6.283185307179586)
```

```
a float
```

```
phiStart = CFloat(0)
```

```
a float
```

```
radius = CFloat(1)
```

```
a float
```

```
thetaLength = CFloat(3.141592653589793)
```

```
a float
```

```
thetaStart = CFloat(0)
```

```
a float
```

```
type = Unicode('SphereBufferGeometry')
```

```
a unicode string
```

widthSegments = CInt(8)
 an int

SphereGeometry

class pythreejs.**SphereGeometry** (*radius=1, widthSegments=8, heightSegments=6, phiStart=0, phiLength=6.283185307179586, thetaStart=0, thetaLength=3.141592653589793*)

SphereGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/SphereGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/SphereGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

widthSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

heightSegments

```
CInt(6, allow_none=False).tag(sync=True)
```

phiStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

phiLength

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

thetaStart

```
CFloat(0, allow_none=False).tag(sync=True)
```

thetaLength

```
CFloat(3.141592653589793, allow_none=False).tag(sync=True)
```

type

```
Unicode("SphereGeometry", allow_none=False).tag(sync=True)
```

heightSegments = CInt(6)
 an int

```

phiLength = CFloat(6.283185307179586)
    a float
phiStart = CFloat(0)
    a float
radius = CFloat(1)
    a float
thetaLength = CFloat(3.141592653589793)
    a float
thetaStart = CFloat(0)
    a float
type = Unicode('SphereGeometry')
    a unicode string
widthSegments = CInt(8)
    an int

```

TetrahedronGeometry

```

class pythreejs.TetrahedronGeometry (radius=1, detail=0)
    TetrahedronGeometry

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TetrahedronGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TetrahedronGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

detail

```
CInt(0, allow_none=False).tag(sync=True)
```

type

```
Unicode("TetrahedronGeometry", allow_none=False).tag(sync=True)
```

```

detail = CInt(0)
    an int

```

```

radius = CFloat(1)
    a float

```

```

type = Unicode('TetrahedronGeometry')
    a unicode string

```

TextGeometry

```

class pythreejs.TextGeometry
    TextGeometry

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TextGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TextGeometry>

type

```
Unicode("TextGeometry", allow_none=False).tag(sync=True)
```

type = `Unicode('TextGeometry')`
a unicode string

TorusBufferGeometry

class `pythreejs.TorusBufferGeometry` (*radius=1, tube=0.4, radialSegments=8, tubularSegments=6, arc=6.283185307179586*)

TorusBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TorusGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TorusGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

tube

```
CFloat(0.4, allow_none=False).tag(sync=True)
```

radialSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

tubularSegments

```
CInt(6, allow_none=False).tag(sync=True)
```

arc

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("TorusBufferGeometry", allow_none=False).tag(sync=True)
```

arc = `CFloat(6.283185307179586)`
a float


```

radialSegments = CInt(8)
    an int
radius = CFloat(1)
    a float
tube = CFloat(0.4)
    a float
tubularSegments = CInt(6)
    an int
type = Unicode('TorusBufferGeometry')
    a unicode string

```

TorusGeometry

```

class pythreejs.TorusGeometry(radius=1, tube=0.4, radialSegments=8, tubularSegments=6,
                               arc=6.283185307179586)

```

TorusGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TorusGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TorusGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

tube

```
CFloat(0.4, allow_none=False).tag(sync=True)
```

radialSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

tubularSegments

```
CInt(6, allow_none=False).tag(sync=True)
```

arc

```
CFloat(6.283185307179586, allow_none=False).tag(sync=True)
```

type

```
Unicode("TorusGeometry", allow_none=False).tag(sync=True)
```

```

arc = CFloat(6.283185307179586)
    a float

```

```

radialSegments = CInt(8)
    an int
radius = CFloat(1)
    a float
tube = CFloat(0.4)
    a float
tubularSegments = CInt(6)
    an int
type = Unicode('TorusGeometry')
    a unicode string

```

TorusKnotBufferGeometry

```

class pythreejs.TorusKnotBufferGeometry(radius=1, tube=0.4, tubularSegments=64, radialSegments=8, p=2, q=3)

```

TorusKnotBufferGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TorusKnotGeometry>

Inherits *BaseBufferGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TorusKnotGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

tube

```
CFloat(0.4, allow_none=False).tag(sync=True)
```

tubularSegments

```
CInt(64, allow_none=False).tag(sync=True)
```

radialSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

p

```
CInt(2, allow_none=False).tag(sync=True)
```

q

```
CInt(3, allow_none=False).tag(sync=True)
```

type

```
Unicode("TorusKnotBufferGeometry", allow_none=False).tag(sync=True)
```

```
p = CInt(2)
    an int
q = CInt(3)
    an int
radialSegments = CInt(8)
    an int
radius = CFloat(1)
    a float
tube = CFloat(0.4)
    a float
tubularSegments = CInt(64)
    an int
type = Unicode('TorusKnotBufferGeometry')
    a unicode string
```

TorusKnotGeometry

```
class pythreejs.TorusKnotGeometry(radius=1, tube=0.4, tubularSegments=64, radialSegments=8, p=2, q=3)
```

TorusKnotGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TorusKnotGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TorusKnotGeometry>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

tube

```
CFloat(0.4, allow_none=False).tag(sync=True)
```

tubularSegments

```
CInt(64, allow_none=False).tag(sync=True)
```

radialSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

p

```
CInt(2, allow_none=False).tag(sync=True)
```

q

```
CInt(3, allow_none=False).tag(sync=True)
```

type

```
Unicode("TorusKnotGeometry", allow_none=False).tag(sync=True)
```

p = CInt(2)
an int

q = CInt(3)
an int

radialSegments = CInt(8)
an int

radius = CFloat(1)
a float

tube = CFloat(0.4)
a float

tubularSegments = CInt(64)
an int

type = Unicode('TorusKnotGeometry')
a unicode string

TubeGeometry

class pythreejs.**TubeGeometry** (*path=None, segments=64, radius=1, radiusSegments=8, close=False*)

TubeGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/TubeGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/TubeGeometry>

path

```
Instance(Curve, allow_none=True).tag(sync=True, **widget_serialization)
```

segments

```
CInt(64, allow_none=False).tag(sync=True)
```

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

radiusSegments

```
CInt(8, allow_none=False).tag(sync=True)
```

close

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("TubeGeometry", allow_none=False).tag(sync=True)
```

close = Bool(False)

a boolean

path = Instance()

a Curve or None

radius = CFloat(1)

a float

radiusSegments = CInt(8)

an int

segments = CInt(64)

an int

type = Unicode('TubeGeometry')

a unicode string

WireframeGeometry

class pythreejs.**WireframeGeometry** (*geometry=None*)

WireframeGeometry

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/geometries/WireframeGeometry>

Inherits *BaseGeometry*.

Three.js docs: <https://threejs.org/docs/#api/geometries/WireframeGeometry>

geometry

```
Union([
    Instance(BaseGeometry, allow_none=True),
    Instance(BaseBufferGeometry, allow_none=True)
]).tag(sync=True, **widget_serialization)
```

type

```
Unicode("WireframeGeometry", allow_none=False).tag(sync=True)
```

```
geometry = Union()  
    a BaseGeometry or None or a BaseBufferGeometry or None  
type = Unicode('WireframeGeometry')  
    a unicode string
```

2.5.9 helpers

ArrowHelper

```
class pythreejs.ArrowHelper
```

```
    ArrowHelper
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/ArrowHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/ArrowHelper>

dir

```
Vector3(default_value=[1, 0, 0]).tag(sync=True)
```

origin

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

length

```
CFloat(1, allow_none=False).tag(sync=True)
```

hex

```
CInt(0, allow_none=False).tag(sync=True)
```

headLength

```
CFloat(None, allow_none=True).tag(sync=True)
```

headWidth

```
CFloat(None, allow_none=True).tag(sync=True)
```

type

```
Unicode("ArrowHelper", allow_none=False).tag(sync=True)
```

```
dir = Vector3((0, 0, 0))  
    a tuple of any type
```

```

headLength = CFloat(None)
    a float
headWidth = CFloat(None)
    a float
hex = CInt(0)
    an int
length = CFloat(1)
    a float
origin = Vector3((0, 0, 0))
    a tuple of any type
type = Unicode('ArrowHelper')
    a unicode string

```

AxesHelper

```

class pythreejs.AxesHelper (size=1)
    AxesHelper

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/AxesHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/AxesHelper>

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("AxesHelper", allow_none=False).tag(sync=True)
```

```

size = CFloat(1)
    a float

```

```

type = Unicode('AxesHelper')
    a unicode string

```

Box3Helper

```

class pythreejs.Box3Helper (box=None, color="yellow")
    Box3Helper

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/PlaneHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/PlaneHelper>

box

```
Instance(Box3, allow_none=True).tag(sync=True, **widget_serialization)
```

color

```
Color("yellow", allow_none=True).tag(sync=True)
```

type

```
Unicode("Box3Helper", allow_none=False).tag(sync=True)
```

box = Instance()
a Box3 or None

color = Color('yellow')
a valid HTML color

type = Unicode('Box3Helper')
a unicode string

BoxHelper

class pythreejs.BoxHelper (*object=None, color="#ffffff"*)
BoxHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/BoxHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/BoxHelper>

object

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

color

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("BoxHelper", allow_none=False).tag(sync=True)
```

color = Color('#ffffff')
a valid HTML color

object = Instance()
an Object3D or None

type = Unicode('BoxHelper')
a unicode string

CameraHelper

class pythreejs.CameraHelper (*camera=None*)
CameraHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/CameraHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/CameraHelper>

camera

```
Instance(Camera, allow_none=True).tag(sync=True, **widget_serialization)
```

type

```
Unicode("CameraHelper", allow_none=False).tag(sync=True)
```

camera = Instance()

a Camera or None

type = Unicode('CameraHelper')

a unicode string

DirectionalLightHelper

class pythreejs.DirectionalLightHelper (*light=None, size=1, color="#ffffff"*)
DirectionalLightHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/DirectionalLightHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/DirectionalLightHelper>

light

```
Instance(DirectionalLight, allow_none=True).tag(sync=True, **widget_
↪ serialization)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("DirectionalLightHelper", allow_none=False).tag(sync=True)
```

```
color = Color('#ffffff')
    a valid HTML color

light = Instance()
    a DirectionalLight or None

size = CFloat(1)
    a float

type = Unicode('DirectionalLightHelper')
    a unicode string
```

FaceNormalsHelper

```
class pythreejs.FaceNormalsHelper (object=None, size=1, color="#ffff00", linewidth=1)
    FaceNormalsHelper
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/FaceNormalsHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/FaceNormalsHelper>

object

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffff00", allow_none=False).tag(sync=True)
```

linewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("FaceNormalsHelper", allow_none=False).tag(sync=True)
```

```
color = Color('#ffff00')
    a valid HTML color
```

```
linewidth = CFloat(1)
    a float
```

```
object = Instance()
    an Object3D or None
```

```
size = CFloat(1)
    a float
```

```
type = Unicode('FaceNormalsHelper')
    a unicode string
```

GridHelper

```
class pythreejs.GridHelper (size=10, divisions=10, colorCenterLine="#444444", color-
    Grid="#888888")
```

GridHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/GridHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/GridHelper>

size

```
CFloat(10, allow_none=False).tag(sync=True)
```

divisions

```
CInt(10, allow_none=False).tag(sync=True)
```

colorCenterLine

```
Color("#444444", allow_none=False).tag(sync=True)
```

colorGrid

```
Color("#888888", allow_none=False).tag(sync=True)
```

type

```
Unicode("GridHelper", allow_none=False).tag(sync=True)
```

```
colorCenterLine = Color('#444444')
    a valid HTML color
```

```
colorGrid = Color('#888888')
    a valid HTML color
```

```
divisions = CInt(10)
    an int
```

```
size = CFloat(10)
    a float
```

```
type = Unicode('GridHelper')
    a unicode string
```

HemisphereLightHelper

class pythreejs.**HemisphereLightHelper** (*light=None, size=1, color="#ffffff"*)
 HemisphereLightHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/HemisphereLightHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/HemisphereLightHelper>

light

```
Instance(HemisphereLight, allow_none=True).tag(sync=True, **widget_
↪serialization)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("HemisphereLightHelper", allow_none=False).tag(sync=True)
```

color = Color('#ffffff')
 a valid HTML color

light = Instance()
 a HemisphereLight or None

size = CFloat(1)
 a float

type = Unicode('HemisphereLightHelper')
 a unicode string

PlaneHelper

class pythreejs.**PlaneHelper** (*plane=None, size=1, color="yellow"*)
 PlaneHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/PlaneHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/PlaneHelper>

plane

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("yellow", allow_none=True).tag(sync=True)
```

type

```
Unicode("PlaneHelper", allow_none=False).tag(sync=True)
```

color = Color('yellow')
a valid HTML color

plane = Instance()
a Plane or None

size = CFloat(1)
a float

type = Unicode('PlaneHelper')
a unicode string

PointLightHelper

class pythreejs.**PointLightHelper** (*light=None, sphereSize=1, color="#ffffff"*)
PointLightHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/PointLightHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/PointLightHelper>

light

```
Instance(PointLight, allow_none=True).tag(sync=True, **widget_serialization)
```

sphereSize

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("PointLightHelper", allow_none=False).tag(sync=True)
```

```
color = Color('#ffffff')
    a valid HTML color

light = Instance()
    a PointLight or None

sphereSize = CFloat(1)
    a float

type = Unicode('PointLightHelper')
    a unicode string
```

PolarGridHelper

```
class pythreejs.PolarGridHelper(radius=10, radials=16, circles=8, divisions=64,
                                color1="#444444", color2="#888888")
```

PolarGridHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/PolarGridHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/PolarGridHelper>

radius

```
CInt(10, allow_none=False).tag(sync=True)
```

radials

```
CInt(16, allow_none=False).tag(sync=True)
```

circles

```
CInt(8, allow_none=False).tag(sync=True)
```

divisions

```
CInt(64, allow_none=False).tag(sync=True)
```

color1

```
Color("#444444", allow_none=False).tag(sync=True)
```

color2

```
Color("#888888", allow_none=False).tag(sync=True)
```

type

```
Unicode("PolarGridHelper", allow_none=False).tag(sync=True)
```

```

circles = CInt(8)
    an int

color1 = Color('#444444')
    a valid HTML color

color2 = Color('#888888')
    a valid HTML color

divisions = CInt(64)
    an int

radials = CInt(16)
    an int

radius = CInt(10)
    an int

type = Unicode('PolarGridHelper')
    a unicode string

```

RectAreaLightHelper

```

class pythreejs.RectAreaLightHelper (light=None, color="#ffffff")
    RectAreaLightHelper

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/RectAreaLightHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/RectAreaLightHelper>

light

```

Instance(RectAreaLight, allow_none=True).tag(sync=True, **widget_
↪serialization)

```

color

```

Color("#ffffff", allow_none=True).tag(sync=True)

```

type

```

Unicode("RectAreaLightHelper", allow_none=False).tag(sync=True)

```

```

color = Color('#ffffff')
    a valid HTML color

```

```

light = Instance()
    a RectAreaLight or None

```

```

type = Unicode('RectAreaLightHelper')
    a unicode string

```

SkeletonHelper

class pythreejs.**SkeletonHelper** (*root=None*)
SkeletonHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/SkeletonHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/SkeletonHelper>

root

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

type

```
Unicode("SkeletonHelper", allow_none=False).tag(sync=True)
```

root = Instance()
an Object3D or None

type = Unicode('SkeletonHelper')
a unicode string

SpotLightHelper

class pythreejs.**SpotLightHelper** (*light=None, color="#ffffff"*)
SpotLightHelper

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/SpotLightHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/SpotLightHelper>

light

```
Instance(SpotLight, allow_none=True).tag(sync=True, **widget_serialization)
```

color

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("SpotLightHelper", allow_none=False).tag(sync=True)
```

color = Color('#ffffff')
a valid HTML color

light = Instance()
a SpotLight or None


```
type = Unicode('SpotLightHelper')
    a unicode string
```

VertexNormalsHelper

```
class pythreejs.VertexNormalsHelper (object=None, size=1, color="#ffff00", linewidth=1)
    VertexNormalsHelper
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/helpers/VertexNormalsHelper>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/helpers/VertexNormalsHelper>

object

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffff00", allow_none=False).tag(sync=True)
```

linewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("VertexNormalsHelper", allow_none=False).tag(sync=True)
```

```
color = Color('#ffff00')
    a valid HTML color
```

```
linewidth = CFloat(1)
    a float
```

```
object = Instance()
    an Object3D or None
```

```
size = CFloat(1)
    a float
```

```
type = Unicode('VertexNormalsHelper')
    a unicode string
```

2.5.10 lights

AmbientLight

class pythreejs.AmbientLight (*color="#ffffff", intensity=1*)
 AmbientLight

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/AmbientLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/AmbientLight>

type

```
Unicode("AmbientLight", allow_none=False).tag(sync=True)
```

type = Unicode('AmbientLight')
 a unicode string

DirectionalLightShadow

class pythreejs.DirectionalLightShadow
 DirectionalLightShadow

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/DirectionalLightShadow>

Inherits *LightShadow*.

Three.js docs: <https://threejs.org/docs/#api/lights/DirectionalLightShadow>

DirectionalLight

class pythreejs.DirectionalLight (*color="#ffffff", intensity=1*)
 DirectionalLight

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/DirectionalLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/DirectionalLight>

target

```
Union([
    Instance(Uninitialized),
    Instance(Object3D),
    ], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↪ **uninitialized_serialization)
```

shadow

```
Union([
    Instance(Uninitialized),
    Instance(LightShadow),
    ], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↪ **uninitialized_serialization)
```

(continues on next page)

(continued from previous page)

type

```
Unicode("DirectionalLight", allow_none=False).tag(sync=True)
```

shadow = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
an Uninitialized or a LightShadow

target = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
an Uninitialized or an Object3D

type = Unicode('DirectionalLight')
a unicode string

HemisphereLight

class pythreejs.HemisphereLight (color="#ffffff", groundColor="#000000", intensity=1)
HemisphereLight

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/HemisphereLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/HemisphereLight>

groundColor

```
Color("#000000", allow_none=False).tag(sync=True)
```

type

```
Unicode("HemisphereLight", allow_none=False).tag(sync=True)
```

groundColor = Color('#000000')
a valid HTML color

type = Unicode('HemisphereLight')
a unicode string

LightShadow

class pythreejs.LightShadow (camera=UninitializedSentinel)
LightShadow

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/LightShadow>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/lights/LightShadow>

camera

```
Union([
    Instance(Uninitialized),
    Instance(Camera),
    ], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↳**uninitialized_serialization)
```

bias

```
CFloat(0, allow_none=False).tag(sync=True)
```

mapSize

```
Vector2(default_value=[512, 512]).tag(sync=True)
```

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

bias = CFloat(0)

a float

camera = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>)

an Uninitialized or a Camera

mapSize = Vector2((0, 0))

a tuple of any type

radius = CFloat(1)

a float

Light

class pythreejs.**Light** (*color="#ffffff", intensity=1*)

Light

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/Light>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/lights/Light>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

intensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("Light", allow_none=False).tag(sync=True)
```

color = **Color**('#ffffff')
a valid HTML color

intensity = **CFloat**(1)
a float

type = **Unicode**('Light')
a unicode string

PointLight

class pythreejs.**PointLight** (*color="#ffffff", intensity=1, distance=0, decay=1*)
PointLight

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/PointLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/PointLight>

power

```
CFloat(12.566370614359172, allow_none=False).tag(sync=True)
```

distance

```
CFloat(0, allow_none=False).tag(sync=True)
```

decay

```
CFloat(1, allow_none=False).tag(sync=True)
```

shadow

```
Union([
    Instance(Uninitialized),
    Instance(LightShadow),
], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↳ **uninitialized_serialization)
```

type

```
Unicode("PointLight", allow_none=False).tag(sync=True)
```

decay = **CFloat**(1)
a float

distance = **CFloat**(0)
a float

power = **CFloat**(12.566370614359172)
a float

```
shadow = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
              an Uninitialized or a LightShadow)
```

```
type = Unicode('PointLight')
      a unicode string
```

RectAreaLight

```
class pythreejs.RectAreaLight (color="#ffffff", intensity=1, width=10, height=10)
    RectAreaLight
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/RectAreaLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/RectAreaLight>

width

```
CFloat(10, allow_none=False).tag(sync=True)
```

height

```
CFloat(10, allow_none=False).tag(sync=True)
```

type

```
Unicode("RectAreaLight", allow_none=False).tag(sync=True)
```

```
height = CFloat(10)
        a float
```

```
type = Unicode('RectAreaLight')
      a unicode string
```

```
width = CFloat(10)
        a float
```

SpotLightShadow

```
class pythreejs.SpotLightShadow
    SpotLightShadow
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/SpotLightShadow>

Inherits *LightShadow*.

Three.js docs: <https://threejs.org/docs/#api/lights/SpotLightShadow>

SpotLight

```
class pythreejs.SpotLight (color="#ffffff", intensity=1, distance=0, angle=1.0471975511965976,
                          penumbra=0, decay=1)
    SpotLight
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/lights/SpotLight>

Inherits *Light*.

Three.js docs: <https://threejs.org/docs/#api/lights/SpotLight>

target

```
Union([
  Instance(Uninitialized),
  Instance(Object3D),
], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↳**uninitialized_serialization)
```

distance

```
CFloat(0, allow_none=False).tag(sync=True)
```

angle

```
CFloat(1.0471975511965976, allow_none=False).tag(sync=True)
```

penumbra

```
CFloat(0, allow_none=False).tag(sync=True)
```

decay

```
CFloat(1, allow_none=False).tag(sync=True)
```

shadow

```
Union([
  Instance(Uninitialized),
  Instance(LightShadow),
], default_value=UninitializedSentinel, allow_none=False).tag(sync=True,
↳**uninitialized_serialization)
```

type

```
Unicode("SpotLight", allow_none=False).tag(sync=True)
```

angle = CFloat(1.0471975511965976)
a float

decay = CFloat(1)
a float

distance = CFloat(0)
a float

penumbra = CFloat(0)
a float

```
shadow = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
              an Uninitialized or a LightShadow)

target = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
              an Uninitialized or an Object3D)

type = Unicode('SpotLight')
       a unicode string
```

2.5.11 loaders

AnimationLoader

```
class pythreejs.AnimationLoader
    AnimationLoader

    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/loaders/AnimationLoader

    Inherits ThreeWidget.

    Three.js docs: https://threejs.org/docs/#api/loaders/AnimationLoader
```

AudioLoader

```
class pythreejs.AudioLoader
    AudioLoader

    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/loaders/AudioLoader

    Inherits ThreeWidget.

    Three.js docs: https://threejs.org/docs/#api/loaders/AudioLoader
```

BufferGeometryLoader

```
class pythreejs.BufferGeometryLoader
    BufferGeometryLoader

    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/loaders/BufferGeometryLoader

    Inherits ThreeWidget.

    Three.js docs: https://threejs.org/docs/#api/loaders/BufferGeometryLoader
```

Cache

```
class pythreejs.Cache
    Cache

    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/loaders/Cache

    Inherits ThreeWidget.

    Three.js docs: https://threejs.org/docs/#api/loaders/Cache
```


CompressedTextureLoader

class pythreejs.**CompressedTextureLoader**
CompressedTextureLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/CompressedTextureLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/CompressedTextureLoader>

CubeTextureLoader

class pythreejs.**CubeTextureLoader**
CubeTextureLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/CubeTextureLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/CubeTextureLoader>

DataTextureLoader

class pythreejs.**DataTextureLoader**
DataTextureLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/DataTextureLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/DataTextureLoader>

FileLoader

class pythreejs.**FileLoader**
FileLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/FileLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/FileLoader>

FontLoader

class pythreejs.**FontLoader**
FontLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/FontLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/FontLoader>

ImageBitmapLoader

class pythreejs.**ImageBitmapLoader**
ImageBitmapLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/ImageBitmapLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/ImageBitmapLoader>

ImageLoader

class pythreejs.**ImageLoader**
ImageLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/ImageLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/ImageLoader>

JSONLoader

class pythreejs.**JSONLoader**
JSONLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/JSONLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/JSONLoader>

Loader

class pythreejs.**Loader**
Loader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/Loader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/Loader>

LoadingManager

class pythreejs.**LoadingManager**
LoadingManager

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/LoadingManager>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/LoadingManager>

MaterialLoader

class pythreejs.**MaterialLoader**
MaterialLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/MaterialLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/MaterialLoader>

ObjectLoader

class pythreejs.**ObjectLoader**
ObjectLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/ObjectLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/ObjectLoader>

TextureLoader

class pythreejs.**TextureLoader**
TextureLoader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/loaders/TextureLoader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/loaders/TextureLoader>

2.5.12 materials

LineBasicMaterial

class pythreejs.**LineBasicMaterial**
LineBasicMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/LineBasicMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/LineBasicMaterial>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

linewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

linecap

```
Unicode("round", allow_none=False).tag(sync=True)
```

linejoin

```
Unicode("round", allow_none=False).tag(sync=True)
```

type

```
Unicode("LineBasicMaterial", allow_none=False).tag(sync=True)
```

color = `Color('#ffffff')`
a valid HTML color

lights = `Bool(False)`
a boolean

linecap = `Unicode('round')`
a unicode string

linejoin = `Unicode('round')`
a unicode string

linewidth = `CFloat(1)`
a float

type = `Unicode('LineBasicMaterial')`
a unicode string

LineDashedMaterial

class `pythreejs.LineDashedMaterial`
`LineDashedMaterial`

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/LineDashedMaterial>

Inherits `Material`.

Three.js docs: <https://threejs.org/docs/#api/materials/LineDashedMaterial>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

linewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

scale

```
CFloat(1, allow_none=False).tag(sync=True)
```

dashSize

```
CFloat(3, allow_none=False).tag(sync=True)
```

gapSize

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("LineDashedMaterial", allow_none=False).tag(sync=True)
```

color = **Color**('#ffffff')
a valid HTML color

dashSize = **CFloat**(3)
a float

gapSize = **CFloat**(1)
a float

lights = **Bool**(False)
a boolean

linewidth = **CFloat**(1)
a float

scale = **CFloat**(1)
a float

type = **Unicode**('LineDashedMaterial')
a unicode string

LineMaterial

class pythreejs.**LineMaterial**
LineMaterial

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/LineMaterial>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

fog

```
Bool(False, allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

linewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

dashScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

dashSize

```
CFloat(1, allow_none=False).tag(sync=True)
```

gapSize

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("LineMaterial", allow_none=False).tag(sync=True)
```

color = **Color**('#ffffff')
a valid HTML color

dashScale = **CFloat**(1)
a float

dashSize = **CFloat**(1)
a float

fog = **Bool**(False)
a boolean

gapSize = **CFloat**(1)
a float

lights = **Bool**(False)
a boolean

linewidth = **CFloat**(1)
a float

```
type = Unicode('LineMaterial')
a unicode string
```

Material

class pythreejs.**Material**

This widget has some manual overrides on the Python side.

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/materials/Material>

alphaTest

```
CFloat(0, allow_none=False).tag(sync=True)
```

blendDst

```
Enum(BlendFactors, "OneMinusSrcAlphaFactor", allow_none=False).tag(sync=True)
```

blendDstAlpha

```
CFloat(0, allow_none=False).tag(sync=True)
```

blending

```
Enum(BlendingMode, "NormalBlending", allow_none=False).tag(sync=True)
```

blendSrc

```
Enum(BlendFactors, "SrcAlphaFactor", allow_none=False).tag(sync=True)
```

blendSrcAlpha

```
CFloat(0, allow_none=False).tag(sync=True)
```

blendEquation

```
Enum(Equations, "AddEquation", allow_none=False).tag(sync=True)
```

blendEquationAlpha

```
CFloat(0, allow_none=False).tag(sync=True)
```

clipIntersection

```
Bool(False, allow_none=False).tag(sync=True)
```

clippingPlanes

```
Tuple().tag(sync=True, **widget_serialization)
```

clipShadows

```
Bool(False, allow_none=False).tag(sync=True)
```

colorWrite

```
Bool(True, allow_none=False).tag(sync=True)
```

defines

```
Dict(default_value=None, allow_none=True).tag(sync=True)
```

depthFunc

```
Enum(DepthMode, "LessEqualDepth", allow_none=False).tag(sync=True)
```

depthTest

```
Bool(True, allow_none=False).tag(sync=True)
```

depthWrite

```
Bool(True, allow_none=False).tag(sync=True)
```

dithering

```
Bool(False, allow_none=False).tag(sync=True)
```

flatShading

```
Bool(False, allow_none=False).tag(sync=True)
```

fog

```
Bool(True, allow_none=False).tag(sync=True)
```

lights

```
Bool(True, allow_none=False).tag(sync=True)
```

name


```
Unicode("", allow_none=False).tag(sync=True)
```

opacity

```
CFloat(1, allow_none=False).tag(sync=True)
```

overdraw

```
CFloat(0, allow_none=False).tag(sync=True)
```

polygonOffset

```
Bool(False, allow_none=False).tag(sync=True)
```

polygonOffsetFactor

```
CFloat(0, allow_none=False).tag(sync=True)
```

polygonOffsetUnits

```
CFloat(0, allow_none=False).tag(sync=True)
```

precision

```
Unicode(None, allow_none=True).tag(sync=True)
```

premultipliedAlpha

```
Bool(False, allow_none=False).tag(sync=True)
```

shadowSide

```
Enum(Side, None, allow_none=True).tag(sync=True)
```

side

```
Enum(Side, "FrontSide", allow_none=False).tag(sync=True)
```

transparent

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("Material", allow_none=False).tag(sync=True)
```

vertexColors

```
Enum(Colors, "NoColors", allow_none=False).tag(sync=True)
```

visible

```
Bool(True, allow_none=False).tag(sync=True)
```

needsUpdate = Bool(False)

a boolean

onNeedsUpdate

MeshBasicMaterial

class pythreejs.**MeshBasicMaterial**

MeshBasicMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshBasicMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshBasicMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

combine

```
Enum(Operations, "MultiplyOperation", allow_none=False).tag(sync=True)
```

envMap

```
Instance(CubeTexture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

reflectivity

```
CFloat(1, allow_none=False).tag(sync=True)
```

refractionRatio

```
CFloat(0.98, allow_none=False).tag(sync=True)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

specularMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

wireframeLinecap

```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinejoin

```
Unicode("round", allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshBasicMaterial", allow_none=False).tag(sync=True)
```

alphaMap = Instance()

a Texture or None

aoMap = Instance()

a Texture or None

aoMapIntensity = CFloat(1)

a float

color = Color('#ffffff')

a valid HTML color

combine = Enum('MultiplyOperation')

any of ['AddOperation', 'MixOperation', 'MultiplyOperation']

envMap = Instance()

a CubeTexture or None

lightMap = Instance()

a Texture or None

lightMapIntensity = CFloat(1)

a float

lights = Bool(False)

a boolean

map = Instance()

a Texture or None

morphTargets = Bool(False)

a boolean

reflectivity = CFloat(1)

a float

refractionRatio = CFloat(0.98)

a float

skinning = Bool(False)

a boolean

specularMap = Instance()

a Texture or None

```

type = Unicode('MeshBasicMaterial')
    a unicode string

wireframe = Bool(False)
    a boolean

wireframeLinecap = Unicode('round')
    a unicode string

wireframeLinejoin = Unicode('round')
    a unicode string

wireframeLinewidth = CFloat(1)
    a float

```

MeshDepthMaterial

```
class pythreejs.MeshDepthMaterial
```

```
MeshDepthMaterial
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshDepthMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshDepthMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

displacementMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

displacementScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

displacementBias

```
CFloat(0, allow_none=False).tag(sync=True)
```

fog

```
Bool(False, allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshDepthMaterial", allow_none=False).tag(sync=True)
```

alphaMap = Instance()
a Texture or None

displacementBias = CFloat(0)
a float

displacementMap = Instance()
a Texture or None

displacementScale = CFloat(1)
a float

fog = Bool(False)
a boolean

lights = Bool(False)
a boolean

map = Instance()
a Texture or None

morphTargets = Bool(False)
a boolean

skinning = Bool(False)
a boolean

type = Unicode('MeshDepthMaterial')
a unicode string

wireframe = Bool(False)
a boolean

```
wireframeLinewidth = CFloat(1)
    a float
```

MeshLambertMaterial

```
class pythreejs.MeshLambertMaterial
    MeshLambertMaterial
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshLambertMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshLambertMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

combine

```
Enum(Operations, "MultiplyOperation", allow_none=False).tag(sync=True)
```

emissive

```
Color("#000000", allow_none=False).tag(sync=True)
```

emissiveMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

emissiveIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

envMap

```
Instance(CubeTexture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphNormals

```
Bool(False, allow_none=False).tag(sync=True)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

reflectivity

```
CFloat(1, allow_none=False).tag(sync=True)
```

refractionRatio

```
CFloat(0.98, allow_none=False).tag(sync=True)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

specularMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinecap


```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinejoin

```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshLambertMaterial", allow_none=False).tag(sync=True)
```

alphaMap = Instance()

a Texture or None

aoMap = Instance()

a Texture or None

aoMapIntensity = CFloat(1)

a float

color = Color('#ffffff')

a valid HTML color

combine = Enum('MultiplyOperation')

any of ['AddOperation', 'MixOperation', 'MultiplyOperation']

emissive = Color('#000000')

a valid HTML color

emissiveIntensity = CFloat(1)

a float

emissiveMap = Instance()

a Texture or None

envMap = Instance()

a CubeTexture or None

lightMap = Instance()

a Texture or None

lightMapIntensity = CFloat(1)

a float

map = Instance()

a Texture or None

morphNormals = Bool(False)

a boolean

morphTargets = Bool(False)

a boolean

reflectivity = CFloat(1)

a float

```

refractionRatio = CFloat(0.98)
    a float

skinning = Bool(False)
    a boolean

specularMap = Instance()
    a Texture or None

type = Unicode('MeshLambertMaterial')
    a unicode string

wireframe = Bool(False)
    a boolean

wireframeLinecap = Unicode('round')
    a unicode string

wireframeLinejoin = Unicode('round')
    a unicode string

wireframeLinewidth = CFloat(1)
    a float

```

MeshMatcapMaterial

```

class pythreejs.MeshMatcapMaterial
    MeshMatcapMaterial

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshMatcapMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshMatcapMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

bumpMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

bumpScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

displacementMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

displacementScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

displacementBias

```
CFloat(0, allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

matcap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphNormals

```
Bool(False, allow_none=False).tag(sync=True)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

normalMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

normalScale

```
Vector2(default_value=[1, 1]).tag(sync=True)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshMatcapMaterial", allow_none=False).tag(sync=True)
```

alphaMap = Instance()
a Texture or None

```

bumpMap = Instance()
    a Texture or None

bumpScale = CFloat(1)
    a float

color = Color('#ffffff')
    a valid HTML color

displacementBias = CFloat(0)
    a float

displacementMap = Instance()
    a Texture or None

displacementScale = CFloat(1)
    a float

lights = Bool(False)
    a boolean

map = Instance()
    a Texture or None

matcap = Instance()
    a Texture or None

morphNormals = Bool(False)
    a boolean

morphTargets = Bool(False)
    a boolean

normalMap = Instance()
    a Texture or None

normalScale = Vector2((0, 0))
    a tuple of any type

skinning = Bool(False)
    a boolean

type = Unicode('MeshMatcapMaterial')
    a unicode string

```

MeshNormalMaterial

```

class pythreejs.MeshNormalMaterial
    MeshNormalMaterial

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshNormalMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshNormalMaterial>

fog

```

Bool(False, allow_none=False).tag(sync=True)

```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshNormalMaterial", allow_none=False).tag(sync=True)
```

fog = Bool(False)
a boolean

lights = Bool(False)
a boolean

morphTargets = Bool(False)
a boolean

type = Unicode('MeshNormalMaterial')
a unicode string

wireframe = Bool(False)
a boolean

wireframeLinewidth = CFloat(1)
a float

MeshPhongMaterial

class pythreejs.**MeshPhongMaterial**
MeshPhongMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshPhongMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshPhongMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

bumpMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

bumpScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

combine

```
Enum(Operations, "MultiplyOperation", allow_none=False).tag(sync=True)
```

displacementMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

displacementScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

displacementBias

```
CFloat(0, allow_none=False).tag(sync=True)
```

emissive

```
Color("#000000", allow_none=False).tag(sync=True)
```

emissiveMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

emissiveIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

envMap

```
Instance(CubeTexture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphNormals

```
Bool(False, allow_none=False).tag(sync=True)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

normalMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

normalScale

```
Vector2(default_value=[1, 1]).tag(sync=True)
```

reflectivity

```
CFloat(1, allow_none=False).tag(sync=True)
```

refractionRatio

```
CFloat(0.98, allow_none=False).tag(sync=True)
```

shininess

```
CFloat(30, allow_none=False).tag(sync=True)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

specular

```
Color("#111111", allow_none=False).tag(sync=True)
```

specularMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

wireframeLinecap

```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinejoin

```
Unicode("round", allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshPhongMaterial", allow_none=False).tag(sync=True)
```

alphaMap = Instance()

a Texture or None

aoMap = Instance()

a Texture or None

aoMapIntensity = CFloat(1)

a float

bumpMap = Instance()

a Texture or None

bumpScale = CFloat(1)

a float

color = **Color**('#ffffff')
a valid HTML color

combine = **Enum**('MultiplyOperation')
any of ['AddOperation', 'MixOperation', 'MultiplyOperation']

displacementBias = **CFloat**(0)
a float

displacementMap = **Instance**()
a Texture or None

displacementScale = **CFloat**(1)
a float

emissive = **Color**('#000000')
a valid HTML color

emissiveIntensity = **CFloat**(1)
a float

emissiveMap = **Instance**()
a Texture or None

envMap = **Instance**()
a CubeTexture or None

lightMap = **Instance**()
a Texture or None

lightMapIntensity = **CFloat**(1)
a float

map = **Instance**()
a Texture or None

morphNormals = **Bool**(False)
a boolean

morphTargets = **Bool**(False)
a boolean

normalMap = **Instance**()
a Texture or None

normalScale = **Vector2**((0, 0))
a tuple of any type

reflectivity = **CFloat**(1)
a float

refractionRatio = **CFloat**(0.98)
a float

shininess = **CFloat**(30)
a float

skinning = **Bool**(False)
a boolean

specular = **Color**('#111111')
a valid HTML color

```

specularMap = Instance()
    a Texture or None

type = Unicode('MeshPhongMaterial')
    a unicode string

wireframe = Bool(False)
    a boolean

wireframeLinecap = Unicode('round')
    a unicode string

wireframeLinejoin = Unicode('round')
    a unicode string

wireframeLinewidth = CFloat(1)
    a float
    
```

MeshPhysicalMaterial

```

class pythreejs.MeshPhysicalMaterial
    MeshPhysicalMaterial
    
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshPhysicalMaterial>

Inherits *MeshStandardMaterial*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshPhysicalMaterial>

clearCoat

```
CFloat(0, allow_none=False).tag(sync=True)
```

clearCoatRoughness

```
CFloat(0, allow_none=False).tag(sync=True)
```

defines

```
Dict(default_value={"PHYSICAL":""}, allow_none=True).tag(sync=True)
```

reflectivity

```
CFloat(0.5, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshPhysicalMaterial", allow_none=False).tag(sync=True)
```

```

clearCoat = CFloat(0)
    a float
    
```

```

clearCoatRoughness = CFloat(0)
    a float
    
```

```

defines = Dict()
    a dict or None with elements of any type

reflectivity = CFloat(0.5)
    a float

type = Unicode('MeshPhysicalMaterial')
    a unicode string

```

MeshStandardMaterial

```

class pythreejs.MeshStandardMaterial
    MeshStandardMaterial

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshStandardMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshStandardMaterial>

alphaMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

aoMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

bumpMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

bumpScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

defines

```
Dict(default_value={"STANDARD":""}, allow_none=True).tag(sync=True)
```

displacementMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

displacementScale

```
CFloat(1, allow_none=False).tag(sync=True)
```

displacementBias

```
CFloat(0, allow_none=False).tag(sync=True)
```

emissive

```
Color("#000000", allow_none=False).tag(sync=True)
```

emissiveMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

emissiveIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

envMap

```
Instance(CubeTexture, allow_none=True).tag(sync=True, **widget_serialization)
```

envMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

lightMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

lightMapIntensity

```
CFloat(1, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

metalness

```
CFloat(0.5, allow_none=False).tag(sync=True)
```

metalnessMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

morphNormals

```
Bool(False, allow_none=False).tag(sync=True)
```

normalMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

normalScale

```
Vector2(default_value=[1, 1]).tag(sync=True)
```

refractionRatio

```
CFloat(0.98, allow_none=False).tag(sync=True)
```

roughness

```
CFloat(0.5, allow_none=False).tag(sync=True)
```

roughnessMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

skinning

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinecap

```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinejoin

```
Unicode("round", allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("MeshStandardMaterial", allow_none=False).tag(sync=True)
```

```
alphaMap = Instance()
    a Texture or None

aoMap = Instance()
    a Texture or None

aoMapIntensity = CFloat(1)
    a float

bumpMap = Instance()
    a Texture or None

bumpScale = CFloat(1)
    a float

color = Color('#ffffff')
    a valid HTML color

defines = Dict()
    a dict or None with elements of any type

displacementBias = CFloat(0)
    a float

displacementMap = Instance()
    a Texture or None

displacementScale = CFloat(1)
    a float

emissive = Color('#000000')
    a valid HTML color

emissiveIntensity = CFloat(1)
    a float

emissiveMap = Instance()
    a Texture or None

envMap = Instance()
    a CubeTexture or None

envMapIntensity = CFloat(1)
    a float
```

```

lightMap = Instance()
    a Texture or None

lightMapIntensity = CFloat(1)
    a float

map = Instance()
    a Texture or None

metalness = CFloat(0.5)
    a float

metalnessMap = Instance()
    a Texture or None

morphNormals = Bool(False)
    a boolean

morphTargets = Bool(False)
    a boolean

normalMap = Instance()
    a Texture or None

normalScale = Vector2((0, 0))
    a tuple of any type

refractionRatio = CFloat(0.98)
    a float

roughness = CFloat(0.5)
    a float

roughnessMap = Instance()
    a Texture or None

skinning = Bool(False)
    a boolean

type = Unicode('MeshStandardMaterial')
    a unicode string

wireframe = Bool(False)
    a boolean

wireframeLinecap = Unicode('round')
    a unicode string

wireframeLinejoin = Unicode('round')
    a unicode string

wireframeLinewidth = CFloat(1)
    a float

```

MeshToonMaterial

```

class pythreejs.MeshToonMaterial
    MeshToonMaterial

```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/MeshToonMaterial>

Inherits *MeshPhongMaterial*.

Three.js docs: <https://threejs.org/docs/#api/materials/MeshToonMaterial>

gradientMap

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

type

```
Unicode("MeshToonMaterial", allow_none=False).tag(sync=True)
```

gradientMap = Instance()

a Texture or None

type = Unicode('MeshToonMaterial')

a unicode string

PointsMaterial

class pythreejs.PointsMaterial

PointsMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/PointsMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/PointsMaterial>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

morphTargets

```
Bool(False, allow_none=False).tag(sync=True)
```

size

```
CFloat(1, allow_none=False).tag(sync=True)
```

sizeAttenuation


```
Bool(True, allow_none=False).tag(sync=True)
```

type

```
Unicode("PointsMaterial", allow_none=False).tag(sync=True)
```

color = `Color('#ffffff')`
a valid HTML color

lights = `Bool(False)`
a boolean

map = `Instance()`
a Texture or None

morphTargets = `Bool(False)`
a boolean

size = `CFloat(1)`
a float

sizeAttenuation = `Bool(True)`
a boolean

type = `Unicode('PointsMaterial')`
a unicode string

RawShaderMaterial

class `pythreejs.RawShaderMaterial`
RawShaderMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/RawShaderMaterial>

Inherits *ShaderMaterial*.

Three.js docs: <https://threejs.org/docs/#api/materials/RawShaderMaterial>

type

```
Unicode("RawShaderMaterial", allow_none=False).tag(sync=True)
```

type = `Unicode('RawShaderMaterial')`
a unicode string

ShaderMaterial

class `pythreejs.ShaderMaterial`
ShaderMaterial

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/ShaderMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/ShaderMaterial>

uniforms

```
Dict (default_value={}, trait=Uniform(allow_none=True), allow_none=False).
↳tag(sync=True, **uniforms_serialization)
```

clipping

```
Bool (False, allow_none=False).tag(sync=True)
```

extensions

```
Dict (default_value={}, allow_none=False).tag(sync=True)
```

fog

```
Bool (False, allow_none=False).tag(sync=True)
```

fragmentShader

```
Unicode("", allow_none=False).tag(sync=True)
```

lights

```
Bool (False, allow_none=False).tag(sync=True)
```

linewidth

```
CFloat (1, allow_none=False).tag(sync=True)
```

morphNormals

```
Bool (False, allow_none=False).tag(sync=True)
```

morphTargets

```
Bool (False, allow_none=False).tag(sync=True)
```

flatShading

```
Bool (False, allow_none=False).tag(sync=True)
```

skinning

```
Bool (False, allow_none=False).tag(sync=True)
```

uniformsNeedUpdate

```
Bool(False, allow_none=False).tag(sync=True)
```

vertexShader

```
Unicode("", allow_none=False).tag(sync=True)
```

wireframe

```
Bool(False, allow_none=False).tag(sync=True)
```

wireframeLinewidth

```
CFloat(1, allow_none=False).tag(sync=True)
```

type

```
Unicode("ShaderMaterial", allow_none=False).tag(sync=True)
```

clipping = Bool(False)

a boolean

extensions = Dict()

a dict with elements of any type

flatShading = Bool(False)

a boolean

fog = Bool(False)

a boolean

fragmentShader = Unicode('')

a unicode string

lights = Bool(False)

a boolean

linewidth = CFloat(1)

a float

morphNormals = Bool(False)

a boolean

morphTargets = Bool(False)

a boolean

skinning = Bool(False)

a boolean

type = Unicode('ShaderMaterial')

a unicode string

uniforms = Dict()

a dict with elements with values that are: a dict or None

uniformsNeedUpdate = Bool(False)

a boolean

```
vertexShader = Unicode('')  
    a unicode string  
wireframe = Bool(False)  
    a boolean  
wireframeLinewidth = CFloat(1)  
    a float
```

ShadowMaterial

```
class pythreejs.ShadowMaterial  
    ShadowMaterial
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/ShadowMaterial>

Inherits *ShaderMaterial*.

Three.js docs: <https://threejs.org/docs/#api/materials/ShadowMaterial>

lights

```
Bool(True, allow_none=False).tag(sync=True)
```

transparent

```
Bool(True, allow_none=False).tag(sync=True)
```

type

```
Unicode("ShadowMaterial", allow_none=False).tag(sync=True)
```

```
lights = Bool(True)  
    a boolean
```

```
transparent = Bool(True)  
    a boolean
```

```
type = Unicode('ShadowMaterial')  
    a unicode string
```

SpriteMaterial

```
class pythreejs.SpriteMaterial  
    SpriteMaterial
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/materials/SpriteMaterial>

Inherits *Material*.

Three.js docs: <https://threejs.org/docs/#api/materials/SpriteMaterial>

color

```
Color("#ffffff", allow_none=False).tag(sync=True)
```

fog

```
Bool(False, allow_none=False).tag(sync=True)
```

lights

```
Bool(False, allow_none=False).tag(sync=True)
```

map

```
Instance(Texture, allow_none=True).tag(sync=True, **widget_serialization)
```

rotation

```
CFloat(0, allow_none=False).tag(sync=True)
```

sizeAttenuation

```
Bool(True, allow_none=False).tag(sync=True)
```

type

```
Unicode("SpriteMaterial", allow_none=False).tag(sync=True)
```

color = Color('#ffffff')

a valid HTML color

fog = Bool(False)

a boolean

lights = Bool(False)

a boolean

map = Instance()

a Texture or None

rotation = CFloat(0)

a float

sizeAttenuation = Bool(True)

a boolean

type = Unicode('SpriteMaterial')

a unicode string

2.5.13 math

interpolants

CubicInterpolant

class pythreejs.CubicInterpolant
CubicInterpolant

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/interpolants/CubicInterpolant>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/interpolants/CubicInterpolant>

DiscreteInterpolant

class pythreejs.DiscreteInterpolant
DiscreteInterpolant

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/interpolants/DiscreteInterpolant>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/interpolants/DiscreteInterpolant>

LinearInterpolant

class pythreejs.LinearInterpolant
LinearInterpolant

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/interpolants/LinearInterpolant>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/interpolants/LinearInterpolant>

QuaternionLinearInterpolant

class pythreejs.QuaternionLinearInterpolant
QuaternionLinearInterpolant

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/interpolants/QuaternionLinearInterpolant>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/interpolants/QuaternionLinearInterpolant>

Box2

class pythreejs.Box2 (*min*=[0, 0], *max*=[0, 0],)
Box2

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Box2>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Box2>

min

```
Vector2 (default_value=[0, 0]) .tag (sync=True)
```

max

```
Vector2 (default_value=[0, 0]) .tag (sync=True)
```

max = **Vector2** ((0, 0))

a tuple of any type

min = **Vector2** ((0, 0))

a tuple of any type

Box3

class pythreejs.**Box3** (min=[0, 0, 0], max=[0, 0, 0],)

Box3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Box3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Box3>

min

```
Vector3 (default_value=[0, 0, 0]) .tag (sync=True)
```

max

```
Vector3 (default_value=[0, 0, 0]) .tag (sync=True)
```

max = **Vector3** ((0, 0, 0))

a tuple of any type

min = **Vector3** ((0, 0, 0))

a tuple of any type

Cylindrical

class pythreejs.**Cylindrical** (radius=1, theta=0, y=0)

Cylindrical

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Cylindrical>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Cylindrical>

radius

```
CFloat(1, allow_none=False).tag(sync=True)
```

theta

```
CFloat(0, allow_none=False).tag(sync=True)
```

y

```
CFloat(0, allow_none=False).tag(sync=True)
```

radius = CFloat(1)
a float

theta = CFloat(0)
a float

y = CFloat(0)
a float

Frustum

class pythreejs.**Frustum** (*p0=None, p1=None, p2=None, p3=None, p4=None, p5=None*)
Frustum

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Frustum>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Frustum>

p0

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

p1

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

p2

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

p3

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

p4

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```


p5

```
Instance(Plane, allow_none=True).tag(sync=True, **widget_serialization)
```

p0 = Instance()
a Plane or None

p1 = Instance()
a Plane or None

p2 = Instance()
a Plane or None

p3 = Instance()
a Plane or None

p4 = Instance()
a Plane or None

p5 = Instance()
a Plane or None

Interpolant

class pythreejs.**Interpolant**
Interpolant

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Interpolant>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Interpolant>

Line3

class pythreejs.**Line3** (*start*=[0, 0, 0], *end*=[0, 0, 0],)
Line3

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Line3>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Line3>

start

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

end

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

end = Vector3((0, 0, 0))
a tuple of any type

start = Vector3((0, 0, 0))
a tuple of any type

Math

class pythreejs.Math

Math

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Math>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Math>

Plane

class pythreejs.Plane (*normal*=[0, 0, 0], *constant*=0,)

Plane

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Plane>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Plane>

normal

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

constant

```
CFloat(0, allow_none=False).tag(sync=True)
```

constant = CFloat(0)

a float

normal = Vector3((0, 0, 0))

a tuple of any type

Quaternion

class pythreejs.Quaternion (*x*=0, *y*=0, *z*=0, *w*=1)

Quaternion

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Quaternion>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Quaternion>

x

```
CFloat(0, allow_none=False).tag(sync=True)
```

y

```
CFloat(0, allow_none=False).tag(sync=True)
```

z

```
CFloat(0, allow_none=False).tag(sync=True)
```

w

```
CFloat(1, allow_none=False).tag(sync=True)
```

w = CFloat(1)
a float

x = CFloat(0)
a float

y = CFloat(0)
a float

z = CFloat(0)
a float

Ray

class pythreejs.**Ray** (*origin*=[0, 0, 0], *direction*=[0, 0, 0],)
Ray

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Ray>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Ray>

origin

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

direction

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

direction = Vector3((0, 0, 0))
a tuple of any type

origin = Vector3((0, 0, 0))
a tuple of any type

Sphere

class pythreejs.**Sphere** (*center*=[0, 0, 0], *radius*=0,)
Sphere

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Sphere>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Sphere>

center

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

radius

```
CFloat(0, allow_none=False).tag(sync=True)
```

center = Vector3((0, 0, 0))
a tuple of any type

radius = CFloat(0)
a float

Spherical

class pythreejs.Spherical

Spherical

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Spherical>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Spherical>

Triangle

class pythreejs.Triangle (a=[0, 0, 0], b=[0, 0, 0], c=[0, 0, 0],)

Triangle

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/math/Triangle>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/math/Triangle>

a

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

b

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

c

```
Vector3(default_value=[0, 0, 0]).tag(sync=True)
```

a = Vector3((0, 0, 0))
a tuple of any type

b = Vector3((0, 0, 0))
a tuple of any type

```
c = Vector3((0, 0, 0))
    a tuple of any type
```

2.5.14 objects

Blackbox

```
class pythreejs.Blackbox
```

A widget with unsynced children.

This widget allows extension authors to expose scene control of a given three object, without attempting to sync its children. This makes it possible for a library to give access to an outer object, without exposing the full object three, and can be useful in avoiding possibly heavy sync operations.

This widget has some manual overrides on the Python side.

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Blackbox>

type

```
Unicode("Blackbox", allow_none=False).tag(sync=True)
```

```
children = None
```

Bone

```
class pythreejs.Bone
```

Bone

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Bone>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Bone>

type

```
Unicode("Bone", allow_none=False).tag(sync=True)
```

```
type = Unicode('Bone')
```

a unicode string

CloneArray

```
class pythreejs.CloneArray (original=None, positions=[], merge=False)
```

CloneArray

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/CloneArray>

original

```
Instance(Object3D, allow_none=True).tag(sync=True, **widget_serialization)
```

positions

```
List(trait=List()).tag(sync=True)
```

merge

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Unicode("CloneArray", allow_none=False).tag(sync=True)
```

merge = Bool(False)
a boolean

original = Instance()
an Object3D or None

positions = List()
a list with values that are: a list

type = Unicode('CloneArray')
a unicode string

Group

class pythreejs.Group
Group

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Group>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Group>

type

```
Unicode("Group", allow_none=False).tag(sync=True)
```

type = Unicode('Group')
a unicode string

LOD

class pythreejs.LOD
LOD

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/LOD>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/objects/LOD>

Line2

class pythreejs.**Line2** (*geometry=UninitializedSentinel, material=UninitializedSentinel*)
Line2

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Mesh*.

Three.js docs: <https://threejs.org/docs/#api/objects/Line2>

material

```
Union([
  Instance(Uninitialized),
  Instance(LineMaterial),
], default_value=UninitializedSentinel, allow_none=True).tag(sync=True,
↳**uninitialized_serialization)
```

geometry

```
Union([
  Instance(Uninitialized),
  Instance(LineGeometry),
], default_value=UninitializedSentinel, allow_none=True).tag(sync=True,
↳**uninitialized_serialization)
```

type

```
Unicode("Line2", allow_none=False).tag(sync=True)
```

geometry = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
an Uninitialized or a LineGeometry)

material = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>
an Uninitialized or a LineMaterial)

type = Unicode('Line2')
a unicode string

LineLoop

class pythreejs.**LineLoop** (*geometry=None, material=None*)
LineLoop

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/LineLoop>

Inherits *Line*.

Three.js docs: <https://threejs.org/docs/#api/objects/LineLoop>

type

```
Unicode("LineLoop", allow_none=False).tag(sync=True)
```

type = Unicode('LineLoop')
a unicode string

LineSegments2

class pythreejs.LineSegments2 (*geometry=UninitializedSentinel, material=UninitializedSentinel*)
LineSegments2

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Mesh*.

Three.js docs: <https://threejs.org/docs/#api/objects/LineSegments2>

material

```
Union([
    Instance(Uninitialized),
    Instance(LineMaterial),
], default_value=UninitializedSentinel, allow_none=True).tag(sync=True,
↳**uninitialized_serialization)
```

geometry

```
Union([
    Instance(Uninitialized),
    Instance(LineSegmentsGeometry),
], default_value=UninitializedSentinel, allow_none=True).tag(sync=True,
↳**uninitialized_serialization)
```

type

```
Unicode("LineSegments2", allow_none=False).tag(sync=True)
```

geometry = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>)
an Uninitialized or a LineSegmentsGeometry

material = Union(<pythreejs.traits.Uninitialized object at 0x7f83db20fe10>)
an Uninitialized or a LineMaterial

type = Unicode('LineSegments2')
a unicode string

LineSegments

class pythreejs.LineSegments (*geometry=None, material=None*)
LineSegments

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/LineSegments>

Inherits *Line*.

Three.js docs: <https://threejs.org/docs/#api/objects/LineSegments>

type

```
Unicode("LineSegments", allow_none=False).tag(sync=True)
```

type = Unicode('LineSegments')
a unicode string

Line

class pythreejs.**Line** (*geometry=None, material=None*)
Line

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Line>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Line>

material

```
Instance(Material, allow_none=True).tag(sync=True, **widget_serialization)
```

geometry

```
Union([
    Instance(BaseGeometry, allow_none=True),
    Instance(BaseBufferGeometry, allow_none=True)
]).tag(sync=True, **widget_serialization)
```

type

```
Unicode("Line", allow_none=False).tag(sync=True)
```

geometry = Union()
a BaseGeometry or None or a BaseBufferGeometry or None

material = Instance()
a Material or None

type = Unicode('Line')
a unicode string

Mesh

class pythreejs.**Mesh** (*geometry=None, material=[]*)
Mesh

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Mesh>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Mesh>

material

```
Union([Instance(Material), Tuple()]).tag(sync=True, **widget_serialization)
```

geometry

```
Union([
    Instance(BaseGeometry, allow_none=False),
    Instance(BaseBufferGeometry, allow_none=False)
]).tag(sync=True, **widget_serialization)
```

drawMode

```
Enum(DrawModes, "TrianglesDrawMode", allow_none=False).tag(sync=True)
```

morphTargetInfluences

```
List().tag(sync=True)
```

type

```
Unicode("Mesh", allow_none=False).tag(sync=True)
```

drawMode = Enum('TrianglesDrawMode')
 any of ['TriangleFanDrawMode', 'TriangleStripDrawMode', 'TrianglesDrawMode']

geometry = Union()
 a BaseGeometry or a BaseBufferGeometry

material = Union()
 a Material or a tuple

morphTargetInfluences = List()
 a list of any type

type = Unicode('Mesh')
 a unicode string

Points

class pythreejs.**Points** (*geometry=None, material=None*)
 Points

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Points>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Points>

material

```
Instance(Material, allow_none=False).tag(sync=True, **widget_serialization)
```

geometry

```
Union([
    Instance(BaseGeometry, allow_none=False),
    Instance(BaseBufferGeometry, allow_none=False)
]).tag(sync=True, **widget_serialization)
```

type

```
Unicode("Points", allow_none=False).tag(sync=True)
```

geometry = Union()
a BaseGeometry or a BaseBufferGeometry

material = Instance()
a Material

type = Unicode('Points')
a unicode string

Skeleton

class pythreejs.**Skeleton** (*bones=[]*)
Skeleton

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Skeleton>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/objects/Skeleton>

bones

```
Tuple().tag(sync=True, **widget_serialization)
```

bones = Tuple()
a tuple of any type

SkinnedMesh

class pythreejs.**SkinnedMesh** (*geometry=None, material=[]*)
SkinnedMesh

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/SkinnedMesh>

Inherits *Mesh*.

Three.js docs: <https://threejs.org/docs/#api/objects/SkinnedMesh>

bindMode

```
Unicode("attached", allow_none=False).tag(sync=True)
```

bindMatrix

```
Matrix4(default_value=[1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1]).
↳tag(sync=True)
```

skeleton

```
Instance(Skeleton, allow_none=True).tag(sync=True, **widget_serialization)
```

type

```
Unicode("SkinnedMesh", allow_none=False).tag(sync=True)
```

bindMatrix = **Matrix4**((1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1))
a tuple of any type

bindMode = **Unicode**('attached')
a unicode string

skeleton = **Instance**()
a Skeleton or None

type = **Unicode**('SkinnedMesh')
a unicode string

Sprite

class pythreejs.**Sprite** (*material=None*)
Sprite

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/objects/Sprite>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/objects/Sprite>

material

```
Instance(SpriteMaterial, allow_none=True).tag(sync=True, **widget_
↳serialization)
```

center

```
Vector2(default_value=[0.5, 0.5]).tag(sync=True)
```

type

```
Unicode("Sprite", allow_none=False).tag(sync=True)
```

center = **Vector2**((0, 0))
a tuple of any type

material = **Instance**()
a SpriteMaterial or None

```
type = Unicode('Sprite')
    a unicode string
```

2.5.15 renderers

webgl

WebGLBufferRenderer

```
class pythreejs.WebGLBufferRenderer
```

```
    WebGLBufferRenderer
```

```
    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/renderers/webgl/
    WebGLBufferRenderer
```

```
    Inherits ThreeWidget.
```

```
    Three.js docs: https://threejs.org/docs/#api/renderers/webgl/WebGLBufferRenderer
```

WebGLCapabilities

```
class pythreejs.WebGLCapabilities
```

```
    WebGLCapabilities
```

```
    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/renderers/webgl/WebGLCapabilities
```

```
    Inherits ThreeWidget.
```

```
    Three.js docs: https://threejs.org/docs/#api/renderers/webgl/WebGLCapabilities
```

WebGLExtensions

```
class pythreejs.WebGLExtensions
```

```
    WebGLExtensions
```

```
    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/renderers/webgl/WebGLExtensions
```

```
    Inherits ThreeWidget.
```

```
    Three.js docs: https://threejs.org/docs/#api/renderers/webgl/WebGLExtensions
```

WebGLGeometries

```
class pythreejs.WebGLGeometries
```

```
    WebGLGeometries
```

```
    Autogenerated by generate-wrappers.js See https://threejs.org/docs/#api/renderers/webgl/WebGLGeometries
```

```
    Inherits ThreeWidget.
```

```
    Three.js docs: https://threejs.org/docs/#api/renderers/webgl/WebGLGeometries
```

WebGLIndexedBufferRenderer

class pythreejs.WebGLIndexedBufferRenderer

WebGLIndexedBufferRenderer

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLIndexedBufferRenderer>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLIndexedBufferRenderer>

WebGLLights

class pythreejs.WebGLLights

WebGLLights

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLLights>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLLights>

WebGLObjects

class pythreejs.WebGLObjects

WebGLObjects

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLObjects>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLObjects>

WebGLProgram

class pythreejs.WebGLProgram

WebGLProgram

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLProgram>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLProgram>

WebGLPrograms

class pythreejs.WebGLPrograms

WebGLPrograms

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLPrograms>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLPrograms>

WebGLProperties

class pythreejs.WebGLProperties

WebGLProperties

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLProperties>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLProperties>

WebGLShader

class pythreejs.WebGLShader

WebGLShader

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLShader>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLShader>

WebGLShadowMap

class pythreejs.WebGLShadowMap

WebGLShadowMap

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLShadowMap>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLShadowMap>

enabled

```
Bool(False, allow_none=False).tag(sync=True)
```

type

```
Enum(ShadowTypes, "PCFShadowMap", allow_none=False).tag(sync=True)
```

enabled = Bool(False)

a boolean

type = Enum('PCFShadowMap')

any of ['BasicShadowMap', 'PCFShadowMap', 'PCFSOFTShadowMap']

WebGLState

class pythreejs.WebGLState

WebGLState

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/webgl/WebGLState>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/webgl/WebGLState>

WebGLRenderTargetCube

class pythreejs.**WebGLRenderTargetCube**
WebGLRenderTargetCube

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/WebGLRenderTargetCube>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/WebGLRenderTargetCube>

WebGLRenderTarget

class pythreejs.**WebGLRenderTarget**
WebGLRenderTarget

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/renderers/WebGLRenderTarget>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/renderers/WebGLRenderTarget>

2.5.16 scenes

FogExp2

class pythreejs.**FogExp2** (*color="white", density=0.00025*)
FogExp2

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/scenes/FogExp2>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/scenes/FogExp2>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

color

```
Color("white", allow_none=False).tag(sync=True)
```

density

```
CFloat(0.00025, allow_none=False).tag(sync=True)
```

color = Color('white')
a valid HTML color

density = CFloat(0.00025)
a float


```
name = Unicode('')
    a unicode string
```

Fog

```
class pythreejs.Fog(color="white", near=1, far=1000)
```

Fog

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/scenes/Fog>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/scenes/Fog>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

color

```
Color("white", allow_none=False).tag(sync=True)
```

near

```
CFloat(1, allow_none=False).tag(sync=True)
```

far

```
CFloat(1000, allow_none=False).tag(sync=True)
```

```
color = Color('white')
```

a valid HTML color

```
far = CFloat(1000)
```

a float

```
name = Unicode('')
```

a unicode string

```
near = CFloat(1)
```

a float

Scene

```
class pythreejs.Scene
```

Scene

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/scenes/Scene>

Inherits *Object3D*.

Three.js docs: <https://threejs.org/docs/#api/scenes/Scene>

fog

```
Union([
  Instance(Fog, allow_none=True),
  Instance(FogExp2, allow_none=True)
]).tag(sync=True, **widget_serialization)
```

overrideMaterial

```
Instance(Material, allow_none=True).tag(sync=True, **widget_serialization)
```

autoUpdate

```
Bool(True, allow_none=False).tag(sync=True)
```

background

```
Color("#ffffff", allow_none=True).tag(sync=True)
```

type

```
Unicode("Scene", allow_none=False).tag(sync=True)
```

autoUpdate = Bool(True)
a boolean

background = Color('#ffffff')
a valid HTML color

fog = Union()
a Fog or None or a FogExp2 or None

overrideMaterial = Instance()
a Material or None

type = Unicode('Scene')
a unicode string

2.5.17 textures

CompressedTexture

class pythreejs.CompressedTexture
CompressedTexture

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/textures/CompressedTexture>

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/CompressedTexture>

CubeTexture

```
class pythreejs.CubeTexture (images=[], mapping="UVMapping",
                             wrapS="ClampToEdgeWrapping", wrapT="ClampToEdgeWrapping",
                             magFilter="LinearFilter", minFilter="LinearMipMapLinearFilter",
                             format="RGBAFormat", type="UnsignedByteType", anisotropy=1)
```

CubeTexture

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/textures/CubeTexture>

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/CubeTexture>

images

```
List().tag(sync=True)
```

images = List()
a list of any type

DataTexture3D

```
class pythreejs.DataTexture3D (data=None, format="RGBAFormat", type="UnsignedByteType",
                                mapping="UVMapping", wrapS="ClampToEdgeWrapping",
                                wrapT="ClampToEdgeWrapping", magFilter="NearestFilter",
                                minFilter="NearestFilter", anisotropy=1)
```

This widget has some manual overrides on the Python side.

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/DataTexture3D>

data

```
WebGLDataUnion().tag(sync=True)
```

minFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

magFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

flipY

```
Bool(False, allow_none=False).tag(sync=True)
```

generateMipmaps

```
Bool(False, allow_none=False).tag(sync=True)
```

DataTexture

```
class pythreejs.DataURL (data=None, format="RGBAFormat", type="UnsignedByteType",
                        mapping="UVMapping", wrapS="ClampToEdgeWrapping",
                        wrapT="ClampToEdgeWrapping", magFilter="NearestFilter",
                        minFilter="NearestFilter", anisotropy=1)
```

This widget has some manual overrides on the Python side.

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/DataTexture>

data

```
WebGLDataUnion().tag(sync=True)
```

minFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

magFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

flipY

```
Bool(False, allow_none=False).tag(sync=True)
```

generateMipmaps

```
Bool(False, allow_none=False).tag(sync=True)
```

DepthTexture

```
class pythreejs.DepthTexture (width=0, height=0, type="UnsignedShortType",
                                wrapS="ClampToEdgeWrapping", wrapT="ClampToEdgeWrapping",
                                magFilter="NearestFilter", minFilter="NearestFilter",
                                anisotropy=1, format="DepthFormat")
```

DepthTexture

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/textures/DepthTexture>

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/DepthTexture>

width

```
CInt(0, allow_none=False).tag(sync=True)
```

height

```
CInt(0, allow_none=False).tag(sync=True)
```

format

```
Enum(DepthFormats, "DepthFormat", allow_none=False).tag(sync=True)
```

type

```
Enum(DataTypes, "UnsignedShortType", allow_none=False).tag(sync=True)
```

minFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

magFilter

```
Enum(Filters, "NearestFilter", allow_none=False).tag(sync=True)
```

flipY

```
Bool(False, allow_none=False).tag(sync=True)
```

generateMipmaps

```
Bool(False, allow_none=False).tag(sync=True)
```

flipY = Bool(False)

a boolean

format = Enum('DepthFormat')

any of ['DepthFormat', 'DepthStencilFormat']

generateMipmaps = Bool(False)

a boolean

height = CInt(0)

an int

magFilter = Enum('NearestFilter')

any of ['LinearFilter', 'LinearMipMapLinearFilter', 'LinearMipMapNearestFilter', 'NearestFilter', 'NearestMipMapLinearFilter', 'NearestMipMapNearestFilter']

minFilter = Enum('NearestFilter')

any of ['LinearFilter', 'LinearMipMapLinearFilter', 'LinearMipMapNearestFilter', 'NearestFilter', 'NearestMipMapLinearFilter', 'NearestMipMapNearestFilter']

type = Enum('UnsignedShortType')

any of ['ByteType', 'FloatType', 'HalfFloatType', 'IntType', 'ShortType', 'UnsignedByteType', 'UnsignedIntType', 'UnsignedShortType']

width = CInt(0)

an int

ImageTexture

```
class pythreejs.ImageTexture (imageUri="", mapping="UVMapping",
                               wrapS="ClampToEdgeWrapping", wrapT="ClampToEdgeWrapping",
                               magFilter="LinearFilter", minFilter="LinearMipMapLinearFilter",
                               format="RGBAFormat",
                               type="UnsignedByteType", anisotropy=1)
```

ImageTexture

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/ImageTexture>

imageUri

```
Unicode("", allow_none=False).tag(sync=True)
```

imageUri = Unicode('')

a unicode string

TextTexture

```
class pythreejs.TextTexture (string="")
```

TextTexture

Autogenerated by generate-wrappers.js This class is a custom class for pythreejs, with no direct corresponding class in three.js.

Inherits *Texture*.

Three.js docs: <https://threejs.org/docs/#api/textures/TextTexture>

color

```
Color("white", allow_none=False).tag(sync=True)
```

fontFace

```
Unicode("Arial", allow_none=False).tag(sync=True)
```

size

```
CInt(12, allow_none=False).tag(sync=True)
```

string

```
Unicode("", allow_none=False).tag(sync=True)
```

squareTexture

```
Bool(True, allow_none=False).tag(sync=True)
```

color = Color('white')

a valid HTML color

fontFace = Unicode('Arial')

a unicode string

size = CInt(12)

an int

squareTexture = Bool(True)

a boolean

string = Unicode('')

a unicode string

Texture

class pythreejs.Texture

Texture

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/textures/Texture>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/textures/Texture>

name

```
Unicode("", allow_none=False).tag(sync=True)
```

mapping

```
Enum(MappingModes, "UVMapping", allow_none=False).tag(sync=True)
```

wrapS

```
Enum(WrappingModes, "ClampToEdgeWrapping", allow_none=False).tag(sync=True)
```

wrapT

```
Enum(WrappingModes, "ClampToEdgeWrapping", allow_none=False).tag(sync=True)
```

magFilter

```
Enum(Filters, "LinearFilter", allow_none=False).tag(sync=True)
```

minFilter

```
Enum(Filters, "LinearMipMapLinearFilter", allow_none=False).tag(sync=True)
```

format

```
Enum(PixelFormats, "RGBAFormat", allow_none=False).tag(sync=True)
```

type

```
Enum(DataTypes, "UnsignedByteType", allow_none=False).tag(sync=True)
```

anisotropy

```
CFloat(1, allow_none=False).tag(sync=True)
```

repeat

```
Vector2(default_value=[1, 1]).tag(sync=True)
```

offset

```
Vector2(default_value=[0, 0]).tag(sync=True)
```

generateMipmaps

```
Bool(True, allow_none=False).tag(sync=True)
```

premultiplyAlpha

```
Bool(False, allow_none=False).tag(sync=True)
```

flipY

```
Bool(True, allow_none=False).tag(sync=True)
```

unpackAlignment

```
CInt(4, allow_none=False).tag(sync=True)
```

encoding

```
Enum(TextureEncodings, "LinearEncoding", allow_none=False).tag(sync=True)
```

version

```
CInt(0, allow_none=False).tag(sync=True)
```

rotation


```
CFloat(0, allow_none=False).tag(sync=True)
```

anisotropy = CFloat(1)

a float

encoding = Enum('LinearEncoding')

any of ['BasicDepthPacking', 'GammaEncoding', 'LinearEncoding', 'LogLuvEncoding', 'RGBADepthPacking', 'RGBDEncoding', 'RGBEEncoding', 'RGBM16Encoding', 'RGBM7Encoding', 'sRGBEncoding']

flipY = Bool(True)

a boolean

format = Enum('RGBAFormat')

any of ['AlphaFormat', 'DepthFormat', 'DepthStencilFormat', 'LuminanceAlphaFormat', 'LuminanceFormat', 'RGBAFormat', 'RGBEFormat', 'RGBFormat', 'RedFormat']

generateMipmaps = Bool(True)

a boolean

magFilter = Enum('LinearFilter')

any of ['LinearFilter', 'LinearMipMapLinearFilter', 'LinearMipMapNearestFilter', 'NearestFilter', 'NearestMipMapLinearFilter', 'NearestMipMapNearestFilter']

mapping = Enum('UVMapping')

any of ['CubeReflectionMapping', 'CubeRefractionMapping', 'CubeUVReflectionMapping', 'CubeUVRefractionMapping', 'EquirectangularReflectionMapping', 'EquirectangularRefractionMapping', 'SphericalReflectionMapping', 'UVMapping']

minFilter = Enum('LinearMipMapLinearFilter')

any of ['LinearFilter', 'LinearMipMapLinearFilter', 'LinearMipMapNearestFilter', 'NearestFilter', 'NearestMipMapLinearFilter', 'NearestMipMapNearestFilter']

name = Unicode('')

a unicode string

offset = Vector2((0, 0))

a tuple of any type

premultiplyAlpha = Bool(False)

a boolean

repeat = Vector2((0, 0))

a tuple of any type

rotation = CFloat(0)

a float

type = Enum('UnsignedByteType')

any of ['ByteType', 'FloatType', 'HalfFloatType', 'IntType', 'ShortType', 'UnsignedByteType', 'UnsignedIntType', 'UnsignedShortType']

unpackAlignment = CInt(4)

an int

version = CInt(0)

an int

wrapS = Enum('ClampToEdgeWrapping')

any of ['ClampToEdgeWrapping', 'MirroredRepeatWrapping', 'RepeatWrapping']

```
wrapT = Enum('ClampToEdgeWrapping')
    any of ['ClampToEdgeWrapping', 'MirroredRepeatWrapping', 'RepeatWrapping']
```

VideoTexture

```
class pythreejs.VideoTexture
```

```
VideoTexture
```

Autogenerated by generate-wrappers.js See <https://threejs.org/docs/#api/textures/VideoTexture>

Inherits *ThreeWidget*.

Three.js docs: <https://threejs.org/docs/#api/textures/VideoTexture>

2.5.18 traits

```
class pythreejs.traits.Color (default_value=traitlets.Undefined, allow_none=False,
                             read_only=None, help=None, config=None, **kwargs)
```

A string holding a valid HTML color such as 'blue', '#060482', '#A80'

```
default_value = traitlets.Undefined
```

```
info_text = 'a valid HTML color'
```

```
validate (obj, value)
```

```
class pythreejs.traits.Euler (default_value=traitlets.Undefined, **kwargs)
```

A trait for a set of Euler angles.

Expressed as a tuple of tree floats (the angles), and the order as a string. See the three.js docs for futher details.

```
default_value = (0, 0, 0, 'XYZ')
```

```
info_text = 'a set of Euler angles'
```

```
class pythreejs.traits.Face3 (**kwargs)
```

A trait for a named tuple corresponding to a three.js Face3.

Accepts named tuples with the field names: ('a', 'b', 'c', 'normal', 'color', 'materialIndex')

```
info_text = 'a named tuple representing a Face3'
```

```
class
```

```
alias of Face3
```

```
class pythreejs.traits.Matrix3 (trait=<class 'traitlets.traitlets.CFloat'>, de-
                               fault_value=traitlets.Undefined, **kwargs)
```

A trait for a 9-tuple corresponding to a three.js Matrix3.

```
default_value = (1, 0, 0, 0, 1, 0, 0, 0, 1)
```

```
info_text = 'a three-by-three matrix (9 element tuple)'
```

```
class pythreejs.traits.Matrix4 (trait=<class 'traitlets.traitlets.CFloat'>, de-
                               fault_value=traitlets.Undefined, **kwargs)
```

A trait for a 16-tuple corresponding to a three.js Matrix4.

```
default_value = (1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1)
```

```
info_text = 'a four-by-four matrix (16 element tuple)'
```

```
class pythreejs.traits.Uniform (default_value=traitlets.Undefined, **kwargs)
```

A dict holding uniforms for a ShaderMaterial

```

class pythreejs.traits.Uninitialized
    Placeholder sentinel used while waiting for a initialization via sync

class pythreejs.traits.Vector2 (trait=<class      'traitlets.traitlets.CFloat'>,      de-
                               fault_value=traitlets.Undefined, **kwargs)
    A trait for a 2-tuple corresponding to a three.js Vector2.

    default_value = (0, 0)

    info_text = 'a two-element vector'

class pythreejs.traits.Vector3 (trait=<class      'traitlets.traitlets.CFloat'>,      de-
                               fault_value=traitlets.Undefined, **kwargs)
    A trait for a 3-tuple corresponding to a three.js Vector3.

    default_value = (0, 0, 0)

    info_text = 'a three-element vector'

class pythreejs.traits.Vector4 (trait=<class      'traitlets.traitlets.CFloat'>,      de-
                               fault_value=traitlets.Undefined, **kwargs)
    A trait for a 4-tuple corresponding to a three.js Vector4.

    default_value = (0, 0, 0, 0)

    info_text = 'a four-element vector'

class pythreejs.traits.WebGLDataUnion (default_value=traitlets.Undefined,      dtype=None,
                                       shape_constraint=None,      kw_array=None,
                                       kw_widget=None, **kwargs)
    A trait that accepts either a numpy array, or an NDArrayWidget reference.

    Also constrains the use of 64-bit arrays, as this is not supported by WebGL.

    validate (obj, value)

```

2.6 Extending pythreejs

While you can do a lot with pythreejs out of the box, you might have some custom rendering you want to do, that would be more efficient to configure as a separate widget. To be able to integrate such objects with pythreejs, the following extension guide can be helpful.

2.6.1 Blackbox object

Pythreejs exports a *Blackbox* Widget, which inherits *Object3D*. The intention is for third-party widget libraries to inherit from it on both the Python and JS side. You would add the traits needed to set up your object, and have the JS side set up the corresponding three.js object. The three.js object itself would not be synced across the wire, which is why it is called a blackbox, but you can still manipulate it in a scene (transforming, putting it as a child, etc.). This can be very efficient e.g. for complex, generated objects, where the final three.js data would be prohibitively expensive to synchronize.

Example implementation

Below is an example implementation for rendering a crystal lattice. It takes a basis structure, and then tiles copies of this basis in x/y/z, potentially generating thousands of spheres.

Note: This example is not a good/optimized crystal structure viewer. It is merely used to convey the concept of a widget with a few parameters translating to something with potentially high amounts of data/objects.

Python:

```
import traitlets
import pythreejs

class CubicLattice(pythreejs.Blackbox):
    _model_name: traitlets.Unicode('CubicLatticeModel').tag(sync=True)
    _model_module = traitlets.Unicode('my_module_name').tag(sync=True)

    basis = traitlets.List(
        trait=pythreejs.Vector3(),
        default_value=[[0, 0, 0]],
        max_length=5
    ).tag(sync=True)

    repetitions = traitlets.List(
        trait=traitlets.Int(),
        default_value=[5, 5, 5],
        min_length=3,
        max_length=3
    ).tag(sync=True)
```

JavaScript:

```
import * as THREE from "three";

import {
    BlackboxModel
} from 'jupyter-threejs';

const atomGeometry = new THREE.SphereBufferGeometry(0.2, 16, 8);
const atomMaterials = [
    new THREE.MeshLambertMaterial({color: 'red'}),
    new THREE.MeshLambertMaterial({color: 'green'}),
    new THREE.MeshLambertMaterial({color: 'yellow'}),
    new THREE.MeshLambertMaterial({color: 'blue'}),
    new THREE.MeshLambertMaterial({color: 'cyan'}),
];

export class CubicLatticeModel extends BlackboxModel {
    defaults() {
        return {...super.defaults(), ...{
            _model_name: 'CubicLatticeModel',
            _model_module: 'my_module_name',
            basis: [[0, 0, 0]],
            repetitions: [5, 5, 5],
        }};
    }

    // This method is called to create the three.js object of the model:
    constructThreeObject() {
        const root = new THREE.Group();
```

(continues on next page)

(continued from previous page)

```

    // Create the children of this group:
    // This is the part that is specific to this example
    this.createLattice(root);
    return root;
}

// This method is called whenever the model changes:
onChange(model, options) {
    super.onChange(model, options);
    // If any of the parameters change, simply rebuild children:
    this.createLattice();
}

// Our custom method to build the lattice:
createLattice(obj) {
    obj = obj || this.obj;

    // Set up the basis to tile:
    const basisInput = this.get('basis');
    const basis = new THREE.Group();
    for (let i=0; i < basisInput.length; ++i) {
        let mesh = new THREE.Mesh(atomGeometry, atomMaterials[i]);
        mesh.position.fromArray(basisInput[i]);
        basis.add(mesh);
    }

    // Tile in x, y, z:
    const [nx, ny, nz] = this.get('repetitions');
    const children = [];
    for (let x = 0; x < nx; ++x) {
        for (let y = 0; y < ny; ++y) {
            for (let z = 0; z < nz; ++z) {
                let copy = basis.clone();
                copy.position.set(x, y, z);
                children.push(copy);
            }
        }
    }

    obj.remove(...obj.children);
    obj.add(...children);
}
}

```

This code should then be wrapped up in a widget extension (see documentation from ipywidgets on how to do this).

Usage:

```

import pythreejs
from IPython.display import display
from my_module import CubicLattice

lattice = CubicLattice(basis=[[0,0,0], [0.5, 0.5, 0.5]])

# Preview the lattice directly:
display(lattice)

```

(continues on next page)

```
# Or put it in a scene:
width=600
height=400
key_light = pythreejs.DirectionalLight(position=[-5, 5, 3], intensity=0.7)
ambient_light = pythreejs.AmbientLight(color='#777777')

camera = pythreejs.PerspectiveCamera(
    position=[-5, 0, -5],
    children=[
        # Have the key light follow the camera:
        key_light
    ],
    aspect=width/height,
)
control = pythreejs.OrbitControls(controlling=camera)

scene = pythreejs.Scene(children=[lattice, camera, ambient_light])

renderer = pythreejs.Renderer(camera=camera,
                               scene=scene,
                               controls=[control],
                               width=width, height=height)

display(renderer)
```




Fig. 1: Figure: Example view of the rendered lattice object.

2.7 Developer install

To install a developer version of pythreejs, you will first need to clone the repository:

```
git clone https://github.com/jupyter-widgets/pythreejs.git
cd pythreejs
```

Next, install it with a develop install using pip:

```
pip install -e .
```

If you are not planning on working on the JS/frontend code, you can simply install the extensions as you would for a *normal install*. For a JS develop install, you should link your extensions:

```
jupyter nbextension install [--sys-prefix / --user / --system] --symlink --py_
↳pythreejs
jupyter nbextension enable [--sys-prefix / --user / --system] --py pythreejs
```

with the [appropriate flag](#). Or, if you are using Jupyterlab:

```
jupyter labextension link ./js
```


p

`pythreejs`, 23

`pythreejs.traits`, 174

Symbols

`_ref_geometry` (pythreejs.BufferGeometry attribute), 47
`_ref_geometry` (pythreejs.Geometry attribute), 49
`_store_ref` (pythreejs.BufferGeometry attribute), 47
`_store_ref` (pythreejs.Geometry attribute), 49

A

`a` (pythreejs.Triangle attribute), 152
`add()` (pythreejs.Object3D method), 54
`all` (pythreejs.Picker attribute), 41
`alphaMap` (pythreejs.MeshBasicMaterial attribute), 118
`alphaMap` (pythreejs.MeshDepthMaterial attribute), 121
`alphaMap` (pythreejs.MeshLambertMaterial attribute), 123
`alphaMap` (pythreejs.MeshMatcapMaterial attribute), 126
`alphaMap` (pythreejs.MeshPhongMaterial attribute), 129
`alphaMap` (pythreejs.MeshStandardMaterial attribute), 135
`alphaTest` (pythreejs.Material attribute), 115
`AmbientLight` (class in pythreejs), 102
`angle` (pythreejs.SpotLight attribute), 107
`AnimationAction` (class in pythreejs), 26
`AnimationClip` (class in pythreejs), 28
`AnimationLoader` (class in pythreejs), 108
`AnimationMixer` (class in pythreejs), 28
`AnimationObjectGroup` (class in pythreejs), 29
`AnimationUtils` (class in pythreejs), 29
`anisotropy` (pythreejs.Texture attribute), 172
`aoMap` (pythreejs.MeshBasicMaterial attribute), 118
`aoMap` (pythreejs.MeshLambertMaterial attribute), 123
`aoMap` (pythreejs.MeshPhongMaterial attribute), 129
`aoMap` (pythreejs.MeshStandardMaterial attribute), 135
`aoMapIntensity` (pythreejs.MeshBasicMaterial attribute), 118
`aoMapIntensity` (pythreejs.MeshLambertMaterial attribute), 123
`aoMapIntensity` (pythreejs.MeshPhongMaterial attribute), 130

`aoMapIntensity` (pythreejs.MeshStandardMaterial attribute), 135
`arc` (pythreejs.TorusBufferGeometry attribute), 84
`arc` (pythreejs.TorusGeometry attribute), 85
`ArcCurve` (class in pythreejs), 57
`array` (pythreejs.BufferAttribute attribute), 46
`array` (pythreejs.InterleavedBuffer attribute), 52
`ArrayCamera` (class in pythreejs), 31
`ArrowHelper` (class in pythreejs), 90
`aspect` (pythreejs.PerspectiveCamera attribute), 36
`aspect` (pythreejs.StereoCamera attribute), 37
`attributes` (pythreejs.BufferGeometry attribute), 47
`Audio` (class in pythreejs), 31
`AudioAnalyser` (class in pythreejs), 30
`AudioListener` (class in pythreejs), 31
`AudioLoader` (class in pythreejs), 108
`autoRotate` (pythreejs.OrbitControls attribute), 39
`autoRotateSpeed` (pythreejs.OrbitControls attribute), 39
`autoUpdate` (pythreejs.Scene attribute), 166
`AxesHelper` (class in pythreejs), 91

B

`b` (pythreejs.Triangle attribute), 152
`background` (pythreejs.Scene attribute), 166
`BaseBufferGeometry` (class in pythreejs), 45
`BaseGeometry` (class in pythreejs), 45
`bias` (pythreejs.LightShadow attribute), 104
`bindMatrix` (pythreejs.SkinnedMesh attribute), 159
`bindMode` (pythreejs.SkinnedMesh attribute), 159
`Blackbox` (class in pythreejs), 153
`blendDst` (pythreejs.Material attribute), 115
`blendDstAlpha` (pythreejs.Material attribute), 115
`blendEquation` (pythreejs.Material attribute), 115
`blendEquationAlpha` (pythreejs.Material attribute), 115
`blending` (pythreejs.Material attribute), 115
`blendSrc` (pythreejs.Material attribute), 115
`blendSrcAlpha` (pythreejs.Material attribute), 115
`Bone` (class in pythreejs), 153
`bones` (pythreejs.Skeleton attribute), 159
`BooleanKeyframeTrack` (class in pythreejs), 25

bottom (pythreejs.OrthographicCamera attribute), 35
 box (pythreejs.Box3Helper attribute), 91
 Box2 (class in pythreejs), 146
 Box3 (class in pythreejs), 147
 Box3Helper (class in pythreejs), 91
 BoxBufferGeometry (class in pythreejs), 59
 BoxGeometry (class in pythreejs), 60
 BoxHelper (class in pythreejs), 92
 BoxLineGeometry (class in pythreejs), 61
 BufferAttribute (class in pythreejs), 46
 BufferGeometry (class in pythreejs), 46
 BufferGeometryLoader (class in pythreejs), 108
 bumpMap (pythreejs.MeshMatcapMaterial attribute), 126
 bumpMap (pythreejs.MeshPhongMaterial attribute), 130
 bumpMap (pythreejs.MeshStandardMaterial attribute), 135
 bumpScale (pythreejs.MeshMatcapMaterial attribute), 126
 bumpScale (pythreejs.MeshPhongMaterial attribute), 130
 bumpScale (pythreejs.MeshStandardMaterial attribute), 135

C

c (pythreejs.Triangle attribute), 152
 Cache (class in pythreejs), 108
 Camera (class in pythreejs), 32
 camera (pythreejs.CameraHelper attribute), 93
 camera (pythreejs.LightShadow attribute), 103
 CameraHelper (class in pythreejs), 93
 cameraL (pythreejs.StereoCamera attribute), 37
 cameraR (pythreejs.StereoCamera attribute), 37
 castShadow (pythreejs.Object3D attribute), 54
 CatmullRomCurve3 (class in pythreejs), 57
 center (pythreejs.Sphere attribute), 151
 center (pythreejs.Sprite attribute), 160
 children (pythreejs.Blackbox attribute), 153
 children (pythreejs.Object3D attribute), 53
 CircleBufferGeometry (class in pythreejs), 62
 CircleGeometry (class in pythreejs), 63
 circles (pythreejs.PolarGridHelper attribute), 98
 clampWhenFinished (pythreejs.AnimationAction attribute), 26
 clearCoat (pythreejs.MeshPhysicalMaterial attribute), 134
 clearCoatRoughness (pythreejs.MeshPhysicalMaterial attribute), 134
 clip (pythreejs.AnimationAction attribute), 26
 clipIntersection (pythreejs.Material attribute), 115
 clipping (pythreejs.ShaderMaterial attribute), 142
 clippingPlanes (pythreejs.Material attribute), 115
 clipShadows (pythreejs.Material attribute), 116
 Clock (class in pythreejs), 48
 CloneArray (class in pythreejs), 153
 close (pythreejs.TubeGeometry attribute), 89

Color (class in pythreejs.traits), 174
 color (pythreejs.Box3Helper attribute), 92
 color (pythreejs.BoxHelper attribute), 92
 color (pythreejs.DirectionallightHelper attribute), 93
 color (pythreejs.FaceNormalsHelper attribute), 94
 color (pythreejs.Fog attribute), 165
 color (pythreejs.FogExp2 attribute), 164
 color (pythreejs.HemisphereLightHelper attribute), 96
 color (pythreejs.Light attribute), 104
 color (pythreejs.LineBasicMaterial attribute), 111
 color (pythreejs.LineDashedMaterial attribute), 112
 color (pythreejs.LineMaterial attribute), 113
 color (pythreejs.MeshBasicMaterial attribute), 118
 color (pythreejs.MeshLambertMaterial attribute), 123
 color (pythreejs.MeshMatcapMaterial attribute), 126
 color (pythreejs.MeshPhongMaterial attribute), 130
 color (pythreejs.MeshStandardMaterial attribute), 135
 color (pythreejs.PlaneHelper attribute), 97
 color (pythreejs.PointLightHelper attribute), 97
 color (pythreejs.PointsMaterial attribute), 140
 color (pythreejs.RectAreaLightHelper attribute), 99
 color (pythreejs.SpotLightHelper attribute), 100
 color (pythreejs.SpriteMaterial attribute), 144
 color (pythreejs.TextTexture attribute), 170
 color (pythreejs.VertexNormalsHelper attribute), 101
 color1 (pythreejs.PolarGridHelper attribute), 98
 color2 (pythreejs.PolarGridHelper attribute), 98
 colorCenterLine (pythreejs.GridHelper attribute), 95
 colorGrid (pythreejs.GridHelper attribute), 95
 ColorKeyframeTrack (class in pythreejs), 25
 colors (pythreejs.Geometry attribute), 48
 colors (pythreejs.LineGeometry attribute), 72
 colors (pythreejs.LineSegmentsGeometry attribute), 73
 colorWrite (pythreejs.Material attribute), 116
 combine (pythreejs.MeshBasicMaterial attribute), 118
 combine (pythreejs.MeshLambertMaterial attribute), 123
 combine (pythreejs.MeshPhongMaterial attribute), 130
 CombinedCamera (class in pythreejs), 32
 CompressedTexture (class in pythreejs), 166
 CompressedTextureLoader (class in pythreejs), 109
 ConeGeometry (class in pythreejs), 64
 constant (pythreejs.Plane attribute), 150
 controlling (pythreejs.Controls attribute), 38
 Controls (class in pythreejs), 37
 CubeCamera (class in pythreejs), 34
 CubeTexture (class in pythreejs), 167
 CubeTextureLoader (class in pythreejs), 109
 CubicBezierCurve (class in pythreejs), 57
 CubicBezierCurve3 (class in pythreejs), 57
 CubicInterpolant (class in pythreejs), 146
 Curve (class in pythreejs), 56
 CurvePath (class in pythreejs), 55
 curveSegments (pythreejs.ShapeGeometry attribute), 80
 CylinderBufferGeometry (class in pythreejs), 65

CylinderGeometry (class in pythreejs), 67
 Cylindrical (class in pythreejs), 147

D

dampingFactor (pythreejs.OrbitControls attribute), 39
 dashScale (pythreejs.LineMaterial attribute), 114
 dashSize (pythreejs.LineDashedMaterial attribute), 113
 dashSize (pythreejs.LineMaterial attribute), 114
 data (pythreejs.DataTexture attribute), 168
 data (pythreejs.DataTexture3D attribute), 167
 data (pythreejs.InterleavedBufferAttribute attribute), 51
 DataTexture (class in pythreejs), 168
 DataTexture3D (class in pythreejs), 167
 DataTextureLoader (class in pythreejs), 109
 decay (pythreejs.PointLight attribute), 105
 decay (pythreejs.SpotLight attribute), 107
 default_value (pythreejs.traits.Color attribute), 174
 default_value (pythreejs.traits.Euler attribute), 174
 default_value (pythreejs.traits.Matrix3 attribute), 174
 default_value (pythreejs.traits.Matrix4 attribute), 174
 default_value (pythreejs.traits.Vector2 attribute), 175
 default_value (pythreejs.traits.Vector3 attribute), 175
 default_value (pythreejs.traits.Vector4 attribute), 175
 defines (pythreejs.Material attribute), 116
 defines (pythreejs.MeshPhysicalMaterial attribute), 134
 defines (pythreejs.MeshStandardMaterial attribute), 135
 density (pythreejs.FogExp2 attribute), 164
 depth (pythreejs.BoxBufferGeometry attribute), 59
 depth (pythreejs.BoxGeometry attribute), 60
 depth (pythreejs.BoxLineGeometry attribute), 62
 depthFunc (pythreejs.Material attribute), 116
 depthSegments (pythreejs.BoxBufferGeometry attribute), 59
 depthSegments (pythreejs.BoxGeometry attribute), 61
 depthSegments (pythreejs.BoxLineGeometry attribute), 62
 depthTest (pythreejs.Material attribute), 116
 DepthTexture (class in pythreejs), 168
 depthWrite (pythreejs.Material attribute), 116
 detail (pythreejs.DodecahedronGeometry attribute), 68
 detail (pythreejs.IcosahedronGeometry attribute), 70
 detail (pythreejs.OctahedronGeometry attribute), 73
 detail (pythreejs.PolyhedronGeometry attribute), 77
 detail (pythreejs.TetrahedronGeometry attribute), 83
 dir (pythreejs.ArrowHelper attribute), 90
 DirectGeometry (class in pythreejs), 48
 direction (pythreejs.Ray attribute), 151
 direction (pythreejs.Raycaster attribute), 55
 DirectionalLight (class in pythreejs), 102
 DirectionalLightHelper (class in pythreejs), 93
 DirectionalLightShadow (class in pythreejs), 102
 DiscreteInterpolant (class in pythreejs), 146
 displacementBias (pythreejs.MeshDepthMaterial attribute), 121

displacementBias (pythreejs.MeshMatcapMaterial attribute), 127
 displacementBias (pythreejs.MeshPhongMaterial attribute), 130
 displacementBias (pythreejs.MeshStandardMaterial attribute), 136
 displacementMap (pythreejs.MeshDepthMaterial attribute), 121
 displacementMap (pythreejs.MeshMatcapMaterial attribute), 126
 displacementMap (pythreejs.MeshPhongMaterial attribute), 130
 displacementMap (pythreejs.MeshStandardMaterial attribute), 135
 displacementScale (pythreejs.MeshDepthMaterial attribute), 121
 displacementScale (pythreejs.MeshMatcapMaterial attribute), 126
 displacementScale (pythreejs.MeshPhongMaterial attribute), 130
 displacementScale (pythreejs.MeshStandardMaterial attribute), 136
 distance (pythreejs.Picker attribute), 41
 distance (pythreejs.PointLight attribute), 105
 distance (pythreejs.SpotLight attribute), 107
 dithering (pythreejs.Material attribute), 116
 divisions (pythreejs.GridHelper attribute), 95
 divisions (pythreejs.PolarGridHelper attribute), 98
 DodecahedronGeometry (class in pythreejs), 68
 drawMode (pythreejs.Mesh attribute), 158
 duration (pythreejs.AnimationClip attribute), 28
 dynamic (pythreejs.BufferAttribute attribute), 46
 dynamic (pythreejs.InterleavedBuffer attribute), 52
 dynamicDampingFactor (pythreejs.TrackballControls attribute), 44

E

EdgesGeometry (class in pythreejs), 69
 EllipseCurve (class in pythreejs), 57
 emissive (pythreejs.MeshLambertMaterial attribute), 123
 emissive (pythreejs.MeshPhongMaterial attribute), 130
 emissive (pythreejs.MeshStandardMaterial attribute), 136
 emissiveIntensity (pythreejs.MeshLambertMaterial attribute), 123
 emissiveIntensity (pythreejs.MeshPhongMaterial attribute), 130
 emissiveIntensity (pythreejs.MeshStandardMaterial attribute), 136
 emissiveMap (pythreejs.MeshLambertMaterial attribute), 123
 emissiveMap (pythreejs.MeshPhongMaterial attribute), 130
 emissiveMap (pythreejs.MeshStandardMaterial attribute), 136

enabled (pythreejs.AnimationAction attribute), 27
 enabled (pythreejs.OrbitControls attribute), 39
 enabled (pythreejs.TrackballControls attribute), 43
 enabled (pythreejs.WebGLShadowMap attribute), 163
 enableDamping (pythreejs.OrbitControls attribute), 39
 enableKeys (pythreejs.OrbitControls attribute), 39
 enablePan (pythreejs.OrbitControls attribute), 39
 enableRotate (pythreejs.OrbitControls attribute), 39
 enableZoom (pythreejs.OrbitControls attribute), 39
 encoding (pythreejs.Texture attribute), 172
 end (pythreejs.Line3 attribute), 149
 envMap (pythreejs.MeshBasicMaterial attribute), 118
 envMap (pythreejs.MeshLambertMaterial attribute), 123
 envMap (pythreejs.MeshPhongMaterial attribute), 131
 envMap (pythreejs.MeshStandardMaterial attribute), 136
 envMapIntensity (pythreejs.MeshStandardMaterial attribute), 136
 Euler (class in pythreejs.traits), 174
 event (pythreejs.Picker attribute), 41
 EventDispatcher (class in pythreejs), 48
 exec_three_obj_method() (pythreejs.ThreeWidget method), 24
 extensions (pythreejs.ShaderMaterial attribute), 142
 ExtrudeGeometry (class in pythreejs), 69
 eyeSep (pythreejs.StereoCamera attribute), 37

F

face (pythreejs.Picker attribute), 41
 Face3 (class in pythreejs.traits), 174
 faceIndex (pythreejs.Picker attribute), 42
 faceNormal (pythreejs.Picker attribute), 41
 FaceNormalsHelper (class in pythreejs), 94
 faces (pythreejs.Geometry attribute), 48
 faces (pythreejs.PolyhedronGeometry attribute), 77
 faceVertexUvs (pythreejs.Geometry attribute), 49
 faceVertices (pythreejs.Picker attribute), 42
 far (pythreejs.CombinedCamera attribute), 33
 far (pythreejs.Fog attribute), 165
 far (pythreejs.OrthographicCamera attribute), 35
 far (pythreejs.PerspectiveCamera attribute), 36
 far (pythreejs.Raycaster attribute), 55
 FileLoader (class in pythreejs), 109
 flatShading (pythreejs.Material attribute), 116
 flatShading (pythreejs.ShaderMaterial attribute), 142
 flipY (pythreejs.DataTexture attribute), 168
 flipY (pythreejs.DataTexture3D attribute), 167
 flipY (pythreejs.DepthTexture attribute), 169
 flipY (pythreejs.Texture attribute), 172
 FlyControls (class in pythreejs), 38
 focus (pythreejs.PerspectiveCamera attribute), 36
 Fog (class in pythreejs), 165
 fog (pythreejs.LineMaterial attribute), 114
 fog (pythreejs.Material attribute), 116
 fog (pythreejs.MeshDepthMaterial attribute), 121

fog (pythreejs.MeshNormalMaterial attribute), 128
 fog (pythreejs.Scene attribute), 165
 fog (pythreejs.ShaderMaterial attribute), 142
 fog (pythreejs.SpriteMaterial attribute), 144
 FogExp2 (class in pythreejs), 164
 Font (class in pythreejs), 56
 fontFace (pythreejs.TextTexture attribute), 170
 FontLoader (class in pythreejs), 109
 format (pythreejs.DepthTexture attribute), 169
 format (pythreejs.Texture attribute), 171
 fov (pythreejs.CombinedCamera attribute), 32
 fov (pythreejs.PerspectiveCamera attribute), 36
 fragmentShader (pythreejs.ShaderMaterial attribute), 142
 freeze() (pythreejs.RenderableWidget method), 24
 from_geometry() (pythreejs.BufferGeometry class method), 47
 from_geometry() (pythreejs.Geometry class method), 49
 Frustum (class in pythreejs), 148
 frustumCulled (pythreejs.Object3D attribute), 54
 func (pythreejs.ParametricGeometry attribute), 74

G

gapSize (pythreejs.LineDashedMaterial attribute), 113
 gapSize (pythreejs.LineMaterial attribute), 114
 generateMipmaps (pythreejs.DataTexture attribute), 168
 generateMipmaps (pythreejs.DataTexture3D attribute), 167
 generateMipmaps (pythreejs.DepthTexture attribute), 169
 generateMipmaps (pythreejs.Texture attribute), 172
 Geometry (class in pythreejs), 48
 geometry (pythreejs.Line attribute), 157
 geometry (pythreejs.Line2 attribute), 155
 geometry (pythreejs.LineSegments2 attribute), 156
 geometry (pythreejs.Mesh attribute), 158
 geometry (pythreejs.Points attribute), 158
 geometry (pythreejs.WireframeGeometry attribute), 89
 gradientMap (pythreejs.MeshToonMaterial attribute), 140
 GridHelper (class in pythreejs), 95
 groundColor (pythreejs.HemisphereLight attribute), 103
 Group (class in pythreejs), 154

H

headLength (pythreejs.ArrowHelper attribute), 90
 headWidth (pythreejs.ArrowHelper attribute), 90
 height (pythreejs.BoxBufferGeometry attribute), 59
 height (pythreejs.BoxGeometry attribute), 60
 height (pythreejs.BoxLineGeometry attribute), 61
 height (pythreejs.CombinedCamera attribute), 33
 height (pythreejs.ConeGeometry attribute), 64
 height (pythreejs.CylinderBufferGeometry attribute), 66
 height (pythreejs.CylinderGeometry attribute), 67
 height (pythreejs.DepthTexture attribute), 168
 height (pythreejs.PlaneBufferGeometry attribute), 75
 height (pythreejs.PlaneGeometry attribute), 76

height (pythreejs.RectAreaLight attribute), 106
heightSegments (pythreejs.BoxBufferGeometry attribute), 59
heightSegments (pythreejs.BoxGeometry attribute), 61
heightSegments (pythreejs.BoxLineGeometry attribute), 62
heightSegments (pythreejs.ConeGeometry attribute), 65
heightSegments (pythreejs.CylinderBufferGeometry attribute), 66
heightSegments (pythreejs.CylinderGeometry attribute), 67
heightSegments (pythreejs.PlaneBufferGeometry attribute), 75
heightSegments (pythreejs.PlaneGeometry attribute), 76
heightSegments (pythreejs.SphereBufferGeometry attribute), 81
heightSegments (pythreejs.SphereGeometry attribute), 82
HemisphereLight (class in pythreejs), 103
HemisphereLightHelper (class in pythreejs), 96
hex (pythreejs.ArrowHelper attribute), 90

I

IcosahedronGeometry (class in pythreejs), 70
ImageBitmapLoader (class in pythreejs), 110
ImageLoader (class in pythreejs), 110
images (pythreejs.CubeTexture attribute), 167
ImageTexture (class in pythreejs), 170
imageUri (pythreejs.ImageTexture attribute), 170
ImmediateRenderObject (class in pythreejs), 59
impersonate (pythreejs.CombinedCamera attribute), 33
index (pythreejs.BufferGeometry attribute), 47
indices (pythreejs.Picker attribute), 42
indices (pythreejs.PolyhedronGeometry attribute), 76
info_text (pythreejs.traits.Color attribute), 174
info_text (pythreejs.traits.Euler attribute), 174
info_text (pythreejs.traits.Face3 attribute), 174
info_text (pythreejs.traits.Matrix3 attribute), 174
info_text (pythreejs.traits.Matrix4 attribute), 174
info_text (pythreejs.traits.Vector2 attribute), 175
info_text (pythreejs.traits.Vector3 attribute), 175
info_text (pythreejs.traits.Vector4 attribute), 175
innerRadius (pythreejs.RingBufferGeometry attribute), 77
innerRadius (pythreejs.RingGeometry attribute), 79
InstancedBufferAttribute (class in pythreejs), 50
InstancedBufferGeometry (class in pythreejs), 50
InstancedInterleavedBuffer (class in pythreejs), 50
intensity (pythreejs.Light attribute), 104
InterleavedBuffer (class in pythreejs), 51
InterleavedBufferAttribute (class in pythreejs), 51
Interpolant (class in pythreejs), 149
interpolation (pythreejs.KeyframeTrack attribute), 30
itemSize (pythreejs.InterleavedBufferAttribute attribute), 51

J

JSONLoader (class in pythreejs), 110

K

KeyframeTrack (class in pythreejs), 29
keyPanSpeed (pythreejs.OrbitControls attribute), 40
klass (pythreejs.traits.Face3 attribute), 174

L

LatheBufferGeometry (class in pythreejs), 70
LatheGeometry (class in pythreejs), 71
Layers (class in pythreejs), 52
left (pythreejs.OrthographicCamera attribute), 34
length (pythreejs.ArrowHelper attribute), 90
Light (class in pythreejs), 104
light (pythreejs.DirectionallightHelper attribute), 93
light (pythreejs.HemisphereLightHelper attribute), 96
light (pythreejs.PointLightHelper attribute), 97
light (pythreejs.RectAreaLightHelper attribute), 99
light (pythreejs.SpotLightHelper attribute), 100
lightMap (pythreejs.MeshBasicMaterial attribute), 119
lightMap (pythreejs.MeshLambertMaterial attribute), 124
lightMap (pythreejs.MeshPhongMaterial attribute), 131
lightMap (pythreejs.MeshStandardMaterial attribute), 136
lightMapIntensity (pythreejs.MeshBasicMaterial attribute), 119
lightMapIntensity (pythreejs.MeshLambertMaterial attribute), 124
lightMapIntensity (pythreejs.MeshPhongMaterial attribute), 131
lightMapIntensity (pythreejs.MeshStandardMaterial attribute), 136
lights (pythreejs.LineBasicMaterial attribute), 111
lights (pythreejs.LineDashedMaterial attribute), 112
lights (pythreejs.LineMaterial attribute), 114
lights (pythreejs.Material attribute), 116
lights (pythreejs.MeshBasicMaterial attribute), 119
lights (pythreejs.MeshDepthMaterial attribute), 121
lights (pythreejs.MeshMatcapMaterial attribute), 127
lights (pythreejs.MeshNormalMaterial attribute), 128
lights (pythreejs.PointsMaterial attribute), 140
lights (pythreejs.ShaderMaterial attribute), 142
lights (pythreejs.ShadowMaterial attribute), 144
lights (pythreejs.SpriteMaterial attribute), 145
LightShadow (class in pythreejs), 103
Line (class in pythreejs), 157
Line2 (class in pythreejs), 155
Line3 (class in pythreejs), 149
LinearInterpolant (class in pythreejs), 146
LineBasicMaterial (class in pythreejs), 111
linecap (pythreejs.LineBasicMaterial attribute), 112
LineCurve (class in pythreejs), 58

LineCurve3 (class in pythreejs), 58
 LineDashedMaterial (class in pythreejs), 112
 lineDistances (pythreejs.Geometry attribute), 49
 LineGeometry (class in pythreejs), 72
 lineJoin (pythreejs.LineBasicMaterial attribute), 112
 LineLoop (class in pythreejs), 155
 LineMaterial (class in pythreejs), 113
 linePrecision (pythreejs.Raycaster attribute), 55
 LineSegments (class in pythreejs), 156
 LineSegments2 (class in pythreejs), 156
 LineSegmentsGeometry (class in pythreejs), 73
 lineWidth (pythreejs.FaceNormalsHelper attribute), 94
 lineWidth (pythreejs.LineBasicMaterial attribute), 111
 lineWidth (pythreejs.LineDashedMaterial attribute), 112
 lineWidth (pythreejs.LineMaterial attribute), 114
 lineWidth (pythreejs.ShaderMaterial attribute), 142
 lineWidth (pythreejs.VertexNormalsHelper attribute), 101
 Loader (class in pythreejs), 110
 LoadingManager (class in pythreejs), 110
 localRoot (pythreejs.AnimationAction attribute), 26
 LOD (class in pythreejs), 154
 log() (pythreejs.RenderableWidget method), 24
 lookAt() (pythreejs.Object3D method), 54
 loop (pythreejs.AnimationAction attribute), 27

M

magFilter (pythreejs.DataTexture attribute), 168
 magFilter (pythreejs.DataTexture3D attribute), 167
 magFilter (pythreejs.DepthTexture attribute), 169
 magFilter (pythreejs.Texture attribute), 171
 map (pythreejs.MeshBasicMaterial attribute), 119
 map (pythreejs.MeshDepthMaterial attribute), 121
 map (pythreejs.MeshLambertMaterial attribute), 124
 map (pythreejs.MeshMatcapMaterial attribute), 127
 map (pythreejs.MeshPhongMaterial attribute), 131
 map (pythreejs.MeshStandardMaterial attribute), 136
 map (pythreejs.PointsMaterial attribute), 140
 map (pythreejs.SpriteMaterial attribute), 145
 mapping (pythreejs.Texture attribute), 171
 mapSize (pythreejs.LightShadow attribute), 104
 matcap (pythreejs.MeshMatcapMaterial attribute), 127
 Material (class in pythreejs), 115
 material (pythreejs.Line attribute), 157
 material (pythreejs.Line2 attribute), 155
 material (pythreejs.LineSegments2 attribute), 156
 material (pythreejs.Mesh attribute), 157
 material (pythreejs.Points attribute), 158
 material (pythreejs.ShapeGeometry attribute), 80
 material (pythreejs.Sprite attribute), 160
 MaterialLoader (class in pythreejs), 111
 Math (class in pythreejs), 150
 matrix (pythreejs.Object3D attribute), 53
 Matrix3 (class in pythreejs.traits), 174
 Matrix4 (class in pythreejs.traits), 174

matrixAutoUpdate (pythreejs.Object3D attribute), 53
 matrixWorld (pythreejs.Object3D attribute), 53
 matrixWorldInverse (pythreejs.Camera attribute), 32
 matrixWorldNeedsUpdate (pythreejs.Object3D attribute), 54
 max (pythreejs.Box2 attribute), 147
 max (pythreejs.Box3 attribute), 147
 maxAzimuthAngle (pythreejs.OrbitControls attribute), 40
 maxDistance (pythreejs.OrbitControls attribute), 40
 maxDistance (pythreejs.TrackballControls attribute), 43
 MaxIndex (pythreejs.BufferGeometry attribute), 47
 maxInstancedCount (pythreejs.InstancedBufferGeometry attribute), 50
 maxPolarAngle (pythreejs.OrbitControls attribute), 40
 maxZoom (pythreejs.OrbitControls attribute), 40
 merge (pythreejs.CloneArray attribute), 154
 Mesh (class in pythreejs), 157
 MeshBasicMaterial (class in pythreejs), 118
 MeshDepthMaterial (class in pythreejs), 121
 MeshLambertMaterial (class in pythreejs), 123
 MeshMatcapMaterial (class in pythreejs), 126
 MeshNormalMaterial (class in pythreejs), 128
 meshPerAttribute (pythreejs.InstancedBufferAttribute attribute), 50
 meshPerAttribute (pythreejs.InstancedInterleavedBuffer attribute), 50
 MeshPhongMaterial (class in pythreejs), 129
 MeshPhysicalMaterial (class in pythreejs), 134
 MeshStandardMaterial (class in pythreejs), 135
 MeshToonMaterial (class in pythreejs), 139
 metalness (pythreejs.MeshStandardMaterial attribute), 136
 metalnessMap (pythreejs.MeshStandardMaterial attribute), 137
 min (pythreejs.Box2 attribute), 147
 min (pythreejs.Box3 attribute), 147
 minAzimuthAngle (pythreejs.OrbitControls attribute), 40
 minDistance (pythreejs.OrbitControls attribute), 40
 minDistance (pythreejs.TrackballControls attribute), 43
 minFilter (pythreejs.DataTexture attribute), 168
 minFilter (pythreejs.DataTexture3D attribute), 167
 minFilter (pythreejs.DepthTexture attribute), 169
 minFilter (pythreejs.Texture attribute), 171
 minPolarAngle (pythreejs.OrbitControls attribute), 40
 minZoom (pythreejs.OrbitControls attribute), 40
 mixer (pythreejs.AnimationAction attribute), 26
 mode (pythreejs.CombinedCamera attribute), 33
 modelViewMatrix (pythreejs.Object3D attribute), 53
 modifiers (pythreejs.Picker attribute), 42
 morphAttributes (pythreejs.BufferGeometry attribute), 47
 morphNormals (pythreejs.Geometry attribute), 49
 morphNormals (pythreejs.MeshLambertMaterial attribute), 124

- morphNormals (pythreejs.MeshMatcapMaterial attribute), 127
 - morphNormals (pythreejs.MeshPhongMaterial attribute), 131
 - morphNormals (pythreejs.MeshStandardMaterial attribute), 137
 - morphNormals (pythreejs.ShaderMaterial attribute), 142
 - morphTargetInfluences (pythreejs.Mesh attribute), 158
 - morphTargets (pythreejs.Geometry attribute), 49
 - morphTargets (pythreejs.MeshBasicMaterial attribute), 119
 - morphTargets (pythreejs.MeshDepthMaterial attribute), 122
 - morphTargets (pythreejs.MeshLambertMaterial attribute), 124
 - morphTargets (pythreejs.MeshMatcapMaterial attribute), 127
 - morphTargets (pythreejs.MeshNormalMaterial attribute), 129
 - morphTargets (pythreejs.MeshPhongMaterial attribute), 131
 - morphTargets (pythreejs.MeshStandardMaterial attribute), 137
 - morphTargets (pythreejs.PointsMaterial attribute), 140
 - morphTargets (pythreejs.ShaderMaterial attribute), 142
 - movementSpeed (pythreejs.FlyControls attribute), 38
 - moveVector (pythreejs.FlyControls attribute), 38
- ## N
- name (pythreejs.AnimationClip attribute), 28
 - name (pythreejs.BaseBufferGeometry attribute), 45
 - name (pythreejs.BaseGeometry attribute), 45
 - name (pythreejs.Fog attribute), 165
 - name (pythreejs.FogExp2 attribute), 164
 - name (pythreejs.KeyframeTrack attribute), 29
 - name (pythreejs.Material attribute), 116
 - name (pythreejs.Object3D attribute), 52
 - name (pythreejs.Texture attribute), 171
 - near (pythreejs.CombinedCamera attribute), 32
 - near (pythreejs.Fog attribute), 165
 - near (pythreejs.OrthographicCamera attribute), 35
 - near (pythreejs.PerspectiveCamera attribute), 36
 - near (pythreejs.Raycaster attribute), 55
 - needsUpdate (pythreejs.BufferAttribute attribute), 46
 - needsUpdate (pythreejs.InterleavedBuffer attribute), 52
 - noPan (pythreejs.TrackballControls attribute), 44
 - normal (pythreejs.Plane attribute), 150
 - normalized (pythreejs.BufferAttribute attribute), 46
 - normalized (pythreejs.InterleavedBufferAttribute attribute), 51
 - normalMap (pythreejs.MeshMatcapMaterial attribute), 127
 - normalMap (pythreejs.MeshPhongMaterial attribute), 131
 - normalMap (pythreejs.MeshStandardMaterial attribute), 127
 - normalMatrix (pythreejs.Object3D attribute), 53
 - normalScale (pythreejs.MeshMatcapMaterial attribute), 127
 - normalScale (pythreejs.MeshPhongMaterial attribute), 131
 - normalScale (pythreejs.MeshStandardMaterial attribute), 137
 - noRoll (pythreejs.TrackballControls attribute), 44
 - noRotate (pythreejs.TrackballControls attribute), 44
 - noZoom (pythreejs.TrackballControls attribute), 44
 - NumberKeyframeTrack (class in pythreejs), 25
- ## O
- object (pythreejs.BoxHelper attribute), 92
 - object (pythreejs.FaceNormalsHelper attribute), 94
 - object (pythreejs.Picker attribute), 42
 - object (pythreejs.VertexNormalsHelper attribute), 101
 - Object3D (class in pythreejs), 52
 - ObjectLoader (class in pythreejs), 111
 - OctahedronGeometry (class in pythreejs), 73
 - offset (pythreejs.InterleavedBufferAttribute attribute), 51
 - offset (pythreejs.Texture attribute), 172
 - onNeedsUpdate (pythreejs.Material attribute), 118
 - opacity (pythreejs.Material attribute), 117
 - openEnded (pythreejs.ConeGeometry attribute), 65
 - openEnded (pythreejs.CylinderBufferGeometry attribute), 66
 - openEnded (pythreejs.CylinderGeometry attribute), 67
 - OrbitControls (class in pythreejs), 39
 - origin (pythreejs.ArrowHelper attribute), 90
 - origin (pythreejs.Ray attribute), 151
 - origin (pythreejs.Raycaster attribute), 54
 - original (pythreejs.CloneArray attribute), 153
 - orthoFar (pythreejs.CombinedCamera attribute), 33
 - OrthographicCamera (class in pythreejs), 34
 - orthoNear (pythreejs.CombinedCamera attribute), 33
 - outerRadius (pythreejs.RingBufferGeometry attribute), 77
 - outerRadius (pythreejs.RingGeometry attribute), 79
 - overdraw (pythreejs.Material attribute), 117
 - overrideMaterial (pythreejs.Scene attribute), 166
- ## P
- p (pythreejs.TorusKnotBufferGeometry attribute), 86
 - p (pythreejs.TorusKnotGeometry attribute), 87
 - p0 (pythreejs.Frustum attribute), 148
 - p1 (pythreejs.Frustum attribute), 148
 - p2 (pythreejs.Frustum attribute), 148
 - p3 (pythreejs.Frustum attribute), 148
 - p4 (pythreejs.Frustum attribute), 148
 - p5 (pythreejs.Frustum attribute), 148
 - panSpeed (pythreejs.OrbitControls attribute), 40

panSpeed (pythreejs.TrackballControls attribute), 43
 ParametricGeometry (class in pythreejs), 74
 Path (class in pythreejs), 56
 path (pythreejs.TubeGeometry attribute), 88
 pause() (pythreejs.AnimationAction method), 27
 paused (pythreejs.AnimationAction attribute), 27
 penumbra (pythreejs.SpotLight attribute), 107
 PerspectiveCamera (class in pythreejs), 36
 phiLength (pythreejs.LatheBufferGeometry attribute), 71
 phiLength (pythreejs.LatheGeometry attribute), 71
 phiLength (pythreejs.SphereBufferGeometry attribute), 81
 phiLength (pythreejs.SphereGeometry attribute), 82
 phiSegments (pythreejs.RingBufferGeometry attribute), 78
 phiSegments (pythreejs.RingGeometry attribute), 79
 phiStart (pythreejs.LatheBufferGeometry attribute), 70
 phiStart (pythreejs.LatheGeometry attribute), 71
 phiStart (pythreejs.SphereBufferGeometry attribute), 81
 phiStart (pythreejs.SphereGeometry attribute), 82
 picked (pythreejs.Picker attribute), 42
 Picker (class in pythreejs), 41
 Plane (class in pythreejs), 150
 plane (pythreejs.PlaneHelper attribute), 96
 PlaneBufferGeometry (class in pythreejs), 75
 PlaneGeometry (class in pythreejs), 75
 PlaneHelper (class in pythreejs), 96
 play() (pythreejs.AnimationAction method), 27
 point (pythreejs.Picker attribute), 41
 PointLight (class in pythreejs), 105
 PointLightHelper (class in pythreejs), 97
 Points (class in pythreejs), 158
 points (pythreejs.LatheBufferGeometry attribute), 70
 points (pythreejs.LatheGeometry attribute), 71
 PointsMaterial (class in pythreejs), 140
 PolarGridHelper (class in pythreejs), 98
 polygonOffset (pythreejs.Material attribute), 117
 polygonOffsetFactor (pythreejs.Material attribute), 117
 polygonOffsetUnits (pythreejs.Material attribute), 117
 PolyhedronGeometry (class in pythreejs), 76
 position (pythreejs.Object3D attribute), 53
 PositionalAudio (class in pythreejs), 31
 positions (pythreejs.CloneArray attribute), 154
 positions (pythreejs.LineGeometry attribute), 72
 positions (pythreejs.LineSegmentsGeometry attribute), 73
 power (pythreejs.PointLight attribute), 105
 precision (pythreejs.Material attribute), 117
 premultipliedAlpha (pythreejs.Material attribute), 117
 premultiplyAlpha (pythreejs.Texture attribute), 172
 Preview (class in pythreejs), 23
 projectionMatrix (pythreejs.Camera attribute), 32
 PropertyBinding (class in pythreejs), 30
 PropertyMixer (class in pythreejs), 30

pythreejs (module), 23
 pythreejs.traits (module), 174

Q

q (pythreejs.TorusKnotBufferGeometry attribute), 86
 q (pythreejs.TorusKnotGeometry attribute), 88
 QuadraticBezierCurve (class in pythreejs), 58
 QuadraticBezierCurve3 (class in pythreejs), 58
 Quaternion (class in pythreejs), 150
 quaternion (pythreejs.Object3D attribute), 53
 QuaternionKeyframeTrack (class in pythreejs), 25
 QuaternionLinearInterpolant (class in pythreejs), 146

R

radials (pythreejs.PolarGridHelper attribute), 98
 radialSegments (pythreejs.ConeGeometry attribute), 64
 radialSegments (pythreejs.TorusBufferGeometry attribute), 84
 radialSegments (pythreejs.TorusGeometry attribute), 85
 radialSegments (pythreejs.TorusKnotBufferGeometry attribute), 86
 radialSegments (pythreejs.TorusKnotGeometry attribute), 87
 radius (pythreejs.CircleBufferGeometry attribute), 62
 radius (pythreejs.CircleGeometry attribute), 63
 radius (pythreejs.ConeGeometry attribute), 64
 radius (pythreejs.Cylindrical attribute), 147
 radius (pythreejs.DodecahedronGeometry attribute), 68
 radius (pythreejs.IcosahedronGeometry attribute), 70
 radius (pythreejs.LightShadow attribute), 104
 radius (pythreejs.OctahedronGeometry attribute), 73
 radius (pythreejs.PolarGridHelper attribute), 98
 radius (pythreejs.PolyhedronGeometry attribute), 77
 radius (pythreejs.Sphere attribute), 152
 radius (pythreejs.SphereBufferGeometry attribute), 80
 radius (pythreejs.SphereGeometry attribute), 82
 radius (pythreejs.TetrahedronGeometry attribute), 83
 radius (pythreejs.TorusBufferGeometry attribute), 84
 radius (pythreejs.TorusGeometry attribute), 85
 radius (pythreejs.TorusKnotBufferGeometry attribute), 86
 radius (pythreejs.TorusKnotGeometry attribute), 87
 radius (pythreejs.TubeGeometry attribute), 88
 radiusBottom (pythreejs.CylinderBufferGeometry attribute), 66
 radiusBottom (pythreejs.CylinderGeometry attribute), 67
 radiusSegments (pythreejs.CylinderBufferGeometry attribute), 66
 radiusSegments (pythreejs.CylinderGeometry attribute), 67
 radiusSegments (pythreejs.TubeGeometry attribute), 89
 radiusTop (pythreejs.CylinderBufferGeometry attribute), 66
 radiusTop (pythreejs.CylinderGeometry attribute), 67

- RawShaderMaterial (class in pythreejs), 141
 - Ray (class in pythreejs), 151
 - ray (pythreejs.Raycaster attribute), 55
 - Raycaster (class in pythreejs), 54
 - receiveShadow (pythreejs.Object3D attribute), 54
 - RectAreaLight (class in pythreejs), 106
 - RectAreaLightHelper (class in pythreejs), 99
 - reflectivity (pythreejs.MeshBasicMaterial attribute), 119
 - reflectivity (pythreejs.MeshLambertMaterial attribute), 124
 - reflectivity (pythreejs.MeshPhongMaterial attribute), 131
 - reflectivity (pythreejs.MeshPhysicalMaterial attribute), 134
 - refractionRatio (pythreejs.MeshBasicMaterial attribute), 119
 - refractionRatio (pythreejs.MeshLambertMaterial attribute), 124
 - refractionRatio (pythreejs.MeshPhongMaterial attribute), 131
 - refractionRatio (pythreejs.MeshStandardMaterial attribute), 137
 - remove() (pythreejs.Object3D method), 54
 - RenderableWidget (class in pythreejs), 23
 - renderOrder (pythreejs.Object3D attribute), 54
 - repeat (pythreejs.Texture attribute), 172
 - repetitions (pythreejs.AnimationAction attribute), 27
 - reset() (pythreejs.OrbitControls method), 41
 - right (pythreejs.OrthographicCamera attribute), 35
 - RingBufferGeometry (class in pythreejs), 77
 - RingGeometry (class in pythreejs), 78
 - rollSpeed (pythreejs.FlyControls attribute), 38
 - root (pythreejs.SkeletonHelper attribute), 100
 - rootObject (pythreejs.AnimationMixer attribute), 28
 - rotateSpeed (pythreejs.OrbitControls attribute), 40
 - rotateSpeed (pythreejs.TrackballControls attribute), 43
 - rotateX() (pythreejs.Object3D method), 54
 - rotateY() (pythreejs.Object3D method), 54
 - rotateZ() (pythreejs.Object3D method), 54
 - rotation (pythreejs.Object3D attribute), 53
 - rotation (pythreejs.SpriteMaterial attribute), 145
 - rotation (pythreejs.Texture attribute), 172
 - rotationVector (pythreejs.FlyControls attribute), 38
 - roughness (pythreejs.MeshStandardMaterial attribute), 137
 - roughnessMap (pythreejs.MeshStandardMaterial attribute), 137
- ## S
- scale (pythreejs.LineDashedMaterial attribute), 113
 - scale (pythreejs.Object3D attribute), 53
 - Scene (class in pythreejs), 165
 - screenSpacePanning (pythreejs.OrbitControls attribute), 41
 - segments (pythreejs.CircleBufferGeometry attribute), 63
 - segments (pythreejs.CircleGeometry attribute), 63
 - segments (pythreejs.LatheBufferGeometry attribute), 70
 - segments (pythreejs.LatheGeometry attribute), 71
 - segments (pythreejs.TubeGeometry attribute), 88
 - send_msg() (pythreejs.RenderableWidget method), 24
 - setRotationFromMatrix() (pythreejs.Object3D method), 54
 - ShaderMaterial (class in pythreejs), 141
 - shadow (pythreejs.DirectionLight attribute), 102
 - shadow (pythreejs.PointLight attribute), 105
 - shadow (pythreejs.SpotLight attribute), 107
 - ShadowMaterial (class in pythreejs), 144
 - shadowSide (pythreejs.Material attribute), 117
 - Shape (class in pythreejs), 56
 - ShapeGeometry (class in pythreejs), 80
 - ShapePath (class in pythreejs), 56
 - shapes (pythreejs.ShapeGeometry attribute), 80
 - shininess (pythreejs.MeshPhongMaterial attribute), 131
 - side (pythreejs.Material attribute), 117
 - size (pythreejs.AxesHelper attribute), 91
 - size (pythreejs.DirectionLightHelper attribute), 93
 - size (pythreejs.FaceNormalsHelper attribute), 94
 - size (pythreejs.GridHelper attribute), 95
 - size (pythreejs.HemisphereLightHelper attribute), 96
 - size (pythreejs.PlaneHelper attribute), 96
 - size (pythreejs.PointsMaterial attribute), 140
 - size (pythreejs.TextTexture attribute), 170
 - size (pythreejs.VertexNormalsHelper attribute), 101
 - sizeAttenuation (pythreejs.PointsMaterial attribute), 140
 - sizeAttenuation (pythreejs.SpriteMaterial attribute), 145
 - Skeleton (class in pythreejs), 159
 - skeleton (pythreejs.SkinnedMesh attribute), 160
 - SkeletonHelper (class in pythreejs), 100
 - skinIndices (pythreejs.Geometry attribute), 49
 - SkinnedMesh (class in pythreejs), 159
 - skinning (pythreejs.MeshBasicMaterial attribute), 119
 - skinning (pythreejs.MeshDepthMaterial attribute), 122
 - skinning (pythreejs.MeshLambertMaterial attribute), 124
 - skinning (pythreejs.MeshMatcapMaterial attribute), 127
 - skinning (pythreejs.MeshPhongMaterial attribute), 132
 - skinning (pythreejs.MeshStandardMaterial attribute), 137
 - skinning (pythreejs.ShaderMaterial attribute), 142
 - skinWeights (pythreejs.Geometry attribute), 49
 - slices (pythreejs.ParametricGeometry attribute), 74
 - specular (pythreejs.MeshPhongMaterial attribute), 132
 - specularMap (pythreejs.MeshBasicMaterial attribute), 119
 - specularMap (pythreejs.MeshLambertMaterial attribute), 124
 - specularMap (pythreejs.MeshPhongMaterial attribute), 132
 - Sphere (class in pythreejs), 151
 - SphereBufferGeometry (class in pythreejs), 80
 - SphereGeometry (class in pythreejs), 82

sphereSize (pythreejs.PointLightHelper attribute), 97
 Spherical (class in pythreejs), 152
 SplineCurve (class in pythreejs), 58
 SpotLight (class in pythreejs), 106
 SpotLightHelper (class in pythreejs), 100
 SpotLightShadow (class in pythreejs), 106
 Sprite (class in pythreejs), 160
 SpriteMaterial (class in pythreejs), 144
 squareTexture (pythreejs.TextTexture attribute), 170
 stacks (pythreejs.ParametricGeometry attribute), 74
 start (pythreejs.Line3 attribute), 149
 staticMoving (pythreejs.TrackballControls attribute), 44
 StereoCamera (class in pythreejs), 37
 stop() (pythreejs.AnimationAction method), 27
 string (pythreejs.TextTexture attribute), 170
 StringKeyframeTrack (class in pythreejs), 26
 syncRate (pythreejs.FlyControls attribute), 38

T

target (pythreejs.DirectionallLight attribute), 102
 target (pythreejs.OrbitControls attribute), 41
 target (pythreejs.SpotLight attribute), 107
 target (pythreejs.TrackballControls attribute), 44
 TetrahedronGeometry (class in pythreejs), 83
 TextGeometry (class in pythreejs), 83
 TextTexture (class in pythreejs), 170
 Texture (class in pythreejs), 171
 TextureLoader (class in pythreejs), 111
 theta (pythreejs.Cylindrical attribute), 148
 thetaLength (pythreejs.CircleBufferGeometry attribute), 63
 thetaLength (pythreejs.CircleGeometry attribute), 64
 thetaLength (pythreejs.ConeGeometry attribute), 65
 thetaLength (pythreejs.CylinderBufferGeometry attribute), 66
 thetaLength (pythreejs.CylinderGeometry attribute), 68
 thetaLength (pythreejs.RingBufferGeometry attribute), 78
 thetaLength (pythreejs.RingGeometry attribute), 79
 thetaLength (pythreejs.SphereBufferGeometry attribute), 81
 thetaLength (pythreejs.SphereGeometry attribute), 82
 thetaSegments (pythreejs.RingBufferGeometry attribute), 78
 thetaSegments (pythreejs.RingGeometry attribute), 79
 thetaStart (pythreejs.CircleBufferGeometry attribute), 63
 thetaStart (pythreejs.CircleGeometry attribute), 64
 thetaStart (pythreejs.ConeGeometry attribute), 65
 thetaStart (pythreejs.CylinderBufferGeometry attribute), 66
 thetaStart (pythreejs.CylinderGeometry attribute), 68
 thetaStart (pythreejs.RingBufferGeometry attribute), 78
 thetaStart (pythreejs.RingGeometry attribute), 79
 thetaStart (pythreejs.SphereBufferGeometry attribute), 81

thetaStart (pythreejs.SphereGeometry attribute), 82
 ThreeWidget (class in pythreejs), 24
 time (pythreejs.AnimationAction attribute), 27
 time (pythreejs.AnimationMixer attribute), 28
 times (pythreejs.KeyframeTrack attribute), 29
 timeScale (pythreejs.AnimationAction attribute), 27
 timeScale (pythreejs.AnimationMixer attribute), 28
 top (pythreejs.OrthographicCamera attribute), 35
 TorusBufferGeometry (class in pythreejs), 84
 TorusGeometry (class in pythreejs), 85
 TorusKnotBufferGeometry (class in pythreejs), 86
 TorusKnotGeometry (class in pythreejs), 87
 TrackballControls (class in pythreejs), 43
 tracks (pythreejs.AnimationClip attribute), 28
 transparent (pythreejs.Material attribute), 117
 transparent (pythreejs.ShadowMaterial attribute), 144
 Triangle (class in pythreejs), 152
 tube (pythreejs.TorusBufferGeometry attribute), 84
 tube (pythreejs.TorusGeometry attribute), 85
 tube (pythreejs.TorusKnotBufferGeometry attribute), 86
 tube (pythreejs.TorusKnotGeometry attribute), 87
 TubeGeometry (class in pythreejs), 88
 tubularSegments (pythreejs.TorusBufferGeometry attribute), 84
 tubularSegments (pythreejs.TorusGeometry attribute), 85
 tubularSegments (pythreejs.TorusKnotBufferGeometry attribute), 86
 tubularSegments (pythreejs.TorusKnotGeometry attribute), 87
 type (pythreejs.AmbientLight attribute), 102
 type (pythreejs.ArrayCamera attribute), 31
 type (pythreejs.ArrowHelper attribute), 90
 type (pythreejs.AxesHelper attribute), 91
 type (pythreejs.BaseBufferGeometry attribute), 45
 type (pythreejs.BaseGeometry attribute), 46
 type (pythreejs.Blackbox attribute), 153
 type (pythreejs.Bone attribute), 153
 type (pythreejs.Box3Helper attribute), 92
 type (pythreejs.BoxBufferGeometry attribute), 60
 type (pythreejs.BoxGeometry attribute), 61
 type (pythreejs.BoxHelper attribute), 92
 type (pythreejs.BoxLineGeometry attribute), 62
 type (pythreejs.BufferGeometry attribute), 47
 type (pythreejs.Camera attribute), 32
 type (pythreejs.CameraHelper attribute), 93
 type (pythreejs.CircleBufferGeometry attribute), 63
 type (pythreejs.CircleGeometry attribute), 64
 type (pythreejs.CloneArray attribute), 154
 type (pythreejs.CombinedCamera attribute), 33
 type (pythreejs.ConeGeometry attribute), 65
 type (pythreejs.CubeCamera attribute), 34
 type (pythreejs.CylinderBufferGeometry attribute), 66
 type (pythreejs.CylinderGeometry attribute), 68
 type (pythreejs.DepthTexture attribute), 169

type (pythreejs.DirectionallLight attribute), 103
 type (pythreejs.DirectionallLightHelper attribute), 93
 type (pythreejs.DodecahedronGeometry attribute), 69
 type (pythreejs.EdgesGeometry attribute), 69
 type (pythreejs.ExtrudeGeometry attribute), 69
 type (pythreejs.FaceNormalsHelper attribute), 94
 type (pythreejs.Geometry attribute), 49
 type (pythreejs.GridHelper attribute), 95
 type (pythreejs.Group attribute), 154
 type (pythreejs.HemisphereLight attribute), 103
 type (pythreejs.HemisphereLightHelper attribute), 96
 type (pythreejs.IcosahedronGeometry attribute), 70
 type (pythreejs.InstancedBufferGeometry attribute), 50
 type (pythreejs.LatheBufferGeometry attribute), 71
 type (pythreejs.LatheGeometry attribute), 72
 type (pythreejs.Light attribute), 104
 type (pythreejs.Line attribute), 157
 type (pythreejs.Line2 attribute), 155
 type (pythreejs.LineBasicMaterial attribute), 112
 type (pythreejs.LineDashedMaterial attribute), 113
 type (pythreejs.LineGeometry attribute), 72
 type (pythreejs.LineLoop attribute), 155
 type (pythreejs.LineMaterial attribute), 114
 type (pythreejs.LineSegments attribute), 157
 type (pythreejs.LineSegments2 attribute), 156
 type (pythreejs.LineSegmentsGeometry attribute), 73
 type (pythreejs.Material attribute), 117
 type (pythreejs.Mesh attribute), 158
 type (pythreejs.MeshBasicMaterial attribute), 120
 type (pythreejs.MeshDepthMaterial attribute), 122
 type (pythreejs.MeshLambertMaterial attribute), 125
 type (pythreejs.MeshMatcapMaterial attribute), 127
 type (pythreejs.MeshNormalMaterial attribute), 129
 type (pythreejs.MeshPhongMaterial attribute), 132
 type (pythreejs.MeshPhysicalMaterial attribute), 134
 type (pythreejs.MeshStandardMaterial attribute), 138
 type (pythreejs.MeshToonMaterial attribute), 140
 type (pythreejs.Object3D attribute), 52
 type (pythreejs.OctahedronGeometry attribute), 73
 type (pythreejs.OrthographicCamera attribute), 35
 type (pythreejs.ParametricGeometry attribute), 74
 type (pythreejs.PerspectiveCamera attribute), 36
 type (pythreejs.PlaneBufferGeometry attribute), 75
 type (pythreejs.PlaneGeometry attribute), 76
 type (pythreejs.PlaneHelper attribute), 97
 type (pythreejs.PointLight attribute), 105
 type (pythreejs.PointLightHelper attribute), 97
 type (pythreejs.Points attribute), 159
 type (pythreejs.PointsMaterial attribute), 141
 type (pythreejs.PolarGridHelper attribute), 98
 type (pythreejs.PolyhedronGeometry attribute), 77
 type (pythreejs.RawShaderMaterial attribute), 141
 type (pythreejs.RectAreaLight attribute), 106
 type (pythreejs.RectAreaLightHelper attribute), 99

type (pythreejs.RingBufferGeometry attribute), 78
 type (pythreejs.RingGeometry attribute), 79
 type (pythreejs.Scene attribute), 166
 type (pythreejs.ShaderMaterial attribute), 143
 type (pythreejs.ShadowMaterial attribute), 144
 type (pythreejs.ShapeGeometry attribute), 80
 type (pythreejs.SkeletonHelper attribute), 100
 type (pythreejs.SkinnedMesh attribute), 160
 type (pythreejs.SphereBufferGeometry attribute), 81
 type (pythreejs.SphereGeometry attribute), 82
 type (pythreejs.SpotLight attribute), 107
 type (pythreejs.SpotLightHelper attribute), 100
 type (pythreejs.Sprite attribute), 160
 type (pythreejs.SpriteMaterial attribute), 145
 type (pythreejs.TetrahedronGeometry attribute), 83
 type (pythreejs.TextGeometry attribute), 84
 type (pythreejs.Texture attribute), 172
 type (pythreejs.TorusBufferGeometry attribute), 84
 type (pythreejs.TorusGeometry attribute), 85
 type (pythreejs.TorusKnotBufferGeometry attribute), 86
 type (pythreejs.TorusKnotGeometry attribute), 88
 type (pythreejs.TubeGeometry attribute), 89
 type (pythreejs.VertexNormalsHelper attribute), 101
 type (pythreejs.WebGLShadowMap attribute), 163
 type (pythreejs.WireframeGeometry attribute), 89

U

Uniform (class in pythreejs.traits), 174
 uniforms (pythreejs.ShaderMaterial attribute), 141
 uniformsNeedUpdate (pythreejs.ShaderMaterial attribute), 142
 Uninitialized (class in pythreejs.traits), 174
 unpackAlignment (pythreejs.Texture attribute), 172
 up (pythreejs.Object3D attribute), 53
 userData (pythreejs.BufferGeometry attribute), 47
 uv (pythreejs.Picker attribute), 42

V

validate (pythreejs.BufferGeometry attribute), 47
 validate() (pythreejs.traits.Color method), 174
 validate() (pythreejs.traits.WebGLDataUnion method), 175
 values (pythreejs.KeyframeTrack attribute), 29
 Vector2 (class in pythreejs.traits), 175
 Vector3 (class in pythreejs.traits), 175
 Vector4 (class in pythreejs.traits), 175
 VectorKeyframeTrack (class in pythreejs), 26
 version (pythreejs.BufferAttribute attribute), 46
 version (pythreejs.InterleavedBuffer attribute), 52
 version (pythreejs.Texture attribute), 172
 vertexColors (pythreejs.Material attribute), 118
 VertexNormalsHelper (class in pythreejs), 101
 vertexShader (pythreejs.ShaderMaterial attribute), 143
 vertices (pythreejs.Geometry attribute), 48

vertices (pythreejs.PolyhedronGeometry attribute), 76
 VideoTexture (class in pythreejs), 174
 visible (pythreejs.Material attribute), 118
 visible (pythreejs.Object3D attribute), 54

W

w (pythreejs.Quaternion attribute), 151
 WebGLBufferRenderer (class in pythreejs), 161
 WebGLCapabilities (class in pythreejs), 161
 WebGLDataUnion (class in pythreejs.traits), 175
 WebGLExtensions (class in pythreejs), 161
 WebGLGeometries (class in pythreejs), 161
 WebGLIndexedBufferRenderer (class in pythreejs), 162
 WebGLLights (class in pythreejs), 162
 WebGLObjects (class in pythreejs), 162
 WebGLProgram (class in pythreejs), 162
 WebGLPrograms (class in pythreejs), 162
 WebGLProperties (class in pythreejs), 163
 WebGLRenderTarget (class in pythreejs), 164
 WebGLRenderTargetCube (class in pythreejs), 164
 WebGLShader (class in pythreejs), 163
 WebGLShadowMap (class in pythreejs), 163
 WebGLState (class in pythreejs), 163
 weighth (pythreejs.AnimationAction attribute), 27
 width (pythreejs.BoxBufferGeometry attribute), 59
 width (pythreejs.BoxGeometry attribute), 60
 width (pythreejs.BoxLineGeometry attribute), 61
 width (pythreejs.CombinedCamera attribute), 33
 width (pythreejs.DepthTexture attribute), 168
 width (pythreejs.PlaneBufferGeometry attribute), 75
 width (pythreejs.PlaneGeometry attribute), 76
 width (pythreejs.RectAreaLight attribute), 106
 widthSegments (pythreejs.BoxBufferGeometry attribute), 59
 widthSegments (pythreejs.BoxGeometry attribute), 60
 widthSegments (pythreejs.BoxLineGeometry attribute), 62
 widthSegments (pythreejs.PlaneBufferGeometry attribute), 75
 widthSegments (pythreejs.PlaneGeometry attribute), 76
 widthSegments (pythreejs.SphereBufferGeometry attribute), 81
 widthSegments (pythreejs.SphereGeometry attribute), 82
 wireframe (pythreejs.MeshBasicMaterial attribute), 119
 wireframe (pythreejs.MeshDepthMaterial attribute), 122
 wireframe (pythreejs.MeshLambertMaterial attribute), 124
 wireframe (pythreejs.MeshNormalMaterial attribute), 129
 wireframe (pythreejs.MeshPhongMaterial attribute), 132
 wireframe (pythreejs.MeshStandardMaterial attribute), 137
 wireframe (pythreejs.ShaderMaterial attribute), 143
 WireframeGeometry (class in pythreejs), 89

wireframeLinecap (pythreejs.MeshBasicMaterial attribute), 120
 wireframeLinecap (pythreejs.MeshLambertMaterial attribute), 124
 wireframeLinecap (pythreejs.MeshPhongMaterial attribute), 132
 wireframeLinecap (pythreejs.MeshStandardMaterial attribute), 137
 wireframeLinejoin (pythreejs.MeshBasicMaterial attribute), 120
 wireframeLinejoin (pythreejs.MeshLambertMaterial attribute), 125
 wireframeLinejoin (pythreejs.MeshPhongMaterial attribute), 132
 wireframeLinejoin (pythreejs.MeshStandardMaterial attribute), 138
 wireframeLinewidth (pythreejs.MeshBasicMaterial attribute), 119
 wireframeLinewidth (pythreejs.MeshDepthMaterial attribute), 122
 wireframeLinewidth (pythreejs.MeshLambertMaterial attribute), 125
 wireframeLinewidth (pythreejs.MeshNormalMaterial attribute), 129
 wireframeLinewidth (pythreejs.MeshPhongMaterial attribute), 132
 wireframeLinewidth (pythreejs.MeshStandardMaterial attribute), 138
 wireframeLinewidth (pythreejs.ShaderMaterial attribute), 143
 wrapS (pythreejs.Texture attribute), 171
 wrapT (pythreejs.Texture attribute), 171

X

x (pythreejs.Quaternion attribute), 150

Y

y (pythreejs.Cylindrical attribute), 148
 y (pythreejs.Quaternion attribute), 150

Z

z (pythreejs.Quaternion attribute), 150
 zeroSlopeAtEnd (pythreejs.AnimationAction attribute), 27
 zeroSlopeAtStart (pythreejs.AnimationAction attribute), 27
 zoom (pythreejs.CombinedCamera attribute), 32
 zoom (pythreejs.OrthographicCamera attribute), 34
 zoom (pythreejs.PerspectiveCamera attribute), 36
 zoomSpeed (pythreejs.OrbitControls attribute), 41
 zoomSpeed (pythreejs.TrackballControls attribute), 43