
RobotPy WPILib Documentation

Release master

RobotPy development team

Mar 25, 2017

| | | |
|----------|------------------------------------|------------|
| 1 | WPILib API | 3 |
| 1.1 | wplib Package | 3 |
| 1.2 | wplib.buttons Package | 106 |
| 1.3 | wplib.command Package | 108 |
| 1.4 | wplib.interfaces Package | 121 |
| 2 | Indices and tables | 129 |
| | Python Module Index | 131 |

RobotPy WPILib is the source code for a 100% python implementation of WPILib, the library used to interface with hardware for the FIRST Robotics Competition. Teams can use this library to write their robot code in Python, a powerful dynamic programming language.

Note: RobotPy is a community project and is not officially supported by FIRST. Please see the [FAQ](#) for more information.

The WPI Robotics library (WPILib) is a set of classes that interfaces to the hardware in the FRC control system and your robot. There are classes to handle sensors, motors, the driver station, and a number of other utility functions like timing and field management. The library is designed to:

- Deal with all the low level interfacing to these components so you can concentrate on solving this year’s “robot problem”. This is a philosophical decision to let you focus on the higher-level design of your robot rather than deal with the details of the processor and the operating system.
- Understand everything at all levels by making the full source code of the library available. You can study (and modify) the algorithms used by the gyro class for oversampling and integration of the input signal or just ask the class for the current robot heading. You can work at any level.

wpilib Package

This is the core of WPILib.

| | |
|---|---|
| <code>wpilib.ADXL345_I2C(port, range)</code> | ADXL345 accelerometer device via i2c |
| <code>wpilib.ADXL345_SPI(port, range)</code> | ADXL345 accelerometer device via spi |
| <code>wpilib.ADXL362(range[, port])</code> | ADXL362 SPI Accelerometer. |
| <code>wpilib.ADXRS450_Gyro([port])</code> | Use a rate gyro to return the robots heading relative to a starting position. |
| <code>wpilib.AnalogAccelerometer(channel)</code> | Analog Accelerometer |
| <code>wpilib.AnalogGyro(channel, ...)</code> | Interface to a gyro device via an <i>AnalogInput</i> |
| <code>wpilib.AnalogInput(channel)</code> | Analog input |
| <code>wpilib.AnalogOutput(channel)</code> | Analog output |
| <code>wpilib.AnalogPotentiometer(channel)</code> | Reads a potentiometer via an <i>AnalogInput</i> |
| <code>wpilib.AnalogTrigger(channel)</code> | Converts an analog signal into a digital signal |
| <code>wpilib.AnalogTriggerOutput(...)</code> | Represents a specific output from an <i>AnalogTrigger</i> |
| <code>wpilib.BuiltInAccelerometer([range])</code> | Built-in accelerometer device |

Continued on next page

Table 1.1 – continued from previous page

| | |
|--|---|
| <code>wplib.CameraServer</code> | Provides a way to launch an out of process cscore-based camera service instance, for streaming or for image processing. |
| <code>wplib.CANJaguar(*args, **kwargs)</code> | |
| <code>wplib.CANTalon(*args, **kwargs)</code> | |
| <code>wplib.Compressor([module])</code> | Class for operating a compressor connected to a PCM (Pneumatic Control Module). |
| <code>wplib.ControllerPower</code> | Provides access to power levels on the roboRIO |
| <code>wplib.Counter(*args, **kwargs)</code> | Counts the number of ticks on a <i>DigitalInput</i> channel. |
| <code>wplib.DigitalGlitchFilter()</code> | Class to enable glitch filtering on a set of digital inputs. |
| <code>wplib.DigitalInput(channel)</code> | Reads a digital input. |
| <code>wplib.DigitalOutput(channel)</code> | Writes to a digital output |
| <code>wplib.DigitalSource(channel, ...)</code> | DigitalSource Interface. |
| <code>wplib.DoubleSolenoid(*args, ...)</code> | Controls 2 channels of high voltage Digital Output on the PCM. |
| <code>wplib.DriverStation()</code> | Provide access to the network communication data to / from the Driver Station. |
| <code>wplib.Encoder(*args, **kwargs)</code> | Class to read quadrature encoders. |
| <code>wplib.Filter(source)</code> | Superclass for filters |
| <code>wplib.GearTooth(channel[, ...])</code> | Interface to the gear tooth sensor supplied by FIRST |
| <code>wplib.GyroBase()</code> | GyroBase is the common base class for Gyro implementations such as <i>AnalogGyro</i> . |
| <code>wplib.I2C(port, deviceAddress[, simPort])</code> | I2C bus interface class. |
| <code>wplib.interfaces.GamepadBase(port)</code> | GamepadBase Interface. |
| <code>wplib.interfaces.GenericHID(port)</code> | GenericHID Interface. |
| <code>wplib.InterruptableSensorBase()</code> | Base for sensors to be used with interrupts |
| <code>wplib.IterativeRobot()</code> | IterativeRobot implements a specific type of Robot Program framework, extending the <i>RobotBase</i> class. |
| <code>wplib.Jaguar(channel)</code> | Texas Instruments / Vex Robotics Jaguar Speed Controller as a PWM device. |
| <code>wplib.Joystick(port[, ...])</code> | Handle input from standard Joysticks connected to the Driver Station. |
| <code>wplib.LinearDigitalFilter(...)</code> | This class implements a linear, digital filter. |
| <code>wplib.LiveWindow</code> | The public interface for putting sensors and actuators on the LiveWindow. |
| <code>wplib.LiveWindowSendable</code> | A special type of object that can be displayed on the live window. |
| <code>wplib.MotorSafety()</code> | Provides mechanisms to safely shutdown motors if they aren't updated often enough. |
| <code>wplib.PIDController(*args, ...)</code> | Can be used to control devices via a PID Control Loop. |
| <code>wplib.PowerDistributionPanel([...])</code> | Use to obtain voltage, current, temperature, power, and energy from the |
| <code>wplib.Preferences()</code> | Provides a relatively simple way to save important values to the roboRIO to access the next time the roboRIO is booted. |
| <code>wplib.PWM(channel)</code> | Raw interface to PWM generation in the FPGA. |
| <code>wplib.PWMSpeedController(channel)</code> | Common base class for all PWM Speed Controllers. |
| <code>wplib.Relay(channel[, direction])</code> | Controls VEX Robotics Spike style relay outputs. |
| <code>wplib.Resource(size)</code> | Tracks resources in the program. |
| <code>wplib.RobotBase()</code> | Implement a Robot Program framework. |
| Continued on next page | |

Table 1.1 – continued from previous page

| | |
|---|--|
| <code>wpiplib.RobotDrive(*args, **kwargs)</code> | Operations on a robot drivetrain based on a definition of the motor configuration. |
| <code>wpiplib.RobotState</code> | Provides an interface to determine the current operating state of the robot code. |
| <code>wpiplib.SafePWM(channel)</code> | A raw PWM interface that implements the <i>MotorSafety</i> interface |
| <code>wpiplib.SampleRobot()</code> | A simple robot base class that knows the standard FRC competition states (disabled, autonomous, or operator controlled). |
| <code>wpiplib.SD540(channel)</code> | Mindsensors SD540 Speed Controller |
| <code>wpiplib.Sendable</code> | The base interface for objects that can be sent over the network |
| <code>wpiplib.SendableChooser()</code> | A useful tool for presenting a selection of options to be displayed on |
| <code>wpiplib.SensorBase</code> | Base class for all sensors |
| <code>wpiplib.Servo(channel)</code> | Standard hobby style servo |
| <code>wpiplib.SmartDashboard</code> | The bridge between robot programs and the SmartDashboard on the laptop |
| <code>wpiplib.Solenoid(*args, **kwargs)</code> | Solenoid class for running high voltage Digital Output. |
| <code>wpiplib.SolenoidBase(moduleNumber)</code> | SolenoidBase class is the common base class for the Solenoid and DoubleSolenoid classes. |
| <code>wpiplib.Spark(channel)</code> | REV Robotics SPARK Speed Controller |
| <code>wpiplib.SPI(port[, simPort])</code> | Represents a SPI bus port |
| <code>wpiplib.Talon(channel)</code> | Cross the Road Electronics (CTRE) Talon and Talon SR Speed Controller via PWM |
| <code>wpiplib.TalonSRX(channel)</code> | Cross the Road Electronics (CTRE) Talon SRX Speed Controller via PWM |
| <code>wpiplib.Timer()</code> | Provides time-related functionality for the robot |
| <code>wpiplib.Ultrasonic(pingChannel, ...)</code> | Ultrasonic rangefinder control |
| <code>wpiplib.Utility</code> | Contains global utility functions |
| <code>wpiplib.Victor(channel)</code> | VEX Robotics Victor 888 Speed Controller via PWM |
| <code>wpiplib.VictorSP(channel)</code> | VEX Robotics Victor SP Speed Controller via PWM |
| <code>wpiplib.XboxController(port)</code> | Handle input from Xbox 360 or Xbox One controllers connected to the Driver Station. |

ADXL345_I2C

class `wpiplib.ADXL345_I2C` (*port*, *range*, *address=None*)

Bases: `wpiplib.SensorBase`

ADXL345 accelerometer device via i2c

Constructor.

Parameters

- **port** (`I2C.Port`) – The I2C port the accelerometer is attached to.
- **range** (`ADXL345_I2C.Range`) – The range (+ or -) that the accelerometer will measure.
- **address** – the I2C address of the accelerometer (0x1D or 0x53)

class `Axes`

Bases: `object`

kX = 0

kY = 2

kZ = 4

class ADXL345_I2C.**Range**

Bases: object

k16G = 3

k2G = 0

k4G = 1

k8G = 2

ADXL345_I2C.**free** ()

ADXL345_I2C.**getAcceleration** (*axis*)

Get the acceleration of one axis in Gs.

Parameters *axis* – The axis to read from.

Returns An object containing the acceleration measured on each axis of the ADXL345 in Gs.

ADXL345_I2C.**getAccelerations** ()

Get the acceleration of all axes in Gs.

Returns X,Y,Z tuple of acceleration measured on all axes of the ADXL345 in Gs.

ADXL345_I2C.**getX** ()

Get the x axis acceleration

Returns The acceleration along the x axis in g-forces

ADXL345_I2C.**getY** ()

Get the y axis acceleration

Returns The acceleration along the y axis in g-forces

ADXL345_I2C.**getZ** ()

Get the z axis acceleration

Returns The acceleration along the z axis in g-forces

ADXL345_I2C.**kAddress = 29**

ADXL345_I2C.**kDataFormatRegister = 49**

ADXL345_I2C.**kDataFormat_FullRes = 8**

ADXL345_I2C.**kDataFormat_IntInvert = 32**

ADXL345_I2C.**kDataFormat_Justify = 4**

ADXL345_I2C.**kDataFormat_SPI = 64**

ADXL345_I2C.**kDataFormat_SelfTest = 128**

ADXL345_I2C.**kDataRegister = 50**

ADXL345_I2C.**kGsPerLSB = 0.00390625**

ADXL345_I2C.**kPowerCtlRegister = 45**

ADXL345_I2C.**kPowerCtl_AutoSleep = 16**

ADXL345_I2C.**kPowerCtl_Link = 32**

`ADXL345_I2C.kPowerCtl1_Measure = 8`

`ADXL345_I2C.kPowerCtl1_Sleep = 4`

`ADXL345_I2C.setRange (range)`

Set the measuring range of the accelerometer.

Parameters `range` (`ADXL345_I2C.Range`) – The maximum acceleration, positive or negative, that the accelerometer will measure.

ADXL345_SPI

`class wpilib.ADXL345_SPI (port, range)`

Bases: `wpilib.SensorBase`

ADXL345 accelerometer device via spi

Constructor. Use this when the device is the first/only device on the bus

Parameters

- **port** (`SPI.Port`) – The SPI port that the accelerometer is connected to
- **range** (`ADXL345_SPI.Range`) – The range (+ or -) that the accelerometer will measure.

`class Axes`

Bases: `object`

`kX = 0`

`kY = 2`

`kZ = 4`

`class ADXL345_SPI.Range`

Bases: `object`

`k16G = 3`

`k2G = 0`

`k4G = 1`

`k8G = 2`

`ADXL345_SPI.free ()`

`ADXL345_SPI.getAcceleration (axis)`

Get the acceleration of one axis in Gs.

Parameters `axis` – The axis to read from.

Returns An object containing the acceleration measured on each axis of the ADXL345 in Gs.

`ADXL345_SPI.getAccelerations ()`

Get the acceleration of all axes in Gs.

Returns X,Y,Z tuple of acceleration measured on all axes of the ADXL345 in Gs.

`ADXL345_SPI.getX ()`

Get the x axis acceleration

Returns The acceleration along the x axis in g-forces

`ADXL345_SPI.getY ()`

Get the y axis acceleration

Returns The acceleration along the y axis in g-forces

`ADXL345_SPI.getZ()`

Get the z axis acceleration

Returns The acceleration along the z axis in g-forces

`ADXL345_SPI.kAddress_MultiByte = 64`

`ADXL345_SPI.kAddress_Read = 128`

`ADXL345_SPI.kDataFormatRegister = 49`

`ADXL345_SPI.kDataFormat_FullRes = 8`

`ADXL345_SPI.kDataFormat_IntInvert = 32`

`ADXL345_SPI.kDataFormat_Justify = 4`

`ADXL345_SPI.kDataFormat_SPI = 64`

`ADXL345_SPI.kDataFormat_SelfTest = 128`

`ADXL345_SPI.kDataRegister = 50`

`ADXL345_SPI.kGsPerLSB = 0.00390625`

`ADXL345_SPI.kPowerCtlRegister = 45`

`ADXL345_SPI.kPowerCtl_AutoSleep = 16`

`ADXL345_SPI.kPowerCtl_Link = 32`

`ADXL345_SPI.kPowerCtl_Measure = 8`

`ADXL345_SPI.kPowerCtl_Sleep = 4`

`ADXL345_SPI.setRange(range)`

Set the measuring range of the accelerometer.

Parameters `range` (`ADXL345_SPI.Range`) – The maximum acceleration, positive or negative, that the accelerometer will measure.

ADXL362

`class wpilib.ADXL362(range, port=None)`

Bases: `wpilib.SensorBase`

ADXL362 SPI Accelerometer.

This class allows access to an Analog Devices ADXL362 3-axis accelerometer.

Constructor.

Parameters

- **range** (`ADXL362.Range`) – The range (+ or -) that the accelerometer will measure.
- **port** (`SPI.Port`) – The SPI port that the accelerometer is connected to

`class Axes`

Bases: `object`

`kX = 0`

`kY = 2`

`kZ = 4`

```

class ADXL362.Range
    Bases: object

    k16G = 3
    k2G = 0
    k4G = 1
    k8G = 2

ADXL362.free ()

ADXL362.getAcceleration (axis)
    Get the acceleration of one axis in Gs.

    Parameters axis – The axis to read from.

    Returns An object containing the acceleration measured on each axis in Gs.

ADXL362.getAccelerations ()
    Get the acceleration of all axes in Gs.

    Returns X,Y,Z tuple of acceleration measured on all axes in Gs.

ADXL362.getX ()
    Get the x axis acceleration

    Returns The acceleration along the x axis in g-forces

ADXL362.getY ()
    Get the y axis acceleration

    Returns The acceleration along the y axis in g-forces

ADXL362.getZ ()
    Get the z axis acceleration

    Returns The acceleration along the z axis in g-forces

ADXL362.kDataRegister = 14
ADXL362.kFilterCtlRegister = 44
ADXL362.kFilterCtl_ODR_100Hz = 3
ADXL362.kFilterCtl_Range2G = 0
ADXL362.kFilterCtl_Range4G = 64
ADXL362.kFilterCtl_Range8G = 128
ADXL362.kPartIdRegister = 2
ADXL362.kPowerCtlRegister = 45
ADXL362.kPowerCtl_AutoSleep = 4
ADXL362.kPowerCtl_Measure = 2
ADXL362.kPowerCtl_UltraLowNoise = 32
ADXL362.kRegRead = 11
ADXL362.kRegWrite = 10
ADXL362.setRange (range)
    Set the measuring range of the accelerometer.

```

Parameters `range` (*ADXL362.Range*) – The maximum acceleration, positive or negative, that the accelerometer will measure.

ADXRS450_Gyro

class `wpiplib.ADXRS450_Gyro` (*port=None*)

Bases: `wpiplib.GyroBase`

Use a rate gyro to return the robots heading relative to a starting position. The Gyro class tracks the robots heading based on the starting position. As the robot rotates the new heading is computed by integrating the rate of rotation returned by the sensor. When the class is instantiated, it does a short calibration routine where it samples the gyro while at rest to determine the default offset. This is subtracted from each sample to determine the heading.

This class is for the digital ADXRS450 gyro sensor that connects via SPI.

Constructor.

Parameters `port` (*SPI.Port*) – The SPI port that the gyro is connected to

calibrate ()

Calibrate the gyro by running for a number of samples and computing the center value. Then use the center value as the Accumulator center value for subsequent measurements.

It's important to make sure that the robot is not moving while the centering calculations are in progress, this is typically done when the robot is first turned on while it's sitting at rest before the competition starts.

Note: Usually you don't need to call this, as it's called when the object is first created. If you do, it will freeze your robot for 5 seconds

free ()

Delete (free) the spi port used for the gyro and stop accumulating.

getAngle ()

Return the actual angle in degrees that the robot is currently facing.

The angle is based on the current accumulator value corrected by the oversampling rate, the gyro type and the A/D calibration values. The angle is continuous, that is it will continue from 360 to 361 degrees. This allows algorithms that wouldn't want to see a discontinuity in the gyro output as it sweeps past from 360 to 0 on the second time around.

Returns the current heading of the robot in degrees. This heading is based on integration of the returned rate from the gyro.

getRate ()

Return the rate of rotation of the gyro

The rate is based on the most recent reading of the gyro value

Returns the current rate in degrees per second

kCalibrationSampleTime = 5.0

kDegreePerSecondPerLSB = 0.0125

kFaultRegister = 10

kHiCSTRegister = 6

kLoCSTRegister = 4

kPIDRegister = 12

kQuadRegister = 8

kRateRegister = 0

kSNHighRegister = 14

kSNLowRegister = 16

kSamplePeriod = 0.001

kTemRegister = 2

reset ()

Reset the gyro. Resets the gyro to a heading of zero. This can be used if there is significant drift in the gyro and it needs to be recalibrated after it has been running.

AnalogAccelerometer

class `wpiplib.AnalogAccelerometer` (*channel*)

Bases: `wpiplib.LiveWindowSendable`

Analog Accelerometer

The accelerometer reads acceleration directly through the sensor. Many sensors have multiple axis and can be treated as multiple devices. Each is calibrated by finding the center value over a period of time.

Constructor. Create a new instance of Accelerometer from either an existing `AnalogChannel` or from an analog channel port index.

Parameters `channel` – port index or an already initialized `AnalogInput`

class `PIDSourceType`

Bases: `object`

A description for the type of output value to provide to a `PIDController`

kDisplacement = 0

kRate = 1

`AnalogAccelerometer.free ()`

`AnalogAccelerometer.getAcceleration ()`

Return the acceleration in Gs.

The acceleration is returned units of Gs.

Returns The current acceleration of the sensor in Gs.

Return type `float`

`AnalogAccelerometer.getPIDSourceType ()`

`AnalogAccelerometer.pidGet ()`

Get the Acceleration for the PID Source parent.

Returns The current acceleration in Gs.

Return type `float`

`AnalogAccelerometer.setPIDSourceType (pidSource)`

Set which parameter you are using as a process control variable.

Parameters `pidSource` (*PIDSource.PIDSourceType*) – An enum to select the parameter.

`AnalogAccelerometer.setSensitivity(sensitivity)`

Set the accelerometer sensitivity.

This sets the sensitivity of the accelerometer used for calculating the acceleration. The sensitivity varies by accelerometer model. There are constants defined for various models.

Parameters `sensitivity` (*float*) – The sensitivity of accelerometer in Volts per G.

`AnalogAccelerometer.setZero(zero)`

Set the voltage that corresponds to 0 G.

The zero G voltage varies by accelerometer model. There are constants defined for various models.

Parameters `zero` (*float*) – The zero G voltage.

AnalogGyro

class `wpiplib.AnalogGyro` (*channel, center=None, offset=None*)

Bases: *wpiplib.GyroBase*

Interface to a gyro device via an *AnalogInput*

Use a rate gyro to return the robots heading relative to a starting position. The Gyro class tracks the robots heading based on the starting position. As the robot rotates the new heading is computed by integrating the rate of rotation returned by the sensor. When the class is instantiated, it does a short calibration routine where it samples the gyro while at rest to determine the default offset. This is subtracted from each sample to determine the heading.

Gyro constructor.

Also initializes the gyro. Calibrate the gyro by running for a number of samples and computing the center value. Then use the center value as the Accumulator center value for subsequent measurements. It's important to make sure that the robot is not moving while the centering calculations are in progress, this is typically done when the robot is first turned on while it's sitting at rest before the competition starts.

Parameters

- **channel** – The analog channel index or *AnalogInput* object that the gyro is connected to. Gyros can only be used on on-board channels 0-1.
- **center** (*int*) – Preset uncalibrated value to use as the accumulator center value
- **offset** (*float*) – Preset uncalibrated value to use as the gyro offset

class `PIDSourceType`

Bases: *object*

A description for the type of output value to provide to a *PIDController*

kDisplacement = 0

kRate = 1

`AnalogGyro.calibrate()`

See *Gyro.calibrate()*

`AnalogGyro.free()`

See *Gyro.free()*

`AnalogGyro.getAngle()`

See `Gyro.getAngle()`

`AnalogGyro.getCenter()`

Return the gyro center value set during calibration to use as a future preset

Returns the current center value

`AnalogGyro.getOffset()`

Return the gyro offset value set during calibration to use as a future preset

Returns the current offset value

`AnalogGyro.getRate()`

See `Gyro.getRate()`

`AnalogGyro.kAverageBits = 0`

`AnalogGyro.kCalibrationSampleTime = 5.0`

`AnalogGyro.kDefaultVoltsPerDegreePerSecond = 0.007`

`AnalogGyro.kOversampleBits = 10`

`AnalogGyro.kSamplesPerSecond = 50.0`

`AnalogGyro.reset()`

See `Gyro.reset()`

`AnalogGyro.setDeadband(volts)`

Set the size of the neutral zone. Any voltage from the gyro less than this amount from the center is considered stationary. Setting a deadband will decrease the amount of drift when the gyro isn't rotating, but will make it less accurate.

Parameters `volts` (*float*) – The size of the deadband in volts

`AnalogGyro.setSensitivity(voltsPerDegreePerSecond)`

Set the gyro sensitivity. This takes the number of volts/degree/second sensitivity of the gyro and uses it in subsequent calculations to allow the code to work with multiple gyros. This value is typically found in the gyro datasheet.

Parameters `voltsPerDegreePerSecond` (*float*) – The sensitivity in Volts/degree/second

AnalogInput

`class wpilib.AnalogInput(channel)`

Bases: `wpilib.SensorBase`

Analog input

Each analog channel is read from hardware as a 12-bit number representing 0V to 5V.

Connected to each analog channel is an averaging and oversampling engine. This engine accumulates the specified (by `setAverageBits()` and `setOversampleBits()`) number of samples before returning a new value. This is not a sliding window average. The only difference between the oversampled samples and the averaged samples is that the oversampled samples are simply accumulated effectively increasing the resolution, while the averaged samples are divided by the number of samples to retain the resolution, but get more stable values.

Construct an analog channel. :param channel: The channel number to represent. 0-3 are on-board 4-7 are on the MXP port.

class PIDSourceTypeBases: `object`A description for the type of output value to provide to a `PIDController`**kDisplacement = 0****kRate = 1**`AnalogInput.channels = <wpilib.resource.Resource object>``AnalogInput.free()``AnalogInput.getAccumulatorCount()`

Read the number of accumulated values.

Read the count of the accumulated values since the accumulator was last `reset()`.**Returns** The number of times samples from the channel were accumulated.`AnalogInput.getAccumulatorOutput()`

Read the accumulated value and the number of accumulated values atomically.

This function reads the value and count from the FPGA atomically. This can be used for averaging.

Returns tuple of (value, count)`AnalogInput.getAccumulatorValue()`

Read the accumulated value.

Read the value that has been accumulating. The accumulator is attached after the oversample and average engine.

Returns The 64-bit value accumulated since the last `reset()`.`AnalogInput.getAverageBits()`Get the number of averaging bits. This gets the number of averaging bits from the FPGA. The actual number of averaged samples is 2^{bits} . The averaging is done automatically in the FPGA.**Returns** The number of averaging bits.`AnalogInput.getAverageValue()`Get a sample from the output of the oversample and average engine for this channel. The sample is 12-bit + the bits configured in `setOversampleBits()`. The value configured in `setAverageBits()` will cause this value to be averaged 2^{bits} number of samples. This is not a sliding window. The sample will not change until $2^{(\text{OversampleBits} + \text{AverageBits})}$ samples have been acquired from this channel. Use `getAverageVoltage()` to get the analog value in calibrated units.**Returns** A sample from the oversample and average engine for this channel.`AnalogInput.getAverageVoltage()`Get a scaled sample from the output of the oversample and average engine for this channel. The value is scaled to units of Volts using the calibrated scaling data from `getLSBWeight()` and `getOffset()`. Using oversampling will cause this value to be higher resolution, but it will update more slowly. Using averaging will cause this value to be more stable, but it will update more slowly.**Returns** A scaled sample from the output of the oversample and average engine for this channel.`AnalogInput.getChannel()`

Get the channel number.

Returns The channel number.`static AnalogInput.getGlobalSampleRate()`

Get the current sample rate.

This assumes one entry in the scan list. This is a global setting for all channels.

Returns Sample rate.

`AnalogInput.getLSBWeight()`

Get the factory scaling least significant bit weight constant. The least significant bit weight constant for the channel that was calibrated in manufacturing and stored in an eeprom.

$\text{Volts} = ((\text{LSB_Weight} * 1e-9) * \text{raw}) - (\text{Offset} * 1e-9)$

Returns Least significant bit weight.

`AnalogInput.getOffset()`

Get the factory scaling offset constant. The offset constant for the channel that was calibrated in manufacturing and stored in an eeprom.

$\text{Volts} = ((\text{LSB_Weight} * 1e-9) * \text{raw}) - (\text{Offset} * 1e-9)$

Returns Offset constant.

`AnalogInput.getOversampleBits()`

Get the number of oversample bits. This gets the number of oversample bits from the FPGA. The actual number of oversampled values is 2^{bits} . The oversampling is done automatically in the FPGA.

Returns The number of oversample bits.

`AnalogInput.getPIDSourceType()`

See `PIDSource.getPIDSourceType()`

`AnalogInput.getValue()`

Get a sample straight from this channel. The sample is a 12-bit value representing the 0V to 5V range of the A/D converter. The units are in A/D converter codes. Use `getVoltage()` to get the analog value in calibrated units.

Returns A sample straight from this channel.

`AnalogInput.getVoltage()`

Get a scaled sample straight from this channel. The value is scaled to units of Volts using the calibrated scaling data from `getLSBWeight()` and `getOffset()`.

Returns A scaled sample straight from this channel.

`AnalogInput.initAccumulator()`

Initialize the accumulator.

`AnalogInput.isAccumulatorChannel()`

Is the channel attached to an accumulator.

Returns The analog channel is attached to an accumulator.

`AnalogInput.kAccumulatorChannels = (0, 1)`

`AnalogInput.kAccumulatorSlot = 1`

`AnalogInput.pidGet()`

Get the average voltage for use with PIDController

Returns the average voltage

`AnalogInput.port`

`AnalogInput.resetAccumulator()`

Resets the accumulator to the initial value.

`AnalogInput.setAccumulatorCenter` (*center*)

Set the center value of the accumulator.

The center value is subtracted from each A/D value before it is added to the accumulator. This is used for the center value of devices like gyros and accelerometers to make integration work and to take the device offset into account when integrating.

This center value is based on the output of the oversampled and averaged source from channel 1. Because of this, any non-zero oversample bits will affect the size of the value for this field.

`AnalogInput.setAccumulatorDeadband` (*deadband*)

Set the accumulator's deadband.

`AnalogInput.setAccumulatorInitialValue` (*initialValue*)

Set an initial value for the accumulator.

This will be added to all values returned to the user.

Parameters `initialValue` – The value that the accumulator should start from when reset.

`AnalogInput.setAverageBits` (*bits*)

Set the number of averaging bits. This sets the number of averaging bits. The actual number of averaged samples is 2^{bits} . The averaging is done automatically in the FPGA.

Parameters `bits` – The number of averaging bits.

`static AnalogInput.setGlobalSampleRate` (*samplesPerSecond*)

Set the sample rate per channel.

This is a global setting for all channels. The maximum rate is 500kS/s divided by the number of channels in use. This is 62500 samples/s per channel if all 8 channels are used.

Parameters `samplesPerSecond` – The number of samples per second.

`AnalogInput.setOversampleBits` (*bits*)

Set the number of oversample bits. This sets the number of oversample bits. The actual number of oversampled values is 2^{bits} . The oversampling is done automatically in the FPGA.

Parameters `bits` – The number of oversample bits.

`AnalogInput.setPIDSourceType` (*pidSource*)

See `PIDSource.setPIDSourceType()`

AnalogOutput

`class wpilib.AnalogOutput` (*channel*)

Bases: `wpilib.SensorBase`

Analog output

Construct an analog output on a specified MXP channel.

Parameters `channel` – The channel number to represent.

`channels` = `<wpilib.resource.Resource object>`

`free()`

Channel destructor.

`getChannel()`

Get the channel of this AnalogOutput.

`getVoltage()`

`port`

`setVoltage` (*voltage*)

AnalogPotentiometer

`class wpilib.AnalogPotentiometer` (*channel*, *fullRange=1.0*, *offset=0.0*)

Bases: `wpilib.LiveWindowSendable`

Reads a potentiometer via an `AnalogInput`

Analog potentiometers read in an analog voltage that corresponds to a position. The position is in whichever units you choose, by way of the scaling and offset constants passed to the constructor.

AnalogPotentiometer constructor.

Use the `fullRange` and `offset` values so that the output produces meaningful values. I.E: you have a 270 degree potentiometer and you want the output to be degrees with the halfway point as 0 degrees. The `fullRange` value is 270.0(degrees) and the `offset` is -135.0 since the halfway point after scaling is 135 degrees.

Parameters

- **channel** (int or `AnalogInput`) – The analog channel this potentiometer is plugged into.
- **fullRange** (*float*) – The scaling to multiply the fraction by to get a meaningful unit. Defaults to 1.0 if unspecified.
- **offset** (*float*) – The offset to add to the scaled value for controlling the zero value. Defaults to 0.0 if unspecified.

`class PIDSourceType`

Bases: `object`

A description for the type of output value to provide to a `PIDController`

kDisplacement = 0

kRate = 1

`AnalogPotentiometer.free` ()

`AnalogPotentiometer.get` ()

Get the current reading of the potentiometer.

Returns The current position of the potentiometer.

Return type float

`AnalogPotentiometer.getPIDSourceType` ()

`AnalogPotentiometer.pidGet` ()

Implement the PIDSource interface.

Returns The current reading.

Return type float

`AnalogPotentiometer.setPIDSourceType` (*pidSource*)

Set which parameter you are using as a process control variable.

Parameters `pidSource` (`PIDSource.PIDSourceType`) – An enum to select the parameter.

AnalogTrigger

`class wpilib.AnalogTrigger` (*channel*)

Bases: `object`

Converts an analog signal into a digital signal

An analog trigger is a way to convert an analog signal into a digital signal using resources built into the FPGA. The resulting digital signal can then be used directly or fed into other digital components of the FPGA such as the counter or encoder modules. The analog trigger module works by comparing analog signals to a voltage range set by the code. The specific return types and meanings depend on the analog trigger mode in use.

Constructor for an analog trigger given a channel number or analog input.

Parameters `channel` – the port index or *AnalogInput* to use for the analog trigger. Treated as an *AnalogInput* if the provided object has a `getChannel` function.

`class AnalogTriggerType`

Bases: `object`

Defines the state in which the *AnalogTrigger* triggers

`kFallingPulse = 3`

`kInWindow = 0`

`kRisingPulse = 2`

`kState = 1`

`AnalogTrigger.createOutput` (*type*)

Creates an *AnalogTriggerOutput* object. Gets an output object that can be used for routing. Caller is responsible for deleting the *AnalogTriggerOutput* object.

Parameters `type` – An enum of the type of output object to create.

Returns An *AnalogTriggerOutput* object.

`AnalogTrigger.free` ()

Release the resources used by this object

`AnalogTrigger.getInWindow` ()

Return the *InWindow* output of the analog trigger. True if the analog input is between the upper and lower limits.

Returns The *InWindow* output of the analog trigger.

`AnalogTrigger.getIndex` ()

Return the index of the analog trigger. This is the FPGA index of this analog trigger instance.

Returns The index of the analog trigger.

`AnalogTrigger.getTriggerState` ()

Return the *TriggerState* output of the analog trigger. True if above upper limit. False if below lower limit. If in Hysteresis, maintain previous state.

Returns The *TriggerState* output of the analog trigger.

`AnalogTrigger.port`

`AnalogTrigger.setAveraged` (*useAveragedValue*)

Configure the analog trigger to use the averaged vs. raw values. If the value is true, then the averaged value is selected for the analog trigger, otherwise the immediate value is used.

Parameters `useAveragedValue` – True to use an averaged value, False otherwise

`AnalogTrigger.setFiltered` (*useFilteredValue*)

Configure the analog trigger to use a filtered value. The analog trigger will operate with a 3 point average rejection filter. This is designed to help with 360 degree pot applications for the period where the pot crosses through zero.

Parameters `useFilteredValue` – True to use a filterd value, False otherwise

`AnalogTrigger.setLimitsRaw` (*lower, upper*)

Set the upper and lower limits of the analog trigger. The limits are given in ADC codes. If oversampling is used, the units must be scaled appropriately.

Parameters

- **lower** – the lower raw limit
- **upper** – the upper raw limit

`AnalogTrigger.setLimitsVoltage` (*lower, upper*)

Set the upper and lower limits of the analog trigger. The limits are given as floating point voltage values.

Parameters

- **lower** – the lower voltage limit
- **upper** – the upper voltage limit

AnalogTriggerOutput

`class wpilib.AnalogTriggerOutput` (*trigger, outputType*)

Bases: `wpilib.DigitalSource`

Represents a specific output from an *AnalogTrigger*

This class is used to get the current output value and also as a *DigitalSource* to provide routing of an output to digital subsystems on the FPGA such as *Counter*, `Encoder:`, and `:class:.Interrupt`.

The `TriggerState` output indicates the primary output value of the trigger. If the analog signal is less than the lower limit, the output is False. If the analog value is greater than the upper limit, then the output is True. If the analog value is in between, then the trigger output state maintains its most recent value.

The `InWindow` output indicates whether or not the analog signal is inside the range defined by the limits.

The `RisingPulse` and `FallingPulse` outputs detect an instantaneous transition from above the upper limit to below the lower limit, and vice versa. These pulses represent a rollover condition of a sensor and can be routed to an up / down counter or to interrupts. Because the outputs generate a pulse, they cannot be read directly. To help ensure that a rollover condition is not missed, there is an average rejection filter available that operates on the upper 8 bits of a 12 bit number and selects the nearest outlier of 3 samples. This will reject a sample that is (due to averaging or sampling) errantly between the two limits. This filter will fail if more than one sample in a row is errantly in between the two limits. You may see this problem if attempting to use this feature with a mechanical rollover sensor, such as a 360 degree no-stop potentiometer without signal conditioning, because the rollover transition is not sharp / clean enough. Using the averaging engine may help with this, but rotational speeds of the sensor will then be limited.

Create an object that represents one of the four outputs from an analog trigger.

Because this class derives from `DigitalSource`, it can be passed into routing functions for `Counter`, `Encoder`, etc.

Parameters

- **trigger** – The trigger for which this is an output.
- **outputType** – An enum that specifies the output on the trigger to represent.

```
class AnalogTriggerType
    Bases: object

    Defines the state in which the AnalogTrigger triggers

    kFallingPulse = 3
    kInWindow = 0
    kRisingPulse = 2
    kState = 1

AnalogTriggerOutput.free()
AnalogTriggerOutput.get()
    Get the state of the analog trigger output.

    Returns The state of the analog trigger output.

    Return type AnalogTriggerType

AnalogTriggerOutput.getAnalogTriggerTypeForRouting()
AnalogTriggerOutput.getChannel()
AnalogTriggerOutput.getPortHandleForRouting()
```

BuiltInAccelerometer

```
class wpilib.BuiltInAccelerometer (range=2)
    Bases: wpilib.LiveWindowSendable

    Built-in accelerometer device

    This class allows access to the roboRIO's internal accelerometer.

    Constructor.

    Parameters range (Accelerometer.Range) – The range the accelerometer will measure. Defaults to +/-8g if unspecified.
```

```
class Range
    Bases: object

    k16G = 3
    k2G = 0
    k4G = 1
    k8G = 2

BuiltInAccelerometer.free()
BuiltInAccelerometer.getX()
    Returns The acceleration of the roboRIO along the X axis in g-forces
    Return type float

BuiltInAccelerometer.getY()
    Returns The acceleration of the roboRIO along the Y axis in g-forces
    Return type float

BuiltInAccelerometer.getZ()
```

Returns The acceleration of the roboRIO along the Z axis in g-forces

Return type float

`BuiltInAccelerometer.setRange(range)`
Set the measuring range of the accelerometer.

Parameters `range` (`BuiltInAccelerometer.Range`) – The maximum acceleration, positive or negative, that the accelerometer will measure.

CameraServer

class `wplib.CameraServer`

Bases: object

Provides a way to launch an out of process cscore-based camera service instance, for streaming or for image processing.

Note: This does not correspond directly to the wplib CameraServer object; that can be found as `cscore.CameraServer`. However, you should not use cscore directly from your robot code, see the documentation for details

classmethod `is_alive()`

Returns True if the CameraServer is still alive

classmethod `launch(vision_py=None)`

Launches the CameraServer process in autocalture mode or using a user-specified python script

Parameters `vision_py` – If specified, this is the relative path to a filename with a function in it

Example usage:

```
wplib.CameraServer.launch("vision.py:main")
```

Warning: You must have robotpy-cscore installed, or this function will fail without returning an error (you will see an error in the console).

CANJaguar

class `wplib.CANJaguar(*args, **kwargs)`

Bases: object

CANTalon

class `wplib.CANTalon(*args, **kwargs)`

Bases: object

Compressor

class `wpiplib.Compressor` (*module=None*)

Bases: `wpiplib.SensorBase`

Class for operating a compressor connected to a PCM (Pneumatic Control Module).

The PCM will automatically run in closed loop mode by default whenever a Solenoid object is created. For most cases the Compressor object does not need to be instantiated or used in a robot program. This class is only required in cases where the robot program needs a more detailed status of the compressor or to enable/disable closed loop control.

Note: you cannot operate the compressor directly from this class as doing so would circumvent the safety provided by using the pressure switch and closed loop control. You can only turn off closed loop control, thereby stopping the compressor from operating.

Makes a new instance of the compressor using the provided CAN device ID.

Parameters `module` – The PCM CAN device ID. (0 - 62 inclusive)

clearAllPCMStickyFaults ()

Clear ALL sticky faults inside PCM that Compressor is wired to.

If a sticky fault is set, then it will be persistently cleared. The compressor might momentarily disable while the flags are being cleared. Do not call this method too frequently, otherwise normal compressor functionality may be prevented.

If no sticky faults are set then this call will have no effect.

enabled ()

Get the enabled status of the compressor.

Returns True if the compressor is on

Return type bool

getClosedLoopControl ()

Gets the current operating mode of the PCM.

Returns True if compressor is operating on closed-loop mode

Return type bool

getCompressorCurrent ()

Get the current being used by the compressor.

Returns Current consumed by the compressor in amps

Return type float

getCompressorCurrentTooHighFault ()

Returns True if PCM is in fault state : Compressor Drive is disabled due to compressor current being too high

getCompressorCurrentTooHighStickyFault ()

Returns True if PCM sticky fault is set : Compressor is disabled due to compressor current being too high

getCompressorNotConnectedFault ()

Returns True if PCM is in fault state : Compressor does not appear to be wired, i.e. compressor is not drawing enough current.

getCompressorNotConnectedStickyFault ()

Returns True if PCM sticky fault is set : Compressor does not appear to be wired, i.e. compressor is not drawing enough current.

getCompressorShortedFault ()

Returns True if PCM is in fault state : Compressor output appears to be shorted

getCompressorShortedStickyFault ()

Returns True if PCM sticky fault is set : Compressor output appears to be shorted

getPressureSwitchValue ()

Get the pressure switch value.

Returns True if the pressure is low

Return type bool

setClosedLoopControl (*on*)

Set the PCM in closed loop control mode.

Parameters *on* (*bool*) – If True sets the compressor to be in closed loop control mode (default)

start ()

Start the compressor running in closed loop control mode.

Use the method in cases where you would like to manually stop and start the compressor for applications such as conserving battery or making sure that the compressor motor doesn't start during critical operations.

stop ()

Stop the compressor from running in closed loop control mode.

Use the method in cases where you would like to manually stop and start the compressor for applications such as conserving battery or making sure that the compressor motor doesn't start during critical operations.

ControllerPower

class `wpilib.ControllerPower`

Bases: `object`

Provides access to power levels on the roboRIO

static `getCurrent3V3` ()

Get the current output of the 3.3V rail

Returns The controller 3.3V rail output current value in Amps

Return type float

static `getCurrent5V` ()

Get the current output of the 5V rail

Returns The controller 5V rail output current value in Amps

Return type float

static `getCurrent6V` ()

Get the current output of the 6V rail

Returns The controller 6V rail output current value in Amps

Return type float

static `getEnabled3V3 ()`

Get the enabled state of the 3.3V rail. The rail may be disabled due to a controller brownout, a short circuit on the rail, or controller over-voltage

Returns True if enabled, False otherwise

Return type bool

static `getEnabled5V ()`

Get the enabled state of the 5V rail. The rail may be disabled due to a controller brownout, a short circuit on the rail, or controller over-voltage

Returns True if enabled, False otherwise

Return type bool

static `getEnabled6V ()`

Get the enabled state of the 6V rail. The rail may be disabled due to a controller brownout, a short circuit on the rail, or controller over-voltage

Returns True if enabled, False otherwise

Return type bool

static `getFaultCount3V3 ()`

Get the count of the total current faults on the 3.3V rail since the controller has booted

Returns The number of faults

Return type int

static `getFaultCount5V ()`

Get the count of the total current faults on the 5V rail since the controller has booted

Returns The number of faults

Return type int

static `getFaultCount6V ()`

Get the count of the total current faults on the 6V rail since the controller has booted

Returns The number of faults

Return type int

static `getInputCurrent ()`

Get the input current to the robot controller

Returns The controller input current value in Amps

Return type float

static `getInputVoltage ()`

Get the input voltage to the robot controller

Returns The controller input voltage value in Volts

Return type float

static `getVoltage3V3 ()`

Get the voltage of the 3.3V rail

Returns The controller 3.3V rail voltage value in Volts

Return type float

static `getVoltage5V()`

Get the voltage of the 5V rail

Returns The controller 5V rail voltage value in Volts

Return type float

static `getVoltage6V()`

Get the voltage of the 6V rail

Returns The controller 6V rail voltage value in Volts

Return type float

Counter

class `wpiplib.Counter(*args, **kwargs)`

Bases: `wpiplib.SensorBase`

Counts the number of ticks on a `DigitalInput` channel.

This is a general purpose class for counting repetitive events. It can return the number of counts, the period of the most recent cycle, and detect when the signal being counted has stopped by supplying a maximum cycle time.

All counters will immediately start counting - `reset()` them if you need them to be zeroed before use.

Counter constructor.

The counter will start counting immediately.

Positional arguments may be either channel numbers, `DigitalSource` sources, or `AnalogTrigger` sources in the following order:

A “source” is any valid single-argument input to `setUpSource()` and `setDownSource()`

- (none)
- upSource
- upSource, down source

And, to keep consistency with Java wpiplib. - encodingType, up source, down source, inverted

If the passed object has a `getPortHandleForRouting` function, it is assumed to be a `DigitalSource`. If the passed object has a `createOutput` function, it is assumed to be an `AnalogTrigger`.

In addition, extra keyword parameters may be provided for mode, inverted, and encodingType.

Parameters

- **upSource** – The source (channel num, `DigitalInput`, or `AnalogTrigger`) that should be used for up counting.
- **downSource** – The source (channel num, `DigitalInput`, or `AnalogTrigger`) that should be used for down counting or direction control.
- **mode** – How and what the counter counts (see `Mode`). Defaults to `Mode.kTwoPulse` for zero or one source, and `Mode.kExternalDirection` for two sources.
- **inverted** – Flips the direction of counting. Defaults to `False` if unspecified. Only used when two sources are specified.

- **encodingType** (*Counter.EncodingType*) – Either k1X or k2X to indicate 1X or 2X decoding. 4X decoding is not supported by Counter; use *Encoder* instead. Defaults to k1X if unspecified. Only used when two sources are specified.

class EncodingType

Bases: object

The number of edges for the counterbase to increment or decrement on

k1X = 0**k2X = 1****k4X = 2****class Counter.Mode**

Bases: object

Mode determines how and what the counter counts

kExternalDirection = 3

external direction mode

kPulseLength = 2

pulse length mode

kSemiperiod = 1

semi period mode

kTwoPulse = 0

two pulse mode

class Counter.PIDSourceType

Bases: object

A description for the type of output value to provide to a *PIDController***kDisplacement = 0****kRate = 1****Counter.allocatedDownSource = False****Counter.allocatedUpSource = False****Counter.clearDownSource ()**

Disable the down counting source to the counter.

Counter.clearUpSource ()

Disable the up counting source to the counter.

Counter.counter**Counter.free ()****Counter.get ()**

Read the current counter value. Read the value at this instant. It may still be running, so it reflects the current value. Next time it is read, it might have a different value.

Counter.getDirection ()

The last direction the counter value changed.

Returns The last direction the counter value changed.**Return type** bool

`Counter.getDistance()`

Read the current scaled counter value. Read the value at this instant, scaled by the distance per pulse (defaults to 1).

Returns Scaled value

Return type float

`Counter.getFPGAIndex()`

Returns The Counter's FPGA index.

`Counter.getPIDSourceType()`

`Counter.getPeriod()`

Get the Period of the most recent count. Returns the time interval of the most recent count. This can be used for velocity calculations to determine shaft speed.

Returns The period of the last two pulses in units of seconds.

Return type float

`Counter.getRate()`

Get the current rate of the Counter. Read the current rate of the counter accounting for the distance per pulse value. The default value for distance per pulse (1) yields units of pulses per second.

Returns The rate in units/sec

Return type float

`Counter.getSamplesToAverage()`

Get the Samples to Average which specifies the number of samples of the timer to average when calculating the period. Perform averaging to account for mechanical imperfections or as oversampling to increase resolution.

Returns The number of samples being averaged (from 1 to 127)

Return type int

`Counter.getStopped()`

Determine if the clock is stopped. Determine if the clocked input is stopped based on the MaxPeriod value set using the `setMaxPeriod()` method. If the clock exceeds the MaxPeriod, then the device (and counter) are assumed to be stopped and it returns True.

Returns Returns True if the most recent counter period exceeds the MaxPeriod value set by `SetMaxPeriod`.

Return type bool

`Counter.pidGet()`

`Counter.reset()`

Reset the Counter to zero. Set the counter value to zero. This doesn't effect the running state of the counter, just sets the current value to zero.

`Counter.setDistancePerPulse(distancePerPulse)`

Set the distance per pulse for this counter. This sets the multiplier used to determine the distance driven based on the count value from the encoder. Set this value based on the Pulses per Revolution and factor in any gearing reductions. This distance can be in any units you like, linear or angular.

Parameters `distancePerPulse` (*float*) – The scale factor that will be used to convert pulses to useful units.

`Counter.setDownSource(*args, **kwargs)`

Set the down counting source for the counter.

This function accepts either a digital channel index, a *DigitalSource*, or an *AnalogTrigger* as positional arguments:

- `source`
- `channel`
- `analogTrigger`
- `analogTrigger, triggerType`

For positional arguments, if the passed object has a *getChannelForRouting* function, it is assumed to be a *DigitalSource*. If the passed object has a *createOutput* function, it is assumed to be an *AnalogTrigger*.

Alternatively, sources and/or channels may be passed as keyword arguments. The behavior of specifying both a source and a number for the same channel is undefined, as is passing both a positional and a keyword argument for the same channel.

Parameters

- **channel** (*int*) – the DIO channel to use as the down source. 0-9 are on-board, 10-25 are on the MXP
- **source** (*DigitalInput*) – The digital source to count
- **analogTrigger** (*AnalogTrigger*) – The analog trigger object that is used for the Up Source
- **triggerType** (*AnalogTriggerType*) – The analog trigger output that will trigger the counter. Defaults to `kState` if not specified.

`Counter.setDownSourceEdge(risingEdge, fallingEdge)`

Set the edge sensitivity on an down counting source. Set the down source to either detect rising edges or falling edges.

Parameters

- **risingEdge** (*bool*) – True to count rising edge
- **fallingEdge** (*bool*) – True to count falling edge

`Counter.setExternalDirectionMode()`

Set external direction mode on this counter. Counts are sourced on the Up counter input. The Down counter input represents the direction to count.

`Counter.setMaxPeriod(maxPeriod)`

Set the maximum period where the device is still considered “moving”. Sets the maximum period where the device is considered moving. This value is used to determine the “stopped” state of the counter using the *getStopped()* method.

Parameters `maxPeriod` (*float or int*) – The maximum period where the counted device is considered moving in seconds.

`Counter.setPIDSourceType(pidSource)`

Set which parameter of the encoder you are using as a process control variable. The counter class supports the rate and distance parameters.

Parameters `pidSource` (*Counter.PIDSourceType*) – An enum to select the parameter.

`Counter.setPulseLengthMode(threshold)`

Configure the counter to count in up or down based on the length of the input pulse. This mode is most useful for direction sensitive gear tooth sensors.

Parameters `threshold` (*float, int*) – The pulse length beyond which the counter counts the opposite direction. Units are seconds.

`Counter.setReverseDirection` (*reverseDirection*)

Set the Counter to return reversed sensing on the direction. This allows counters to change the direction they are counting in the case of 1X and 2X quadrature encoding only. Any other counter mode isn't supported.

Parameters `reverseDirection` (*bool*) – True if the value counted should be negated.

`Counter.setSamplesToAverage` (*samplesToAverage*)

Set the Samples to Average which specifies the number of samples of the timer to average when calculating the period. Perform averaging to account for mechanical imperfections or as oversampling to increase resolution.

Parameters `samplesToAverage` (*int*) – The number of samples to average from 1 to 127.

`Counter.setSemiPeriodMode` (*highSemiPeriod*)

Set Semi-period mode on this counter. Counts up on both rising and falling edges.

Parameters `highSemiPeriod` (*bool*) – True to count up on both rising and falling

`Counter.setUpDownCounterMode` ()

Set standard up / down counting mode on this counter. Up and down counts are sourced independently from two inputs.

`Counter.setUpSource` (**args, **kwargs*)

Set the up counting source for the counter.

This function accepts either a digital channel index, a *DigitalSource*, or an *AnalogTrigger* as positional arguments:

- `source`
- `channel`
- `analogTrigger`
- `analogTrigger, triggerType`

For positional arguments, if the passed object has a *getPortHandleForRouting* function, it is assumed to be a *DigitalSource*. If the passed object has a *createOutput* function, it is assumed to be an *AnalogTrigger*.

Alternatively, sources and/or channels may be passed as keyword arguments. The behavior of specifying both a source and a number for the same channel is undefined, as is passing both a positional and a keyword argument for the same channel.

Parameters

- **channel** (*int*) – the DIO channel to use as the up source. 0-9 are on-board, 10-25 are on the MXP
- **source** (*DigitalInput*) – The digital source to count
- **analogTrigger** (*AnalogTrigger*) – The analog trigger object that is used for the Up Source
- **triggerType** (*AnalogTriggerType*) – The analog trigger output that will trigger the counter. Defaults to `kState` if not specified.

`Counter.setUpSourceEdge` (*risingEdge, fallingEdge*)

Set the edge sensitivity on an up counting source. Set the up source to either detect rising edges or falling edges.

Parameters

- **risingEdge** (*bool*) – True to count rising edge
- **fallingEdge** (*bool*) – True to count falling edge

Counter.setUpdateWhenEmpty (*enabled*)

Select whether you want to continue updating the event timer output when there are no samples captured. The output of the event timer has a buffer of periods that are averaged and posted to a register on the FPGA. When the timer detects that the event source has stopped (based on the `MaxPeriod`) the buffer of samples to be averaged is emptied. If you enable update when empty, you will be notified of the stopped source and the event time will report 0 samples. If you disable update when empty, the most recent average will remain on the output until a new sample is acquired. You will never see 0 samples output (except when there have been no events since an FPGA reset) and you will likely not see the stopped bit become true (since it is updated at the end of an average and there are no samples to average).

Parameters **enabled** (*bool*) – True to continue updating

DigitalGlitchFilter

class `wpiplib.DigitalGlitchFilter`

Bases: `wpiplib.SensorBase`

Class to enable glitch filtering on a set of digital inputs. This class will manage adding and removing digital inputs from a FPGA glitch filter. The filter lets the user configure the time that an input must remain high or low before it is classified as high or low.

add (*input*)

Assigns the *DigitalSource*, *Encoder*, or *Counter* to this glitch filter.

Parameters **input** – The object to add

filterAllocated = [False, False, False]

free ()

getPeriodCycles ()

Gets the number of FPGA cycles that the input must hold steady to pass through this glitch filter.

Returns The number of cycles.

getPeriodNanoSeconds ()

Gets the number of nanoseconds that the input must hold steady to pass through this glitch filter.

Returns The number of nanoseconds.

mutex = <unlocked_thread.lock object>

remove (*input*)

Removes this filter from the given input object

setPeriodCycles (*fpga_cycles*)

Sets the number of FPGA cycles that the input must hold steady to pass through this glitch filter.

Parameters **fpga_cycles** – The number of FPGA cycles.

setPeriodNanoSeconds (*nanoseconds*)

Sets the number of nanoseconds that the input must hold steady to pass through this glitch filter.

Parameters **nanoseconds** – The number of nanoseconds.

DigitalInput

class `wpiplib.DigitalInput` (*channel*)

Bases: `wpiplib.DigitalSource`

Reads a digital input.

This class will read digital inputs and return the current value on the channel. Other devices such as encoders, gear tooth sensors, etc. that are implemented elsewhere will automatically allocate digital inputs and outputs as required. This class is only for devices like switches etc. that aren't implemented anywhere else.

Create an instance of a Digital Input class. Creates a digital input given a channel.

Parameters `channel` (*int*) – the DIO channel for the digital input. 0-9 are on-board, 10-25 are on the MXP

free ()

get ()

Get the value from a digital input channel. Retrieve the value of a single digital input channel from the FPGA.

Returns the state of the digital input

Return type bool

getAnalogTriggerTypeForRouting ()

Get the analog trigger type.

Returns false

Return type int

getChannel ()

Get the channel of the digital input.

Returns The GPIO channel number that this object represents.

Return type int

getPortHandleForRouting ()

Get the HAL Port Handle.

Returns The HAL Handle to the specified source

isAnalogTrigger ()

Is this an analog trigger.

Returns true if this is an analog trigger

Return type bool

DigitalOutput

class `wpiplib.DigitalOutput` (*channel*)

Bases: `wpiplib.DigitalSource`

Writes to a digital output

Other devices that are implemented elsewhere will automatically allocate digital inputs and outputs as required.

Create an instance of a digital output.

Parameters `channel` – the DIO channel for the digital output. 0-9 are on-board, 10-25 are on the MXP

disablePWM()

Change this line from a PWM output back to a static Digital Output line.

Free up one of the 6 DO PWM generator resources that were in use.

enablePWM(*initialDutyCycle*)

Enable a PWM Output on this line.

Allocate one of the 6 DO PWM generator resources.

Supply the initial duty-cycle to output so as to avoid a glitch when first starting.

The resolution of the duty cycle is 8-bit for low frequencies (1kHz or less) but is reduced the higher the frequency of the PWM signal is.

Parameters `initialDutyCycle` (*float*) – The duty-cycle to start generating. [0..1]

free()

Free the resources associated with a digital output.

get()

Gets the value being output from the Digital Output.

Returns the state of the digital output

Return type bool

getAnalogTriggerTypeForRouting()

Get the analog trigger type.

Returns false

Return type int

getChannel()

Returns The GPIO channel number that this object represents.

getPortHandleForRouting()

Get the HAL Port Handle.

Returns The HAL Handle to the specified source

isAnalogTrigger()

Is this an analog trigger.

Returns true if this is an analog trigger

Return type bool

isPulsing()

Determine if the pulse is still going. Determine if a previously started pulse is still going.

Returns True if pulsing

Return type bool

pulse(*pulseLength*, *args)

Generate a single pulse. There can only be a single pulse going at any time.

Parameters

- `channel` – Unused. Deprecated 2017.1.1.
- `pulseLength` (*float*) – The length of the pulse.

pwmGenerator**set** (*value*)

Set the value of a digital output.

Parameters **value** (*bool*) – True is on, off is False**setPWMRate** (*rate*)

Change the PWM frequency of the PWM output on a Digital Output line.

The valid range is from 0.6 Hz to 19 kHz. The frequency resolution is logarithmic.

There is only one PWM frequency for all channels.

Parameters **rate** (*float*) – The frequency to output all digital output PWM signals.**updateDutyCycle** (*dutyCycle*)

Change the duty-cycle that is being generated on the line.

The resolution of the duty cycle is 8-bit for low frequencies (1kHz or less) but is reduced the higher the frequency of the PWM signal is.

Parameters **dutyCycle** (*float*) – The duty-cycle to change to. [0..1]

DigitalSource

class `wpiplib.DigitalSource` (*channel*, *input*)Bases: `wpiplib.InterruptableSensorBase`

DigitalSource Interface. The DigitalSource represents all the possible inputs for a counter or a quadrature encoder. The source may be either a digital input or an analog input. If the caller just provides a channel, then a digital input will be constructed and freed when finished for the source. The source can either be a digital input or analog trigger but not both.

Parameters

- **channel** (*int*) – Port for the digital input
- **input** (*int*) – True if input, False otherwise

channels = <`wpiplib.resource.Resource` object>**free** ()**getChannel** ()**handle****isAnalogTrigger** ()

DoubleSolenoid

class `wpiplib.DoubleSolenoid` (**args*, ***kwargs*)Bases: `wpiplib.SolenoidBase`

Controls 2 channels of high voltage Digital Output on the PCM.

The DoubleSolenoid class is typically used for pneumatics solenoids that have two positions controlled by two separate channels.

Constructor.

Arguments can be supplied as positional or keyword. Acceptable positional argument combinations are:

- forwardChannel, reverseChannel
- moduleNumber, forwardChannel, reverseChannel

Alternatively, the above names can be used as keyword arguments.

Parameters

- **moduleNumber** – The module number of the solenoid module to use.
- **forwardChannel** – The forward channel number on the module to control (0..7)
- **reverseChannel** – The reverse channel number on the module to control (0..7)

class Value

Bases: object

Possible values for a DoubleSolenoid.

kForward = 1

kOff = 0

kReverse = 2

DoubleSolenoid.**free**()

Mark the solenoid as freed.

DoubleSolenoid.**get**()

Read the current value of the solenoid.

Returns The current value of the solenoid.

Return type *DoubleSolenoid.Value*

DoubleSolenoid.**isFwdSolenoidBlackListed**()

Check if the forward solenoid is blacklisted. If a solenoid is shorted, it is added to the blacklist and disabled until power cycle, or until faults are cleared. See `clearAllPCMStickyFaults()`

Returns If solenoid is disabled due to short.

DoubleSolenoid.**isRevSolenoidBlackListed**()

Check if the reverse solenoid is blacklisted. If a solenoid is shorted, it is added to the blacklist and disabled until power cycle, or until faults are cleared. See `clearAllPCMStickyFaults()`

Returns If solenoid is disabled due to short.

DoubleSolenoid.**set**(value)

Set the value of a solenoid.

Parameters **value** (*DoubleSolenoid.Value*) – The value to set (Off, Forward, Reverse)

DriverStation

class `wpiplib.DriverStation`

Bases: object

Provide access to the network communication data to / from the Driver Station.

DriverStation constructor.

The single `DriverStation` instance is created statically with the instance static member variable, you should never create a `DriverStation` instance.

class `Alliance`

Bases: `object`

The robot alliance that the robot is a part of

Blue = 1

Invalid = 2

Red = 0

`DriverStation.InAutonomous` (*entering*)

Only to be used to tell the Driver Station what code you claim to be executing for diagnostic purposes only.

Parameters entering – If True, starting autonomous code; if False, leaving autonomous code

`DriverStation.InDisabled` (*entering*)

Only to be used to tell the Driver Station what code you claim to be executing for diagnostic purposes only.

Parameters entering – If True, starting disabled code; if False, leaving disabled code

`DriverStation.InOperatorControl` (*entering*)

Only to be used to tell the Driver Station what code you claim to be executing for diagnostic purposes only.

Parameters entering – If True, starting teleop code; if False, leaving teleop code

`DriverStation.InTest` (*entering*)

Only to be used to tell the Driver Station what code you claim to be executing for diagnostic purposes only.

Parameters entering – If True, starting test code; if False, leaving test code

`DriverStation.getAlliance` ()

Get the current alliance from the FMS.

Returns The current alliance

Return type `DriverStation.Alliance`

`DriverStation.getBatteryVoltage` ()

Read the battery voltage.

Returns The battery voltage in Volts.

classmethod `DriverStation.getInstance` ()

Gets the global instance of the `DriverStation`

Returns `DriverStation`

`DriverStation.getJoystickAxisType` (*stick, axis*)

Returns the types of Axes on a given joystick port.

Parameters

- **stick** (*int*) – The joystick port number
- **axis** (*int*) – The target axis

:returns An integer that reports type of axis the axis is reporting to be

`DriverStation.getJoystickIsXbox` (*stick*)

Gets the value of `isXbox` on a joystick

Parameters stick (*int*) – The joystick port number

:returns A boolean that returns the value of `isXbox`

`DriverStation.getJoystickName (stick)`

Gets the name of a joystick

Parameters `stick (int)` – The joystick port number

:returns The joystick name.

`DriverStation.getJoystickType (stick)`

Gets the value of type on a joystick

Parameters `stick (int)` – The joystick port number

:returns An integer that returns the value of type.

`DriverStation.getLocation ()`

Gets the location of the team's driver station controls.

Returns The location of the team's driver station controls: 1, 2, or 3

`DriverStation.getMatchTime ()`

Return the approximate match time. The FMS does not currently send the official match time to the robots, but does send an approximate match time. The value will count down the time remaining in the current period (auto or teleop).

Warning: This is not an official time (so it cannot be used to argue with referees or guarantee that a function will trigger before a match ends).

The Practice Match function of the DS approximates the behaviour seen on the field.

Returns Time remaining in current match period (auto or teleop) in seconds

`DriverStation.getStickAxis (stick, axis)`

Get the value of the axis on a joystick. This depends on the mapping of the joystick connected to the specified port.

Parameters

- `stick (int)` – The joystick port number
- `axis (int)` – The analog axis value to read from the joystick.

Returns The value of the axis on the joystick.

`DriverStation.getStickAxisCount (stick)`

Returns the number of axes on a given joystick port

Parameters `stick (int)` – The joystick port number

Returns The number of axes on the indicated joystick

`DriverStation.getStickButton (stick, button)`

The state of a button on the joystick. Button indexes begin at 1.

Parameters

- `stick (int)` – The joystick port number
- `button (int)` – The button index, beginning at 1.

Returns The state of the button.

`DriverStation.getStickButtonCount (stick)`

Gets the number of buttons on a joystick

Parameters `stick (int)` – The joystick port number

Returns The number of buttons on the indicated joystick.

`DriverStation.getStickButtons (stick)`

The state of all the buttons on the joystick.

Parameters `stick (int)` – The joystick port number

Returns The state of all buttons, as a bit array.

`DriverStation.getStickPOV (stick, pov)`

Get the state of a POV on the joystick.

Parameters

- `stick (int)` – The joystick port number
- `pov (int)` – which POV

Returns The angle of the POV in degrees, or -1 if the POV is not pressed.

`DriverStation.getStickPOVCount (stick)`

Returns the number of POVs on a given joystick port

Parameters `stick (int)` – The joystick port number

Returns The number of POVs on the indicated joystick

`DriverStation.isAutonomous ()`

Gets a value indicating whether the Driver Station requires the robot to be running in autonomous mode.

Returns True if autonomous mode should be enabled, False otherwise.

`DriverStation.isBrownedOut ()`

Check if the system is browned out.

Returns True if the system is browned out.

`DriverStation.isDSAttached ()`

Is the driver station attached to the robot?

Returns True if the robot is being controlled by a driver station.

`DriverStation.isDisabled ()`

Gets a value indicating whether the Driver Station requires the robot to be disabled.

Returns True if the robot should be disabled, False otherwise.

`DriverStation.isEnabled ()`

Gets a value indicating whether the Driver Station requires the robot to be enabled.

Returns True if the robot is enabled, False otherwise.

`DriverStation.isFMSAttached ()`

Is the driver station attached to a Field Management System?

Returns True if the robot is competing on a field being controlled by a Field Management System

`DriverStation.isNewControlData ()`

Has a new control packet from the driver station arrived since the last time this function was called?

Returns True if the control data has been updated since the last call.

`DriverStation.isOperatorControl ()`

Gets a value indicating whether the Driver Station requires the robot to be running in operator-controlled mode.

Returns True if operator-controlled mode should be enabled, False otherwise.

`DriverStation.isSysActive()`

Gets a value indicating whether the FPGA outputs are enabled. The outputs may be disabled if the robot is disabled or e-stopped, the watchdog has expired, or if the roboRIO browns out.

Returns True if the FPGA outputs are enabled.

`DriverStation.isTest()`

Gets a value indicating whether the Driver Station requires the robot to be running in test mode.

Returns True if test mode should be enabled, False otherwise.

`DriverStation.kJoystickPorts = 6`

The number of joystick ports

`DriverStation.release()`

Kill the thread

static `DriverStation.reportError(error, printTrace)`

Report error to Driver Station, and also prints error to `sys.stderr`. Optionally appends stack trace to error message.

Parameters `printTrace` – If True, append stack trace to error string

static `DriverStation.reportWarning(error, printTrace)`

Report warning to Driver Station, and also prints error to `sys.stderr`. Optionally appends stack trace to error message.

Parameters `printTrace` – If True, append stack trace to warning string

`DriverStation.waitForData(timeout=None)`

Wait for new data or for timeout, whichever ever comes first. If timeout is None, wait for new data only.

Parameters `timeout` – The maximum time in seconds to wait.

Returns True if there is new data, otherwise False

Encoder

class `wpiplib.Encoder(*args, **kwargs)`

Bases: `wpiplib.SensorBase`

Class to read quadrature encoders.

Quadrature encoders are devices that count shaft rotation and can sense direction. The output of the Encoder class is an integer that can count either up or down, and can go negative for reverse direction counting. When creating Encoders, a direction can be supplied that inverts the sense of the output to make code more readable if the encoder is mounted such that forward movement generates negative values. Quadrature encoders have two digital outputs, an A Channel and a B Channel, that are out of phase with each other to allow the FPGA to do direction sensing.

All encoders will immediately start counting - `reset()` them if you need them to be zeroed before use.

Instance variables:

- `aSource`: The A phase of the quad encoder
- `bSource`: The B phase of the quad encoder
- `indexSource`: The index source (available on some encoders)

Encoder constructor. Construct a Encoder given a and b channels and optionally an index channel.

The encoder will start counting immediately.

The a, b, and optional index channel arguments may be either channel numbers or *DigitalSource* sources. There may also be a boolean reverseDirection, and an encodingType according to the following list.

- aSource, bSource
- aSource, bSource, reverseDirection
- aSource, bSource, reverseDirection, encodingType
- aSource, bSource, indexSource, reverseDirection
- aSource, bSource, indexSource
- aChannel, bChannel
- aChannel, bChannel, reverseDirection
- aChannel, bChannel, reverseDirection, encodingType
- aChannel, bChannel, indexChannel, reverseDirection
- aChannel, bChannel, indexChannel

For positional arguments, if the passed object has a *getPortHandleForRouting* function, it is assumed to be a DigitalSource.

Alternatively, sources and/or channels may be passed as keyword arguments. The behavior of specifying both a source and a number for the same channel is undefined, as is passing both a positional and a keyword argument for the same channel.

In addition, keyword parameters may be provided for reverseDirection and inputType.

Parameters

- **aSource** – The source that should be used for the a channel.
- **bSource** – The source that should be used for the b channel.
- **indexSource** – The source that should be used for the index channel.
- **aChannel** – The digital input index that should be used for the a channel.
- **bChannel** – The digital input index that should be used for the b channel.
- **indexChannel** – The digital input index that should be used for the index channel.
- **reverseDirection** – Represents the orientation of the encoder and inverts the output values if necessary so forward represents positive values. Defaults to False if unspecified.
- **encodingType** (*Encoder.EncodingType*) – Either k1X, k2X, or k4X to indicate 1X, 2X or 4X decoding. If 4X is selected, then an encoder FPGA object is used and the returned counts will be 4x the encoder spec'd value since all rising and falling edges are counted. If 1X or 2X are selected then a counter object will be used and the returned value will either exactly match the spec'd count or be double (2x) the spec'd count. Defaults to k4X if unspecified.

class EncodingType

Bases: object

The number of edges for the counterbase to increment or decrement on

k1X = 0

k2X = 1

k4X = 2

class Encoder.**IndexingType**

Bases: object

kResetOnFallingEdge = 2

kResetOnRisingEdge = 3

kResetWhileHigh = 0

kResetWhileLow = 1

class Encoder.**PIDSourceType**

Bases: object

A description for the type of output value to provide to a *PIDController*

kDisplacement = 0

kRate = 1

Encoder.**encoder**

Encoder.**free**()

Encoder.**get**()

Gets the current count. Returns the current count on the Encoder. This method compensates for the decoding type.

Returns Current count from the Encoder adjusted for the 1x, 2x, or 4x scale factor.

Encoder.**getDirection**()

The last direction the encoder value changed.

Returns The last direction the encoder value changed.

Encoder.**getDistance**()

Get the distance the robot has driven since the last reset.

Returns The distance driven since the last reset as scaled by the value from *setDistancePerPulse()*.

Encoder.**getEncodingScale**()

Returns The encoding scale factor 1x, 2x, or 4x, per the requested encodingType. Used to divide raw edge counts down to spec'd counts.

Encoder.**getFPGAIndex**()

Returns The Encoder's FPGA index

Encoder.**getPIDSourceType**()

Encoder.**getPeriod**()

Returns the period of the most recent pulse. Returns the period of the most recent Encoder pulse in seconds. This method compensates for the decoding type.

Deprecated since version Use: *getRate()* in favor of this method. This returns unscaled periods and *getRate()* scales using value from *getDistancePerPulse()*.

Returns Period in seconds of the most recent pulse.

Encoder.**getRate**()

Get the current rate of the encoder. Units are distance per second as scaled by the value from *setDistancePerPulse()*.

returns The current rate of the encoder.

`Encoder.getRaw()`

Gets the raw value from the encoder. The raw value is the actual count unscaled by the 1x, 2x, or 4x scale factor.

Returns Current raw count from the encoder

`Encoder.getSamplesToAverage()`

Get the Samples to Average which specifies the number of samples of the timer to average when calculating the period. Perform averaging to account for mechanical imperfections or as oversampling to increase resolution.

Returns The number of samples being averaged (from 1 to 127)

`Encoder.getStopped()`

Determine if the encoder is stopped. Using the MaxPeriod value, a boolean is returned that is True if the encoder is considered stopped and False if it is still moving. A stopped encoder is one where the most recent pulse width exceeds the MaxPeriod.

Returns True if the encoder is considered stopped.

`Encoder.pidGet()`

Implement the PIDSource interface.

Returns The current value of the selected source parameter.

`Encoder.reset()`

Reset the Encoder distance to zero. Resets the current count to zero on the encoder.

`Encoder.setDistancePerPulse(distancePerPulse)`

Set the distance per pulse for this encoder. This sets the multiplier used to determine the distance driven based on the count value from the encoder. Do not include the decoding type in this scale. The library already compensates for the decoding type. Set this value based on the encoder's rated Pulses per Revolution and factor in gearing reductions following the encoder shaft. This distance can be in any units you like, linear or angular.

Parameters `distancePerPulse` – The scale factor that will be used to convert pulses to useful units.

`Encoder.setIndexSource(source, indexing_type=3)`

Set the index source for the encoder. When this source rises, the encoder count automatically resets.

Parameters

- **source** – Either an initialized DigitalSource or a DIO channel number
- **indexing_type** – The state that will cause the encoder to reset

Type Either a DigitalInput or number

Type A value from `wplib.IndexingType`

`Encoder.setMaxPeriod(maxPeriod)`

Sets the maximum period for stopped detection. Sets the value that represents the maximum period of the Encoder before it will assume that the attached device is stopped. This timeout allows users to determine if the wheels or other shaft has stopped rotating. This method compensates for the decoding type.

Parameters `maxPeriod` – The maximum time between rising and falling edges before the FPGA will report the device stopped. This is expressed in seconds.

`Encoder.setMinRate(minRate)`

Set the minimum rate of the device before the hardware reports it stopped.

Parameters `minRate` – The minimum rate. The units are in distance per second as scaled by the value from `setDistancePerPulse()`.

`Encoder.setPIDSourceType(pidSource)`

Set which parameter of the encoder you are using as a process control variable. The encoder class supports the rate and distance parameters.

Parameters `pidSource` – An enum to select the parameter.

`Encoder.setReverseDirection(reverseDirection)`

Set the direction sensing for this encoder. This sets the direction sensing on the encoder so that it could count in the correct software direction regardless of the mounting.

Parameters `reverseDirection` – True if the encoder direction should be reversed

`Encoder.setSamplesToAverage(samplesToAverage)`

Set the Samples to Average which specifies the number of samples of the timer to average when calculating the period. Perform averaging to account for mechanical imperfections or as oversampling to increase resolution.

TODO: Should this raise an exception, so that the user has to deal with giving an incorrect value?

Parameters `samplesToAverage` – The number of samples to average from 1 to 127.

Filter

`class wpilib.Filter(source)`

Bases: `object`

Superclass for filters

Constructor.

Parameters `source` (`PIDSource`, callable) –

`get()`

Returns the current filter estimate without also inserting new data as `pidGet()` would do.

Returns The current filter estimate

`getPIDSourceType()`

`pidGet()`

`pidGetSource()`

Calls `PIDGet()` of source

Returns Current value of source

`reset()`

Reset the filter state

`setPIDSourceType(pidSourceType)`

GearTooth

`class wpilib.GearTooth(channel, directionSensitive=False)`

Bases: `wpilib.Counter`

Interface to the gear tooth sensor supplied by FIRST

Currently there is no reverse sensing on the gear tooth sensor, but in future versions we might implement the necessary timing in the FPGA to sense direction.

Construct a GearTooth sensor.

Parameters

- **channel** (*int*) – The DIO channel index or DigitalSource that the sensor is connected to.
- **directionSensitive** (*bool*) – True to enable the pulse length decoding in hardware to specify count direction. Defaults to False.

enableDirectionSensing (*directionSensitive*)

free ()

kGearToothThreshold = 5.5e-05

GyroBase

class `wpiplib.GyroBase`

Bases: `wpiplib.SensorBase`

GyroBase is the common base class for Gyro implementations such as `AnalogGyro`.

class `PIDSourceType`

Bases: `object`

A description for the type of output value to provide to a `PIDController`

kDisplacement = 0

kRate = 1

`GyroBase.calibrate` ()

`GyroBase.getAngle` ()

`GyroBase.getPIDSourceType` ()

`GyroBase.getRate` ()

`GyroBase.pidGet` ()

Get the output of the gyro for use with PIDControllers. May be the angle or rate depending on the set `PIDSourceType`

Returns the current angle according to the gyro

Return type float

`GyroBase.reset` ()

`GyroBase.setPIDSourceType` (*pidSource*)

Set which parameter of the gyro you are using as a process control variable. The Gyro class supports the rate and angle parameters.

Parameters `pidSource` (`PIDSource.PIDSourceType`) – An enum to select the parameter.

I2C

class `wpiplib.I2C` (*port, deviceAddress, simPort=None*)

Bases: `object`

I2C bus interface class.

This class is intended to be used by sensor (and other I2C device) drivers. It probably should not be used directly.

Example usage:

```
i2c = wpilib.I2C(wpilib.I2C.Port.kOnboard, 4)

# Write bytes 'text', and receive 4 bytes in data
data = i2c.transaction(b'text', 4)
```

Constructor.

Parameters

- **port** (*I2C.Port*) – The I2C port the device is connected to.
- **deviceAddress** – The address of the device on the I2C bus.
- **simPort** – This must be an object that implements all of the `i2c*` functions from `hal_impl` that you use. See `test_i2c.py` for an example.

class Port

Bases: `object`

kMXP = 1

kOnboard = 0

I2C.**addressOnly** ()

Attempt to address a device on the I2C bus.

This allows you to figure out if there is a device on the I2C bus that responds to the address specified in the constructor.

Returns Transfer Aborted... False for success, True for aborted.

I2C.**free** ()

I2C.**port**

I2C.**read** (*registerAddress, count*)

Execute a read transaction with the device.

Read bytes from a device. Most I2C devices will auto-increment the register pointer internally allowing you to read consecutive registers on a device in a single transaction.

Parameters

- **registerAddress** – The register to read first in the transaction.
- **count** – The number of bytes to read in the transaction.

Returns The data read from the device.

Return type iterable of bytes

I2C.**readOnly** (*count*)

Execute a read only transaction with the device.

Read bytes from a device. This method does not write any data to prompt the device.

Parameters **count** – The number of bytes to read in the transaction.

Returns The data read from the device.

Return type iterable of bytes

`I2C.transaction` (*dataToSend*, *receiveSize*)

Generic transaction.

This is a lower-level interface to the I2C hardware giving you more control over each transaction.

Parameters

- **dataToSend** (*iterable of bytes*) – Buffer of data to send as part of the transaction.
- **receiveSize** (*int*) – Number of bytes to read from the device.

Returns Data received from the device.

Return type iterable of bytes

`I2C.verifySensor` (*registerAddress*, *expected*)

Verify that a device's registers contain expected values.

Most devices will have a set of registers that contain a known value that can be used to identify them. This allows an I2C device driver to easily verify that the device contains the expected value.

The device must support and be configured to use register auto-increment.

Parameters

- **registerAddress** – The base register to start reading from the device.
- **expected** – The values expected from the device.

Returns True if the sensor was verified to be connected

`I2C.write` (*registerAddress*, *data*)

Execute a write transaction with the device.

Write a single byte to a register on a device and wait until the transaction is complete.

Parameters

- **registerAddress** – The address of the register on the device to be written.
- **data** – The byte to write to the register on the device.

Returns Transfer Aborted... False for success, True for aborted.

`I2C.writeBulk` (*data*)

Execute a write transaction with the device.

Write multiple bytes to a register on a device and wait until the transaction is complete.

Parameters **data** (*iterable of bytes*) – The data to write to the device.

Returns Transfer Aborted... False for success, True for aborted.

Usage:

```
# send byte string
failed = i2c.writeBulk(b'stuff')

# send list of integers
failed = i2c.write([0x01, 0x02])
```

GamepadBase

class `wpiplib.interfaces.GamepadBase` (*port*)

Bases: `wpiplib.interfaces.GenericHID`

GamepadBase Interface.

getBumper (*hand*)

Is the bumper pressed.

Parameters *hand* – which hand

Returns true if the bumper is pressed

getName ()

getPOV (*pov=0*)

getPOVCount ()

getRawAxis (*axis*)

getRawButton (*button*)

getStickButton (*hand=None*)

getType ()

setOutput (*outputNumber, value*)

setOutputs (*value*)

setRumble (*type, value*)

GenericHID

class `wpiplib.interfaces.GenericHID` (*port*)

Bases: `object`

GenericHID Interface.

class `HIDType` (*value*)

Bases: `object`

kHID1stPerson = 24

kHIDDriving = 22

kHIDFlight = 23

kHIDGamepad = 21

kHIDJoystick = 20

kUnknown = -1

kXInputArcadePad = 19

kXInputArcadeStick = 3

kXInputDancePad = 5

kXInputDrumKit = 8

kXInputFlightStick = 4

kXInputGamepad = 1

```

kXInputGuitar = 6
kXInputGuitar2 = 7
kXInputGuitar3 = 11
kXInputUnknown = 0
kXInputWheel = 2

```

class `GenericHID.Hand`
Bases: `object`

Which hand the Human Interface Device is associated with.

```

kLeft = 0
    Left Hand
kRight = 1
    Right Hand

```

class `GenericHID.RumbleType`
Bases: `object`

Represents a rumble output on the JoyStick.

```

kLeftRumble = 0
    Left Hand
kRightRumble = 1
    Right Hand

```

`GenericHID.getName()`
Get the name of the HID.

Returns the name of the HID.

`GenericHID.getPOV(pov=0)`
Get the angle in degrees of a POV on the HID.

The POV angles start at 0 in the up direction, and increase clockwise (eg right is 90, upper-left is 315).

Parameters `pov` – The index of the POV to read (starting at 0)

Returns the angle of the POV in degrees, or -1 if the POV is not pressed.

`GenericHID.getPOVCount()`
For the current HID, return the number of POVs.

`GenericHID.getPort()`
Get the port number of the HID.

Returns The port number of the HID.

`GenericHID.getRawAxis(which)`
Get the raw axis.

Parameters `which` – index of the axis

Returns the raw value of the selected axis

`GenericHID.getRawButton(button)`
Is the given button pressed.

Parameters `button` – which button number

Returns the angle of the POV in degrees, or -1 if the POV is not pressed.

`GenericHID.getType()`

Get the type of the HID.

Returns the type of the HID.

`GenericHID.getX(hand=None)`

Get the x position of HID.

Parameters `hand` – which hand, left or right

Returns the x position

`GenericHID.getY(hand=None)`

Get the y position of the HID.

Parameters `hand` – which hand, left or right

Returns the y position

`GenericHID.setOutput(outputNumber, value)`

Set a single HID output value for the HID.

Parameters

- **outputNumber** – The index of the output to set (1-32)
- **value** – The value to set the output to

`GenericHID.setOutputs(value)`

Set all HID output values for the HID.

Parameters `value` – The 32 bit output value (1 bit for each output)

`GenericHID.setRumble(type, value)`

Set the rumble output for the HID. The DS currently supports 2 rumble values, left rumble and right rumble.

Parameters

- **type** – Which rumble value to set
- **value** – The normalized value (0 to 1) to set the rumble to

InterruptableSensorBase

`class wpilib.InterruptableSensorBase`

Bases: `wpilib.SensorBase`

Base for sensors to be used with interrupts

Create a new InterruptableSensorBase

`allocateInterrupts(watcher)`

Allocate the interrupt

Parameters `watcher` – True if the interrupt should be in synchronous mode where the user program will have to explicitly wait for the interrupt to occur.

`cancelInterrupts()`

Cancel interrupts on this device. This deallocates all the chipobject structures and disables any interrupts.

`disableInterrupts()`

Disable Interrupts without without deallocating structures.

enableInterrupts ()

Enable interrupts to occur on this input. Interrupts are disabled when the RequestInterrupt call is made. This gives time to do the setup of the other options before starting to field interrupts.

getAnalogTriggerTypeForRouting ()**getPortHandleForRouting ()****interrupt****readFallingTimestamp ()**

Return the timestamp for the falling interrupt that occurred most recently. This is in the same time domain as getClock(). The falling-edge interrupt should be enabled with setUpSourceEdge.

Returns Timestamp in seconds since boot.

readRisingTimestamp ()

Return the timestamp for the rising interrupt that occurred most recently. This is in the same time domain as getClock(). The rising-edge interrupt should be enabled with setUpSourceEdge.

Returns Timestamp in seconds since boot.

requestInterrupts (handler=None)

Request one of the 8 interrupts asynchronously on this digital input.

Parameters **handler** – (optional) The function that will be called whenever there is an interrupt on this device. Request interrupts in synchronous mode where the user program interrupt handler will be called when an interrupt occurs. The default is interrupt on rising edges only. If not specified, the user program will have to explicitly wait for the interrupt to occur using waitForInterrupt.

setUpSourceEdge (risingEdge, fallingEdge)

Set which edge to trigger interrupts on

Parameters

- **risingEdge** – True to interrupt on rising edge
- **fallingEdge** – True to interrupt on falling edge

waitForInterrupt (timeout, ignorePrevious=True)

In synchronous mode, wait for the defined interrupt to occur. You should **NOT** attempt to read the sensor from another thread while waiting for an interrupt. This is not threadsafe, and can cause memory corruption

Parameters

- **timeout** – Timeout in seconds
- **ignorePrevious** – If True (default), ignore interrupts that happened before waitForInterrupt was called.

IterativeRobot

class wpilib.IterativeRobot

Bases: *wpilib.RobotBase*

IterativeRobot implements a specific type of Robot Program framework, extending the *RobotBase* class.

The IterativeRobot class is intended to be subclassed by a user creating a robot program.

This class is intended to implement the “old style” default code, by providing the following functions which are called by the main loop, *startCompetition()*, at the appropriate times:

- *robotInit()* – provide for initialization at robot power-on

init() functions – each of the following functions is called once when the appropriate mode is entered:

- `disabledInit()` – called only when first disabled
- `autonomousInit()` – called each and every time autonomous is entered from another mode
- `teleopInit()` – called each and every time teleop is entered from another mode
- `testInit()` – called each and every time test mode is entered from another mode

Periodic() functions – each of these functions is called iteratively at the appropriate periodic rate (aka the “slow loop”). The period of the iterative robot is synced to the driver station control packets, giving a periodic frequency of about 50Hz (50 times per second).

- `disabledPeriodic()`
- `autonomousPeriodic()`
- `teleopPeriodic()`
- `testPeriodic()`

Constructor for `RobotIterativeBase`.

The constructor initializes the instance variables for the robot to indicate the status of initialization for disabled, autonomous, and teleop code.

Warning: If you override `__init__` in your robot class, you must call the base class constructor. This must be used to ensure that the communications code starts.

autonomousInit()

Initialization code for autonomous mode should go here.

Users should override this method for initialization code which will be called each time the robot enters autonomous mode.

autonomousPeriodic()

Periodic code for autonomous mode should go here.

Users should override this method for code which will be called each time a new packet is received from the driver station and the robot is in autonomous mode.

Packets are received approximately every 20ms. Fixed loop timing is not guaranteed due to network timing variability and the function may not be called at all if the Driver Station is disconnected. For most use cases the variable timing will not be an issue. If your code does require guaranteed fixed periodic timing, consider using `Notifier` or `PIDController` instead.

disabledInit()

Initialization code for disabled mode should go here.

Users should override this method for initialization code which will be called each time the robot enters disabled mode.

disabledPeriodic()

Periodic code for disabled mode should go here.

Users should override this method for code which will be called each time a new packet is received from the driver station and the robot is in disabled mode.

Packets are received approximately every 20ms. Fixed loop timing is not guaranteed due to network timing variability and the function may not be called at all if the Driver Station is disconnected. For most use cases the variable timing will not be an issue. If your code does require guaranteed fixed periodic timing, consider using `Notifier` or `PIDController` instead.

logger = <logging.Logger object>

A python logging object that you can use to send messages to the log. It is recommended to use this instead of print statements.

robotInit ()

Robot-wide initialization code should go here.

Users should override this method for default Robot-wide initialization which will be called when the robot is first powered on. It will be called exactly 1 time.

Note: It is simpler to override this function instead of defining a constructor for your robot class

robotPeriodic ()

Periodic code for all robot modes should go here.

This function is called each time a new packet is received from the driver station.

Packets are received approximately every 20ms. Fixed loop timing is not guaranteed due to network timing variability and the function may not be called at all if the Driver Station is disconnected. For most use cases the variable timing will not be an issue. If your code does require guaranteed fixed periodic timing, consider using Notifier or PIDController instead.

startCompetition ()

Provide an alternate “main loop” via startCompetition().

teleopInit ()

Initialization code for teleop mode should go here.

Users should override this method for initialization code which will be called each time the robot enters teleop mode.

teleopPeriodic ()

Periodic code for teleop mode should go here.

Users should override this method for code which will be called each time a new packet is received from the driver station and the robot is in teleop mode.

Packets are received approximately every 20ms. Fixed loop timing is not guaranteed due to network timing variability and the function may not be called at all if the Driver Station is disconnected. For most use cases the variable timing will not be an issue. If your code does require guaranteed fixed periodic timing, consider using Notifier or PIDController instead.

testInit ()

Initialization code for test mode should go here.

Users should override this method for initialization code which will be called each time the robot enters test mode.

testPeriodic ()

Periodic code for test mode should go here.

Users should override this method for code which will be called each time a new packet is received from the driver station and the robot is in test mode.

Packets are received approximately every 20ms. Fixed loop timing is not guaranteed due to network timing variability and the function may not be called at all if the Driver Station is disconnected. For most use cases the variable timing will not be an issue. If your code does require guaranteed fixed periodic timing, consider using Notifier or PIDController instead.

Jaguar

class `wpiplib.Jaguar` (*channel*)

Bases: `wpiplib.PWMSpeedController`

Texas Instruments / Vex Robotics Jaguar Speed Controller as a PWM device.

Constructor.

Parameters **channel** – The PWM channel that the Jaguar is attached to. 0-9 are on-board, 10-19 are on the MXP port

Joystick

class `wpiplib.Joystick` (*port, numAxisTypes=None, numButtonTypes=None*)

Bases: `wpiplib.interfaces.JoystickBase`

Handle input from standard Joysticks connected to the Driver Station.

This class handles standard input that comes from the Driver Station. Each time a value is requested the most recent value is returned. There is a single class instance for each joystick and the mapping of ports to hardware buttons depends on the code in the Driver Station.

Construct an instance of a joystick.

The joystick index is the USB port on the Driver Station.

This constructor is intended for use by subclasses to configure the number of constants for axes and buttons.

Parameters

- **port** (*int*) – The port on the Driver Station that the joystick is plugged into.
- **numAxisTypes** (*int*) – The number of axis types.
- **numButtonTypes** (*int*) – The number of button types.

class `AxisType`

Bases: `object`

Represents an analog axis on a joystick.

kNumAxis = 5

kThrottle = 4

kTwist = 3

kX = 0

kY = 1

kZ = 2

class `Joystick.ButtonType`

Bases: `object`

Represents a digital button on the Joystick

kNumButton = 2

kTop = 1

kTrigger = 0

`Joystick.flush_outputs()`

Flush all joystick HID & rumble output values to the HAL

`Joystick.GetAxis(axis)`

For the current joystick, return the axis determined by the argument.

This is for cases where the joystick axis is returned programmatically, otherwise one of the previous functions would be preferable (for example `getX()`).

Parameters `axis` (`Joystick.AxisType`) – The axis to read.

Returns The value of the axis.

Return type float

`Joystick.GetAxisChannel(axis)`

Get the channel currently associated with the specified axis.

Parameters `axis` (`int`) – The axis to look up the channel for.

Returns The channel for the axis.

Return type int

`Joystick.GetAxisCount()`

For the current joystick, return the number of axis

`Joystick.GetAxisType(axis)`

Get the axis type of a joystick axis.

Returns the axis type of a joystick axis.

`Joystick.getBumper(hand=None)`

This is not supported for the Joystick.

This method is only here to complete the GenericHID interface.

Parameters `hand` – This parameter is ignored for the Joystick class and is only here to complete the GenericHID interface.

Returns The state of the bumper (always False)

Return type bool

`Joystick.getButton(button)`

Get buttons based on an enumerated type.

The button type will be looked up in the list of buttons and then read.

Parameters `button` (`Joystick.ButtonType`) – The type of button to read.

Returns The state of the button.

Return type bool

`Joystick.getButtonCount()`

For the current joystick, return the number of buttons

:rtype int

`Joystick.getDirectionDegrees()`

Get the direction of the vector formed by the joystick and its origin in degrees.

Returns The direction of the vector in degrees

Return type float

`Joystick.getDirectionRadians()`

Get the direction of the vector formed by the joystick and its origin in radians.

Returns The direction of the vector in radians

Return type float

`Joystick.getIsXbox()`

Get the value of isXbox for the current joystick.

Returns A boolean that is true if the controller is an xbox controller.

`Joystick.getMagnitude()`

Get the magnitude of the direction vector formed by the joystick's current position relative to its origin.

Returns The magnitude of the direction vector

Return type float

`Joystick.getName()`

Get the name of the HID.

Returns The name of the HID.

`Joystick.getPOV(pov=0)`

`Joystick.getPOVCount()`

`Joystick.getRawAxis(axis)`

Get the value of the axis.

Parameters `axis` (*int*) – The axis to read, starting at 0.

Returns The value of the axis.

Return type float

`Joystick.getRawButton(button)`

Get the button value (starting at button 1).

The buttons are returned in a single 16 bit value with one bit representing the state of each button. The appropriate button is returned as a boolean value.

Parameters `button` (*int*) – The button number to be read (starting at 1).

Returns The state of the button.

Return type bool

`Joystick.getThrottle()`

Get the throttle value of the current joystick.

This depends on the mapping of the joystick connected to the current port.

Returns The Throttle value of the joystick.

Return type float

`Joystick.getTop(hand=None)`

Read the state of the top button on the joystick.

Look up which button has been assigned to the top and read its state.

Parameters `hand` – This parameter is ignored for the Joystick class and is only here to complete the GenericHID interface.

Returns The state of the top button.

Return type bool

`Joystick.getTrigger` (*hand=None*)

Read the state of the trigger on the joystick.

Look up which button has been assigned to the trigger and read its state.

Parameters **hand** – This parameter is ignored for the Joystick class and is only here to complete the GenericHID interface.

Returns The state of the trigger.

Return type bool

`Joystick.getTwist` ()

Get the twist value of the current joystick.

This depends on the mapping of the joystick connected to the current port.

Returns The Twist value of the joystick.

Return type float

`Joystick.getType` ()

Get the type of the HID.

Returns the type of the HID.

`Joystick.getX` (*hand=None*)

Get the X value of the joystick.

This depends on the mapping of the joystick connected to the current port.

Parameters **hand** – Unused

Returns The X value of the joystick.

Return type float

`Joystick.getY` (*hand=None*)

Get the Y value of the joystick.

This depends on the mapping of the joystick connected to the current port.

Parameters **hand** – Unused

Returns The Y value of the joystick.

Return type float

`Joystick.getZ` (*hand=None*)

`Joystick.kDefaultThrottleAxis = 3`

`Joystick.kDefaultTopButton = 2`

`Joystick.kDefaultTriggerButton = 1`

`Joystick.kDefaultTwistAxis = 2`

`Joystick.kDefaultXAxis = 0`

`Joystick.kDefaultYAxis = 1`

`Joystick.kDefaultZAxis = 2`

`Joystick.setAxisChannel` (*axis, channel*)

Set the channel associated with a specified axis.

Parameters

- **axis** (*int*) – The axis to set the channel for.
- **channel** (*int*) – The channel to set the axis to.

Joystick.**setOutput** (*outputNumber, value*)

Joystick.**setOutputs** (*value*)

Joystick.**setRumble** (*type, value*)

Set the rumble output for the joystick. The DS currently supports 2 rumble values, left rumble and right rumble

Parameters

- **type** (`Joystick.RumbleType`) – Which rumble value to set
- **value** (*float*) – The normalized value (0 to 1) to set the rumble to

LinearDigitalFilter

class `wpiplib.LinearDigitalFilter` (*source, ffGains, fbGains*)

Bases: `wpiplib.Filter`

This class implements a linear, digital filter. All types of FIR and IIR filters are supported. Static factory methods are provided to create commonly used types of filters.

Filters are of the form:

$$y[n] = (b_0 * x[n] + b_1 * x[n-1] + \dots + b_P * x[n-P]) - (a_0 * y[n-1] + a_1 * y[n-2] + \dots + a_Q * y[n-Q])$$

Where:

- $y[n]$ is the output at time “n”
- $x[n]$ is the input at time “n”
- $y[n-1]$ is the output from the LAST time step (“n-1”)
- $x[n-1]$ is the input from the LAST time step (“n-1”)
- $b_0 \dots b_P$ are the “feedforward” (FIR) gains
- $a_0 \dots a_Q$ are the “feedback” (IIR) gains

Note: IMPORTANT! Note the “-” sign in front of the feedback term! This is a common convention in signal processing.

What can linear filters do? Basically, they can filter, or diminish, the effects of undesirable input frequencies. High frequencies, or rapid changes, can be indicative of sensor noise or be otherwise undesirable. A “low pass” filter smoothes out the signal, reducing the impact of these high frequency components. Likewise, a “high pass” filter gets rid of slow-moving signal components, letting you detect large changes more easily.

Example FRC applications of filters:

- Getting rid of noise from an analog sensor input (note: the roboRIO’s FPGA can do this faster in hardware)
- Smoothing out joystick input to prevent the wheels from slipping or the robot from tipping
- Smoothing motor commands so that unnecessary strain isn’t put on electrical or mechanical components

- If you use clever gains, you can make a PID controller out of this class!

For more on filters, I highly recommend the following articles:

- http://en.wikipedia.org/wiki/Linear_filter
- http://en.wikipedia.org/wiki/Iir_filter
- http://en.wikipedia.org/wiki/Fir_filter

Note: `pidGet()` should be called by the user on a known, regular period. You can set up a Notifier to do this (look at the `PIDController` class), or do it “inline” with code in a periodic function.

Note: For ALL filters, gains are necessarily a function of frequency. If you make a filter that works well for you at, say, 100Hz, you will most definitely need to adjust the gains if you then want to run it at 200Hz! Combining this with Note 1 - the impetus is on YOU as a developer to make sure `pidGet()` gets called at the desired, constant frequency!

There are static methods you can use to build common filters:

- `highPass()`
- `movingAverage()`
- `singlePoleIIR()`

Constructor. Create a linear FIR or IIR filter

Parameters

- **source** (`PIDSource`, callable) – The `PIDSource` object that is used to get values
- **ffGains** (`list`, `tuple`) – The “feed forward” or FIR gains
- **fbGains** (`list`, `tuple`) – The “feed back” or IIR gains

get()

Returns the current filter estimate without also inserting new data as `pidGet()` would do.

Returns The current filter estimate

static highPass (`source`, `timeConstant`, `period`)

Creates a first-order high-pass filter of the form:

$$y[n] = \text{gain} * x[n] + (-\text{gain}) * x[n-1] + \text{gain} * y[n-1]$$

where $\text{gain} = e^{(-dt / T)}$, T is the time constant in seconds

This filter is stable for time constants greater than zero

Parameters

- **source** (`PIDSource`, callable) – The `PIDSource` object that is used to get values
- **timeConstant** (`float`) – The discrete-time time constant in seconds
- **period** (`float`) – The period in seconds between samples taken by the user

Returns `LinearDigitalFilter`

static movingAverage (`source`, `taps`)

Creates a K-tap FIR moving average filter of the form:

$$y[n] = 1/k * (x[k] + x[k-1] + \dots + x[0])$$

This filter is always stable.

Parameters

- **source** (*PIDSource*, callable) – The PIDSource object that is used to get values
- **taps** – The number of samples to average over. Higher = smoother but slower

Raises `ValueError` if number of taps is less than 1

Returns *LinearDigitalFilter*

`pidGet ()`

Calculates the next value of the filter

Returns The filtered value at this step

`reset ()`

Reset the filter state

`static singlePoleIIR (source, timeConstant, period)`

Creates a one-pole IIR low-pass filter of the form:

$$y[n] = (1-gain)*x[n] + gain*y[n-1]$$

Where $gain = e^{(-dt / T)}$, T is the time constant in seconds

This filter is stable for time constants greater than zero

Parameters

- **source** (*PIDSource*, callable) – The PIDSource object that is used to get values
- **timeConstant** (*float*) – The discrete-time time constant in seconds
- **period** (*float*) – The period in seconds between samples taken by the user

Returns *LinearDigitalFilter*

LiveWindow

`class wpilib.LiveWindow`

Bases: `object`

The public interface for putting sensors and actuators on the LiveWindow.

`static addActuator (subsystem, name, component)`

Add an Actuator associated with the subsystem and with call it by the given name.

Parameters

- **subsystem** – The subsystem this component is part of.
- **name** – The name of this component.
- **component** – A `LiveWindowSendable` component that represents a actuator.

`static addActuatorChannel (moduleType, channel, component)`

Add Actuator to LiveWindow. The components are shown with the module type, slot and channel like this: `Servo[0,2]` for a servo object connected to the first digital module and PWM port 2.

Parameters

- **moduleType** – A string that defines the module name in the label for the value
- **channel** – The channel number the device is plugged into (usually PWM)
- **component** – The reference to the object being added

static addActuatorModuleChannel (*moduleType, moduleNumber, channel, component*)

Add Actuator to LiveWindow. The components are shown with the module type, slot and channel like this: Servo[0,2] for a servo object connected to the first digital module and PWM port 2.

Parameters

- **moduleType** – A string that defines the module name in the label for the value
- **moduleNumber** – The number of the particular module type
- **channel** – The channel number the device is plugged into (usually PWM)
- **component** – The reference to the object being added

static addSensor (*subsystem, name, component*)

Add a Sensor associated with the subsystem and with call it by the given name.

Parameters

- **subsystem** – The subsystem this component is part of.
- **name** – The name of this component.
- **component** – A LiveWindowSendable component that represents a sensor.

static addSensorChannel (*moduleType, channel, component*)

Add Sensor to LiveWindow. The components are shown with the type and channel like this: Gyro[0] for a gyro object connected to the first analog channel.

Parameters

- **moduleType** – A string indicating the type of the module used in the naming (above)
- **channel** – The channel number the device is connected to
- **component** – A reference to the object being added

components = {}

firstTime = True

static initializeLiveWindowComponents ()

Initialize all the LiveWindow elements the first time we enter LiveWindow mode. By holding off creating the NetworkTable entries, it allows them to be redefined before the first time in LiveWindow mode. This allows default sensor and actuator values to be created that are replaced with the custom names from users calling addActuator and addSensor.

liveWindowEnabled = False

livewindowTable = None

static removeComponent (*component*)

Removes a component from LiveWindow.

Parameters component – The reference to the object being removed.

static run ()

The run method is called repeatedly to keep the values refreshed on the screen in test mode.

sensors = set()

static setEnabled (*enabled*)

Set the enabled state of LiveWindow. If it's being enabled, turn off the scheduler and remove all the commands from the queue and enable all the components registered for LiveWindow. If it's being disabled, stop all the registered components and reenable the scheduler.

TODO: add code to disable PID loops when enabling LiveWindow. The commands should reenable the PID loops themselves when they get rescheduled. This prevents arms from starting to move around, etc. after a period of adjusting them in LiveWindow mode.

statusTable = None

static updateValues ()

Puts all sensor values on the live window.

LiveWindowSendable

class `wplib.LiveWindowSendable`

Bases: `wplib.Sendable`

A special type of object that can be displayed on the live window.

MotorSafety

class `wplib.MotorSafety`

Bases: `object`

Provides mechanisms to safely shutdown motors if they aren't updated often enough.

The MotorSafety object is constructed for every object that wants to implement the Motor Safety protocol. The helper object has the code to actually do the timing and call the motors `stop()` method when the timeout expires. The motor object is expected to call the `feed()` method whenever the motors value is updated.

The constructor for a MotorSafety object. The helper object is constructed for every object that wants to implement the Motor Safety protocol. The helper object has the code to actually do the timing and call the motors `stop()` method when the timeout expires. The motor object is expected to call the `feed()` method whenever the motors value is updated.

DEFAULT_SAFETY_EXPIRATION = 0.1

check ()

Check if this motor has exceeded its timeout. This method is called periodically to determine if this motor has exceeded its timeout value. If it has, the stop method is called, and the motor is shut down until its value is updated again.

static checkMotors ()

Check the motors to see if any have timed out. This static method is called periodically to poll all the motors and stop any that have timed out.

feed ()

Feed the motor safety object. Resets the timer on this object that is used to do the timeouts.

getExpiration ()

Retrieve the timeout value for the corresponding motor safety object.

Returns the timeout value in seconds.

Return type float

helpers = <_weakrefset.WeakSet object>

`helpers_lock = <unlocked_thread.lock object>`

`isAlive()`

Determine if the motor is still operating or has timed out.

Returns True if the motor is still operating normally and hasn't timed out.

Return type float

`isSafetyEnabled()`

Return the state of the motor safety enabled flag. Return if the motor safety is currently enabled for this device.

Returns True if motor safety is enforced for this device

Return type bool

`setExpiration(expirationTime)`

Set the expiration time for the corresponding motor safety object.

Parameters `expirationTime` (*float*) – The timeout value in seconds.

`setSafetyEnabled(enabled)`

Enable/disable motor safety for this device. Turn on and off the motor safety option for this PWM object.

Parameters `enabled` (*bool*) – True if motor safety is enforced for this object

PIDController

`class wpilib.PIDController(*args, **kwargs)`

Bases: `wpilib.LiveWindowSendable`

Can be used to control devices via a PID Control Loop.

Creates a separate thread which reads the given `PIDSource` and takes care of the integral calculations, as well as writing the given `PIDOutput`.

This feedback controller runs in discrete time, so time deltas are not used in the integral and derivative calculations. Therefore, the sample rate affects the controller's behavior for a given set of PID constants.

Allocate a PID object with the given constants for P, I, D, and F

Arguments can be structured as follows:

- `Kp`, `Ki`, `Kd`, `Kf`, `PIDSource`, `PIDOutput`, `period`
- `Kp`, `Ki`, `Kd`, `PIDSource`, `PIDOutput`, `period`
- `Kp`, `Ki`, `Kd`, `PIDSource`, `PIDOutput`
- `Kp`, `Ki`, `Kd`, `Kf`, `PIDSource`, `PIDOutput`

Parameters

- **Kp** (*float or int*) – the proportional coefficient
- **Ki** (*float or int*) – the integral coefficient
- **Kd** (*float or int*) – the derivative coefficient
- **Kf** (*float or int*) – the feed forward term
- **source** (A function, or an object that implements `PIDSource`) – Called to get values
- **output** (A function, or an object that implements `PIDOutput`) – Receives the output percentage

- **period** (*float or int*) – the loop time for doing calculations. This particularly effects calculations of the integral and differential terms. The default is 50ms.

AbsoluteTolerance_onTarget (*value*)

class PIDSourceType

Bases: object

A description for the type of output value to provide to a *PIDController*

kDisplacement = 0

kRate = 1

PIDController.**PercentageTolerance_onTarget** (*percentage*)

PIDController.**calculateFeedForward** ()

Calculate the feed forward term

Both of the provided feed forward calculations are velocity feed forwards. If a different feed forward calculation is desired, the user can override this function and provide his or her own. This function does no synchronization because the *PIDController* class only calls it in synchronized code, so be careful if calling it oneself.

If a velocity PID controller is being used, the F term should be set to 1 over the maximum setpoint for the output. If a position PID controller is being used, the F term should be set to 1 over the maximum speed for the output measured in setpoint units per this controller's update period (see the default period in this class's constructor).

PIDController.**disable** ()

Stop running the *PIDController*, this sets the output to zero before stopping.

PIDController.**enable** ()

Begin running the *PIDController*.

PIDController.**free** ()

Free the PID object

PIDController.**get** ()

Return the current PID result. This is always centered on zero and constrained the the max and min outs.

Returns the latest calculated output

PIDController.**getAvgError** ()

Returns the current difference of the error over the past few iterations. You can specify the number of iterations to average with *setToleranceBuffer* () (defaults to 1). *getAvgError* () is used for the *onTarget* () function.

Returns the current average of the error

PIDController.**getContinuousError** (*error*)

Wraps error around for continuous inputs. The original error is returned if continuous mode is disabled. This is an unsynchronized function.

Parameters *error* – The current error of the PID controller.

Returns Error for continuous inputs.

PIDController.**getD** ()

Get the Differential coefficient.

Returns differential coefficient

- `PIDController.getDeltaSetpoint()`
Returns the change in setpoint over time of the PIDController
- Returns** the change in setpoint over time
- `PIDController.getError()`
Returns the current difference of the input from the setpoint.
- Returns** the current error
- `PIDController.getF()`
Get the Feed forward coefficient.
- Returns** feed forward coefficient
- `PIDController.getI()`
Get the Integral coefficient
- Returns** integral coefficient
- `PIDController.getP()`
Get the Proportional coefficient.
- Returns** proportional coefficient
- `PIDController.getPIDSourceType(pidSourceType)`
Returns the type of input the PID controller is using
- Returns** the PID controller input type
- `PIDController.getSetpoint()`
Returns the current setpoint of the PIDController.
- Returns** the current setpoint
- `PIDController.instances = 0`
- `PIDController.isAvgErrorValid()`
Returns whether or not any values have been collected. If no values have been collected, `getAvgError` is 0, which is invalid.
- Returns** True if `getAvgError()` is currently valid.
- `PIDController.isEnabled()`
Return True if PIDController is enabled.
- `PIDController.is-enabled()`
Return True if PIDController is enabled.
- `PIDController.kDefaultPeriod = 0.05`
- `PIDController.onTarget()`
Return True if the error is within the percentage of the total input range, determined by `setTolerance`. This assumes that the maximum and minimum input were set using `setInput()`.
- Returns** True if the error is less than the tolerance
- `PIDController.reset()`
Reset the previous error, the integral term, and disable the controller.
- `PIDController.setAbsoluteTolerance(absvalue)`
Set the absolute error which is considered tolerable for use with `onTarget()`.
- Parameters** `absvalue` – absolute error which is tolerable in the units of the input object

`PIDController.setContinuous` (*continuous=True*)

Set the PID controller to consider the input to be continuous. Rather than using the max and min in as constraints, it considers them to be the same point and automatically calculates the shortest route to the setpoint.

Parameters `continuous` – Set to True turns on continuous, False turns off continuous

`PIDController.setInputRange` (*minimumInput, maximumInput*)

Sets the maximum and minimum values expected from the input.

Parameters

- `minimumInput` – the minimum percentage expected from the input
- `maximumInput` – the maximum percentage expected from the output

`PIDController.setOutputRange` (*minimumOutput, maximumOutput*)

Sets the minimum and maximum values to write.

Parameters

- `minimumOutput` – the minimum percentage to write to the output
- `maximumOutput` – the maximum percentage to write to the output

`PIDController.setPID` (*p, i, d, f=0.0*)

Set the PID Controller gain parameters. Set the proportional, integral, and differential coefficients.

Parameters

- `p` – Proportional coefficient
- `i` – Integral coefficient
- `d` – Differential coefficient
- `f` – Feed forward coefficient (optional, default is 0.0)

`PIDController.setPIDSourceType` (*pidSourceType*)

Sets what type of input the PID controller will use

Parameters `pidSourceType` – the type of input

`PIDController.setPercentTolerance` (*percentage*)

Set the percentage error which is considered tolerable for use with `onTarget()`. (Input of 15.0 = 15 percent)

Parameters `percentage` – percent error which is tolerable

`PIDController.setSetpoint` (*setpoint*)

Set the setpoint for the PIDController Clears the queue for `GetAvgError()`.

Parameters `setpoint` – the desired setpoint

`PIDController.setTolerance` (*percent*)

Set the percentage error which is considered tolerable for use with `onTarget()`. (Input of 15.0 = 15 percent)

Parameters `percent` – error which is tolerable

Deprecated since version 2015.1: Use `setPercentTolerance()` or `setAbsoluteTolerance()` instead.

`PIDController.setToleranceBuffer` (*bufLength*)

Set the number of previous error samples to average for tolerancing. When determining whether a mechanism is on target, the user may want to use a rolling average of previous measurements instead of a precise

position or velocity. This is useful for noisy sensors which return a few erroneous measurements when the mechanism is on target. However, the mechanism will not register as on target for at least the specified `bufLength` cycles.

Parameters `bufLength` (*int*) – Number of previous cycles to average.

PowerDistributionPanel

class `wpiplib.PowerDistributionPanel` (*module=0*)

Bases: `wpiplib.SensorBase`

Use to obtain voltage, current, temperature, power, and energy from the Power Distribution Panel over CAN

Parameters `module` (*int*) – CAN ID of the PDP

clearStickyFaults ()

Clear all pdp sticky faults

getCurrent (*channel*)

Query the current of a single channel of the PDP

Returns The current of one of the PDP channels (channels 0-15) in Amperes

Return type float

getTemperature ()

Query the temperature of the PDP

Returns The temperature of the PDP in degrees Celsius

Return type float

getTotalCurrent ()

Query the current of all monitored PDP channels (0-15)

Returns The total current drawn from the PDP channels in Amperes

Return type float

getTotalEnergy ()

Query the total energy drawn from the monitored PDP channels

Returns The total energy drawn from the PDP channels in Joules

Return type float

getTotalPower ()

Query the total power drawn from the monitored PDP channels

Returns The total power drawn from the PDP channels in Watts

Return type float

getVoltage ()

Query the input voltage of the PDP

Returns The voltage of the PDP in volts

Return type float

resetTotalEnergy ()

Reset the total energy to 0

Preferences

class `wpilib.Preferences`

Bases: `object`

Provides a relatively simple way to save important values to the roboRIO to access the next time the roboRIO is booted.

This class loads and saves from a file inside the roboRIO. The user can not access the file directly, but may modify values at specific fields which will then be saved to the file when `save()` is called.

This class is thread safe.

This will also interact with `networktables.NetworkTable` by creating a table called “Preferences” with all the key-value pairs. To save using `NetworkTable`, simply set the boolean at position `~S A V E~` to true. Also, if the value of any variable is `”` in the `NetworkTable`, then that represents non-existence in the `Preferences` table.

Creates a preference class that will automatically read the file in a different thread. Any call to its methods will be blocked until the thread is finished reading.

TABLE_NAME = ‘Preferences’

containsKey (*key*)

Returns whether or not there is a key with the given name.

Parameters **key** – the key

Returns True if there is a value at the given key

getBoolean (*key, backup=None*)

Returns the boolean at the given key. If this table does not have a value for that position, then the given backup value will be returned.

Parameters

- **key** – the key
- **backup** – the value to return if none exists in the table

Returns either the value in the table, or the backup

getFloat (*key, backup=None*)

Returns the float at the given key. If this table does not have a value for that position, then the given backup value will be returned.

Parameters

- **key** – the key
- **backup** – the value to return if none exists in the table

Returns either the value in the table, or the backup

Raises `TableKeyNotFoundException` if key cannot be found

static getInstance ()

Returns the preferences instance.

Returns the preferences instance

getInt (*key, backup=None*)

Returns the int at the given key. If this table does not have a value for that position, then the given backup value will be returned.

Parameters

- **key** – the key
- **backup** – the value to return if none exists in the table

Returns either the value in the table, or the backup

Raises `TableKeyNotDefinedException` if key cannot be found

getKeys ()

Returns a list of the keys

getString (*key*, *backup=None*)

Returns the string at the given key. If this table does not have a value for that position, then the given backup value will be returned.

Parameters

- **key** – the key
- **backup** – the value to return if none exists in the table

Returns either the value in the table, or the backup

keys ()

Python style get list of keys.

putBoolean (*key*, *value*)

Puts the given float into the preferences table.

The key may not have any whitespace nor an equals sign.

This will NOT save the value to memory between power cycles, to do that you must call `save ()` (which must be used with care) at some point after calling this.

Parameters

- **key** – the key
- **value** – the value

putFloat (*key*, *value*)

Puts the given float into the preferences table.

The key may not have any whitespace nor an equals sign.

This will NOT save the value to memory between power cycles, to do that you must call `save ()` (which must be used with care) at some point after calling this.

Parameters

- **key** – the key
- **value** – the value

putInt (*key*, *value*)

Puts the given int into the preferences table.

The key may not have any whitespace nor an equals sign.

This will NOT save the value to memory between power cycles, to do that you must call `save ()` (which must be used with care) at some point after calling this.

Parameters

- **key** – the key
- **value** – the value

putString (*key*, *value*)

Puts the given string into the preferences table.

The value may not have quotation marks, nor may the key have any whitespace nor an equals sign.

This will NOT save the value to memory between power cycles, to do that you must call `save()` (which must be used with care) at some point after calling this.

Parameters

- **key** – the key
- **value** – the value

remove (*key*)

Remove a preference

Parameters **key** – the key

valueChangedEx (*source*, *key*, *value*, *isNew*)

PWM

class `wpiplib.PWM` (*channel*)

Bases: `wpiplib.LiveWindowSendable`

Raw interface to PWM generation in the FPGA.

The values supplied as arguments for PWM outputs range from -1.0 to 1.0. They are mapped to the hardware dependent values, in this case 0-2000 for the FPGA. Changes are immediately sent to the FPGA, and the update occurs at the next FPGA cycle. There is no delay.

As of revision 0.1.10 of the FPGA, the FPGA interprets the 0-2000 values as follows:

- 2000 = full “forward”
- 1999 to 1001 = linear scaling from “full forward” to “center”
- 1000 = center value
- 999 to 2 = linear scaling from “center” to “full reverse”
- 1 = minimum pulse width (currently .5ms)
- 0 = disabled (i.e. PWM output is held low)

`kDefaultPwmPeriod` is the 1x period (5.05 ms). In hardware, the period scaling is implemented as an output squelch to get longer periods for old devices.

- 20ms periods (50 Hz) are the “safest” setting in that this works for all devices
- 20ms periods seem to be desirable for Vex Motors
- 20ms periods are the specified period for HS-322HD servos, but work reliably down to 10.0 ms; starting at about 8.5ms, the servo sometimes hums and get hot; by 5.0ms the hum is nearly continuous
- 10ms periods work well for Victor 884
- 5ms periods allows higher update rates for Luminary Micro Jaguar speed controllers. Due to the shipping firmware on the Jaguar, we can’t run the update period less than 5.05 ms.

Allocate a PWM given a channel.

Parameters **channel** (*int*) – The PWM channel number. 0-9 are on-board, 10-19 are on the MXP port

class PeriodMultiplierBases: `object`

Represents the amount to multiply the minimum servo-pulse pwm period by.

k1X = 1

Period Multiplier: don't skip pulses.

k2X = 2

Period Multiplier: skip every other pulse.

k4X = 4

Period Multiplier: skip three out of four pulses.

PWM.**enableDeadbandElimination** (*eliminateDeadband*)

Optionally eliminate the deadband from a speed controller.

Parameters **eliminateDeadband** (*bool*) – If True, set the motor curve on the Jaguar to eliminate the deadband in the middle of the range. Otherwise, keep the full range without modifying any values.

PWM.**free** ()

Free the PWM channel.

Free the resource associated with the PWM channel and set the value to 0.

PWM.**getChannel** ()

Gets the channel number associated with the PWM Object.

Returns The channel number.**Return type** `int`PWM.**getPosition** ()

Get the PWM value in terms of a position.

This is intended to be used by servos.

Note: `setBounds()` must be called first.

Returns The position the servo is set to between 0.0 and 1.0.**Return type** `float`PWM.**getRaw** ()

Get the PWM value directly from the hardware.

Read a raw value from a PWM channel.

Returns Raw PWM control value. Range: 0 - 255.**Return type** `int`PWM.**getRawBounds** ()

Gets the bounds on the PWM pulse widths. This Gets the bounds on the PWM values for a particular type of controller. The values determine the upper and lower speeds as well as the deadband bracket.

Returns tuple of (max, deadbandMax, center, deadbandMin, min)PWM.**getSpeed** ()

Get the PWM value in terms of speed.

This is intended to be used by speed controllers.

Note: `setBounds()` must be called first.

Returns The most recently set speed between -1.0 and 1.0.

Return type float

PWM.**handle**

PWM.**setBounds** (*max*, *deadbandMax*, *center*, *deadbandMin*, *min*)

Set the bounds on the PWM pulse widths.

This sets the bounds on the PWM values for a particular type of controller. The values determine the upper and lower speeds as well as the deadband bracket.

Parameters

- **max** (*float*) – The max PWM pulse width in ms
- **deadbandMax** (*float*) – The high end of the deadband range pulse width in ms
- **center** (*float*) – The center (off) pulse width in ms
- **deadbandMin** (*float*) – The low end of the deadband pulse width in ms
- **min** (*float*) – The minimum pulse width in ms

PWM.**setDisabled** ()

Temporarily disables the PWM output. The next set call will reenable the output.

PWM.**setPeriodMultiplier** (*mult*)

Slow down the PWM signal for old devices.

Parameters **mult** (PWM.*PeriodMultiplier*) – The period multiplier to apply to this channel

PWM.**setPosition** (*pos*)

Set the PWM value based on a position.

This is intended to be used by servos.

Note: `setBounds()` must be called first.

Parameters **pos** (*float*) – The position to set the servo between 0.0 and 1.0.

PWM.**setRaw** (*value*)

Set the PWM value directly to the hardware.

Write a raw value to a PWM channel.

Parameters **value** (*int*) – Raw PWM value. Range 0 - 255.

PWM.**setRawBounds** (*max*, *deadbandMax*, *center*, *deadbandMin*, *min*)

Set the bounds on the PWM values. This sets the bounds on the PWM values for a particular each type of controller. The values determine the upper and lower speeds as well as the deadband bracket.

Parameters

- **max** (*int*) – The Minimum pwm value
- **deadbandMax** (*int*) – The high end of the deadband range

- **center** (*int*) – The center speed (off)
- **deadbandMin** (*int*) – The low end of the deadband range
- **min** (*int*) – The minimum pwm value

Deprecated since version 2017.0.0: Recommended to set bounds in ms using `setBounds()` instead

PWM.**setSpeed** (*speed*)

Set the PWM value based on a speed.

This is intended to be used by speed controllers.

Note: `setBounds()` must be called first.

Parameters **speed** (*float*) – The speed to set the speed controller between -1.0 and 1.0.

PWM.**setZeroLatch** ()

PWMSpeedController

class `wpiplib.PWMSpeedController` (*channel*)

Bases: `wpiplib.SafePWM`

Common base class for all PWM Speed Controllers.

free ()

get ()

Get the recently set value of the PWM.

Returns The most recently set value for the PWM between -1.0 and 1.0.

Return type float

getInverted ()

Common interface for inverting the direction of a speed controller.

Returns The state of inversion (True is inverted)

pidWrite (*output*)

Write out the PID value as seen in the PIDOutput base object.

Parameters **output** (*float*) – Write out the PWM value as was found in the PIDController.

set (*speed*)

Set the PWM value.

The PWM value is set using a range of -1.0 to 1.0, appropriately scaling the value for the FPGA.

Parameters **speed** (*float*) – The speed to set. Value should be between -1.0 and 1.0.

setInverted (*isInverted*)

Common interface for inverting the direction of a speed controller.

Parameters **isInverted** – The state of inversion (True is inverted).

Relay

class `wpiplib.Relay` (*channel*, *direction=None*)

Bases: `wpiplib.SensorBase`, `wpiplib.LiveWindowSendable`, `wpiplib.MotorSafety`

Controls VEX Robotics Spike style relay outputs.

Relays are intended to be connected to Spikes or similar relays. The relay channels controls a pair of channels that are either both off, one on, the other on, or both on. This translates into two Spike outputs at 0v, one at 12v and one at 0v, one at 0v and the other at 12v, or two Spike outputs at 12V. This allows off, full forward, or full reverse control of motors without variable speed. It also allows the two channels (forward and reverse) to be used independently for something that does not care about voltage polarity (like a solenoid).

Relay constructor given a channel.

Initially the relay is set to both lines at 0v.

Parameters

- **channel** (*int*) – The channel number for this relay (0-3)
- **direction** (*Relay.Direction*) – The direction that the Relay object will control. If not specified, defaults to allowing both directions.

class `Direction`

Bases: `object`

The Direction(s) that a relay is configured to operate in.

kBoth = 0

Both directions are valid

kForward = 1

Only forward is valid

kReverse = 2

Only reverse is valid

class `Relay.Value`

Bases: `object`

The state to drive a Relay to.

kForward = 2

Forward

kOff = 0

Off

kOn = 1

On for relays with defined direction

kReverse = 3

Reverse

`Relay.forwardHandle`

`Relay.free()`

`Relay.get()`

Get the Relay State

Gets the current state of the relay.

When set to `kForwardOnly` or `kReverseOnly`, value is returned as `kOn/kOff` not `kForward/kReverse` (per the recommendation in `Set`)

Returns The current state of the relay

Return type `Relay.Value`

`Relay.getChannel()`

Get the channel number.

Returns The channel number.

`Relay.getDescription()`

`Relay.relayChannels = <wpilib.resource.Resource object>`

`Relay.reverseHandle`

`Relay.set(value)`

Set the relay state.

Valid values depend on which directions of the relay are controlled by the object.

When set to `kBothDirections`, the relay can be set to any of the four states: `0v-0v`, `12v-0v`, `0v-12v`, `12v-12v`

When set to `kForwardOnly` or `kReverseOnly`, you can specify the constant for the direction or you can simply specify `kOff` and `kOn`. Using only `kOff` and `kOn` is recommended.

Parameters `value` (`Relay.Value`) – The state to set the relay.

`Relay.setDirection(direction)`

Set the Relay Direction.

Changes which values the relay can be set to depending on which direction is used.

Valid inputs are `kBothDirections`, `kForwardOnly`, and `kReverseOnly`.

Parameters `direction` (`Relay.Direction`) – The direction for the relay to operate in

`Relay.stopMotor()`

Resource

`class wpilib.Resource(size)`

Bases: `object`

Tracks resources in the program.

The `Resource` class is a convenient way of keeping track of allocated arbitrary resources in the program. Resources are just indices that have an lower and upper bound that are tracked by this class. In the library they are used for tracking allocation of hardware channels but this is purely arbitrary. The resource class does not do any actual allocation, but simply tracks if a given index is currently in use.

Allocate storage for a new instance of `Resource`. Allocate a `bool` array of values that will get initialized to indicate that no resources have been allocated yet. The indices of the resources are `0..size-1`.

Parameters `size` – The number of blocks to allocate

`allocate(obj, index=None)`

Allocate a resource.

When `index` is `None` or unspecified, a free resource value within the range is located and returned after it is marked allocated. Otherwise, it is verified unallocated, then returned.

Parameters

- **obj** – The object requesting the resource.
- **index** – The resource to allocate

Returns The index of the allocated block.

Raises `IndexError` – If there are no resources available to be allocated or the specified index is already used.

free (*index*)

Force-free an allocated resource. After a resource is no longer needed, for example a destructor is called for a channel assignment class, free will release the resource value so it can be reused somewhere else in the program.

Parameters `index` – The index of the resource to free.

RobotBase

class `wplib.RobotBase`

Bases: `object`

Implement a Robot Program framework.

The `RobotBase` class is intended to be subclassed by a user creating a robot program. Overridden `autonomous()` and `operatorControl()` methods are called at the appropriate time as the match proceeds. In the current implementation, the Autonomous code will run to completion before the OperatorControl code could start. In the future the Autonomous code might be spawned as a task, then killed at the end of the Autonomous period.

User code should be placed in the constructor that runs before the Autonomous or Operator Control period starts. The constructor will run to completion before Autonomous is entered.

Warning: If you override `__init__` in your robot class, you must call the base class constructor. This must be used to ensure that the communications code starts.

free ()

Free the resources for a `RobotBase` class.

static initializeHardwareConfiguration ()

Common initialization for all robot programs.

isAutonomous ()

Determine if the robot is currently in Autonomous mode as determined by the field controls.

Returns True if the robot is currently operating Autonomously

Return type `bool`

isDisabled ()

Determine if the Robot is currently disabled.

Returns True if the Robot is currently disabled by the field controls.

Return type `bool`

isEnabled ()

Determine if the Robot is currently enabled.

Returns True if the Robot is currently enabled by the field controls.

Return type `bool`

isNewDataAvailable ()

Indicates if new data is available from the driver station.

Returns Has new data arrived over the network since the last time this function was called?

Return type bool

isOperatorControl ()

Determine if the robot is currently in Operator Control mode as determined by the field controls.

Returns True if the robot is currently operating in Tele-Op mode

Return type bool

static isReal ()

Returns If the robot is running in the real world.

Return type bool

static isSimulation ()

Returns If the robot is running in simulation.

Return type bool

isTest ()

Determine if the robot is currently in Test mode as determined by the driver station.

Returns True if the robot is currently operating in Test mode.

Return type bool

static main (robot_cls)

Starting point for the applications.

startCompetition ()

Provide an alternate “main loop” via startCompetition().

RobotDrive

class `wpiplib.RobotDrive (*args, **kwargs)`

Bases: `wpiplib.MotorSafety`

Operations on a robot drivetrain based on a definition of the motor configuration.

The robot drive class handles basic driving for a robot. Currently, 2 and 4 motor tank and mecanum drive trains are supported. In the future other drive types like swerve might be implemented. Motor channel numbers are passed supplied on creation of the class. Those are used for either the drive function (intended for hand created drive code, such as autonomous) or with the Tank/Arcade functions intended to be used for Operator Control driving.

Constructor for RobotDrive.

Either 2 or 4 motors can be passed to the constructor to implement a two or four wheel drive system, respectively.

When positional arguments are used, these are the two accepted orders:

- leftMotor, rightMotor
- frontLeftMotor, rearLeftMotor, frontRightMotor, rearRightMotor

Alternatively, the above names can be used as keyword arguments.

Either channel numbers or motor controllers can be passed (determined by whether the passed object has a *set* function). If channel numbers are passed, the `motorController` keyword argument, if present, is the motor controller class to use; if unspecified, *Talon* is used.

class `MotorType`

Bases: `object`

The location of a motor on the robot for the purpose of driving.

`kFrontLeft = 0`

Front left

`kFrontRight = 1`

Front right

`kRearLeft = 2`

Rear left

`kRearRight = 3`

Rear right

`RobotDrive.arcadeDrive(*args, **kwargs)`

Provide tank steering using the stored robot configuration.

Either one or two joysticks (with optional specified axis) or two raw values may be passed positionally, along with an optional `squaredInputs` boolean. The valid positional combinations are:

- `stick`
- `stick, squaredInputs`
- `moveStick, moveAxis, rotateStick, rotateAxis`
- `moveStick, moveAxis, rotateStick, rotateAxis, squaredInputs`
- `moveValue, rotateValue`
- `moveValue, rotateValue, squaredInputs`

Alternatively, the above names can be used as keyword arguments. The behavior of mixes of keyword arguments in other than the combinations above is undefined.

If specified positionally, the value and joystick versions are disambiguated by looking for a *getY* function on the stick.

Parameters

- **`stick`** – The joystick to use for Arcade single-stick driving. The Y-axis will be selected for forwards/backwards and the X-axis will be selected for rotation rate.
- **`moveStick`** – The Joystick object that represents the forward/backward direction.
- **`moveAxis`** – The axis on the `moveStick` object to use for forwards/backwards (typically `Y_AXIS`).
- **`rotateStick`** – The Joystick object that represents the rotation value.
- **`rotateAxis`** – The axis on the rotation object to use for the rotate right/left (typically `X_AXIS`).
- **`moveValue`** – The value to use for forwards/backwards.
- **`rotateValue`** – The value to use for the rotate right/left.
- **`squaredInputs`** – Setting this parameter to `True` decreases the sensitivity at lower speeds. Defaults to `True` if unspecified.

`RobotDrive.drive` (*outputMagnitude*, *curve*)

Drive the motors at “outputMagnitude” and “curve”.

Both `outputMagnitude` and `curve` are -1.0 to +1.0 values, where 0.0 represents stopped and not turning. `curve < 0` will turn left and `curve > 0` will turn right.

The algorithm for steering provides a constant turn radius for any normal speed range, both forward and backward. Increasing `m_sensitivity` causes sharper turns for fixed values of `curve`.

This function will most likely be used in an autonomous routine.

Parameters

- **outputMagnitude** – The speed setting for the outside wheel in a turn, forward or backwards, +1 to -1.
- **curve** – The rate of turn, constant for different forward speeds. Set `curve < 0` for left turn or `curve > 0` for right turn.

Set `curve = e-r/w` to get a turn radius `r` for wheelbase `w` of your robot. Conversely, turn radius `r = -ln(curve)*w` for a given value of `curve` and wheelbase `w`.

`RobotDrive.free` ()

`RobotDrive.getDescription` ()

`RobotDrive.getNumMotors` ()

`RobotDrive.holonomicDrive` (*magnitude*, *direction*, *rotation*)

Holonomic Drive method for Mecanum wheeled robots.

This is an alias to `mecanumDrive_Polar` () for backward compatibility.

Parameters

- **magnitude** – The speed that the robot should drive in a given direction. [-1.0..1.0]
- **direction** – The direction the robot should drive. The direction and magnitude are independent of the rotation rate.
- **rotation** – The rate of rotation for the robot that is completely independent of the magnitude or direction. [-1.0..1.0]

`RobotDrive.kArcadeRatioCurve_Reported = False`

`RobotDrive.kArcadeStandard_Reported = False`

`RobotDrive.kDefaultExpirationTime = 0.1`

`RobotDrive.kDefaultMaxOutput = 1.0`

`RobotDrive.kDefaultSensitivity = 0.5`

`RobotDrive.kMaxNumberOfMotors = 4`

`RobotDrive.kMecanumCartesian_Reported = False`

`RobotDrive.kMecanumPolar_Reported = False`

`RobotDrive.kTank_Reported = False`

static `RobotDrive.limit` (*num*)

Limit motor values to the -1.0 to +1.0 range.

`RobotDrive.mecanumDrive_Cartesian` (*x*, *y*, *rotation*, *gyroAngle*)

Drive method for Mecanum wheeled robots.

A method for driving with Mecanum wheeled robots. There are 4 wheels on the robot, arranged so that the front and back wheels are toed in 45 degrees. When looking at the wheels from the top, the roller axles should form an X across the robot.

This is designed to be directly driven by joystick axes.

Parameters

- **x** – The speed that the robot should drive in the X direction. [-1.0..1.0]
- **y** – The speed that the robot should drive in the Y direction. This input is inverted to match the forward == -1.0 that joysticks produce. [-1.0..1.0]
- **rotation** – The rate of rotation for the robot that is completely independent of the translation. [-1.0..1.0]
- **gyroAngle** – The current angle reading from the gyro. Use this to implement field-oriented controls.

`RobotDrive.mecanumDrive_Polar` (*magnitude, direction, rotation*)

Drive method for Mecanum wheeled robots.

A method for driving with Mecanum wheeled robots. There are 4 wheels on the robot, arranged so that the front and back wheels are toed in 45 degrees. When looking at the wheels from the top, the roller axles should form an X across the robot.

Parameters

- **magnitude** – The speed that the robot should drive in a given direction.
- **direction** – The direction the robot should drive in degrees. The direction and magnitude are independent of the rotation rate.
- **rotation** – The rate of rotation for the robot that is completely independent of the magnitude or direction. [-1.0..1.0]

`static RobotDrive.normalize` (*wheelSpeeds*)

Normalize all wheel speeds if the magnitude of any wheel is greater than 1.0.

`static RobotDrive.rotateVector` (*x, y, angle*)

Rotate a vector in Cartesian space.

`RobotDrive.setInvertedMotor` (*motor, isInverted*)

Invert a motor direction.

This is used when a motor should run in the opposite direction as the drive code would normally run it. Motors that are direct drive would be inverted, the drive code assumes that the motors are geared with one reversal.

Parameters

- **motor** – The motor index to invert.
- **isInverted** – True if the motor should be inverted when operated.

`RobotDrive.setLeftRightMotorOutputs` (*leftOutput, rightOutput*)

Set the speed of the right and left motors.

This is used once an appropriate drive setup function is called such as `twoWheelDrive()`. The motors are set to “leftSpeed” and “rightSpeed” and includes flipping the direction of one side for opposing motors.

Parameters

- **leftOutput** – The speed to send to the left side of the robot.
- **rightOutput** – The speed to send to the right side of the robot.

`RobotDrive.setMaxOutput` (*maxOutput*)

Configure the scaling factor for using RobotDrive with motor controllers in a mode other than PercentVbus.

Parameters `maxOutput` – Multiplied with the output percentage computed by the drive functions.

`RobotDrive.setSensitivity` (*sensitivity*)

Set the turning sensitivity.

This only impacts the drive() entry-point.

Parameters `sensitivity` – Effectively sets the turning sensitivity (or turn radius for a given value)

`RobotDrive.stopMotor` ()

`RobotDrive.tankDrive` (**args, **kwargs*)

Provide tank steering using the stored robot configuration.

Either two joysticks (with optional specified axis) or two raw values may be passed positionally, along with an optional squaredInputs boolean. The valid positional combinations are:

- `leftStick, rightStick`
- `leftStick, rightStick, squaredInputs`
- `leftStick, leftAxis, rightStick, rightAxis`
- `leftStick, leftAxis, rightStick, rightAxis, squaredInputs`
- `leftValue, rightValue`
- `leftValue, rightValue, squaredInputs`

Alternatively, the above names can be used as keyword arguments. The behavior of mixes of keyword arguments in other than the combinations above is undefined.

If specified positionally, the value and joystick versions are disambiguated by looking for a *getY* function.

Parameters

- **leftStick** – The joystick to control the left side of the robot.
- **leftAxis** – The axis to select on the left side Joystick object (defaults to the Y axis if unspecified).
- **rightStick** – The joystick to control the right side of the robot.
- **rightAxis** – The axis to select on the right side Joystick object (defaults to the Y axis if unspecified).
- **leftValue** – The value to control the left side of the robot.
- **rightValue** – The value to control the right side of the robot.
- **squaredInputs** – Setting this parameter to True decreases the sensitivity at lower speeds. Defaults to True if unspecified.

RobotState

`class wpilib.RobotState`

Bases: `object`

Provides an interface to determine the current operating state of the robot code.

`impl = None`

```
static isAutonomous ()
static isDisabled ()
static isEnabled ()
static isOperatorControl ()
static isTest ()
```

SafePWM

```
class wpilib.SafePWM(channel)
```

Bases: *wpilib.PWM*, *wpilib.MotorSafety*

A raw PWM interface that implements the *MotorSafety* interface

Constructor for a SafePWM object taking a channel number.

Parameters **channel** (*int*) – The channel number to be used for the underlying PWM object. 0-9 are on-board, 10-19 are on the MXP port.

```
disable ()
```

```
getDescription ()
```

```
stopMotor ()
```

Stop the motor associated with this PWM object. This is called by the MotorSafety object when it has a timeout for this PWM and needs to stop it from running.

SampleRobot

```
class wpilib.SampleRobot
```

Bases: *wpilib.RobotBase*

A simple robot base class that knows the standard FRC competition states (disabled, autonomous, or operator controlled).

You can build a simple robot program off of this by overriding the *robotinit()*, *disabled()*, *autonomous()* and *operatorControl()* methods. The *startCompetition()* method will call these methods (sometimes repeatedly) depending on the state of the competition.

Alternatively you can override the *robotMain()* method and manage all aspects of the robot yourself (not recommended).

Warning: While it may look like a good choice to use for your code if you're inexperienced, don't. Unless you know what you are doing, complex code will be much more difficult under this system. Use *IterativeRobot* or command based instead if you're new.

```
autonomous ()
```

Autonomous should go here. Users should add autonomous code to this method that should run while the field is in the autonomous period.

Called once each time the robot enters the autonomous state.

```
disabled ()
```

Disabled should go here. Users should overload this method to run code that should run while the field is disabled.

Called once each time the robot enters the disabled state.

logger = <logging.Logger object>

A python logging object that you can use to send messages to the log. It is recommended to use this instead of print statements.

operatorControl ()

Operator control (tele-operated) code should go here. Users should add Operator Control code to this method that should run while the field is in the Operator Control (tele-operated) period.

Called once each time the robot enters the operator-controlled state.

robotInit ()

Robot-wide initialization code should go here.

Users should override this method for default Robot-wide initialization which will be called when the robot is first powered on. It will be called exactly 1 time.

Note: It is simpler to override this function instead of defining a constructor for your robot class

Warning: the Driver Station “Robot Code” light and FMS “Robot Ready” indicators will be off until RobotInit() exits. Code in robotInit() that waits for enable will cause the robot to never indicate that the code is ready, causing the robot to be bypassed in a match.

robotMain ()

Robot main program for free-form programs.

This should be overridden by user subclasses if the intent is to not use the autonomous() and operatorControl() methods. In that case, the program is responsible for sensing when to run the autonomous and operator control functions in their program.

This method will be called immediately after the constructor is called. If it has not been overridden by a user subclass (i.e. the default version runs), then the robotInit(), disabled(), autonomous() and operatorControl() methods will be called.

If you override this function, you must call `hal.HALNetworkCommunicationObserveUserProgramStarting()` to indicate that your robot is ready to be enabled, as it will not be called for you.

Warning: Nobody actually wants to override this function. Neither do you.

startCompetition ()

Start a competition. This code tracks the order of the field starting to ensure that everything happens in the right order. Repeatedly run the correct method, either Autonomous or OperatorControl when the robot is enabled. After running the correct method, wait for some state to change, either the other mode starts or the robot is disabled. Then go back and wait for the robot to be enabled again.

test ()

Test code should go here. Users should add test code to this method that should run while the robot is in test mode.

SD540

class `wplib.SD540` (*channel*)
Bases: `wplib.PWMSpeedController`

Mindsensors SD540 Speed Controller

Constructor.

Parameters `channel` – The PWM channel that the SD540 is attached to. 0-9 are on-board, 10-19 are on the MXP port

Note: Note that the SD540 uses the following bounds for PWM values. These values should work reasonably well for most controllers, but if users experience issues such as asymmetric behavior around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the SD540 User Manual available from Mindsensors.

- 2.05ms = full “forward”
 - 1.55ms = the “high end” of the deadband range
 - 1.50ms = center of the deadband range (off)
 - 1.44ms = the “low end” of the deadband range
 - .94ms = full “reverse”
-

Sendable

class `wplib.Sendable`
Bases: `object`

The base interface for objects that can be sent over the network through network tables

SendableChooser

class `wplib.SendableChooser`
Bases: `wplib.Sendable`

A useful tool for presenting a selection of options to be displayed on the SmartDashboard

For instance, you may wish to be able to select between multiple autonomous modes. You can do this by putting every possible Command you want to run as an autonomous into a SendableChooser and then put it into the SmartDashboard to have a list of options appear on the laptop. Once autonomous starts, simply ask the SendableChooser what the selected value is.

Example:

```
# This shows the user two options on the SmartDashboard
chooser = wplib.SendableChooser()
chooser.addObject('option1', '1')
chooser.addObject('option2', '2')

wplib.SmartDashboard.putData('Choice', chooser)

# .. later, ask to see what the user selected?
value = chooser.getSelected()
```

Instantiates a `SendableChooser`.

DEFAULT = 'default'

OPTIONS = 'options'

SELECTED = 'selected'

addDefault (*name, object*)

Add the given object to the list of options and marks it as the default. Functionally, this is very close to `addObject(...)` except that it will use this as the default option if none other is explicitly selected.

Parameters

- **name** – the name of the option
- **object** – the option

addObject (*name, object*)

Adds the given object to the list of options. On the SmartDashboard on the desktop, the object will appear as the given name.

Parameters

- **name** – the name of the option
- **object** – the option

getSelected ()

Returns the object associated with the selected option. If there is none selected, it will return the default. If there is none selected and no default, then it will return `None`.

Returns the object associated with the selected option

SensorBase

class `wpiplib.SensorBase`

Bases: `wpiplib.LiveWindowSendable`

Base class for all sensors

Stores most recent status information as well as containing utility functions for checking channels and error processing.

static checkAnalogInputChannel (*channel*)

Check that the analog input number is value. Verify that the analog input number is one of the legal channel numbers. Channel numbers are 0-based.

Parameters **channel** – The channel number to check.

static checkAnalogOutputChannel (*channel*)

Check that the analog input number is value. Verify that the analog input number is one of the legal channel numbers. Channel numbers are 0-based.

Parameters **channel** – The channel number to check.

static checkDigitalChannel (*channel*)

Check that the digital channel number is valid. Verify that the channel number is one of the legal channel numbers. Channel numbers are 0-based.

Parameters **channel** – The channel number to check.

static checkPDPChannel (*channel*)

Verify that the power distribution channel number is within limits. Channel numbers are 0-based.

Parameters `channel` – The channel number to check.

static `checkPDPModule` (*module*)

Verify that the power distribution module number is within limits. Module numbers are 0-based.

Parameters `module` – The module number to check.

static `checkPWMChannel` (*channel*)

Check that the digital channel number is valid. Verify that the channel number is one of the legal channel numbers. Channel numbers are 0-based.

Parameters `channel` – The channel number to check.

static `checkRelayChannel` (*channel*)

Check that the digital channel number is valid. Verify that the channel number is one of the legal channel numbers. Channel numbers are 0-based.

Parameters `channel` – The channel number to check.

static `checkSolenoidChannel` (*channel*)

Verify that the solenoid channel number is within limits. Channel numbers are 0-based.

Parameters `channel` – The channel number to check.

static `checkSolenoidModule` (*moduleNumber*)

Verify that the solenoid module is correct.

Parameters `moduleNumber` – The solenoid module module number to check.

defaultSolenoidModule = 0

Default solenoid module

free ()

Free the resources used by this object

static `getDefaultSolenoidModule` ()

Get the number of the default solenoid module.

Returns The number of the default solenoid module.

kAnalogInputChannels = 8

Number of analog input channels per roboRIO

kAnalogOutputChannels = 2

Number of analog output channels per roboRIO

kDigitalChannels = 31

Number of digital channels per roboRIO

kPCModules = 63

Number of PCM modules

kPDPChannels = 16

Number of power distribution channels per PDP

kPDPModules = 63

Number of power distribution channels per PDP

kPwmChannels = 20

Number of PWM channels per roboRIO

kRelayChannels = 4

Number of relay channels per roboRIO

kSolenoidChannels = 8

Number of solenoid channels per module

kSystemClockTicksPerMicrosecond = 40

Ticks per microsecond

static setDefaultSolenoidModule (*moduleNumber*)

Set the default location for the Solenoid module.

Parameters **moduleNumber** – The number of the solenoid module to use.

Servo

class `wpiplib.Servo` (*channel*)

Bases: `wpiplib.PWM`

Standard hobby style servo

The range parameters default to the appropriate values for the Hitec HS-322HD servo provided in the FIRST Kit of Parts in 2008.

Constructor.

- By default `kDefaultMaxServoPWM` ms is used as the maxPWM value

- By default `kDefaultMinServoPWM` ms is used as the minPWM value

Parameters **channel** (*int*) – The PWM channel to which the servo is attached. 0-9 are on-board, 10-19 are on the MXP port.

free ()

get ()

Get the servo position.

Servo values range from 0.0 to 1.0 corresponding to the range of full left to full right.

Returns Position from 0.0 to 1.0.

Return type float

getAngle ()

Get the servo angle.

Assume that the servo angle is linear with respect to the PWM value (big assumption, need to test).

Returns The angle in degrees to which the servo is set.

Return type float

getServoAngleRange ()

kDefaultMaxServoPWM = 2.4

kDefaultMinServoPWM = 0.6

kMaxServoAngle = 180.0

kMinServoAngle = 0.0

set (*value*)

Set the servo position.

Servo values range from 0.0 to 1.0 corresponding to the range of full left to full right.

Parameters `value` (*float*) – Position from 0.0 to 1.0.

setAngle (*degrees*)

Set the servo angle.

Assumes that the servo angle is linear with respect to the PWM value (big assumption, need to test).

Servo angles that are out of the supported range of the servo simply “saturate” in that direction. In other words, if the servo has a range of (X degrees to Y degrees) then angles of less than X result in an angle of X being set and angles of more than Y degrees result in an angle of Y being set.

Parameters `degrees` (*float*) – The angle in degrees to set the servo.

SmartDashboard

class `wpiplib.SmartDashboard`

Bases: `object`

The bridge between robot programs and the SmartDashboard on the laptop

When a value is put into the SmartDashboard, it pops up on the SmartDashboard on the remote host. Users can put values into and get values from the SmartDashboard.

These values can also be accessed by a NetworkTables client via the ‘SmartDashboard’ table:

```
from networktables import NetworkTable
sd = NetworkTable.getTable('SmartDashboard')

# sd.putXXX and sd.getXXX work as expected here
```

classmethod `clearFlags` (*key, flags*)

Clears flags on the specified key in this table. The key can not be null.

Parameters

- **key** – the key name
- **flags** – the flags to clear (bitmask)

classmethod `clearPersistent` (*key*)

Stop making a key’s value persistent through program restarts. The key cannot be null.

Parameters `key` – the key name

classmethod `containsKey` (*key*)

Checks the table and tells if it contains the specified key.

Parameters `key` – key the key to search for

Returns true if the table has a value assigned to the given key

classmethod `delete` (*key*)

Deletes the specified key in this table. The key can not be null.

Parameters `key` – the key name

classmethod `getBoolean` (*key, defaultValue=<class ‘wpiplib.smartdashboard.SmartDashboard._defaultValueSentry’>*)

Returns the boolean the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod **getBooleanArray** (*key*, *defaultValue*=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>)

Returns the boolean array the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod **getData** (*key*)

Returns the value at the specified key.

Parameters **key** (*str*) – the key

Returns the value

Raises `KeyError` if the key doesn't exist

classmethod **getDouble** (*key*, *defaultValue*=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>)

Returns the number the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod **getFlags** (*key*)

Returns the flags for the specified key.

Parameters **key** – the key name

Returns the flags, or 0 if the key is not defined

classmethod **getInt** (*key*, *defaultValue*=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>)

Returns the number the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up

- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod `getKeys` (*types=0*)

Get array of keys in the table.

Parameters **types** – bitmask of types; 0 is treated as a “don't care”.

Returns keys currently in the table

classmethod `getNumber` (*key, defaultValue=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>*)

Returns the number the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod `getNumberArray` (*key, defaultValue=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>*)

Returns the number array the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod `getRaw` (*key, defaultValue=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>*)

Returns the raw value (byte array) the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod getString (*key*, *defaultValue*=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>)
Returns the string the key maps to. If the key does not exist or is of different type, it will return the default value; if that is not provided, it will throw a `KeyError`.

Calling this method without passing `defaultValue` is deprecated.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** – returned if the key doesn't exist

Returns the value associated with the given key or the given default value if there is no value associated with the key

Raises `KeyError` if the key doesn't exist and `defaultValue` is not provided.

classmethod getStringArray (*key*, *defaultValue*=<class 'wpilib.smartdashboard.SmartDashboard._defaultValueSentry'>)
Returns the string array the key maps to. If the key does not exist or is of different type, it will return the default value.

Parameters

- **key** (*str*) – the key to look up
- **defaultValue** (*list(str)*) – the value to be returned if no value is found

Returns the value associated with the given key or the given default value if there is no value associated with the key

Return type `list(str)`

Raises `KeyError` – If the value doesn't exist and no default is provided, or if it is the wrong type

classmethod isPersistent (*key*)

Returns whether the value is persistent through program restarts. The key cannot be null.

Parameters **key** – the key name

Returns True if the value is persistent.

classmethod putBoolean (*key*, *value*)

Put a boolean in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

:return False if the table key already exists with a different type

classmethod putBooleanArray (*key*, *value*)

Put a boolean array in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod putData (**args*, ***kwargs*)

Maps the specified key to the specified value in this table. The value can be retrieved by calling the `get` method with a key that is equal to the original key.

Two argument formats are supported: key, data:

Parameters

- **key** (*str*) – the key (cannot be None)
- **data** – the value

Or the single argument “value”:

Parameters **value** – the named value (getName is called to retrieve the value)

classmethod **putDouble** (*key, value*)

Put a number in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putInt** (*key, value*)

Put a number in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putNumber** (*key, value*)

Put a number in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putNumberArray** (*key, value*)

Put a number array in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putRaw** (*key, value*)

Put a raw value (byte array) in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putString** (*key, value*)

Put a string in the table.

Parameters

- **key** – the key to be assigned to
- **value** – the value that will be assigned

Returns False if the table key already exists with a different type

classmethod **putStringArray** (*key, value*)

Put a string array in the table

Parameters

- **key** (*str*) – the key to be assigned to
- **value** (*list (str)*) – the value that will be assigned

Returns False if the table key already exists with a different type

Return type bool

classmethod **setDefaultBoolean** (*key, defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod **setDefaultBooleanArray** (*key, defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod **setDefaultNumber** (*key, defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod **setDefaultNumberArray** (*key, defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod **setDefaultRaw** (*key, defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod `setDefaultString` (*key*, *defaultValue*)

Gets the current value in the table, setting it if it does not exist.

Parameters

- **key** – the key
- **defaultValue** – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

classmethod `setDefaultStringArray` (*key*, *defaultValue*)

If the key doesn't currently exist, then the specified value will be assigned to the key.

Parameters

- **key** (*str*) – the key to be assigned to
- **defaultValue** (*list (str)*) – the default value to set if key doesn't exist.

Returns False if the table key exists with a different type

Return type bool

classmethod `setFlags` (*key*, *flags*)

Sets flags on the specified key in this table. The key can not be null.

Parameters

- **key** – the key name
- **flags** – the flags to set (bitmask)

classmethod `setPersistent` (*key*)

Makes a key's value persistent through program restarts. The key cannot be null.

Parameters **key** – the key name

`table = None`

`tablesToData = {}`

Solenoid

class `wplib.Solenoid` (**args*, ***kwargs*)

Bases: `wplib.SolenoidBase`

Solenoid class for running high voltage Digital Output.

The Solenoid class is typically used for pneumatic solenoids, but could be used for any device within the current spec of the PCM.

Constructor.

Arguments can be supplied as positional or keyword. Acceptable positional argument combinations are:

- channel
- moduleNumber, channel

Alternatively, the above names can be used as keyword arguments.

Parameters

- **moduleNumber** (*int*) – The CAN ID of the PCM the solenoid is attached to
- **channel** (*int*) – The channel on the PCM to control (0..7)

free()

Mark the solenoid as freed.

get()

Read the current value of the solenoid.

Returns True if the solenoid output is on or false if the solenoid output is off.

Return type bool

isBlackListed()

Check if the solenoid is blacklisted. If a solenoid is shorted, it is added to the blacklist and disabled until power cycle, or until faults are cleared. See `clearAllPCMStickyFaults()`

Returns If solenoid is disabled due to short.

set(on)

Set the value of a solenoid.

Parameters **on** (*bool*) – True will turn the solenoid output on. False will turn the solenoid output off.

solenoidHandle

SolenoidBase

class `wpiplib.SolenoidBase` (*moduleNumber*)

Bases: `wpiplib.SensorBase`

SolenoidBase class is the common base class for the Solenoid and DoubleSolenoid classes.

Constructor.

Parameters **moduleNumber** – The PCM CAN ID

clearAllPCMStickyFaults()

Clear ALL sticky faults inside the PCM that Solenoid is wired to.

If a sticky fault is set, then it will be persistently cleared. Compressor drive maybe momentarily disable while flages are being cleared. Care should be taken to not call this too frequently, otherwise normal compressor functionality may be prevented.

If no sticky faults are set then this call will have no effect.

getAll()

Read all 8 solenoids from the module used by this solenoid as a single byte.

Returns The current value of all 8 solenoids on this module.

getPCMSolenoidBlackList()

Reads complete solenoid blacklist for all 8 solenoids as a single byte. If a solenoid is shorted, it is added to the blacklist and disabled until power cycle, or until faults are cleared. See `clearAllPCMStickyFaults()`

Returns The solenoid blacklist of all 8 solenoids on the module.

`getPCMSolenoidVoltageFault ()`

Returns True if PCM is in fault state : The common highside solenoid voltage rail is too low, most likely a solenoid channel has been shorted.

`getPCMSolenoidVoltageStickyFault ()`

Returns True if PCM Sticky fault is set : The common highside solenoid voltage rail is too low, most likely a solenoid channel has been shorted.

Spark

class `wpiplib.Spark` (*channel*)

Bases: `wpiplib.PWMSpeedController`

REV Robotics SPARK Speed Controller

Constructor.

Parameters `channel1` – The PWM channel that the SPARK is attached to. 0-9 are on-board, 10-19 are on the MXP port

Note: Note that the SD540 uses the following bounds for PWM values. These values should work reasonably well for most controllers, but if users experience issues such as asymmetric behavior around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the SD540 User Manual available from Mindsensors.

- 2.003ms = full “forward”
 - 1.55ms = the “high end” of the deadband range
 - 1.50ms = center of the deadband range (off)
 - 1.46ms = the “low end” of the deadband range
 - .999ms = full “reverse”
-

SPI

class `wpiplib.SPI` (*port*, *simPort=None*)

Bases: `object`

Represents a SPI bus port

Example usage:

```
spi = wpiplib.SPI(wpiplib.SPI.Port.kOnboardCS0)

# Write bytes 'text', and receive something
data = spi.transaction(b'text')
```

Constructor

Parameters

- `port` (`SPI.Port`) – the physical SPI port
- `simPort` – This must be an object that implements all of the `spi*` functions from `hal_impl` that you use. See `test_spi.py` for an example.

class Port

Bases: object

kMXP = 4**kOnboardCS0 = 0****kOnboardCS1 = 1****kOnboardCS2 = 2****kOnboardCS3 = 3**SPI.**devices = 0**SPI.**free ()**SPI.**freeAccumulator ()**

Frees the accumulator.

SPI.**getAccumulatorAverage ()**

Read the average of the accumulated value.

Returns The accumulated average value (value / count).SPI.**getAccumulatorCount ()**

Read the number of accumulated values.

Read the count of the accumulated values since the accumulator was last Reset().

Returns The number of times samples from the channel were accumulated.SPI.**getAccumulatorLastValue ()**

Read the last value read by the accumulator engine.

SPI.**getAccumulatorOutput ()**

Read the accumulated value and the number of accumulated values atomically.

This function reads the value and count atomically. This can be used for averaging.

Returns tuple of (value, count)SPI.**getAccumulatorValue ()**

Read the accumulated value.

Returns The 64-bit value accumulated since the last Reset().SPI.**initAccumulator** (*period, cmd, xfer_size, valid_mask, valid_value, data_shift, data_size, is_signed, big_endian*)

Initialize the accumulator.

Parameters

- **period** – Time between reads
- **cmd** – SPI command to send to request data
- **xfer_size** – SPI transfer size, in bytes
- **valid_mask** – Mask to apply to received data for validity checking
- **valid_data** – After valid_mask is applied, required matching value for validity checking
- **data_shift** – Bit shift to apply to received data to get actual data value
- **data_size** – Size (in bits) of data field
- **is_signed** – Is data field signed?

- **big_endian** – Is device big endian?

SPI.port

SPI.read (*initiate, size*)

Read a word from the receive FIFO.

Waits for the current transfer to complete if the receive FIFO is empty.

If the receive FIFO is empty, there is no active transfer, and *initiate* is `False`, errors.

Parameters

- **initiate** – If `True`, this function pushes “0” into the transmit buffer and initiates a transfer. If `False`, this function assumes that data is already in the receive FIFO from a previous write.
- **size** – Number of bytes to read.

Returns received data bytes

SPI.resetAccumulator ()

Resets the accumulator to zero.

SPI.setAccumulatorCenter (*center*)

Set the center value of the accumulator.

The center value is subtracted from each value before it is added to the accumulator. This is used for the center value of devices like gyros and accelerometers to make integration work and to take the device offset into account when integrating.

SPI.setAccumulatorDeadband (*deadband*)

Set the accumulator’s deadband.

SPI.setChipSelectActiveHigh ()

Configure the chip select line to be active high.

SPI.setChipSelectActiveLow ()

Configure the chip select line to be active low.

SPI.setClockActiveHigh ()

Configure the clock output line to be active high. This is sometimes called clock polarity low or clock idle low.

SPI.setClockActiveLow ()

Configure the clock output line to be active low. This is sometimes called clock polarity high or clock idle high.

SPI.setClockRate (*hz*)

Configure the rate of the generated clock signal. The default value is 500,000 Hz. The maximum value is 4,000,000 Hz.

Parameters hz – The clock rate in Hertz.

SPI.setLSBFirst ()

Configure the order that bits are sent and received on the wire to be least significant bit first.

SPI.setMSBFirst ()

Configure the order that bits are sent and received on the wire to be most significant bit first.

SPI.setSampleDataOnFalling ()

Configure that the data is stable on the falling edge and the data changes on the rising edge.

SPI.setSampleDataOnRising ()

Configure that the data is stable on the rising edge and the data changes on the falling edge.

`SPI.transaction` (*dataToSend*)

Perform a simultaneous read/write transaction with the device

Parameters `dataToSend` (*iterable of bytes*) – The data to be written out to the device

Returns data received from the device

Usage:

```
# send byte string
data = spi.transaction(b'stuff')

# send list of integers
data = spi.transaction([0x01, 0x02])
```

`SPI.write` (*dataToSend*)

Write data to the slave device. Blocks until there is space in the output FIFO.

If not running in output only mode, also saves the data received on the MISO input during the transfer into the receive FIFO.

Parameters `dataToSend` (*iterable of bytes*) – Data to send

Returns Number of bytes written

Usage:

```
# send byte string
writeCount = spi.write(b'stuff')

# send list of integers
writeCount = spi.write([0x01, 0x02])
```

Talon

`class wpilib.Talon` (*channel*)

Bases: `wpilib.PWMSpeedController`

Cross the Road Electronics (CTRE) Talon and Talon SR Speed Controller via PWM

Constructor for a Talon (original or Talon SR)

Parameters `channel` (*int*) – The PWM channel that the Talon is attached to. 0-9 are on-board, 10-19 are on the MXP port

Note: The Talon uses the following bounds for PWM values. These values should work reasonably well for most controllers, but if users experience issues such as asymmetric behavior around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the Talon User Manual available from CTRE.

- 2.037ms = full “forward”
 - 1.539ms = the “high end” of the deadband range
 - 1.513ms = center of the deadband range (off)
 - 1.487ms = the “low end” of the deadband range
 - 0.989ms = full “reverse”
-

TalonSRX

class `wpiplib.TalonSRX` (*channel*)

Bases: `wpiplib.PWMSpeedController`

Cross the Road Electronics (CTRE) Talon SRX Speed Controller via PWM

See also:

See `CANTalon` for CAN control of Talon SRX.

Constructor for a TalonSRX connected via PWM.

Parameters `channel` (*int*) – The PWM channel that the TalonSRX is attached to. 0-9 are on-board, 10-19 are on the MXP port.

Note: The TalonSRX uses the following bounds for PWM values. These values should work reasonably well for most controllers, but if users experience issues such as asymmetric behavior around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the TalonSRX User Manual available from CTRE.

- 2.004ms = full “forward”
 - 1.520ms = the “high end” of the deadband range
 - 1.500ms = center of the deadband range (off)
 - 1.480ms = the “low end” of the deadband range
 - 0.997ms = full “reverse”
-

Timer

class `wpiplib.Timer`

Bases: `object`

Provides time-related functionality for the robot

Note: Prefer to use this module for time functions, instead of the `time` module in the standard library. This will make it easier for your code to work properly in simulation.

static `delay` (*seconds*)

Pause the thread for a specified time. Pause the execution of the thread for a specified period of time given in seconds. Motors will continue to run at their last assigned values, and sensors will continue to update. Only the thread containing the wait will pause until the wait time is expired.

Parameters `seconds` (*float*) – Length of time to pause

Warning: If you’re tempted to use this function for autonomous mode to time transitions between actions, don’t do it!

Delaying the main robot thread for more than a few milliseconds is generally discouraged, and will cause problems and possibly leave the robot unresponsive.

get ()

Get the current time from the timer. If the clock is running it is derived from the current system clock the start time stored in the timer class. If the clock is not running, then return the time when it was last stopped.

Returns Current time value for this timer in seconds

Return type float

static getFPGATimestamp ()

Return the system clock time in seconds. Return the time from the FPGA hardware clock in seconds since the FPGA started.

Returns Robot running time in seconds.

Return type float

static getMatchTime ()

Return the approximate match time. The FMS does not currently send the official match time to the robots. This returns the time since the enable signal sent from the Driver Station. At the beginning of autonomous, the time is reset to 0.0 seconds. At the beginning of teleop, the time is reset to +15.0 seconds. If the robot is disabled, this returns 0.0 seconds.

Warning: This is not an official time (so it cannot be used to argue with referees).

Returns Match time in seconds since the beginning of autonomous

Return type float

getMsClock ()

Returns the system clock time in milliseconds.

Return type int

hasPeriodPassed (period)

Check if the period specified has passed and if it has, advance the start time by that period. This is useful to decide if it's time to do periodic work without drifting later by the time it took to get around to checking.

Parameters **period** – The period to check for (in seconds).

Returns If the period has passed.

Return type bool

reset ()

Reset the timer by setting the time to 0. Make the timer startTime the current time so new requests will be relative now.

start ()

Start the timer running. Just set the running flag to true indicating that all time requests should be relative to the system clock.

stop ()

Stop the timer. This computes the time as of now and clears the running flag, causing all subsequent time requests to be read from the accumulated time rather than looking at the system clock.

Ultrasonic

`class wpilib.Ultrasonic (pingChannel, echoChannel, units=0)`

Bases: `wpilib.SensorBase`

Ultrasonic rangefinder control

The Ultrasonic rangefinder measures absolute distance based on the round-trip time of a ping generated by the controller. These sensors use two transducers, a speaker and a microphone both tuned to the ultrasonic range. A common ultrasonic sensor, the Davenport SRF04 requires a short pulse to be generated on a digital channel. This causes the chirp to be emitted. A second line becomes high as the ping is transmitted and goes low when the echo is received. The time that the line is high determines the round trip distance (time of flight).

Create an instance of the Ultrasonic Sensor. This is designed to supchannel the Davenport SRF04 and Vex ultrasonic sensors.

Parameters

- **pingChannel** – The digital output channel that sends the pulse to initiate the sensor sending the ping.
- **echoChannel** – The digital input channel that receives the echo. The length of time that the echo is high represents the round trip time of the ping, and the distance.
- **units** – The units returned in either kInches or kMillimeters

`class PIDSourceType`

Bases: `object`

A description for the type of output value to provide to a `PIDController`

kDisplacement = 0

kRate = 1

`class Ultrasonic.Unit`

Bases: `object`

The units to return when `PIDGet` is called

kInches = 0

kMillimeters = 1

`Ultrasonic.automaticEnabled = False`

Automatic round robin mode

`Ultrasonic.free ()`

`Ultrasonic.getDistanceUnits ()`

Get the current `DistanceUnit` that is used for the `PIDSource` interface.

Returns The type of `DistanceUnit` that is being used.

`Ultrasonic.getPIDSourceType ()`

`Ultrasonic.getRangeInches ()`

Get the range in inches from the ultrasonic sensor.

Returns Range in inches of the target returned from the ultrasonic sensor. If there is no valid value yet, i.e. at least one measurement hasn't completed, then return 0.

Return type `float`

`Ultrasonic.getRangeMM ()`

Get the range in millimeters from the ultrasonic sensor.

Returns Range in millimeters of the target returned by the ultrasonic sensor. If there is no valid value yet, i.e. at least one measurement hasn't completed, then return 0.

Return type float

`Ultrasonic.instances = 0`

`static Ultrasonic.isAutomaticMode()`

`Ultrasonic.isEnabled()`

Is the ultrasonic enabled.

Returns True if the ultrasonic is enabled

`Ultrasonic.isRangeValid()`

Check if there is a valid range measurement. The ranges are accumulated in a counter that will increment on each edge of the echo (return) signal. If the count is not at least 2, then the range has not yet been measured, and is invalid.

Returns True if the range is valid

Return type bool

`Ultrasonic.kMaxUltrasonicTime = 0.1`

Max time (ms) between readings.

`Ultrasonic.kPingTime = 9.999999999999999e-06`

Time (sec) for the ping trigger pulse.

`Ultrasonic.kPriority = 90`

Priority that the ultrasonic round robin task runs.

`Ultrasonic.kSpeedOfSoundInchesPerSec = 13560.0`

`Ultrasonic.pidGet()`

Get the range in the current DistanceUnit (PIDSOURCE interface).

Returns The range in DistanceUnit

Return type float

`Ultrasonic.ping()`

Single ping to ultrasonic sensor. Send out a single ping to the ultrasonic sensor. This only works if automatic (round robin) mode is disabled. A single ping is sent out, and the counter should count the semi-period when it comes in. The counter is reset to make the current value invalid.

`Ultrasonic.sensors = <_weakrefset.WeakSet object>`

ultrasonic sensor list

`Ultrasonic.setAutomaticMode(enabling)`

Turn Automatic mode on/off. When in Automatic mode, all sensors will fire in round robin, waiting a set time between each sensor.

Parameters **enabling** (*bool*) – Set to true if round robin scheduling should start for all the ultrasonic sensors. This scheduling method assures that the sensors are non-interfering because no two sensors fire at the same time. If another scheduling algorithm is preferred, it can be implemented by pinging the sensors manually and waiting for the results to come back.

`Ultrasonic.setDistanceUnits(units)`

Set the current DistanceUnit that should be used for the PIDSOURCE interface.

Parameters **units** – The DistanceUnit that should be used.

`Ultrasonic.setEnabled(enable)`

Set if the ultrasonic is enabled.

Parameters `enable` (*bool*) – set to True to enable the ultrasonic

`Ultrasonic.setPIDSourceType(pidSource)`

Set which parameter you are using as a process control variable.

Parameters `pidSource` (*PIDSource.PIDSourceType*) – An enum to select the parameter.

static `Ultrasonic.ultrasonicChecker()`

Background task that goes through the list of ultrasonic sensors and pings each one in turn. The counter is configured to read the timing of the returned echo pulse.

Warning: DANGER WILL ROBINSON, DANGER WILL ROBINSON: This code runs as a task and assumes that none of the ultrasonic sensors will change while it's running. If one does, then this will certainly break. Make sure to disable automatic mode before changing anything with the sensors!!

Utility

class `wpilib.Utility`

Bases: `object`

Contains global utility functions

static `getFPGARevision()`

Return the FPGA Revision number. The format of the revision is 3 numbers. The 12 most significant bits are the Major Revision. the next 8 bits are the Minor Revision. The 12 least significant bits are the Build Number.

Returns FPGA Revision number.

Return type `int`

static `getFPGATime()`

Read the microsecond timer from the FPGA.

Returns The current time in microseconds according to the FPGA.

Return type `int`

static `getFPGAVersion()`

Return the FPGA Version number.

Returns FPGA Version number.

Return type `int`

static `getUserButton()`

Get the state of the "USER" button on the roboRIO.

Returns True if the button is currently pressed down

Return type `bool`

Victor

class `wpiplib.Victor` (*channel*)

Bases: `wpiplib.PWMSpeedController`

VEX Robotics Victor 888 Speed Controller via PWM

The Vex Robotics Victor 884 Speed Controller can also be used with this class but may need to be calibrated per the Victor 884 user manual.

Note: The Victor uses the following bounds for PWM values. These values were determined empirically and optimized for the Victor 888. These values should work reasonably well for Victor 884 controllers also but if users experience issues such as asymmetric behaviour around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the Victor 884 User Manual available from VEX Robotics: <http://content.vexrobotics.com/docs/ifi-v884-users-manual-9-25-06.pdf>

- 2.027ms = full “forward”
 - 1.525ms = the “high end” of the deadband range
 - 1.507ms = center of the deadband range (off)
 - 1.49ms = the “low end” of the deadband range
 - 1.026ms = full “reverse”
-

Constructor.

Parameters `channel` (*int*) – The PWM channel that the Victor is attached to. 0-9 are on-board, 10-19 are on the MXP port

VictorSP

class `wpiplib.VictorSP` (*channel*)

Bases: `wpiplib.PWMSpeedController`

VEX Robotics Victor SP Speed Controller via PWM

Constructor.

Parameters `channel` (*int*) – The PWM channel that the VictorSP is attached to. 0-9 are on-board, 10-19 are on the MXP port.

Note: The Talon uses the following bounds for PWM values. These values should work reasonably well for most controllers, but if users experience issues such as asymmetric behavior around the deadband or inability to saturate the controller in either direction, calibration is recommended. The calibration procedure can be found in the VictorSP User Manual.

- 2.004ms = full “forward”
 - 1.520ms = the “high end” of the deadband range
 - 1.500ms = center of the deadband range (off)
 - 1.480ms = the “low end” of the deadband range
 - 0.997ms = full “reverse”
-

XboxController

`class wpilib.XboxController` (*port*)

Bases: `wpilib.interfaces.GamepadBase`

Handle input from Xbox 360 or Xbox One controllers connected to the Driver Station.

This class handles Xbox input that comes from the Driver Station. Each time a value is requested the most recent value is returned. There is a single class instance for each controller and the mapping of ports to hardware buttons depends on the code in the Driver Station.

Construct an instance of an XboxController. The XboxController index is the USB port on the Driver Station.

Parameters `port` – The port on the Driver Station that the joystick is plugged into

`getAButton` ()

Read the value of the A button on the controller

Returns The state of the A button

Return type boolean

`getBButton` ()

Read the value of the B button on the controller

Returns The state of the B button

Return type boolean

`getBackButton` ()

Read the value of the back button on the controller

Returns The state of the back button

Return type boolean

`getBumper` (*hand*)

Read the values of the bumper button on the controller.

Parameters `hand` – Side of controller whose value should be returned.

Returns The state of the button

Return type boolean

`getName` ()

`getPOV` (*pov*)

`getPOVCount` ()

`getRawAxis` (*axis*)

Get the value of the axis

Parameters `axis` – The axis to read, starting at 0

Returns The value of the axis

Return type float

`getRawButton` (*button*)

Get the button value (starting at button 1)

Parameters `button` – The button number to be read (starting at 1)

Returns The state of the button

Return type boolean

getStartButton ()

Read the value of the start button on the controller

Returns The state of the start button

Return type boolean

getStickButton (*hand*)

Read the values of the stick button on the controller

Parameters **hand** – Side of the controller whose value should be returned

Returns The state of the button

Return type boolean

getTriggerAxis (*hand*)

Get the trigger axis value of the controller.

Parameters **hand** – Side of controller whose value should be returned

Returns The trigger axis value of the controller

Return type float

getType ()**getX (*hand*)**

Get the X axis value of the controller.

Parameters **hand** – Side of controller whose value should be returned

Returns The X axis value of the controller

Return type float

getXButton ()

Read the value of the X button on the controller

Returns The state of the X button

Return type boolean

getY (*hand*)

Get the Y axis value of the controller.

Parameters **hand** – Side of controller whose value should be returned

Returns The Y axis value of the controller

Return type float

getYButton ()

Read the value of the Y button on the controller

Returns The state of the Y button

Return type boolean

setOutput (*outputNumber, value*)**setOutputs (*value*)****setRumble (*type_, value*)**

wpiLib.buttons Package

Classes in this package are used to interface various types of buttons to a command-based robot.

If you are not using the Command framework, you can ignore these classes.

| | |
|---|--|
| <code>wpiLib.buttons.Button</code> | This class provides an easy way to link commands to OI inputs. |
| <code>wpiLib.buttons.InternalButton(...)</code> | This class is intended to be used within a program. |
| <code>wpiLib.buttons.JoystickButton(...)</code> | Create a joystick button for triggering commands. |
| <code>wpiLib.buttons.NetworkButton(...)</code> | |
| <code>wpiLib.buttons.Trigger</code> | This class provides an easy way to link commands to inputs. |

Button

class `wpiLib.buttons.Button`

Bases: `wpiLib.buttons.Trigger`

This class provides an easy way to link commands to OI inputs.

It is very easy to link a button to a command. For instance, you could link the trigger button of a joystick to a “score” command.

This class represents a subclass of `Trigger` that is specifically aimed at buttons on an operator interface as a common use case of the more generalized `Trigger` objects. This is a simple wrapper around `Trigger` with the method names renamed to fit the `Button` object use.

cancelWhenPressed (*command*)

Cancel the command when the button is pressed.

Parameters **command** –

toggleWhenPressed (*command*)

Toggles the command whenever the button is pressed (on then off then on).

Parameters **command** –

whenPressed (*command*)

Starts the given command whenever the button is newly pressed.

Parameters **command** – the command to start

whenReleased (*command*)

Starts the command when the button is released.

Parameters **command** – the command to start

whileHeld (*command*)

Constantly starts the given command while the button is held.

`Command.start()` will be called repeatedly while the button is held, and will be canceled when the button is released.

Parameters **command** – the command to start

InternalButton

class `wpiplib.buttons.InternalButton` (*inverted=False*)

Bases: `wpiplib.buttons.Button`

This class is intended to be used within a program. The programmer can manually set its value. Includes a setting for whether or not it should invert its value.

Creates an InternalButton which is inverted depending on the input.

Parameters **inverted** – If False, then this button is pressed when set to True, otherwise it is pressed when set to False.

get ()

setInverted (*inverted*)

setPressed (*pressed*)

JoystickButton

class `wpiplib.buttons.JoystickButton` (*joystick, buttonNumber*)

Bases: `wpiplib.buttons.Button`

Create a joystick button for triggering commands.

Parameters

- **joystick** – The GenericHID object that has the button (e.g. `Joystick`, `KinectStick`, etc)
- **buttonNumber** – The button number (see `GenericHID.getRawButton()`)

get ()

Gets the value of the joystick button.

Returns The value of the joystick button

NetworkButton

class `wpiplib.buttons.NetworkButton` (*table, field*)

Bases: `wpiplib.buttons.Button`

get ()

Trigger

class `wpiplib.buttons.Trigger`

Bases: `object`

This class provides an easy way to link commands to inputs.

It is very easy to link a button to a command. For instance, you could link the trigger button of a joystick to a “score” command.

It is encouraged that teams write a subclass of Trigger if they want to have something unusual (for instance, if they want to react to the user holding a button while the robot is reading a certain sensor input). For this, they only have to write the `get()` method to get the full functionality of the Trigger class.

cancelWhenActive (*command*)

Cancels a command when the trigger becomes active.

Parameters **command** – the command to cancel

get ()

Returns whether or not the trigger is active

This method will be called repeatedly a command is linked to the Trigger.

Returns whether or not the trigger condition is active.

grab ()

Returns whether *get* () returns True or the internal table for *SmartDashboard* use is pressed.

toggleWhenActive (*command*)

Toggles a command when the trigger becomes active.

Parameters **command** – the command to toggle

whenActive (*command*)

Starts the given command whenever the trigger just becomes active.

Parameters **command** – the command to start

whenInactive (*command*)

Starts the command when the trigger becomes inactive.

Parameters **command** – the command to start

whileActive (*command*)

Constantly starts the given command while the button is held.

`Command.start()` will be called repeatedly while the trigger is active, and will be canceled when the trigger becomes inactive.

Parameters **command** – the command to start

wpilib.command Package

Objects in this package allow you to implement a robot using Command-based programming. Command based programming is a design pattern to help you organize your robot programs, by organizing your robot program into components based on *Command* and *Subsystem*

The python implementation of the Command framework closely follows the Java language implementation. RobotPy has several examples of command based robots available.

Each one of the objects in the Command framework has detailed documentation available. If you need more information, for examples, tutorials, and other detailed information on programming your robot using this pattern, we recommend that you consult the Java version of the [FRC Control System documentation](#)

| | |
|--|---|
| <code>wpilib.command.Command([name, timeout])</code> | The Command class is at the very core of the entire command framework. |
| <code>wpilib.command.CommandGroup([name])</code> | A CommandGroup is a list of commands which are executed in sequence. |
| <code>wpilib.command.ConditionalCommand(name)</code> | A ConditionalCommand is a <i>Command</i> that starts one of two commands. |
| <code>wpilib.command.InstantCommand([name])</code> | A command that has no duration. |
| Continued on next page | |

Table 1.3 – continued from previous page

| | |
|---|---|
| <code>wpiplib.command.PIDCommand(p, i, d)</code> | This class defines a Command which interacts heavily with a PID loop. |
| <code>wpiplib.command.PIDSubsystem(p, i, d)</code> | This class is designed to handle the case where there is a Subsystem which uses a single {@link PIDController} almost constantly (for instance, an elevator which attempts to stay at a constant height). |
| <code>wpiplib.command.PrintCommand(message)</code> | A PrintCommand is a command which prints out a string when it is initialized, and then immediately finishes. |
| <code>wpiplib.command.Scheduler()</code> | The Scheduler is a singleton which holds the top-level running commands. |
| <code>wpiplib.command.StartCommand(...)</code> | A StartCommand will call the start() method of another command when it is initialized and will finish immediately. |
| <code>wpiplib.command.Subsystem([name])</code> | This class defines a major component of the robot. |
| <code>wpiplib.command.TimedCommand(...)</code> | A command that runs for a set period of time. |
| <code>wpiplib.command.WaitCommand(timeout)</code> | A WaitCommand will wait for a certain amount of time before finishing. |
| <code>wpiplib.command.WaitForChildren(...)</code> | This command will only finish if whatever <i>CommandGroup</i> it is in has no active children. |
| <code>wpiplib.command.WaitUntilCommand(time)</code> | This will wait until the game clock reaches some value, then continue to the next command. |

Command

class `wpiplib.command.Command` (*name=None, timeout=None*)

Bases: `wpiplib.Sendable`

The Command class is at the very core of the entire command framework. Every command can be started with a call to `start()`. Once a command is started it will call `initialize()`, and then will repeatedly call `execute()` until `isFinished()` returns True. Once it does, `end()` will be called.

However, if at any point while it is running `cancel()` is called, then the command will be stopped and `interrupted()` will be called.

If a command uses a *Subsystem*, then it should specify that it does so by calling the `requires()` method in its constructor. Note that a Command may have multiple requirements, and `requires()` should be called for each one.

If a command is running and a new command with shared requirements is started, then one of two things will happen. If the active command is interruptible, then `cancel()` will be called and the command will be removed to make way for the new one. If the active command is not interruptible, the other one will not even be started, and the active one will continue functioning.

See also:

Subsystem, CommandGroup

Creates a new command.

Parameters

- **name** – The name for this command; if unspecified or None, The name of this command will be set to its class name.
- **timeout** – The time (in seconds) before this command “times out”. Default is no timeout. See `isTimedOut()`.

cancel ()

This will cancel the current command.

This will cancel the current command eventually. It can be called multiple times. And it can be called when the command is not running. If the command is running though, then the command will be marked as canceled and eventually removed.

Warning: A command can not be canceled if it is a part of a *CommandGroup*, you must cancel the *CommandGroup* instead.

clearRequirements ()

Clears list of subsystem requirements. This is only used by *ConditionalCommand* so cancelling the chosen command works properly in *CommandGroup*.

doesRequire (system)

Checks if the command requires the given *Subsystem*.

Parameters *system* – the system

Returns whether or not the subsystem is required, or False if given None.

end ()

Called when the command ended peacefully. This is where you may want to wrap up loose ends, like shutting off a motor that was being used in the command.

execute ()

The execute method is called repeatedly until this Command either finishes or is canceled.

getGroup ()

Returns the *CommandGroup* that this command is a part of. Will return None if this Command is not in a group.

Returns the *CommandGroup* that this command is a part of (or None if not in group)

getName ()

Returns the name of this command. If no name was specified in the constructor, then the default is the name of the class.

Returns the name of this command

getRequirements ()

Returns the requirements (as a set of Subsystems) of this command

initialize ()

The initialize method is called the first time this Command is run after being started.

interrupted ()

Called when the command ends because somebody called cancel() or another command shared the same requirements as this one, and booted it out.

This is where you may want to wrap up loose ends, like shutting off a motor that was being used in the command.

Generally, it is useful to simply call the end() method within this method, as done here.

isCanceled ()

Returns whether or not this has been canceled.

Returns whether or not this has been canceled

isFinished()

Returns whether this command is finished. If it is, then the command will be removed and `end()` will be called.

It may be useful for a team to reference the `isTimedOut()` method for time-sensitive commands, or override `TimedCommand`.

If you do not specify `isFinished` in your command, the command will only end if interrupted or canceled. If you want a command that executes only once and then ends, override `InstantCommand`.

Returns whether this command is finished.

See `isTimedOut()`

See

class `.TimedCommand`

See

class `.InstantCommand`

isInterruptible()

Returns whether or not this command can be interrupted.

Returns whether or not this command can be interrupted

isRunning()

Returns whether or not the command is running. This may return true even if the command has just been canceled, as it may not have yet called `interrupted()`.

Returns whether or not the command is running

isTimedOut()

Returns whether or not the `timeSinceInitialized()` method returns a number which is greater than or equal to the timeout for the command. If there is no timeout, this will always return false.

Returns whether the time has expired

lockChanges()

Prevents further changes from being made

removed()

Called when the command has been removed. This will call `interrupted()` or `end()`.

requires(subsystem)

This method specifies that the given `Subsystem` is used by this command. This method is crucial to the functioning of the Command System in general.

Note that the recommended way to call this method is in the constructor.

Parameters `subsystem` – the `Subsystem` required

run()

The run method is used internally to actually run the commands.

Returns whether or not the command should stay within the Scheduler.

setInterruptible(interruptible)

Sets whether or not this command can be interrupted.

Parameters `interruptible` – whether or not this command can be interrupted

setParent(parent)

Sets the parent of this command. No actual change is made to the group.

Parameters `parent` – the parent

setRunWhenDisabled (*run*)

Sets whether or not this `{@link Command}` should run when the robot is disabled.

By default a command will not run when the robot is disabled, and will in fact be canceled.

Parameters `run` – whether or not this command should run when the robot is disabled

setTimeout (*seconds*)

Sets the timeout of this command.

Parameters `seconds` – the timeout (in seconds)

See `isTimedOut()`

start ()

Starts up the command. Gets the command ready to start. Note that the command will eventually start, however it will not necessarily do so immediately, and may in fact be canceled before `initialize` is even called.

startRunning ()

This is used internally to mark that the command has been started. The lifecycle of a command is:

- `startRunning()` is called.
- `run()` is called (multiple times potentially)
- `removed()` is called

It is very important that `startRunning()` and `removed()` be called in order or some assumptions of the code will be broken.

startTiming ()

Called to indicate that the timer should start. This is called right before `initialize()` is, inside the `run()` method.

timeSinceInitialized ()

Returns the time since this command was initialized (in seconds). This function will work even if there is no specified timeout.

Returns the time since this command was initialized (in seconds).

willRunWhenDisabled ()

Returns whether or not this `Command` will run when the robot is disabled, or if it will cancel itself.

CommandGroup

class `wpi.lib.command.CommandGroup` (*name=None*)

Bases: `wpi.lib.command.Command`

A `CommandGroup` is a list of commands which are executed in sequence.

Commands in a `CommandGroup` are added using the `addSequential()` method and are called sequentially. `CommandGroups` are themselves `Commands` and can be given to other `CommandGroups`.

`CommandGroups` will carry all of the requirements of their subcommands. Additional requirements can be specified by calling `requires()` normally in the constructor.

`CommandGroups` can also execute commands in parallel, simply by adding them using `addParallel(...)`.

See also:

`Command`, `Subsystem`

Creates a new CommandGroup with the given name.

Parameters **name** – the name for this command group (optional). If None, the name of this command will be set to its class name.

class Entry (*command, state, timeout*)

Bases: object

BRANCH_CHILD = 2

BRANCH_PEER = 1

IN_SEQUENCE = 0

isTimedOut ()

CommandGroup.**addParallel** (*command, timeout=None*)

Adds a new child Command to the group (with an optional timeout). The Command will be started after all the previously added Commands.

Once the Command is started, it will run until it finishes, is interrupted, or the time expires (if a timeout is provided), whichever is sooner. Note that the given Command will have no knowledge that it is on a timer.

Instead of waiting for the child to finish, a CommandGroup will have it run at the same time as the subsequent Commands. The child will run until either it finishes, the timeout expires, a new child with conflicting requirements is started, or the main sequence runs a Command with conflicting requirements. In the latter two cases, the child will be canceled even if it says it can't be interrupted.

Note that any requirements the given Command has will be added to the group. For this reason, a Command's requirements can not be changed after being added to a group.

It is recommended that this method be called in the constructor.

Parameters

- **command** – The command to be added
- **timeout** – The timeout (in seconds) (optional)

CommandGroup.**addSequential** (*command, timeout=None*)

Adds a new Command to the group (with an optional timeout). The Command will be started after all the previously added Commands.

Once the Command is started, it will be run until it finishes or the time expires, whichever is sooner (if a timeout is provided). Note that the given Command will have no knowledge that it is on a timer.

Note that any requirements the given Command has will be added to the group. For this reason, a Command's requirements can not be changed after being added to a group.

It is recommended that this method be called in the constructor.

Parameters

- **command** – The Command to be added
- **timeout** – The timeout (in seconds) (optional)

CommandGroup.**cancelConflicts** (*command*)

CommandGroup.**end** ()

CommandGroup.**execute** ()

CommandGroup.**initialize** ()

CommandGroup.**interrupted** ()

`CommandGroup.isFinished()`

Returns True if all the Commands in this group have been started and have finished.

Teams may override this method, although they should probably reference `super().isFinished()` if they do.

Returns whether this `CommandGroup` is finished

`CommandGroup.isInterruptible()`

Returns whether or not this group is interruptible. A command group will be uninterruptible if `setInterruptible(False)` was called or if it is currently running an uninterruptible command or child.

Returns whether or not this `CommandGroup` is interruptible.

ConditionalCommand

`class wpilib.command.ConditionalCommand(name, onTrue=None, onFalse=None)`

Bases: `wpilib.command.Command`

A `ConditionalCommand` is a `Command` that starts one of two commands.

A `ConditionalCommand` uses `m_condition` to determine whether it should run `m_onTrue` or `m_onFalse`.

A `ConditionalCommand` adds the proper `Command` to the `Scheduler` during `initialize()` and then `isFinished()` will return true once that `Command` has finished executing.

If no `Command` is specified for `m_onFalse`, the occurrence of that condition will be a no-op.

@see `Command` @see `Scheduler`

Creates a new `ConditionalCommand` with given name and `onTrue` and `onFalse` Commands.

Users of this constructor should also override `condition()`.

Parameters

- **name** – the name for this command group
- **onTrue** – The `Command` to execute if `{@link ConditionalCommand#condition()}` returns true
- **onFalse** – The `Command` to execute if `{@link ConditionalCommand#condition()}` returns false

`condition()`

The Condition to test to determine which `Command` to run.

Returns true if `m_onTrue` should be run or false if `m_onFalse` should be run.

`interrupted()`

`isFinished()`

InstantCommand

`class wpilib.command.InstantCommand(name=None)`

Bases: `wpilib.command.Command`

A command that has no duration. Subclasses should implement the `initialize()` method to carry out desired actions.

`isFinished()`

PIDCommand

class `wpiilib.command.PIDCommand` (*p*, *i*, *d*, *period=None*, *f=0.0*, *name=None*)

Bases: `wpiilib.command.Command`

This class defines a Command which interacts heavily with a PID loop.

It provides some convenience methods to run an internal PIDController. It will also start and stop said PIDController when the PIDCommand is first initialized and ended/interrupted.

Instantiates a PIDCommand that will use the given *p*, *i* and *d* values. It will use the class name as its name unless otherwise specified. It will also space the time between PID loop calculations to be equal to the given period.

Parameters

- **p** – the proportional value
- **i** – the integral value
- **d** – the derivative value
- **period** – the time (in seconds) between calculations (optional)
- **f** – the feed forward value
- **name** – the name (optional)

getPIDController ()

Returns the PIDController used by this PIDCommand. Use this if you would like to fine tune the pid loop.

Notice that calling `setSetpoint(...)` on the controller will not result in the setpoint being trimmed to be in the range defined by `setSetpointRange(...)`.

Returns the PIDController used by this PIDCommand

getPosition ()

Returns the current position

Returns the current position

getSetpoint ()

Returns the setpoint.

Returns the setpoint

returnPIDInput ()

Returns the input for the pid loop.

It returns the input for the pid loop, so if this command was based off of a gyro, then it should return the angle of the gyro

All subclasses of PIDCommand must override this method.

This method will be called in a different thread then the *Scheduler* thread.

Returns the value the pid loop should use as input

setSetpoint (*setpoint*)

Sets the setpoint to the given value. If `setRange()` was called, then the given setpoint will be trimmed to fit within the range.

Parameters *setpoint* – the new setpoint

setSetpointRelative (*deltaSetpoint*)

Adds the given value to the setpoint. If `setRange()` was used, then the bounds will still be honored by this method.

Parameters `deltaSetpoint` – the change in the setpoint

usePIDOutput (*output*)

Uses the value that the pid loop calculated. The calculated value is the “output” parameter. This method is a good time to set motor values, maybe something along the lines of *driveline.tankDrive(output, -output)*.

All subclasses of `PIDCommand` should override this method.

This method will be called in a different thread than the Scheduler thread.

Parameters `output` – the value the pid loop calculated

PIDSubsystem

class `wpiplib.command.PIDSubsystem` (*p, i, d, period=None, f=0.0, name=None*)

Bases: `wpiplib.command.Subsystem`

This class is designed to handle the case where there is a Subsystem which uses a single {[@link PIDController](#)} almost constantly (for instance, an elevator which attempts to stay at a constant height).

It provides some convenience methods to run an internal `PIDController`. It also allows access to the internal `PIDController` in order to give total control to the programmer.

Instantiates a `PIDSubsystem` that will use the given *p*, *i* and *d* values. It will use the class name as its name unless otherwise specified. It will also space the time between PID loop calculations to be equal to the given period.

Parameters

- **p** – the proportional value
- **i** – the integral value
- **d** – the derivative value
- **period** – the time (in seconds) between calculations (optional)
- **f** – the feed forward value
- **name** – the name (optional)

disable ()

Disables the internal `PIDController`

enable ()

Enables the internal `PIDController`

getPIDController ()

Returns the `PIDController` used by this `PIDSubsystem`. Use this if you would like to fine tune the pid loop.

Notice that calling `setSetpoint()` on the controller will not result in the setpoint being trimmed to be in the range defined by `setSetpointRange()`.

Returns the `PIDController` used by this `PIDSubsystem`

getPosition ()

Returns the current position

Returns the current position

getSetpoint ()

Returns the setpoint.

Returns the setpoint

onTarget ()

Return True if the error is within the percentage of the total input range, determined by `setAbsoluteTolerance` or `setPercentTolerance`. This assumes that the maximum and minimum input were set using `setInput`.

Returns True if the error is less than the tolerance

returnPIDInput ()

Returns the input for the pid loop.

It returns the input for the pid loop, so if this command was based off of a gyro, then it should return the angle of the gyro

All subclasses of `PIDSubsystem` must override this method.

This method will be called in a different thread then the Scheduler thread.

Returns the value the pid loop should use as input

setAbsoluteTolerance (*t*)

Set the absolute error which is considered tolerable for use with `OnTarget`.

Parameters *t* – The absolute tolerance (same range as the `PIDInput` values)

setInputRange (*minimumInput*, *maximumInput*)

Sets the maximum and minimum values expected from the input.

Parameters

- **minimumInput** – the minimum value expected from the input
- **maximumInput** – the maximum value expected from the output

setOutputRange (*minimumOutput*, *maximumOutput*)

Sets the maximum and minimum values to write.

Parameters

- **minimumOutput** – the minimum value to write to the output
- **maximumOutput** – the maximum value to write to the output

setPercentTolerance (*p*)

Set the percentage error which is considered tolerable for use with `OnTarget`.

Parameters *p* – The percentage tolerance (value of 15.0 == 15 percent)

setSetpoint (*setpoint*)

Sets the setpoint to the given value. If `setRange` () was called, then the given setpoint will be trimmed to fit within the range.

Parameters *setpoint* – the new setpoint

setSetpointRelative (*deltaSetpoint*)

Adds the given value to the setpoint. If `setRange` () was used, then the bounds will still be honored by this method.

Parameters *deltaSetpoint* – the change in the setpoint

usePIDOutput (*output*)

Uses the value that the pid loop calculated. The calculated value is the “output” parameter. This method is a good time to set motor values, maybe something along the lines of `driveline.tankDrive(output, -output)`.

All subclasses of `PIDSubsystem` should override this method.

This method will be called in a different thread then the Scheduler thread.

Parameters *output* – the value the pid loop calculated

PrintCommand

class `wplib.command.PrintCommand`(*message*)
Bases: `wplib.command.InstantCommand`

A PrintCommand is a command which prints out a string when it is initialized, and then immediately finishes.

It is useful if you want a `CommandGroup` to print out a string when it reaches a certain point.

Instantiates a PrintCommand which will print the given message when it is run.

Parameters `message` – the message to print

initialize ()

Scheduler

class `wplib.command.Scheduler`
Bases: `wplib.Sendable`

The Scheduler is a singleton which holds the top-level running commands. It is in charge of both calling the command's `run()` method and to make sure that there are no two commands with conflicting requirements running.

It is fine if teams wish to take control of the Scheduler themselves, all that needs to be done is to call `Scheduler.getInstance().run()` often to have Commands function correctly. However, this is already done for you if you use the CommandBased Robot template.

See also:

[*Command*](#)

Instantiates a Scheduler.

add (*command*)

Adds the command to the Scheduler. This will not add the `Command` immediately, but will instead wait for the proper time in the `run()` loop before doing so. The command returns immediately and does nothing if given null.

Adding a `Command` to the `Scheduler` involves the Scheduler removing any Command which has shared requirements.

Parameters `command` – the command to add

addButton (*button*)

Adds a button to the Scheduler. The Scheduler will poll the button during its `run()`.

Parameters `button` – the button to add

disable ()

Disable the command scheduler.

enable ()

Enable the command scheduler.

static getInstance ()

Returns the Scheduler, creating it if one does not exist.

Returns the Scheduler

getName ()

getType ()

registerSubsystem (*system*)

Registers a *Subsystem* to this Scheduler, so that the Scheduler might know if a default Command needs to be run. All *Subsystem* objects should call this.

Parameters **system** – the system

remove (*command*)

Removes the *Command* from the Scheduler.

Parameters **command** – the command to remove

removeAll ()

Removes all commands

run ()

Runs a single iteration of the loop. This method should be called often in order to have a functioning Command system. The loop has five stages:

- Poll the Buttons
- Execute/Remove the Commands
- Send values to SmartDashboard
- Add Commands
- Add Defaults

StartCommand

class `wpiilib.command.StartCommand` (*commandToStart*)

Bases: `wpiilib.command.InstantCommand`

A StartCommand will call the start() method of another command when it is initialized and will finish immediately.

Instantiates a StartCommand which will start the given command whenever its initialize() is called.

Parameters **commandToStart** – the *Command* to start

initialize ()

Subsystem

class `wpiilib.command.Subsystem` (*name=None*)

Bases: `wpiilib.Sendable`

This class defines a major component of the robot.

A good example of a subsystem is the driveline, or a claw if the robot has one.

All motors should be a part of a subsystem. For instance, all the wheel motors should be a part of some kind of “Driveline” subsystem.

Subsystems are used within the command system as requirements for Command. Only one command which requires a subsystem can run at a time. Also, subsystems can have default commands which are started if there is no command running which requires this subsystem.

See also:

Command

Creates a subsystem.

Parameters `name` – the name of the subsystem; if `None`, it will be set to the name of the class.

confirmCommand()

Call this to alert Subsystem that the current command is actually the command. Sometimes, the Subsystem is told that it has no command while the Scheduler is going through the loop, only to be soon after given a new one. This will avoid that situation.

getCurrentCommand()

Returns the command which currently claims this subsystem.

Returns the command which currently claims this subsystem

getDefaultCommand()

Returns the default command (or `None` if there is none).

Returns the default command

getName()

Returns the name of this subsystem, which is by default the class name.

Returns the name of this subsystem

initDefaultCommand()

Initialize the default command for a subsystem. By default subsystems have no default command, but if they do, the default command is set with this method. It is called on all Subsystems by `CommandBase` in the users program after all the Subsystems are created.

setCurrentCommand(*command*)

Sets the current command

Parameters `command` – the new current command

setDefaultCommand(*command*)

Sets the default command. If this is not called or is called with `None`, then there will be no default command for the subsystem.

Parameters `command` – the default command (or `None` if there should be none)

| |
|---|
| Warning: This should NOT be called in a constructor if the subsystem is a singleton. |
|---|

TimedCommand

class `wpiplib.command.TimedCommand` (*name*, *timeoutInSeconds*)

Bases: `wpiplib.command.Command`

A command that runs for a set period of time.

isFinished()

WaitCommand

class `wpiplib.command.WaitCommand` (*timeout*, *name=None*)

Bases: `wpiplib.command.TimedCommand`

A `WaitCommand` will wait for a certain amount of time before finishing. It is useful if you want a `CommandGroup` to pause for a moment.

See also:

CommandGroup

Instantiates a WaitCommand with the given timeout.

Parameters

- **timeout** – the time the command takes to run
- **name** – the name of the command (optional)

WaitForChildren

class wpilib.command.**WaitForChildren** (*name=None, timeout=None*)

Bases: *wpilib.command.Command*

This command will only finish if whatever *CommandGroup* it is in has no active children. If it is not a part of a CommandGroup, then it will finish immediately. If it is itself an active child, then the CommandGroup will never end.

This class is useful for the situation where you want to allow anything running in parallel to finish, before continuing in the main CommandGroup sequence.

Creates a new command.

Parameters

- **name** – The name for this command; if unspecified or None, The name of this command will be set to its class name.
- **timeout** – The time (in seconds) before this command “times out”. Default is no timeout. See `isTimedOut()`.

isFinished()

WaitUntilCommand

class wpilib.command.**WaitUntilCommand** (*time*)

Bases: *wpilib.command.Command*

This will wait until the game clock reaches some value, then continue to the next command.

isFinished()

wpilib.interfaces Package

This package contains objects that can be used to determine the requirements of various interfaces used in WPILib.

Generally, the python version of WPILib does not require that you inherit from any of these interfaces, but instead will allow you to use custom objects as long as they have the same methods.

| | |
|---|--|
| <i>wpilib.interfaces.Accelerometer</i> | Interface for 3-axis accelerometers |
| <i>wpilib.interfaces.Controller</i> | An interface for controllers. |
| <i>wpilib.interfaces.CounterBase</i> | Interface for counting the number of ticks on a digital input channel. |
| <i>wpilib.interfaces.GenericHID(port)</i> | GenericHID Interface. |
| <i>wpilib.interfaces.Gyro</i> | Interface for yaw rate gyros |

Continued on next page

Table 1.4 – continued from previous page

| | |
|---|---|
| <code>wpi.lib.interfaces.NamedSendable</code> | The interface for sendable objects that gives the sendable a default name in the Smart Dashboard. |
| <code>wpi.lib.interfaces.PIDInterface</code> | |
| <code>wpi.lib.interfaces.PIDOutput</code> | This interface allows <code>PIDController</code> to write its results to its output. |
| <code>wpi.lib.interfaces.PIDSource</code> | This interface allows for <code>PIDController</code> to automatically read from this object. |
| <code>wpi.lib.interfaces.Potentiometer</code> | |
| <code>wpi.lib.interfaces.SpeedController</code> | Interface for speed controlling devices. |

Accelerometer

class `wpi.lib.interfaces.Accelerometer`

Bases: `object`

Interface for 3-axis accelerometers

class `Range`

Bases: `object`

k16G = 3

k2G = 0

k4G = 1

k8G = 2

`Accelerometer.getX()`

Common interface for getting the x axis acceleration

Returns The acceleration along the x axis in g-forces

`Accelerometer.getY()`

Common interface for getting the y axis acceleration

Returns The acceleration along the y axis in g-forces

`Accelerometer.getZ()`

Common interface for getting the z axis acceleration

Returns The acceleration along the z axis in g-forces

`Accelerometer.setRange(range)`

Common interface for setting the measuring range of an accelerometer.

Parameters `range` – The maximum acceleration, positive or negative, that the accelerometer will measure. Not all accelerometers support all ranges.

Controller

class `wpi.lib.interfaces.Controller`

Bases: `object`

An interface for controllers. Controllers run control loops, the most common are PID controllers and there are variants, but this includes anything that is controlling an actuator in a separate thread.

disable()

Stops the control loop from running until explicitly re-enabled by calling `enable()`.

enable()
Allows the control loop to run.

CounterBase

class `wpiilib.interfaces.CounterBase`

Bases: `object`

Interface for counting the number of ticks on a digital input channel. Encoders, Gear tooth sensors, and counters should all subclass this so it can be used to build more advanced classes for control and driving.

All counters will immediately start counting - `reset()` them if you need them to be zeroed before use.

class `EncodingType`

Bases: `object`

The number of edges for the counterbase to increment or decrement on

k1X = 0

Count only the rising edge

k2X = 1

Count both the rising and falling edge

k4X = 2

Count rising and falling on both channels

`CounterBase.get()`

Get the count

Returns the count

`CounterBase.getDirection()`

Determine which direction the counter is going

Returns True for one direction, False for the other

`CounterBase.getPeriod()`

Get the time between the last two edges counted

Returns the time between the last two ticks in seconds

`CounterBase.getStopped()`

Determine if the counter is not moving

Returns True if the counter has not changed for the max period

`CounterBase.reset()`

Reset the count to zero

`CounterBase.setMaxPeriod(maxPeriod)`

Set the maximum time between edges to be considered stalled

Parameters `maxPeriod` – the maximum period in seconds

GenericHID

class `wpiilib.interfaces.GenericHID(port)`

Bases: `object`

GenericHID Interface.

```
class HIDType (value)
```

```
    Bases: object
```

```
    kHID1stPerson = 24
```

```
    kHIDDriving = 22
```

```
    kHIDFlight = 23
```

```
    kHIDGamepad = 21
```

```
    kHIDJoystick = 20
```

```
    kUnknown = -1
```

```
    kXInputArcadePad = 19
```

```
    kXInputArcadeStick = 3
```

```
    kXInputDancePad = 5
```

```
    kXInputDrumKit = 8
```

```
    kXInputFlightStick = 4
```

```
    kXInputGamepad = 1
```

```
    kXInputGuitar = 6
```

```
    kXInputGuitar2 = 7
```

```
    kXInputGuitar3 = 11
```

```
    kXInputUnknown = 0
```

```
    kXInputWheel = 2
```

```
class GenericHID.Hand
```

```
    Bases: object
```

Which hand the Human Interface Device is associated with.

```
    kLeft = 0
```

```
        Left Hand
```

```
    kRight = 1
```

```
        Right Hand
```

```
class GenericHID.RumbleType
```

```
    Bases: object
```

Represents a rumble output on the JoyStick.

```
    kLeftRumble = 0
```

```
        Left Hand
```

```
    kRightRumble = 1
```

```
        Right Hand
```

```
GenericHID.getName ()
```

```
    Get the name of the HID.
```

```
    Returns the name of the HID.
```

```
GenericHID.getPOV (pov=0)
```

```
    Get the angle in degrees of a POV on the HID.
```

The POV angles start at 0 in the up direction, and increase clockwise (eg right is 90, upper-left is 315).

Parameters **pov** – The index of the POV to read (starting at 0)

Returns the angle of the POV in degrees, or -1 if the POV is not pressed.

`GenericHID.getPOVCount()`

For the current HID, return the number of POVs.

`GenericHID.getPort()`

Get the port number of the HID.

Returns The port number of the HID.

`GenericHID.getRawAxis(which)`

Get the raw axis.

Parameters **which** – index of the axis

Returns the raw value of the selected axis

`GenericHID.getRawButton(button)`

Is the given button pressed.

Parameters **button** – which button number

Returns the angle of the POV in degrees, or -1 if the POV is not pressed.

`GenericHID.getType()`

Get the type of the HID.

Returns the type of the HID.

`GenericHID.getX(hand=None)`

Get the x position of HID.

Parameters **hand** – which hand, left or right

Returns the x position

`GenericHID.getY(hand=None)`

Get the y position of the HID.

Parameters **hand** – which hand, left or right

Returns the y position

`GenericHID.setOutput(outputNumber, value)`

Set a single HID output value for the HID.

Parameters

- **outputNumber** – The index of the output to set (1-32)
- **value** – The value to set the output to

`GenericHID.setOutputs(value)`

Set all HID output values for the HID.

Parameters **value** – The 32 bit output value (1 bit for each output)

`GenericHID.setRumble(type, value)`

Set the rumble output for the HID. The DS currently supports 2 rumble values, left rumble and right rumble.

Parameters

- **type** – Which rumble value to set
- **value** – The normalized value (0 to 1) to set the rumble to

Gyro

class `wpiilib.interfaces.Gyro`

Bases: `object`

Interface for yaw rate gyros

calibrate ()

Calibrate the gyro by running for a number of samples and computing the center value. Then use the center value as the Accumulator center value for subsequent measurements.

It's important to make sure that the robot is not moving while the centering calculations are in progress, this is typically done when the robot is first turned on while it's sitting at rest before the competition starts.

Note: Usually you don't need to call this, as it's called when the object is first created. If you do, it will freeze your robot for 5 seconds

free ()

Free the resources used by the gyro

getAngle ()

Return the actual angle in degrees that the robot is currently facing.

The angle is based on the current accumulator value corrected by the oversampling rate, the gyro type and the A/D calibration values. The angle is continuous, that is it will continue from 360 to 361 degrees. This allows algorithms that wouldn't want to see a discontinuity in the gyro output as it sweeps past from 360 to 0 on the second time around.

Returns the current heading of the robot in degrees. This heading is based on integration of the returned rate from the gyro.

getRate ()

Return the rate of rotation of the gyro

The rate is based on the most recent reading of the gyro analog value

Returns the current rate in degrees per second

reset ()

Reset the gyro. Resets the gyro to a heading of zero. This can be used if there is significant drift in the gyro and it needs to be recalibrated after it has been running.

NamedSendable

class `wpiilib.interfaces.NamedSendable`

Bases: `wpiilib.Sendable`

The interface for sendable objects that gives the sendable a default name in the Smart Dashboard.

getName ()

Returns The name of the subtable of SmartDashboard that the `Sendable` object will use

PIDInterface

class `wpiilib.interfaces.PIDInterface`

Bases: `wpiilib.interfaces.Controller`

```

disable ()
enable ()
getD ()
getError ()
getI ()
getP ()
getSetpoint ()
isEnabled ()
reset ()
setPID (p, i, d)
setSetpoint (setpoint)

```

PIDOutput

class `wpiplib.interfaces.PIDOutput`

Bases: `object`

This interface allows `PIDController` to write its results to its output.

pidWrite (*output*)

Set the output to the value calculated by `PIDController`.

Parameters `output` – the value calculated by `PIDController`

PIDSource

class `wpiplib.interfaces.PIDSource`

Bases: `object`

This interface allows for `PIDController` to automatically read from this object.

class `PIDSourceType`

Bases: `object`

A description for the type of output value to provide to a `PIDController`

kDisplacement = 0

kRate = 1

static `PIDSource.from_obj_or_callable` (*objc*)

Utility method that gets a `PIDSource` object

Parameters `objc` – An object that implements the `PIDSource` interface, or a callable

Returns an object that implements the `PIDSource` interface

`PIDSource.getPIDSourceType` ()

Get which parameter of the device you are using as a process control variable.

Returns the currently selected PID source parameter

`PIDSource.pidGet()`

Get the result to use in `PIDController`

Returns the result to use in `PIDController`

`PIDSource.setPIDSourceType(pidSource)`

Set which parameter of the device you are using as a process control variable.

Parameters `pidSource` (`PIDSourceType`) – An enum to select the parameter.

Potentiometer

`class wpilib.interfaces.Potentiometer`

Bases: `wpilib.interfaces.PIDSource`

`get()`

SpeedController

`class wpilib.interfaces.SpeedController`

Bases: `wpilib.interfaces.PIDOutput`

Interface for speed controlling devices.

`disable()`

Disable the speed controller.

`get()`

Common interface for getting the current set speed of a speed controller.

Returns The current set speed. Value is between -1.0 and 1.0.

`getInverted()`

Common interface for determining if a speed controller is in the inverted state or not.

Returns True if in inverted state

`set(speed)`

Common interface for setting the speed of a speed controller.

Parameters `speed` – The speed to set. Value should be between -1.0 and 1.0.

`setInverted(isInverted)`

Common interface for inverting direction of a speed controller.

Parameters `isInverted` – The state of inversion

`stopMotor()`

Stops motor movement. Motor can be moved again by calling `set` without having to re-enable the motor.

CHAPTER 2

Indices and tables

- `genindex`
- `modindex`
- `search`

W

- wpilib, 3
- wpilib.adxl345_i2c, 5
- wpilib.adxl345_spi, 7
- wpilib.adxl362, 8
- wpilib.adxrs450_gyro, 10
- wpilib.analogaccelerometer, 11
- wpilib.analoggyro, 12
- wpilib.analoginput, 13
- wpilib.analogoutput, 16
- wpilib.analogpotentiometer, 17
- wpilib.analogtrigger, 18
- wpilib.analogtriggeroutput, 19
- wpilib.builtinaccelerometer, 20
- wpilib.buttons, 106
- wpilib.buttons.button, 106
- wpilib.buttons.internalbutton, 107
- wpilib.buttons.joystickbutton, 107
- wpilib.buttons.networkbutton, 107
- wpilib.buttons.trigger, 107
- wpilib.cameraserver, 21
- wpilib.canjaguar, 21
- wpilib.cantalon, 21
- wpilib.command, 108
- wpilib.command.command, 109
- wpilib.command.commandgroup, 112
- wpilib.command.conditionalcommand, 114
- wpilib.command.instantcommand, 114
- wpilib.command.pidcommand, 115
- wpilib.command.pidsubsystem, 116
- wpilib.command.printcommand, 118
- wpilib.command.scheduler, 118
- wpilib.command.startcommand, 119
- wpilib.command.subsystem, 119
- wpilib.command.timedcommand, 120
- wpilib.command.waitcommand, 120
- wpilib.command.waitforchildren, 121
- wpilib.command.waituntilcommand, 121
- wpilib.compressor, 22
- wpilib.controllerpower, 23
- wpilib.counter, 25
- wpilib.digitalglitchfilter, 30
- wpilib.digitalinput, 31
- wpilib.digitaloutput, 31
- wpilib.digitalsource, 33
- wpilib.doublesolenoid, 33
- wpilib.driverstation, 34
- wpilib.encoder, 38
- wpilib.filter, 42
- wpilib.geartooth, 42
- wpilib.gyrobase, 43
- wpilib.i2c, 43
- wpilib.interfaces, 121
- wpilib.interfaces.accelerometer, 122
- wpilib.interfaces.controller, 122
- wpilib.interfaces.counterbase, 123
- wpilib.interfaces.gamepadbase, 46
- wpilib.interfaces.generichid, 46
- wpilib.interfaces.gyro, 126
- wpilib.interfaces.namesendable, 126
- wpilib.interfaces.pidinterface, 126
- wpilib.interfaces.pidoutput, 127
- wpilib.interfaces.pidsource, 127
- wpilib.interfaces.potentiometer, 128
- wpilib.interfaces.speedcontroller, 128
- wpilib.interruptablesensorbase, 48
- wpilib.iterativerobot, 49
- wpilib.jaguar, 52
- wpilib.joystick, 52
- wpilib.lineardigitalfilter, 56
- wpilib.livewindow, 58
- wpilib.livewindowsendable, 60
- wpilib.motorsafety, 60
- wpilib.pidcontroller, 61
- wpilib.powerdistributionpanel, 65
- wpilib.preferences, 66
- wpilib.pwm, 68
- wpilib.pwmspeedcontroller, 71
- wpilib.relay, 72

wpilib.resource, 73
wpilib.robotbase, 74
wpilib.robotdrive, 75
wpilib.robotstate, 79
wpilib.safepwm, 80
wpilib.samplerobot, 80
wpilib.sd540, 82
wpilib.sendable, 82
wpilib.sendablechooser, 82
wpilib.sensorbase, 83
wpilib.servo, 85
wpilib.smartdashboard, 86
wpilib.solenoid, 92
wpilib.solenoidbase, 93
wpilib.spark, 94
wpilib.spi, 94
wpilib.talon, 97
wpilib.talonsrx, 98
wpilib.timer, 98
wpilib.ultrasonic, 100
wpilib.utility, 102
wpilib.victor, 103
wpilib.victorsp, 103
wpilib.xboxcontroller, 104

A

- AbsoluteTolerance_onTarget() (wpilib.pidcontroller.PIDController method), 62
 Accelerometer (class in wpilib.interfaces.accelerometer), 122
 Accelerometer.Range (class in wpilib.interfaces.accelerometer), 122
 add() (wpilib.command.scheduler.Scheduler method), 118
 add() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
 addActuator() (wpilib.livewindow.LiveWindow static method), 58
 addActuatorChannel() (wpilib.livewindow.LiveWindow static method), 58
 addActuatorModuleChannel() (wpilib.livewindow.LiveWindow static method), 59
 addButton() (wpilib.command.scheduler.Scheduler method), 118
 addDefault() (wpilib.sendablechooser.SendableChooser method), 83
 addObject() (wpilib.sendablechooser.SendableChooser method), 83
 addParallel() (wpilib.command.commandgroup.CommandGroup method), 113
 addressOnly() (wpilib.i2c.I2C method), 44
 addSensor() (wpilib.livewindow.LiveWindow static method), 59
 addSensorChannel() (wpilib.livewindow.LiveWindow static method), 59
 addSequential() (wpilib.command.commandgroup.CommandGroup method), 113
 ADXL345_I2C (class in wpilib.adxl345_i2c), 5
 ADXL345_I2C.Axes (class in wpilib.adxl345_i2c), 5
 ADXL345_I2C.Range (class in wpilib.adxl345_i2c), 6
 ADXL345_SPI (class in wpilib.adxl345_spi), 7
 ADXL345_SPI.Axes (class in wpilib.adxl345_spi), 7
 ADXL345_SPI.Range (class in wpilib.adxl345_spi), 7
 ADXL362 (class in wpilib.adxl362), 8
 ADXL362.Axes (class in wpilib.adxl362), 8
 ADXL362.Range (class in wpilib.adxl362), 8
 ADXRS450_Gyro (class in wpilib.adxrs450_gyro), 10
 allocate() (wpilib.resource.Resource method), 73
 allocatedDownSource (wpilib.counter.Counter attribute), 26
 allocatedUpSource (wpilib.counter.Counter attribute), 26
 allocateInterrupts() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 48
 AnalogAccelerometer (class in wpilib.analogaccelerometer), 11
 AnalogAccelerometer.PIDSourceType (class in wpilib.analogaccelerometer), 11
 AnalogGyro (class in wpilib.analoggyro), 12
 AnalogGyro.PIDSourceType (class in wpilib.analoggyro), 12
 AnalogInput (class in wpilib.analoginput), 13
 AnalogInput.PIDSourceType (class in wpilib.analoginput), 13
 AnalogOutput (class in wpilib.analogoutput), 16
 AnalogPotentiometer (class in wpilib.analogpotentiometer), 17
 AnalogPotentiometer.PIDSourceType (class in wpilib.analogpotentiometer), 17
 AnalogTrigger (class in wpilib.analogtrigger), 18
 AnalogTrigger.AnalogTriggerType (class in wpilib.analogtrigger), 18
 AnalogTriggerOutput (class in wpilib.analogtriggeroutput), 19
 AnalogTriggerOutput.AnalogTriggerType (class in wpilib.analogtriggeroutput), 19
 arcadeDrive() (wpilib.robotdrive.RobotDrive method), 76
 automaticEnabled (wpilib.ultrasonic.Ultrasonic attribute), 100
 autonomous() (wpilib.samplerobot.SampleRobot method), 80
 autonomousInit() (wpilib.iterativerobot.IterativeRobot method), 50

autonomousPeriodic() (wpilib.iterativerobot.IterativeRobot method), 50

B

Blue (wpilib.driverstation.DriverStation.Alliance attribute), 35

BRANCH_CHILD (wpilib.command.commandgroup.CommandGroup attribute), 113

BRANCH_PEER (wpilib.command.commandgroup.CommandGroup attribute), 113

BuiltInAccelerometer (class in wpilib.builtinaccelerometer), 20

BuiltInAccelerometer.Range (class in wpilib.builtinaccelerometer), 20

Button (class in wpilib.buttons.button), 106

C

calculateFeedForward() (wpilib.pidcontroller.PIDController method), 62

calibrate() (wpilib.adxrs450_gyro.ADXRS450_Gyro method), 10

calibrate() (wpilib.analoggyro.AnalogGyro method), 12

calibrate() (wpilib.gyrobase.GyroBase method), 43

calibrate() (wpilib.interfaces.gyro.Gyro method), 126

CameraServer (class in wpilib.cameraserver), 21

cancel() (wpilib.command.command.Command method), 109

cancelConflicts() (wpilib.command.commandgroup.CommandGroup method), 113

cancelInterrupts() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 48

cancelWhenActive() (wpilib.buttons.trigger.Trigger method), 107

cancelWhenPressed() (wpilib.buttons.button.Button method), 106

CANJaguar (class in wpilib.canjaguar), 21

CANTalon (class in wpilib.cantalon), 21

channels (wpilib.analoginput.AnalogInput attribute), 14

channels (wpilib.analogoutput.AnalogOutput attribute), 16

channels (wpilib.digitalsource.DigitalSource attribute), 33

check() (wpilib.motorsafety.MotorSafety method), 60

checkAnalogInputChannel() (wpilib.sensorbase.SensorBase static method), 83

checkAnalogOutputChannel() (wpilib.sensorbase.SensorBase static method), 83

checkDigitalChannel() (wpilib.sensorbase.SensorBase static method), 83

checkMotors() (wpilib.motorsafety.MotorSafety static method), 60

checkPDPChannel() (wpilib.sensorbase.SensorBase static method), 83

checkPDPModule() (wpilib.sensorbase.SensorBase static method), 84

checkPWMChannel() (wpilib.sensorbase.SensorBase static method), 84

checkRelayChannel() (wpilib.sensorbase.SensorBase static method), 84

checkSolenoidChannel() (wpilib.sensorbase.SensorBase static method), 84

checkSolenoidModule() (wpilib.sensorbase.SensorBase static method), 84

clearAllPCMStickyFaults() (wpilib.compressor.Compressor method), 22

clearAllPCMStickyFaults() (wpilib.solenoidbase.SolenoidBase method), 93

clearDownSource() (wpilib.counter.Counter method), 26

clearFlags() (wpilib.smartdashboard.SmartDashboard class method), 86

clearPersistent() (wpilib.smartdashboard.SmartDashboard class method), 86

clearRequirements() (wpilib.command.command.Command method), 110

clearStickyFaults() (wpilib.powerdistributionpanel.PowerDistributionPanel method), 65

clearUpSource() (wpilib.counter.Counter method), 26

Command (class in wpilib.command.command), 109

CommandGroup (class in wpilib.command.commandgroup), 112

CommandGroup.Entry (class in wpilib.command.commandgroup), 113

components (wpilib.livewindow.LiveWindow attribute), 59

Compressor (class in wpilib.compressor), 22

condition() (wpilib.command.conditionalcommand.ConditionalCommand method), 114

ConditionalCommand (class in wpilib.command.conditionalcommand), 114

confirmCommand() (wpilib.command.subsystem.Subsystem method), 120

containsKey() (wpilib.preferences.Preferences method), 66

containsKey() (wpilib.smartdashboard.SmartDashboard class method), 86

Controller (class in wpilib.interfaces.controller), 122

ControllerPower (class in wpilib.controllerpower), 23

Counter (class in wpilib.counter), 25

counter (wpilib.counter.Counter attribute), 26

Counter.EncodingType (class in wpilib.counter), 26

Counter.Mode (class in wpilib.counter), 26

Counter.PIDSourceType (class in wpilib.counter), 26

CounterBase (class in wpilib.interfaces.counterbase), 123

CounterBase.EncodingType (class in wpilib.interfaces.counterbase), 123

createOutput() (wpilib.analogtrigger.AnalogTrigger method), 18

D

DEFAULT (wpilib.sendablechooser.SendableChooser attribute), 83

DEFAULT_SAFETY_EXPIRATION (wpilib.motorsafety.MotorSafety attribute), 60

defaultSolenoidModule (wpilib.sensorbase.SensorBase attribute), 84

delay() (wpilib.timer.Timer static method), 98

delete() (wpilib.smartdashboard.SmartDashboard class method), 86

devices (wpilib.spi.SPI attribute), 95

DigitalGlitchFilter (class in wpilib.digitalglitchfilter), 30

DigitalInput (class in wpilib.digitalinput), 31

DigitalOutput (class in wpilib.digitaloutput), 31

DigitalSource (class in wpilib.digitalsource), 33

disable() (wpilib.command.pidsubsystem.PIDSubsystem method), 116

disable() (wpilib.command.scheduler.Scheduler method), 118

disable() (wpilib.interfaces.controller.Controller method), 122

disable() (wpilib.interfaces.pidinterface.PIDInterface method), 126

disable() (wpilib.interfaces.speedcontroller.SpeedController method), 128

disable() (wpilib.pidcontroller.PIDController method), 62

disable() (wpilib.safe_pwm.SafePWM method), 80

disabled() (wpilib.samplerobot.SampleRobot method), 80

disabledInit() (wpilib.iterativerobot.IterativeRobot method), 50

disabledPeriodic() (wpilib.iterativerobot.IterativeRobot method), 50

disableInterrupts() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 48

disablePWM() (wpilib.digitaloutput.DigitalOutput method), 32

doesRequire() (wpilib.command.command.Command method), 110

DoubleSolenoid (class in wpilib.doublesolenoid), 33

DoubleSolenoid.Value (class in wpilib.doublesolenoid), 34

drive() (wpilib.robotdrive.RobotDrive method), 76

DriverStation (class in wpilib.driverstation), 34

DriverStation.Alliance (class in wpilib.driverstation), 35

E

enable() (wpilib.command.pidsubsystem.PIDSubsystem method), 116

enable() (wpilib.command.scheduler.Scheduler method), 118

enable() (wpilib.interfaces.controller.Controller method), 122

enable() (wpilib.interfaces.pidinterface.PIDInterface method), 127

enable() (wpilib.pidcontroller.PIDController method), 62

enabled() (wpilib.compressor.Compressor method), 22

enableDeadbandElimination() (wpilib.pwm.PWM method), 69

enableDirectionSensing() (wpilib.geartooth.GearTooth method), 43

enableInterrupts() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 48

enablePWM() (wpilib.digitaloutput.DigitalOutput method), 32

Encoder (class in wpilib.encoder), 38

encoder (wpilib.encoder.Encoder attribute), 40

Encoder.EncodingType (class in wpilib.encoder), 39

Encoder.IndexingType (class in wpilib.encoder), 40

Encoder.PIDSourceType (class in wpilib.encoder), 40

end() (wpilib.command.command.Command method), 110

end() (wpilib.command.commandgroup.CommandGroup method), 113

execute() (wpilib.command.command.Command method), 110

execute() (wpilib.command.commandgroup.CommandGroup method), 113

F

feed() (wpilib.motorsafety.MotorSafety method), 60

Filter (class in wpilib.filter), 42

filterAllocated (wpilib.digitalglitchfilter.DigitalGlitchFilter attribute), 30

firstTime (wpilib.livewindow.LiveWindow attribute), 59

flush_outputs() (wpilib.joystick.Joystick method), 52

forwardHandle (wpilib.relay.Relay attribute), 72

FreeBasedADXL345_I2C (wpilib.adxl345_i2c.ADXL345_I2C method), 6

free() (wpilib.adxl345_spi.ADXL345_SPI method), 7

free() (wpilib.adxl362.ADXL362 method), 9

free() (wpilib.adxrs450_gyro.ADXRS450_Gyro method), 10

free() (wpilib.analogaccelerometer.AnalogAccelerometer method), 11

free() (wpilib.analoggyro.AnalogGyro method), 12

free() (wpilib.analoginput.AnalogInput method), 14

free() (wpilib.analogoutput.AnalogOutput method), 16

free() (wpilib.analogpotentiometer.AnalogPotentiometer method), 17

free() (wpilib.analogtrigger.AnalogTrigger method), 18

free() (wpilib.analogtriggeroutput.AnalogTriggerOutput method), 20

- free() (wpilib.builtinaccelerometer.BuiltInAccelerometer method), 20
 - free() (wpilib.counter.Counter method), 26
 - free() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
 - free() (wpilib.digitalinput.DigitalInput method), 31
 - free() (wpilib.digitaloutput.DigitalOutput method), 32
 - free() (wpilib.digitalsource.DigitalSource method), 33
 - free() (wpilib.doublesolenoid.DoubleSolenoid method), 34
 - free() (wpilib.encoder.Encoder method), 40
 - free() (wpilib.geartooth.GearTooth method), 43
 - free() (wpilib.i2c.I2C method), 44
 - free() (wpilib.interfaces.gyro.Gyro method), 126
 - free() (wpilib.pidcontroller.PIDController method), 62
 - free() (wpilib.pwm.PWM method), 69
 - free() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
 - free() (wpilib.relay.Relay method), 72
 - free() (wpilib.resource.Resource method), 74
 - free() (wpilib.robotbase.RobotBase method), 74
 - free() (wpilib.robotdrive.RobotDrive method), 77
 - free() (wpilib.sensorbase.SensorBase method), 84
 - free() (wpilib.servo.Servo method), 85
 - free() (wpilib.solenoid.Solenoid method), 93
 - free() (wpilib.spi.SPI method), 95
 - free() (wpilib.ultrasonic.Ultrasonic method), 100
 - freeAccumulator() (wpilib.spi.SPI method), 95
 - from_obj_or_callable() (wpilib.interfaces.pidsource.PIDSource static method), 127
- ## G
- GamepadBase (class in wpilib.interfaces.gamepadbase), 46
 - GearTooth (class in wpilib.geartooth), 42
 - GenericHID (class in wpilib.interfaces.generichid), 46, 123
 - GenericHID.Hand (class in wpilib.interfaces.generichid), 47, 124
 - GenericHID.HIDType (class in wpilib.interfaces.generichid), 46, 123
 - GenericHID.RumbleType (class in wpilib.interfaces.generichid), 47, 124
 - get() (wpilib.analogpotentiometer.AnalogPotentiometer method), 17
 - get() (wpilib.analogtriggeroutput.AnalogTriggerOutput method), 20
 - get() (wpilib.buttons.internalbutton.InternalButton method), 107
 - get() (wpilib.buttons.joystickbutton.JoystickButton method), 107
 - get() (wpilib.buttons.networkbutton.NetworkButton method), 107
 - get() (wpilib.buttons.trigger.Trigger method), 108
 - get() (wpilib.counter.Counter method), 26
 - get() (wpilib.digitalinput.DigitalInput method), 31
 - get() (wpilib.digitaloutput.DigitalOutput method), 32
 - get() (wpilib.doublesolenoid.DoubleSolenoid method), 34
 - get() (wpilib.encoder.Encoder method), 40
 - get() (wpilib.filter.Filter method), 42
 - get() (wpilib.interfaces.counterbase.CounterBase method), 123
 - get() (wpilib.interfaces.potentiometer.Potentiometer method), 128
 - get() (wpilib.interfaces.speedcontroller.SpeedController method), 128
 - get() (wpilib.lineardigitalfilter.LinearDigitalFilter method), 57
 - get() (wpilib.pidcontroller.PIDController method), 62
 - get() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
 - get() (wpilib.relay.Relay method), 72
 - get() (wpilib.servo.Servo method), 85
 - get() (wpilib.solenoid.Solenoid method), 93
 - get() (wpilib.timer.Timer method), 98
 - getAButton() (wpilib.xboxcontroller.XboxController method), 104
 - getAcceleration() (wpilib.adx1345_i2c.ADXL345_I2C method), 6
 - getAcceleration() (wpilib.adx1345_spi.ADXL345_SPI method), 7
 - getAcceleration() (wpilib.adx1362.ADXL362 method), 9
 - getAcceleration() (wpilib.analogaccelerometer.AnalogAccelerometer method), 11
 - getAccelerations() (wpilib.adx1345_i2c.ADXL345_I2C method), 6
 - getAccelerations() (wpilib.adx1345_spi.ADXL345_SPI method), 7
 - getAccelerations() (wpilib.adx1362.ADXL362 method), 9
 - getAccumulatorAverage() (wpilib.spi.SPI method), 95
 - getAccumulatorCount() (wpilib.analoginput.AnalogInput method), 14
 - getAccumulatorCount() (wpilib.spi.SPI method), 95
 - getAccumulatorLastValue() (wpilib.spi.SPI method), 95
 - getAccumulatorOutput() (wpilib.analoginput.AnalogInput method), 14
 - getAccumulatorOutput() (wpilib.spi.SPI method), 95
 - getAccumulatorValue() (wpilib.analoginput.AnalogInput method), 14
 - getAccumulatorValue() (wpilib.spi.SPI method), 95
 - getAll() (wpilib.solenoidbase.SolenoidBase method), 93
 - getAlliance() (wpilib.driverstation.DriverStation method), 35
 - getAnalogTriggerTypeForRouting() (wpilib.analogtriggeroutput.AnalogTriggerOutput method), 20
 - getAnalogTriggerTypeForRouting()

(wpilib.digitalinput.DigitalInput method), 31
 getAnalogTriggerTypeForRouting() (wpilib.digitaloutput.DigitalOutput method), 32
 getAnalogTriggerTypeForRouting() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
 getAngle() (wpilib.adxrs450_gyro.ADXRS450_Gyro method), 10
 getAngle() (wpilib.analoggyro.AnalogGyro method), 12
 getAngle() (wpilib.gyrobase.GyroBase method), 43
 getAngle() (wpilib.interfaces.gyro.Gyro method), 126
 getAngle() (wpilib.servo.Servo method), 85
 getAverageBits() (wpilib.analoginput.AnalogInput method), 14
 getAverageValue() (wpilib.analoginput.AnalogInput method), 14
 getAverageVoltage() (wpilib.analoginput.AnalogInput method), 14
 getAvgError() (wpilib.pidcontroller.PIDController method), 62
 getAxis() (wpilib.joystick.Joystick method), 53
 getAxisChannel() (wpilib.joystick.Joystick method), 53
 getAxisCount() (wpilib.joystick.Joystick method), 53
 getAxisType() (wpilib.joystick.Joystick method), 53
 getBackButton() (wpilib.xboxcontroller.XboxController method), 104
 getBatteryVoltage() (wpilib.driverstation.DriverStation method), 35
 getBButton() (wpilib.xboxcontroller.XboxController method), 104
 getBoolean() (wpilib.preferences.Preferences method), 66
 getBoolean() (wpilib.smartdashboard.SmartDashboard class method), 86
 getBooleanArray() (wpilib.smartdashboard.SmartDashboard class method), 87
 getBumper() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
 getBumper() (wpilib.joystick.Joystick method), 53
 getBumper() (wpilib.xboxcontroller.XboxController method), 104
 getButton() (wpilib.joystick.Joystick method), 53
 getButtonCount() (wpilib.joystick.Joystick method), 53
 getCenter() (wpilib.analoggyro.AnalogGyro method), 13
 getChannel() (wpilib.analoginput.AnalogInput method), 14
 getChannel() (wpilib.analogoutput.AnalogOutput method), 16
 getChannel() (wpilib.analogtriggeroutput.AnalogTriggerOutput method), 20
 getChannel() (wpilib.digitalinput.DigitalInput method), 31
 getChannel() (wpilib.digitaloutput.DigitalOutput method), 32
 getChannel() (wpilib.digitalsource.DigitalSource method), 33
 getChannel() (wpilib.pwm.PWM method), 69
 getChannel() (wpilib.relay.Relay method), 73
 getClosedLoopControl() (wpilib.compressor.Compressor method), 22
 getCompressorCurrent() (wpilib.compressor.Compressor method), 22
 getCompressorCurrentTooHighFault() (wpilib.compressor.Compressor method), 22
 getCompressorCurrentTooHighStickyFault() (wpilib.compressor.Compressor method), 22
 getCompressorNotConnectedFault() (wpilib.compressor.Compressor method), 22
 getCompressorNotConnectedStickyFault() (wpilib.compressor.Compressor method), 22
 getCompressorShortedFault() (wpilib.compressor.Compressor method), 23
 getCompressorShortedStickyFault() (wpilib.compressor.Compressor method), 23
 getContinuousError() (wpilib.pidcontroller.PIDController method), 62
 getCurrent() (wpilib.powerdistributionpanel.PowerDistributionPanel method), 65
 getCurrent3V3() (wpilib.controllerpower.ControllerPower static method), 23
 getCurrent5V() (wpilib.controllerpower.ControllerPower static method), 23
 getCurrent6V() (wpilib.controllerpower.ControllerPower static method), 23
 getCurrentCommand() (wpilib.command.subsystem.Subsystem method), 120
 getD() (wpilib.interfaces.pidinterface.PIDInterface method), 127
 getD() (wpilib.pidcontroller.PIDController method), 62
 getData() (wpilib.smartdashboard.SmartDashboard class method), 87
 getDefaultCommand() (wpilib.command.subsystem.Subsystem method), 120
 getDefaultSolenoidModule() (wpilib.sensorbase.SensorBase static method), 84
 getDeltaSetpoint() (wpilib.pidcontroller.PIDController method), 62
 getDescription() (wpilib.relay.Relay method), 73
 getDescription() (wpilib.robotdrive.RobotDrive method),

- 77
- getDescription() (wpilib.safepwm.SafePWM method), 80
 - getDirection() (wpilib.counter.Counter method), 26
 - getDirection() (wpilib.encoder.Encoder method), 40
 - getDirection() (wpilib.interfaces.counterbase.CounterBase method), 123
 - getDirectionDegrees() (wpilib.joystick.Joystick method), 53
 - getDirectionRadians() (wpilib.joystick.Joystick method), 53
 - getDistance() (wpilib.counter.Counter method), 26
 - getDistance() (wpilib.encoder.Encoder method), 40
 - getDistanceUnits() (wpilib.ultrasonic.Ultrasonic method), 100
 - getDouble() (wpilib.smartdashboard.SmartDashboard class method), 87
 - getEnabled3V3() (wpilib.controllerpower.ControllerPower static method), 23
 - getEnabled5V() (wpilib.controllerpower.ControllerPower static method), 24
 - getEnabled6V() (wpilib.controllerpower.ControllerPower static method), 24
 - getEncodingScale() (wpilib.encoder.Encoder method), 40
 - getError() (wpilib.interfaces.pidinterface.PIDInterface method), 127
 - getError() (wpilib.pidcontroller.PIDController method), 63
 - getExpiration() (wpilib.motorsafety.MotorSafety method), 60
 - getF() (wpilib.pidcontroller.PIDController method), 63
 - getFaultCount3V3() (wpilib.controllerpower.ControllerPower static method), 24
 - getFaultCount5V() (wpilib.controllerpower.ControllerPower static method), 24
 - getFaultCount6V() (wpilib.controllerpower.ControllerPower static method), 24
 - getFlags() (wpilib.smartdashboard.SmartDashboard class method), 87
 - getFloat() (wpilib.preferences.Preferences method), 66
 - getFPGAIndex() (wpilib.counter.Counter method), 27
 - getFPGAIndex() (wpilib.encoder.Encoder method), 40
 - getFPGARevision() (wpilib.utility.Utility static method), 102
 - getFPGATime() (wpilib.utility.Utility static method), 102
 - getFPGATimestamp() (wpilib.timer.Timer static method), 99
 - getFPGAVersion() (wpilib.utility.Utility static method), 102
 - getGlobalSampleRate() (wpilib.analoginput.AnalogInput static method), 14
 - getGroup() (wpilib.command.command.Command method), 110
 - getI() (wpilib.interfaces.pidinterface.PIDInterface method), 127
 - getI() (wpilib.pidcontroller.PIDController method), 63
 - getIndex() (wpilib.analogtrigger.AnalogTrigger method), 18
 - getInputCurrent() (wpilib.controllerpower.ControllerPower static method), 24
 - getInputVoltage() (wpilib.controllerpower.ControllerPower static method), 24
 - getInstance() (wpilib.command.scheduler.Scheduler static method), 118
 - getInstance() (wpilib.driverstation.DriverStation class method), 35
 - getInstance() (wpilib.preferences.Preferences static method), 66
 - getInt() (wpilib.preferences.Preferences method), 66
 - getInt() (wpilib.smartdashboard.SmartDashboard class method), 87
 - getInverted() (wpilib.interfaces.speedcontroller.SpeedController method), 128
 - getInverted() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
 - getInWindow() (wpilib.analogtrigger.AnalogTrigger method), 18
 - getIsXbox() (wpilib.joystick.Joystick method), 54
 - getJoystickAxisType() (wpilib.driverstation.DriverStation method), 35
 - getJoystickIsXbox() (wpilib.driverstation.DriverStation method), 35
 - getJoystickName() (wpilib.driverstation.DriverStation method), 35
 - getJoystickType() (wpilib.driverstation.DriverStation method), 36
 - getKeys() (wpilib.preferences.Preferences method), 67
 - getKeys() (wpilib.smartdashboard.SmartDashboard class method), 88
 - getLocation() (wpilib.driverstation.DriverStation method), 36
 - getLSBWeight() (wpilib.analoginput.AnalogInput method), 15
 - getMagnitude() (wpilib.joystick.Joystick method), 54
 - getMatchTime() (wpilib.driverstation.DriverStation method), 36
 - getMatchTime() (wpilib.timer.Timer static method), 99
 - getMsClock() (wpilib.timer.Timer method), 99
 - getName() (wpilib.command.command.Command method), 110
 - getName() (wpilib.command.scheduler.Scheduler method), 118
 - getName() (wpilib.command.subsystem.Subsystem method), 120
 - getName() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
 - getName() (wpilib.interfaces.genericid.GenericHID method), 47, 124
 - getName() (wpilib.interfaces.namedsendable.NamedSendable

- method), 126
- getName() (wpilib.joystick.Joystick method), 54
- getName() (wpilib.xboxcontroller.XboxController method), 104
- getNumber() (wpilib.smartdashboard.SmartDashboard class method), 88
- getNumberArray() (wpilib.smartdashboard.SmartDashboard class method), 88
- getNumMotors() (wpilib.robotdrive.RobotDrive method), 77
- getOffset() (wpilib.analoggyro.AnalogGyro method), 13
- getOffset() (wpilib.analoginput.AnalogInput method), 15
- getOversampleBits() (wpilib.analoginput.AnalogInput method), 15
- getP() (wpilib.interfaces.pidinterface.PIDInterface method), 127
- getP() (wpilib.pidcontroller.PIDController method), 63
- getPCMSolenoidBlackList() (wpilib.solenoidbase.SolenoidBase method), 93
- getPCMSolenoidVoltageFault() (wpilib.solenoidbase.SolenoidBase method), 93
- getPCMSolenoidVoltageStickyFault() (wpilib.solenoidbase.SolenoidBase method), 94
- getPeriod() (wpilib.counter.Counter method), 27
- getPeriod() (wpilib.encoder.Encoder method), 40
- getPeriod() (wpilib.interfaces.counterbase.CounterBase method), 123
- getPeriodCycles() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
- getPeriodNanoSeconds() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
- getPIDController() (wpilib.command.pidcommand.PIDCommand method), 115
- getPIDController() (wpilib.command.pidsubsystem.PIDSubsystem method), 116
- getPIDSourceType() (wpilib.analogaccelerometer.AnalogAccelerometer method), 11
- getPIDSourceType() (wpilib.analoginput.AnalogInput method), 15
- getPIDSourceType() (wpilib.analogpotentiometer.AnalogPotentiometer method), 17
- getPIDSourceType() (wpilib.counter.Counter method), 27
- getPIDSourceType() (wpilib.encoder.Encoder method), 40
- getPIDSourceType() (wpilib.filter.Filter method), 42
- getPIDSourceType() (wpilib.gyrobase.GyroBase method), 43
- getPIDSourceType() (wpilib.interfaces.pidsource.PIDSource method), 127
- getPIDSourceType() (wpilib.pidcontroller.PIDController method), 63
- getPIDSourceType() (wpilib.ultrasonic.Ultrasonic method), 100
- getPort() (wpilib.interfaces.generichid.GenericHID method), 47, 125
- getPortHandleForRouting() (wpilib.analogtriggeroutput.AnalogTriggerOutput method), 20
- getPortHandleForRouting() (wpilib.digitalinput.DigitalInput method), 31
- getPortHandleForRouting() (wpilib.digitaloutput.DigitalOutput method), 32
- getPortHandleForRouting() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
- getPosition() (wpilib.command.pidcommand.PIDCommand method), 115
- getPosition() (wpilib.command.pidsubsystem.PIDSubsystem method), 116
- getPosition() (wpilib.pwm.PWM method), 69
- getPOV() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
- getPOV() (wpilib.interfaces.generichid.GenericHID method), 47, 124
- getPOV() (wpilib.joystick.Joystick method), 54
- getPOV() (wpilib.xboxcontroller.XboxController method), 104
- getPOVCount() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
- getPOVCount() (wpilib.interfaces.generichid.GenericHID method), 47, 125
- getPOVCount() (wpilib.joystick.Joystick method), 54
- getPOVCount() (wpilib.xboxcontroller.XboxController method), 104
- getPressureSwitchValue() (wpilib.compressor.Compressor method), 23
- getRange() (wpilib.ultrasonic.Ultrasonic method), 100
- getRangeMM() (wpilib.ultrasonic.Ultrasonic method), 100
- getRate() (wpilib.adxrs450_gyro.ADXRS450_Gyro method), 10
- getRate() (wpilib.analoggyro.AnalogGyro method), 13
- getRate() (wpilib.counter.Counter method), 27
- getRate() (wpilib.encoder.Encoder method), 40
- getRate() (wpilib.gyrobase.GyroBase method), 43
- getRate() (wpilib.interfaces.gyro.Gyro method), 126
- getRaw() (wpilib.encoder.Encoder method), 41
- getRaw() (wpilib.pwm.PWM method), 69
- getRaw() (wpilib.smartdashboard.SmartDashboard class method), 88

[getRawAxis\(\) \(wpilib.interfaces.gamepadbase.GamepadBase method\), 46](#)
[getRawAxis\(\) \(wpilib.interfaces.generichid.GenericHID method\), 47, 125](#)
[getRawAxis\(\) \(wpilib.joystick.Joystick method\), 54](#)
[getRawAxis\(\) \(wpilib.xboxcontroller.XboxController method\), 104](#)
[getRawBounds\(\) \(wpilib.pwm.PWM method\), 69](#)
[getRawButton\(\) \(wpilib.interfaces.gamepadbase.GamepadBase method\), 46](#)
[getRawButton\(\) \(wpilib.interfaces.generichid.GenericHID method\), 47, 125](#)
[getRawButton\(\) \(wpilib.joystick.Joystick method\), 54](#)
[getRawButton\(\) \(wpilib.xboxcontroller.XboxController method\), 104](#)
[getRequirements\(\) \(wpilib.command.command.Command method\), 110](#)
[getSamplesToAverage\(\) \(wpilib.counter.Counter method\), 27](#)
[getSamplesToAverage\(\) \(wpilib.encoder.Encoder method\), 41](#)
[getSelected\(\) \(wpilib.sendablechooser.SendableChooser method\), 83](#)
[getServoAngleRange\(\) \(wpilib.servo.Servo method\), 85](#)
[getSetpoint\(\) \(wpilib.command.pidcommand.PIDCommand method\), 115](#)
[getSetpoint\(\) \(wpilib.command.pidsubsystem.PIDSubsystem method\), 116](#)
[getSetpoint\(\) \(wpilib.interfaces.pidinterface.PIDInterface method\), 127](#)
[getSetpoint\(\) \(wpilib.pidcontroller.PIDController method\), 63](#)
[getSpeed\(\) \(wpilib.pwm.PWM method\), 69](#)
[getStartButton\(\) \(wpilib.xboxcontroller.XboxController method\), 104](#)
[getStickAxis\(\) \(wpilib.driverstation.DriverStation method\), 36](#)
[getStickAxisCount\(\) \(wpilib.driverstation.DriverStation method\), 36](#)
[getStickButton\(\) \(wpilib.driverstation.DriverStation method\), 36](#)
[getStickButton\(\) \(wpilib.interfaces.gamepadbase.GamepadBase method\), 46](#)
[getStickButton\(\) \(wpilib.xboxcontroller.XboxController method\), 105](#)
[getStickButtonCount\(\) \(wpilib.driverstation.DriverStation method\), 36](#)
[getStickButtons\(\) \(wpilib.driverstation.DriverStation method\), 37](#)
[getStickPOV\(\) \(wpilib.driverstation.DriverStation method\), 37](#)
[getStickPOVCount\(\) \(wpilib.driverstation.DriverStation method\), 37](#)
[getStopped\(\) \(wpilib.counter.Counter method\), 27](#)
[getStopped\(\) \(wpilib.encoder.Encoder method\), 41](#)
[getStopped\(\) \(wpilib.interfaces.counterbase.CounterBase method\), 123](#)
[getString\(\) \(wpilib.preferences.Preferences method\), 67](#)
[getString\(\) \(wpilib.smartdashboard.SmartDashboard class method\), 88](#)
[getStringArray\(\) \(wpilib.smartdashboard.SmartDashboard class method\), 89](#)
[getTemperature\(\) \(wpilib.powerdistributionpanel.PowerDistributionPanel method\), 65](#)
[getThrottle\(\) \(wpilib.joystick.Joystick method\), 54](#)
[getTop\(\) \(wpilib.joystick.Joystick method\), 54](#)
[getTotalCurrent\(\) \(wpilib.powerdistributionpanel.PowerDistributionPanel method\), 65](#)
[getTotalEnergy\(\) \(wpilib.powerdistributionpanel.PowerDistributionPanel method\), 65](#)
[getTotalPower\(\) \(wpilib.powerdistributionpanel.PowerDistributionPanel method\), 65](#)
[getTrigger\(\) \(wpilib.joystick.Joystick method\), 55](#)
[getTriggerAxis\(\) \(wpilib.xboxcontroller.XboxController method\), 105](#)
[getTriggerState\(\) \(wpilib.analogtrigger.AnalogTrigger method\), 18](#)
[getTwist\(\) \(wpilib.joystick.Joystick method\), 55](#)
[getType\(\) \(wpilib.command.scheduler.Scheduler method\), 118](#)
[getType\(\) \(wpilib.interfaces.gamepadbase.GamepadBase method\), 46](#)
[getType\(\) \(wpilib.interfaces.generichid.GenericHID method\), 47, 125](#)
[getType\(\) \(wpilib.joystick.Joystick method\), 55](#)
[getType\(\) \(wpilib.xboxcontroller.XboxController method\), 105](#)
[getUserButton\(\) \(wpilib.utility.Utility static method\), 102](#)
[getValue\(\) \(wpilib.analoginput.AnalogInput method\), 15](#)
[getVoltage\(\) \(wpilib.analoginput.AnalogInput method\), 15](#)
[getVoltage\(\) \(wpilib.analogoutput.AnalogOutput method\), 16](#)
[getVoltage\(\) \(wpilib.powerdistributionpanel.PowerDistributionPanel method\), 65](#)
[getVoltage3V3\(\) \(wpilib.controllerpower.ControllerPower static method\), 24](#)
[getVoltage5V\(\) \(wpilib.controllerpower.ControllerPower static method\), 24](#)
[getVoltage6V\(\) \(wpilib.controllerpower.ControllerPower static method\), 25](#)
[getX\(\) \(wpilib.adxl345_i2c.ADXL345_I2C method\), 6](#)
[getX\(\) \(wpilib.adxl345_spi.ADXL345_SPI method\), 7](#)
[getX\(\) \(wpilib.adxl362.ADXL362 method\), 9](#)
[getX\(\) \(wpilib.builtinaccelerometer.BuiltInAccelerometer method\), 20](#)
[getX\(\) \(wpilib.interfaces.accelerometer.Accelerometer method\), 122](#)

- [getX\(\)](#) (wpilib.interfaces.genericid.GenericHID method), 48, 125
[getX\(\)](#) (wpilib.joystick.Joystick method), 55
[getX\(\)](#) (wpilib.xboxcontroller.XboxController method), 105
[getXButton\(\)](#) (wpilib.xboxcontroller.XboxController method), 105
[getY\(\)](#) (wpilib.adxl345_i2c.ADXL345_I2C method), 6
[getY\(\)](#) (wpilib.adxl345_spi.ADXL345_SPI method), 7
[getY\(\)](#) (wpilib.adxl362.ADXL362 method), 9
[getY\(\)](#) (wpilib.builtinaccelerometer.BuiltInAccelerometer method), 20
[getY\(\)](#) (wpilib.interfaces.accelerometer.Accelerometer method), 122
[getY\(\)](#) (wpilib.interfaces.genericid.GenericHID method), 48, 125
[getY\(\)](#) (wpilib.joystick.Joystick method), 55
[getY\(\)](#) (wpilib.xboxcontroller.XboxController method), 105
[getYButton\(\)](#) (wpilib.xboxcontroller.XboxController method), 105
[getZ\(\)](#) (wpilib.adxl345_i2c.ADXL345_I2C method), 6
[getZ\(\)](#) (wpilib.adxl345_spi.ADXL345_SPI method), 8
[getZ\(\)](#) (wpilib.adxl362.ADXL362 method), 9
[getZ\(\)](#) (wpilib.builtinaccelerometer.BuiltInAccelerometer method), 20
[getZ\(\)](#) (wpilib.interfaces.accelerometer.Accelerometer method), 122
[getZ\(\)](#) (wpilib.joystick.Joystick method), 55
[grab\(\)](#) (wpilib.buttons.trigger.Trigger method), 108
[Gyro](#) (class in wpilib.interfaces.gyro), 126
[GyroBase](#) (class in wpilib.gyrobase), 43
[GyroBase.PIDSourceType](#) (class in wpilib.gyrobase), 43
- ## H
- [handle](#) (wpilib.digitalsource.DigitalSource attribute), 33
[handle](#) (wpilib.pwm.PWM attribute), 70
[hasPeriodPassed\(\)](#) (wpilib.timer.Timer method), 99
[helpers](#) (wpilib.motorsafety.MotorSafety attribute), 60
[helpers_lock](#) (wpilib.motorsafety.MotorSafety attribute), 60
[highPass\(\)](#) (wpilib.lineardigitalfilter.LinearDigitalFilter static method), 57
[holonomicDrive\(\)](#) (wpilib.robotdrive.RobotDrive method), 77
- ## I
- [I2C](#) (class in wpilib.i2c), 43
[I2C.Port](#) (class in wpilib.i2c), 44
[impl](#) (wpilib.robotstate.RobotState attribute), 79
[IN_SEQUENCE](#) (wpilib.command.commandgroup.CommandGroup attribute), 113
[InAutonomous\(\)](#) (wpilib.driverstation.DriverStation method), 35
[InDisabled\(\)](#) (wpilib.driverstation.DriverStation method), 35
[initAccumulator\(\)](#) (wpilib.analoginput.AnalogInput method), 15
[initAccumulator\(\)](#) (wpilib.spi.SPI method), 95
[initDefaultCommand\(\)](#) (wpilib.command.subsystem.Subsystem method), 120
[initialize\(\)](#) (wpilib.command.command.Command method), 110
[initialize\(\)](#) (wpilib.command.commandgroup.CommandGroup method), 113
[initialize\(\)](#) (wpilib.command.printcommand.PrintCommand method), 118
[initialize\(\)](#) (wpilib.command.startcommand.StartCommand method), 119
[initializeHardwareConfiguration\(\)](#) (wpilib.robotbase.RobotBase static method), 74
[initializeLiveWindowComponents\(\)](#) (wpilib.livewindow.LiveWindow static method), 59
[InOperatorControl\(\)](#) (wpilib.driverstation.DriverStation method), 35
[instances](#) (wpilib.pidcontroller.PIDController attribute), 63
[instances](#) (wpilib.ultrasonic.Ultrasonic attribute), 101
[InstantCommand](#) (class in wpilib.command.instantcommand), 114
[InternalButton](#) (class in wpilib.buttons.internalbutton), 107
[interrupt](#) (wpilib.interruptablesensorbase.InterruptableSensorBase attribute), 49
[InterruptableSensorBase](#) (class in wpilib.interruptablesensorbase), 48
[interrupted\(\)](#) (wpilib.command.command.Command method), 110
[interrupted\(\)](#) (wpilib.command.commandgroup.CommandGroup method), 113
[interrupted\(\)](#) (wpilib.command.conditionalcommand.ConditionalCommand method), 114
[InTest\(\)](#) (wpilib.driverstation.DriverStation method), 35
[Invalid](#) (wpilib.driverstation.DriverStation.Alliance attribute), 35
[is_alive\(\)](#) (wpilib.cameraserver.CameraServer class method), 21
[isAccumulatorChannel\(\)](#) (wpilib.analoginput.AnalogInput method), 15
[isAlive\(\)](#) (wpilib.motorsafety.MotorSafety method), 61
[isAnalogTrigger\(\)](#) (wpilib.digitalinput.DigitalInput method), 31
[isAnalogTrigger\(\)](#) (wpilib.digitaloutput.DigitalOutput method), 32
[isAnalogTrigger\(\)](#) (wpilib.digitalsource.DigitalSource method), 33

- isAutomaticMode() (wpilib.ultrasonic.Ultrasonic static method), 101
- isAutonomous() (wpilib.driverstation.DriverStation method), 37
- isAutonomous() (wpilib.robotbase.RobotBase method), 74
- isAutonomous() (wpilib.robotstate.RobotState static method), 80
- isAvgErrorValid() (wpilib.pidcontroller.PIDController method), 63
- isBlackListed() (wpilib.solenoid.Solenoid method), 93
- isBrownedOut() (wpilib.driverstation.DriverStation method), 37
- isCanceled() (wpilib.command.command.Command method), 110
- isDisabled() (wpilib.driverstation.DriverStation method), 37
- isDisabled() (wpilib.robotbase.RobotBase method), 74
- isDisabled() (wpilib.robotstate.RobotState static method), 80
- isDSAttached() (wpilib.driverstation.DriverStation method), 37
- isEnabled() (wpilib.pidcontroller.PIDController method), 63
- isEnabled() (wpilib.driverstation.DriverStation method), 37
- isEnabled() (wpilib.interfaces.pidinterface.PIDInterface method), 127
- isEnabled() (wpilib.pidcontroller.PIDController method), 63
- isEnabled() (wpilib.robotbase.RobotBase method), 74
- isEnabled() (wpilib.robotstate.RobotState static method), 80
- isEnabled() (wpilib.ultrasonic.Ultrasonic method), 101
- isFinished() (wpilib.command.command.Command method), 110
- isFinished() (wpilib.command.commandgroup.CommandGroup method), 113
- isFinished() (wpilib.command.conditionalcommand.ConditionalCommand method), 114
- isFinished() (wpilib.command.instantcommand.InstantCommand method), 114
- isFinished() (wpilib.command.timedcommand.TimedCommand method), 120
- isFinished() (wpilib.command.waitforchildren.WaitForChildren method), 121
- isFinished() (wpilib.command.waituntilcommand.WaitUntilCommand method), 121
- isFMSAttached() (wpilib.driverstation.DriverStation method), 37
- isFwdSolenoidBlackListed() (wpilib.doublesolenoid.DoubleSolenoid method), 34
- isInterruptible() (wpilib.command.command.Command method), 111
- isInterruptible() (wpilib.command.commandgroup.CommandGroup method), 114
- isNewControlData() (wpilib.driverstation.DriverStation method), 37
- isNewDataAvailable() (wpilib.robotbase.RobotBase method), 74
- isOperatorControl() (wpilib.driverstation.DriverStation method), 37
- isOperatorControl() (wpilib.robotbase.RobotBase method), 75
- isOperatorControl() (wpilib.robotstate.RobotState static method), 80
- isPersistent() (wpilib.smartdashboard.SmartDashboard class method), 89
- isPulsing() (wpilib.digitaloutput.DigitalOutput method), 32
- isRangeValid() (wpilib.ultrasonic.Ultrasonic method), 101
- isReal() (wpilib.robotbase.RobotBase static method), 75
- isRevSolenoidBlackListed() (wpilib.doublesolenoid.DoubleSolenoid method), 34
- isRunning() (wpilib.command.command.Command method), 111
- isSafetyEnabled() (wpilib.motorsafety.MotorSafety method), 61
- isSimulation() (wpilib.robotbase.RobotBase static method), 75
- isSysActive() (wpilib.driverstation.DriverStation method), 38
- isTest() (wpilib.driverstation.DriverStation method), 38
- isTest() (wpilib.robotbase.RobotBase method), 75
- isTest() (wpilib.robotstate.RobotState static method), 80
- isTimedOut() (wpilib.command.command.Command method), 111
- isTimedOut() (wpilib.command.commandgroup.CommandGroup.Entry method), 113
- IterativeRobot (class in wpilib.iterativerobot), 49

J

- Jaguar (class in wpilib.jaguar), 52
- Joystick (class in wpilib.joystick), 52
- Joystick.AxisType (class in wpilib.joystick), 52
- Joystick.ButtonType (class in wpilib.joystick), 52
- JoystickButton (class in wpilib.buttons.joystickbutton), 107

K

- k16G (wpilib.adxl345_i2c.ADXL345_I2C.Range attribute), 6
- k16G (wpilib.adxl345_spi.ADXL345_SPI.Range attribute), 7
- k16G (wpilib.adxl362.ADXL362.Range attribute), 9

- k16G (wpilib.builtinaccelerometer.BuiltInAccelerometer.Range attribute), 20
- k16G (wpilib.interfaces.accelerometer.Accelerometer.Range attribute), 122
- k1X (wpilib.counter.Counter.EncodingType attribute), 26
- k1X (wpilib.encoder.Encoder.EncodingType attribute), 39
- k1X (wpilib.interfaces.counterbase.CounterBase.EncodingType attribute), 123
- k1X (wpilib.pwm.PWM.PeriodMultiplier attribute), 69
- k2G (wpilib.adx1345_i2c.ADXL345_I2C.Range attribute), 6
- k2G (wpilib.adx1345_spi.ADXL345_SPI.Range attribute), 7
- k2G (wpilib.adx1362.ADXL362.Range attribute), 9
- k2G (wpilib.builtinaccelerometer.BuiltInAccelerometer.Range attribute), 20
- k2G (wpilib.interfaces.accelerometer.Accelerometer.Range attribute), 122
- k2X (wpilib.counter.Counter.EncodingType attribute), 26
- k2X (wpilib.encoder.Encoder.EncodingType attribute), 39
- k2X (wpilib.interfaces.counterbase.CounterBase.EncodingType attribute), 123
- k2X (wpilib.pwm.PWM.PeriodMultiplier attribute), 69
- k4G (wpilib.adx1345_i2c.ADXL345_I2C.Range attribute), 6
- k4G (wpilib.adx1345_spi.ADXL345_SPI.Range attribute), 7
- k4G (wpilib.adx1362.ADXL362.Range attribute), 9
- k4G (wpilib.builtinaccelerometer.BuiltInAccelerometer.Range attribute), 20
- k4G (wpilib.interfaces.accelerometer.Accelerometer.Range attribute), 122
- k4X (wpilib.counter.Counter.EncodingType attribute), 26
- k4X (wpilib.encoder.Encoder.EncodingType attribute), 39
- k4X (wpilib.interfaces.counterbase.CounterBase.EncodingType attribute), 123
- k4X (wpilib.pwm.PWM.PeriodMultiplier attribute), 69
- k8G (wpilib.adx1345_i2c.ADXL345_I2C.Range attribute), 6
- k8G (wpilib.adx1345_spi.ADXL345_SPI.Range attribute), 7
- k8G (wpilib.adx1362.ADXL362.Range attribute), 9
- k8G (wpilib.builtinaccelerometer.BuiltInAccelerometer.Range attribute), 20
- k8G (wpilib.interfaces.accelerometer.Accelerometer.Range attribute), 122
- kAccumulatorChannels (wpilib.analoginput.AnalogInput attribute), 15
- kAccumulatorSlot (wpilib.analoginput.AnalogInput attribute), 15
- kAddress (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kAddress_MultiByte (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kAddress_Read (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kAnalogInputChannels (wpilib.sensorbase.SensorBase attribute), 84
- kAnalogOutputChannels (wpilib.sensorbase.SensorBase attribute), 84
- kArcadeRatioCurve_Reported (wpilib.robotdrive.RobotDrive attribute), 77
- kArcadeStandard_Reported (wpilib.robotdrive.RobotDrive attribute), 77
- kAverageBits (wpilib.analoggyro.AnalogGyro attribute), 13
- kBoth (wpilib.relay.Relay.Direction attribute), 72
- kCalibrationSampleTime (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kCalibrationSampleTime (wpilib.analoggyro.AnalogGyro attribute), 13
- kDataFormat_FullRes (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormat_FullRes (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataFormat_IntInvert (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormat_IntInvert (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataFormat_Justify (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormat_Justify (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataFormat_SelfTest (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormat_SelfTest (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataFormat_SPI (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormat_SPI (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataFormatRegister (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataFormatRegister (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataRegister (wpilib.adx1345_i2c.ADXL345_I2C attribute), 6
- kDataRegister (wpilib.adx1345_spi.ADXL345_SPI attribute), 8
- kDataRegister (wpilib.adx1362.ADXL362 attribute), 9
- kDefaultExpirationTime (wpilib.robotdrive.RobotDrive attribute), 8

- attribute), 77
- kDefaultMaxOutput (wpilib.robotdrive.RobotDrive attribute), 77
- kDefaultMaxServoPWM (wpilib.servo.Servo attribute), 85
- kDefaultMinServoPWM (wpilib.servo.Servo attribute), 85
- kDefaultPeriod (wpilib.pidcontroller.PIDController attribute), 63
- kDefaultSensitivity (wpilib.robotdrive.RobotDrive attribute), 77
- kDefaultThrottleAxis (wpilib.joystick.Joystick attribute), 55
- kDefaultTopButton (wpilib.joystick.Joystick attribute), 55
- kDefaultTriggerButton (wpilib.joystick.Joystick attribute), 55
- kDefaultTwistAxis (wpilib.joystick.Joystick attribute), 55
- kDefaultVoltsPerDegreePerSecond (wpilib.analoggyro.AnalogGyro attribute), 13
- kDefaultXAxis (wpilib.joystick.Joystick attribute), 55
- kDefaultYAxis (wpilib.joystick.Joystick attribute), 55
- kDefaultZAxis (wpilib.joystick.Joystick attribute), 55
- kDegreePerSecondPerLSB (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kDigitalChannels (wpilib.sensorbase.SensorBase attribute), 84
- kDisplacement (wpilib.analogaccelerometer.AnalogAccelerometer.PIDSourceType attribute), 11
- kDisplacement (wpilib.analoggyro.AnalogGyro.PIDSourceType attribute), 12
- kDisplacement (wpilib.analoginput.AnalogInput.PIDSourceType attribute), 14
- kDisplacement (wpilib.analogpotentiometer.AnalogPotentiometer.PIDSourceType attribute), 17
- kDisplacement (wpilib.counter.Counter.PIDSourceType attribute), 26
- kDisplacement (wpilib.encoder.Encoder.PIDSourceType attribute), 40
- kDisplacement (wpilib.gyrobase.GyroBase.PIDSourceType attribute), 43
- kDisplacement (wpilib.interfaces.pidsource.PIDSource.PIDSourceType attribute), 127
- kDisplacement (wpilib.pidcontroller.PIDController.PIDSourceType attribute), 62
- kDisplacement (wpilib.ultrasonic.Ultrasonic.PIDSourceType attribute), 100
- kExternalDirection (wpilib.counter.Counter.Mode attribute), 26
- keys() (wpilib.preferences.Preferences method), 67
- kFallingPulse (wpilib.analogtrigger.AnalogTrigger.AnalogTriggerType attribute), 18
- kFallingPulse (wpilib.analogtriggeroutput.AnalogTriggerOutput.AnalogTriggerType attribute), 20
- kFaultRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kFilterCtl_ODR_100Hz (wpilib.adxl362.ADXL362 attribute), 9
- kFilterCtl_Range2G (wpilib.adxl362.ADXL362 attribute), 9
- kFilterCtl_Range4G (wpilib.adxl362.ADXL362 attribute), 9
- kFilterCtl_Range8G (wpilib.adxl362.ADXL362 attribute), 9
- kFilterCtlRegister (wpilib.adxl362.ADXL362 attribute), 9
- kForward (wpilib.doublesolenoid.DoubleSolenoid.Value attribute), 34
- kForward (wpilib.relay.Relay.Direction attribute), 72
- kForward (wpilib.relay.Relay.Value attribute), 72
- kFrontLeft (wpilib.robotdrive.RobotDrive.MotorType attribute), 76
- kFrontRight (wpilib.robotdrive.RobotDrive.MotorType attribute), 76
- kGearToothThreshold (wpilib.geartooth.GearTooth attribute), 43
- kGsPerLSB (wpilib.adxl345_i2c.ADXL345_I2C attribute), 6
- kGsPerLSB (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kHiCSTRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kHID1stPerson (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
- kHIDDriving (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
- kHIDFlight (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
- kHIDGamepad (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
- kHIDJoystick (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
- kInches (wpilib.ultrasonic.Ultrasonic.Unit attribute), 100
- kInWindow (wpilib.analogtrigger.AnalogTrigger.AnalogTriggerType attribute), 18
- kIsWindowType (wpilib.analogtriggeroutput.AnalogTriggerOutput.AnalogTriggerType attribute), 20
- kJoystickPorts (wpilib.driverstation.DriverStation attribute), 38
- kLeft (wpilib.interfaces.generichid.GenericHID.Hand attribute), 47, 124
- kLeftRumble (wpilib.interfaces.generichid.GenericHID.RumbleType attribute), 47, 124
- kLoCSTRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kMaxNumberOfMotors (wpilib.robotdrive.RobotDrive

- attribute), 77
- kMaxServoAngle (wpilib.servo.Servo attribute), 85
- kMaxUltrasonicTime (wpilib.ultrasonic.Ultrasonic attribute), 101
- kMecanumCartesian_Reported (wpilib.robotdrive.RobotDrive attribute), 77
- kMecanumPolar_Reported (wpilib.robotdrive.RobotDrive attribute), 77
- kMillimeters (wpilib.ultrasonic.Ultrasonic.Unit attribute), 100
- kMinServoAngle (wpilib.servo.Servo attribute), 85
- kMXP (wpilib.i2c.I2C.Port attribute), 44
- kMXP (wpilib.spi.SPI.Port attribute), 95
- kNumAxis (wpilib.joystick.Joystick.AxisType attribute), 52
- kNumButton (wpilib.joystick.Joystick.ButtonType attribute), 52
- kOff (wpilib.doublesolenoid.DoubleSolenoid.Value attribute), 34
- kOff (wpilib.relay.Relay.Value attribute), 72
- kOn (wpilib.relay.Relay.Value attribute), 72
- kOnboard (wpilib.i2c.I2C.Port attribute), 44
- kOnboardCS0 (wpilib.spi.SPI.Port attribute), 95
- kOnboardCS1 (wpilib.spi.SPI.Port attribute), 95
- kOnboardCS2 (wpilib.spi.SPI.Port attribute), 95
- kOnboardCS3 (wpilib.spi.SPI.Port attribute), 95
- kOversampleBits (wpilib.analoggyro.AnalogGyro attribute), 13
- kPartIdRegister (wpilib.adxl362.ADXL362 attribute), 9
- kPCMMModules (wpilib.sensorbase.SensorBase attribute), 84
- kPDPChannels (wpilib.sensorbase.SensorBase attribute), 84
- kPDPModules (wpilib.sensorbase.SensorBase attribute), 84
- kPIDRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 10
- kPingTime (wpilib.ultrasonic.Ultrasonic attribute), 101
- kPowerCtl_AutoSleep (wpilib.adxl345_i2c.ADXL345_I2C attribute), 6
- kPowerCtl_AutoSleep (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kPowerCtl_AutoSleep (wpilib.adxl362.ADXL362 attribute), 9
- kPowerCtl_Link (wpilib.adxl345_i2c.ADXL345_I2C attribute), 6
- kPowerCtl_Link (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kPowerCtl_Measure (wpilib.adxl345_i2c.ADXL345_I2C attribute), 6
- kPowerCtl_Measure (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kPowerCtl_Measure (wpilib.adxl362.ADXL362 attribute), 9
- kPowerCtl_Sleep (wpilib.adxl345_i2c.ADXL345_I2C attribute), 7
- kPowerCtl_Sleep (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kPowerCtl_UltraLowNoise (wpilib.adxl362.ADXL362 attribute), 9
- kPowerCtlRegister (wpilib.adxl345_i2c.ADXL345_I2C attribute), 6
- kPowerCtlRegister (wpilib.adxl345_spi.ADXL345_SPI attribute), 8
- kPowerCtlRegister (wpilib.adxl362.ADXL362 attribute), 9
- kPriority (wpilib.ultrasonic.Ultrasonic attribute), 101
- kPulseLength (wpilib.counter.Counter.Mode attribute), 26
- kPwmChannels (wpilib.sensorbase.SensorBase attribute), 84
- kQuadRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
- kRate (wpilib.analogaccelerometer.AnalogAccelerometer.PIDSourceType attribute), 11
- kRate (wpilib.analoggyro.AnalogGyro.PIDSourceType attribute), 12
- kRate (wpilib.analoginput.AnalogInput.PIDSourceType attribute), 14
- kRate (wpilib.analogpotentiometer.AnalogPotentiometer.PIDSourceType attribute), 17
- kRate (wpilib.counter.Counter.PIDSourceType attribute), 26
- kRate (wpilib.encoder.Encoder.PIDSourceType attribute), 40
- kRate (wpilib.gyrobase.GyroBase.PIDSourceType attribute), 43
- kRate (wpilib.interfaces.pidsource.PIDSource.PIDSourceType attribute), 127
- kRate (wpilib.pidcontroller.PIDController.PIDSourceType attribute), 62
- kRate (wpilib.ultrasonic.Ultrasonic.PIDSourceType attribute), 100
- kRateRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
- kRearLeft (wpilib.robotdrive.RobotDrive.MotorType attribute), 76
- kRearRight (wpilib.robotdrive.RobotDrive.MotorType attribute), 76
- kRegRead (wpilib.adxl362.ADXL362 attribute), 9
- kRegWrite (wpilib.adxl362.ADXL362 attribute), 9
- kRelayChannels (wpilib.sensorbase.SensorBase attribute), 84
- kResetOnFallingEdge (wpilib.encoder.Encoder.IndexingType attribute), 40
- kResetOnRisingEdge (wpilib.encoder.Encoder.IndexingType attribute), 40

- attribute), 40
 - kResetWhileHigh (wpilib.encoder.Encoder.IndexingType attribute), 40
 - kResetWhileLow (wpilib.encoder.Encoder.IndexingType attribute), 40
 - kReverse (wpilib.doublesolenoid.DoubleSolenoid.Value attribute), 34
 - kReverse (wpilib.relay.Relay.Direction attribute), 72
 - kReverse (wpilib.relay.Relay.Value attribute), 72
 - kRight (wpilib.interfaces.generichid.GenericHID.Hand attribute), 47, 124
 - kRightRumble (wpilib.interfaces.generichid.GenericHID.RumbleType attribute), 47, 124
 - kRisingPulse (wpilib.analogtrigger.AnalogTrigger.AnalogTriggerType attribute), 18
 - kRisingPulse (wpilib.analogtriggeroutput.AnalogTriggerOutput.AnalogTriggerType attribute), 20
 - kSamplePeriod (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
 - kSamplesPerSecond (wpilib.analoggyro.AnalogGyro attribute), 13
 - kSemiperiod (wpilib.counter.Counter.Mode attribute), 26
 - kSNHighRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
 - kSNLowRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
 - kSolenoidChannels (wpilib.sensorbase.SensorBase attribute), 84
 - kSpeedOfSoundInchesPerSec (wpilib.ultrasonic.Ultrasonic attribute), 101
 - kState (wpilib.analogtrigger.AnalogTrigger.AnalogTriggerType attribute), 18
 - kState (wpilib.analogtriggeroutput.AnalogTriggerOutput.AnalogTriggerType attribute), 20
 - kSystemClockTicksPerMicrosecond (wpilib.sensorbase.SensorBase attribute), 85
 - kTank_Reported (wpilib.robotdrive.RobotDrive attribute), 77
 - kTemRegister (wpilib.adxrs450_gyro.ADXRS450_Gyro attribute), 11
 - kThrottle (wpilib.joystick.Joystick.AxisType attribute), 52
 - kTop (wpilib.joystick.Joystick.ButtonType attribute), 52
 - kTrigger (wpilib.joystick.Joystick.ButtonType attribute), 52
 - kTwist (wpilib.joystick.Joystick.AxisType attribute), 52
 - kTwoPulse (wpilib.counter.Counter.Mode attribute), 26
 - kUnknown (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kX (wpilib.adxl345_i2c.ADXL345_I2C.Axes attribute), 5
 - kX (wpilib.adxl345_spi.ADXL345_SPI.Axes attribute), 7
 - kX (wpilib.adxl362.ADXL362.Axes attribute), 8
 - kX (wpilib.joystick.Joystick.AxisType attribute), 52
 - kXInputArcadePad (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputArcadeStick (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputDancePad (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputDrumKit (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputFlightStick (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputGamepad (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputGuitar (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 46, 124
 - kXInputGuitar2 (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 47, 124
 - kXInputGuitar3 (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 47, 124
 - kXInputUnknown (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 47, 124
 - kXInputWheel (wpilib.interfaces.generichid.GenericHID.HIDType attribute), 47, 124
 - kY (wpilib.adxl345_i2c.ADXL345_I2C.Axes attribute), 6
 - kY (wpilib.adxl345_spi.ADXL345_SPI.Axes attribute), 7
 - kY (wpilib.adxl362.ADXL362.Axes attribute), 8
 - kY (wpilib.joystick.Joystick.AxisType attribute), 52
 - kZ (wpilib.adxl345_i2c.ADXL345_I2C.Axes attribute), 6
 - kZ (wpilib.adxl345_spi.ADXL345_SPI.Axes attribute), 7
 - kZ (wpilib.adxl362.ADXL362.Axes attribute), 8
 - kZ (wpilib.joystick.Joystick.AxisType attribute), 52
- ## L
- launch() (wpilib.cameraserver.CameraServer class method), 21
 - limit() (wpilib.robotdrive.RobotDrive static method), 77
 - LinearDigitalFilter (class in wpilib.lineardigitalfilter), 56
 - LiveWindow (class in wpilib.livewindow), 58
 - liveWindowEnabled (wpilib.livewindow.LiveWindow attribute), 59
 - LiveWindowSendable (class in wpilib.livewindow.sendable), 60
 - livewindowTable (wpilib.livewindow.LiveWindow attribute), 59
 - lockChanges() (wpilib.command.command.Command method), 111
 - logger (wpilib.iterativerobot.IterativeRobot attribute), 50
 - logger (wpilib.samplerobot.SampleRobot attribute), 81
- ## M
- main() (wpilib.robotbase.RobotBase static method), 75
 - mecanumDrive_Cartesian() (wpilib.robotdrive.RobotDrive method),

- 77
 mecanumDrive_Polar() (wpilib.robotdrive.RobotDrive method), 78
 MotorSafety (class in wpilib.motorsafety), 60
 movingAverage() (wpilib.linear.digitalfilter.LinearDigitalFilter static method), 57
 mutex (wpilib.digitalglitchfilter.DigitalGlitchFilter attribute), 30
- ## N
- NamedSendable (class in wpilib.interfaces.namedsendable), 126
 NetworkButton (class in wpilib.buttons.networkbutton), 107
 normalize() (wpilib.robotdrive.RobotDrive static method), 78
- ## O
- onTarget() (wpilib.command.pidsubsystem.PIDSubsystem method), 116
 onTarget() (wpilib.pidcontroller.PIDController method), 63
 operatorControl() (wpilib.samplerobot.SampleRobot method), 81
 OPTIONS (wpilib.sendablechooser.SendableChooser attribute), 83
- ## P
- PercentageTolerance_onTarget() (wpilib.pidcontroller.PIDController method), 62
 PIDCommand (class in wpilib.command.pidcommand), 115
 PIDController (class in wpilib.pidcontroller), 61
 PIDController.PIDSourceType (class in wpilib.pidcontroller), 62
 pidGet() (wpilib.analogaccelerometer.AnalogAccelerometer method), 11
 pidGet() (wpilib.analoginput.AnalogInput method), 15
 pidGet() (wpilib.analogpotentiometer.AnalogPotentiometer method), 17
 pidGet() (wpilib.counter.Counter method), 27
 pidGet() (wpilib.encoder.Encoder method), 41
 pidGet() (wpilib.filter.Filter method), 42
 pidGet() (wpilib.gyrobase.GyroBase method), 43
 pidGet() (wpilib.interfaces.pidsource.PIDSource method), 127
 pidGet() (wpilib.linear.digitalfilter.LinearDigitalFilter method), 58
 pidGet() (wpilib.ultrasonic.Ultrasonic method), 101
 pidGetSource() (wpilib.filter.Filter method), 42
 PIDInterface (class in wpilib.interfaces.pidinterface), 126
 PIDOutput (class in wpilib.interfaces.pidoutput), 127
 PIDSource (class in wpilib.interfaces.pidsource), 127
 PIDSource.PIDSourceType (class in wpilib.interfaces.pidsource), 127
 PIDSubsystem (class in wpilib.command.pidsubsystem), 116
 pidWrite() (wpilib.interfaces.pidoutput.PIDOutput method), 127
 pidWrite() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
 ping() (wpilib.ultrasonic.Ultrasonic method), 101
 port (wpilib.analoginput.AnalogInput attribute), 15
 port (wpilib.analogoutput.AnalogOutput attribute), 16
 port (wpilib.analogtrigger.AnalogTrigger attribute), 18
 port (wpilib.i2c.I2C attribute), 44
 port (wpilib.spi.SPI attribute), 96
 Potentiometer (class in wpilib.interfaces.potentiometer), 128
 PowerDistributionPanel (class in wpilib.powerdistributionpanel), 65
 Preferences (class in wpilib.preferences), 66
 PrintCommand (class in wpilib.command.printcommand), 118
 pulse() (wpilib.digitaloutput.DigitalOutput method), 32
 putBoolean() (wpilib.preferences.Preferences method), 67
 putBoolean() (wpilib.smartdashboard.SmartDashboard class method), 89
 putBooleanArray() (wpilib.smartdashboard.SmartDashboard class method), 89
 putData() (wpilib.smartdashboard.SmartDashboard class method), 89
 putDouble() (wpilib.smartdashboard.SmartDashboard class method), 90
 putFloat() (wpilib.preferences.Preferences method), 67
 putInt() (wpilib.preferences.Preferences method), 67
 putInt() (wpilib.smartdashboard.SmartDashboard class method), 90
 putNumber() (wpilib.smartdashboard.SmartDashboard class method), 90
 putNumberArray() (wpilib.smartdashboard.SmartDashboard class method), 90
 putRaw() (wpilib.smartdashboard.SmartDashboard class method), 90
 putString() (wpilib.preferences.Preferences method), 67
 putString() (wpilib.smartdashboard.SmartDashboard class method), 90
 putStringArray() (wpilib.smartdashboard.SmartDashboard class method), 91
 PWM (class in wpilib.pwm), 68
 PWM.PeriodMultiplier (class in wpilib.pwm), 68
 pwmGenerator (wpilib.digitaloutput.DigitalOutput attribute), 32
 PWMSpeedController (class in wpilib.pwmspeedcontroller), 71

R

- read() (wpilib.i2c.I2C method), 44
- read() (wpilib.spi.SPI method), 96
- readFallingTimestamp() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
- readOnly() (wpilib.i2c.I2C method), 44
- readRisingTimestamp() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
- Red (wpilib.driverstation.DriverStation.Alliance attribute), 35
- registerSubsystem() (wpilib.command.scheduler.Scheduler method), 118
- Relay (class in wpilib.relay), 72
- Relay.Direction (class in wpilib.relay), 72
- Relay.Value (class in wpilib.relay), 72
- relayChannels (wpilib.relay.Relay attribute), 73
- release() (wpilib.driverstation.DriverStation method), 38
- remove() (wpilib.command.scheduler.Scheduler method), 119
- remove() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
- remove() (wpilib.preferences.Preferences method), 68
- removeAll() (wpilib.command.scheduler.Scheduler method), 119
- removeComponent() (wpilib.livewindow.LiveWindow static method), 59
- removed() (wpilib.command.command.Command method), 111
- reportError() (wpilib.driverstation.DriverStation static method), 38
- reportWarning() (wpilib.driverstation.DriverStation static method), 38
- requestInterrupts() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
- requires() (wpilib.command.command.Command method), 111
- reset() (wpilib.adxrs450_gyro.ADXRS450_Gyro method), 11
- reset() (wpilib.analoggyro.AnalogGyro method), 13
- reset() (wpilib.counter.Counter method), 27
- reset() (wpilib.encoder.Encoder method), 41
- reset() (wpilib.filter.Filter method), 42
- reset() (wpilib.gyrobase.GyroBase method), 43
- reset() (wpilib.interfaces.counterbase.CounterBase method), 123
- reset() (wpilib.interfaces.gyro.Gyro method), 126
- reset() (wpilib.interfaces.pidinterface.PIDInterface method), 127
- reset() (wpilib.lineardigitalfilter.LinearDigitalFilter method), 58
- reset() (wpilib.pidcontroller.PIDController method), 63
- reset() (wpilib.timer.Timer method), 99
- resetAccumulator() (wpilib.analoginput.AnalogInput method), 15
- resetAccumulator() (wpilib.spi.SPI method), 96
- resetTotalEnergy() (wpilib.powerdistributionpanel.PowerDistributionPanel method), 65
- Resource (class in wpilib.resource), 73
- returnPIDInput() (wpilib.command.pidcommand.PIDCommand method), 115
- returnPIDInput() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
- reverseHandle (wpilib.relay.Relay attribute), 73
- RobotBase (class in wpilib.robotbase), 74
- RobotDrive (class in wpilib.robotdrive), 75
- RobotDrive.MotorType (class in wpilib.robotdrive), 76
- robotInit() (wpilib.iterativerobot.IterativeRobot method), 51
- robotInit() (wpilib.samplerobot.SampleRobot method), 81
- robotMain() (wpilib.samplerobot.SampleRobot method), 81
- robotPeriodic() (wpilib.iterativerobot.IterativeRobot method), 51
- RobotState (class in wpilib.robotstate), 79
- rotateVector() (wpilib.robotdrive.RobotDrive static method), 78
- run() (wpilib.command.command.Command method), 111
- run() (wpilib.command.scheduler.Scheduler method), 119
- run() (wpilib.livewindow.LiveWindow static method), 59

S

- SafePWM (class in wpilib.safepwm), 80
- SampleRobot (class in wpilib.samplerobot), 80
- Scheduler (class in wpilib.command.scheduler), 118
- SD540 (class in wpilib.sd540), 82
- SELECTED (wpilib.sendablechooser.SendableChooser attribute), 83
- Sendable (class in wpilib.sendable), 82
- SendableChooser (class in wpilib.sendablechooser), 82
- SensorBase (class in wpilib.sensorbase), 83
- sensors (wpilib.livewindow.LiveWindow attribute), 59
- sensors (wpilib.ultrasonic.Ultrasonic attribute), 101
- Servo (class in wpilib.servo), 85
- set() (wpilib.digitaloutput.DigitalOutput method), 33
- set() (wpilib.doublesolenoid.DoubleSolenoid method), 34
- set() (wpilib.interfaces.speedcontroller.SpeedController method), 128
- set() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
- set() (wpilib.relay.Relay method), 73
- set() (wpilib.servo.Servo method), 85
- set() (wpilib.solenoid.Solenoid method), 93
- setAbsoluteTolerance() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
- setAbsoluteTolerance() (wpilib.pidcontroller.PIDController method), 63

- setAccumulatorCenter() (wpilib.analoginput.AnalogInput method), 15
 setAccumulatorCenter() (wpilib.spi.SPI method), 96
 setAccumulatorDeadband() (wpilib.analoginput.AnalogInput method), 16
 setAccumulatorDeadband() (wpilib.spi.SPI method), 96
 setAccumulatorInitialValue() (wpilib.analoginput.AnalogInput method), 16
 setAngle() (wpilib.servo.Servo method), 86
 setAutomaticMode() (wpilib.ultrasonic.Ultrasonic method), 101
 setAverageBits() (wpilib.analoginput.AnalogInput method), 16
 setAveraged() (wpilib.analogtrigger.AnalogTrigger method), 18
 setAxisChannel() (wpilib.joystick.Joystick method), 55
 setBounds() (wpilib.pwm.PWM method), 70
 setChipSelectActiveHigh() (wpilib.spi.SPI method), 96
 setChipSelectActiveLow() (wpilib.spi.SPI method), 96
 setClockActiveHigh() (wpilib.spi.SPI method), 96
 setClockActiveLow() (wpilib.spi.SPI method), 96
 setClockRate() (wpilib.spi.SPI method), 96
 setClosedLoopControl() (wpilib.compressor.Compressor method), 23
 setContinuous() (wpilib.pidcontroller.PIDController method), 63
 setCurrentCommand() (wpilib.command.subsystem.Subsystem method), 120
 setDeadband() (wpilib.analoggyro.AnalogGyro method), 13
 setDefaultBoolean() (wpilib.smartdashboard.SmartDashboard class method), 91
 setDefaultBooleanArray() (wpilib.smartdashboard.SmartDashboard class method), 91
 setDefaultCommand() (wpilib.command.subsystem.Subsystem method), 120
 setDefaultNumber() (wpilib.smartdashboard.SmartDashboard class method), 91
 setDefaultNumberArray() (wpilib.smartdashboard.SmartDashboard class method), 91
 setDefaultRaw() (wpilib.smartdashboard.SmartDashboard class method), 91
 setDefaultSolenoidModule() (wpilib.sensorbase.SensorBase static method), 85
 setDefaultString() (wpilib.smartdashboard.SmartDashboard class method), 92
 setDefaultStringArray() (wpilib.smartdashboard.SmartDashboard class method), 92
 setDirection() (wpilib.relay.Relay method), 73
 setDisabled() (wpilib.pwm.PWM method), 70
 setDistancePerPulse() (wpilib.counter.Counter method), 27
 setDistancePerPulse() (wpilib.encoder.Encoder method), 41
 setDistanceUnits() (wpilib.ultrasonic.Ultrasonic method), 101
 setDownSource() (wpilib.counter.Counter method), 27
 setDownSourceEdge() (wpilib.counter.Counter method), 28
 setEnabled() (wpilib.livewindow.LiveWindow static method), 59
 setEnabled() (wpilib.ultrasonic.Ultrasonic method), 101
 setExpiration() (wpilib.motorsafety.MotorSafety method), 61
 setExternalDirectionMode() (wpilib.counter.Counter method), 28
 setFiltered() (wpilib.analogtrigger.AnalogTrigger method), 18
 setFlags() (wpilib.smartdashboard.SmartDashboard class method), 92
 setGlobalSampleRate() (wpilib.analoginput.AnalogInput static method), 16
 setIndexSource() (wpilib.encoder.Encoder method), 41
 setInputRange() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
 setInputRange() (wpilib.pidcontroller.PIDController method), 64
 setInterruptible() (wpilib.command.command.Command method), 111
 setInverted() (wpilib.buttons.internalbutton.InternalButton method), 107
 setInverted() (wpilib.interfaces.speedcontroller.SpeedController method), 128
 setInverted() (wpilib.pwmspeedcontroller.PWMSpeedController method), 71
 setInvertedMotor() (wpilib.robotdrive.RobotDrive method), 78
 setLeftRightMotorOutputs() (wpilib.robotdrive.RobotDrive method), 78
 setLimitsRaw() (wpilib.analogtrigger.AnalogTrigger method), 19
 setLimitsVoltage() (wpilib.analogtrigger.AnalogTrigger method), 19
 setLSBFirst() (wpilib.spi.SPI method), 96
 setMaxOutput() (wpilib.robotdrive.RobotDrive method), 78
 setMaxPeriod() (wpilib.counter.Counter method), 28
 setMaxPeriod() (wpilib.encoder.Encoder method), 41
 setMaxPeriod() (wpilib.interfaces.counterbase.CounterBase method), 123
 setMinRate() (wpilib.encoder.Encoder method), 41
 setMSBFirst() (wpilib.spi.SPI method), 96

- setOutput() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
- setOutput() (wpilib.interfaces.generichid.GenericHID method), 48, 125
- setOutput() (wpilib.joystick.Joystick method), 56
- setOutput() (wpilib.xboxcontroller.XboxController method), 105
- setOutputRange() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
- setOutputRange() (wpilib.pidcontroller.PIDController method), 64
- setOutputs() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
- setOutputs() (wpilib.interfaces.generichid.GenericHID method), 48, 125
- setOutputs() (wpilib.joystick.Joystick method), 56
- setOutputs() (wpilib.xboxcontroller.XboxController method), 105
- setOversampleBits() (wpilib.analoginput.AnalogInput method), 16
- setParent() (wpilib.command.command.Command method), 111
- setPercentTolerance() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
- setPercentTolerance() (wpilib.pidcontroller.PIDController method), 64
- setPeriodCycles() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
- setPeriodMultiplier() (wpilib.pwm.PWM method), 70
- setPeriodNanoSeconds() (wpilib.digitalglitchfilter.DigitalGlitchFilter method), 30
- setPersistent() (wpilib.smartdashboard.SmartDashboard class method), 92
- setPID() (wpilib.interfaces.pidinterface.PIDInterface method), 127
- setPID() (wpilib.pidcontroller.PIDController method), 64
- setPIDSourceType() (wpilib.analogaccelerometer.AnalogAccelerometer method), 11
- setPIDSourceType() (wpilib.analoginput.AnalogInput method), 16
- setPIDSourceType() (wpilib.analogpotentiometer.AnalogPotentiometer method), 17
- setPIDSourceType() (wpilib.counter.Counter method), 28
- setPIDSourceType() (wpilib.encoder.Encoder method), 42
- setPIDSourceType() (wpilib.filter.Filter method), 42
- setPIDSourceType() (wpilib.gyrobase.GyroBase method), 43
- setPIDSourceType() (wpilib.interfaces.pidsource.PIDSource method), 128
- setPIDSourceType() (wpilib.pidcontroller.PIDController method), 64
- setPIDSourceType() (wpilib.ultrasonic.Ultrasonic method), 102
- setPosition() (wpilib.pwm.PWM method), 70
- setPressed() (wpilib.buttons.internalbutton.InternalButton method), 107
- setPulseLengthMode() (wpilib.counter.Counter method), 28
- setPWMRate() (wpilib.digitaloutput.DigitalOutput method), 33
- setRange() (wpilib.adxl345_i2c.ADXL345_I2C method), 7
- setRange() (wpilib.adxl345_spi.ADXL345_SPI method), 8
- setRange() (wpilib.adxl362.ADXL362 method), 9
- setRange() (wpilib.builtinaccelerometer.BuiltInAccelerometer method), 21
- setRange() (wpilib.interfaces.accelerometer.Accelerometer method), 122
- setRaw() (wpilib.pwm.PWM method), 70
- setRawBounds() (wpilib.pwm.PWM method), 70
- setReverseDirection() (wpilib.counter.Counter method), 29
- setReverseDirection() (wpilib.encoder.Encoder method), 42
- setRumble() (wpilib.interfaces.gamepadbase.GamepadBase method), 46
- setRumble() (wpilib.interfaces.generichid.GenericHID method), 48, 125
- setRumble() (wpilib.joystick.Joystick method), 56
- setRumble() (wpilib.xboxcontroller.XboxController method), 105
- setRunWhenDisabled() (wpilib.command.command.Command method), 112
- setSafetyEnabled() (wpilib.motorsafety.MotorSafety method), 61
- setSampleDataOnFalling() (wpilib.spi.SPI method), 96
- setSampleDataOnRising() (wpilib.spi.SPI method), 96
- setSamplesToAverage() (wpilib.counter.Counter method), 29
- setSamplesToAverage() (wpilib.encoder.Encoder method), 42
- setSemiPeriodMode() (wpilib.counter.Counter method), 29
- setSensitivity() (wpilib.analogaccelerometer.AnalogAccelerometer method), 12
- setSensitivity() (wpilib.analoggyro.AnalogGyro method), 13
- setSensitivity() (wpilib.robotdrive.RobotDrive method), 79
- setSetpoint() (wpilib.command.pidcommand.PIDCommand method), 115
- setSetpoint() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
- setSetpoint() (wpilib.interfaces.pidinterface.PIDInterface method), 127
- setSetpoint() (wpilib.pidcontroller.PIDController method), 64

- method), 64
 - setSetpointRelative() (wpilib.command.pidcommand.PIDCommand method), 115
 - setSetpointRelative() (wpilib.command.pidsubsystem.PIDSubsystem method), 117
 - setSpeed() (wpilib.pwm.PWM method), 71
 - setTimeout() (wpilib.command.command.Command method), 112
 - setTolerance() (wpilib.pidcontroller.PIDController method), 64
 - setToleranceBuffer() (wpilib.pidcontroller.PIDController method), 64
 - setUpdateWhenEmpty() (wpilib.counter.Counter method), 30
 - setUpDownCounterMode() (wpilib.counter.Counter method), 29
 - setUpSource() (wpilib.counter.Counter method), 29
 - setUpSourceEdge() (wpilib.counter.Counter method), 29
 - setUpSourceEdge() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49
 - setVoltage() (wpilib.analogoutput.AnalogOutput method), 17
 - setZero() (wpilib.analogaccelerometer.AnalogAccelerometer method), 12
 - setZeroLatch() (wpilib.pwm.PWM method), 71
 - singlePoleIIR() (wpilib.linearfilter.LinearDigitalFilter static method), 58
 - SmartDashboard (class in wpilib.smartdashboard), 86
 - Solenoid (class in wpilib.solenoid), 92
 - SolenoidBase (class in wpilib.solenoidbase), 93
 - solenoidHandle (wpilib.solenoid.Solenoid attribute), 93
 - Spark (class in wpilib.spark), 94
 - SpeedController (class in wpilib.interfaces.speedcontroller), 128
 - SPI (class in wpilib.spi), 94
 - SPI.Port (class in wpilib.spi), 94
 - start() (wpilib.command.command.Command method), 112
 - start() (wpilib.compressor.Compressor method), 23
 - start() (wpilib.timer.Timer method), 99
 - StartCommand (class in wpilib.command.startcommand), 119
 - startCompetition() (wpilib.iterativerobot.IterativeRobot method), 51
 - startCompetition() (wpilib.robotbase.RobotBase method), 75
 - startCompetition() (wpilib.samplerobot.SampleRobot method), 81
 - startRunning() (wpilib.command.command.Command method), 112
 - startTiming() (wpilib.command.command.Command method), 112
 - statusTable (wpilib.livewindow.LiveWindow attribute), 60
 - stop() (wpilib.compressor.Compressor method), 23
 - stop() (wpilib.timer.Timer method), 99
 - stopMotor() (wpilib.interfaces.speedcontroller.SpeedController method), 128
 - stopMotor() (wpilib.relay.Relay method), 73
 - stopMotor() (wpilib.robotdrive.RobotDrive method), 79
 - stopMotor() (wpilib.safepwm.SafePWM method), 80
 - Subsystem (class in wpilib.command.subsystem), 119
- ## T
- table (wpilib.smartdashboard.SmartDashboard attribute), 92
 - TABLE_NAME (wpilib.preferences.Preferences attribute), 66
 - tablesToData (wpilib.smartdashboard.SmartDashboard attribute), 92
 - Talon (class in wpilib.talon), 97
 - TalonSRX (class in wpilib.talonsrx), 98
 - tableDrive() (wpilib.robotdrive.RobotDrive method), 79
 - teleopInit() (wpilib.iterativerobot.IterativeRobot method), 51
 - teleopPeriodic() (wpilib.iterativerobot.IterativeRobot method), 51
 - test() (wpilib.samplerobot.SampleRobot method), 81
 - testInit() (wpilib.iterativerobot.IterativeRobot method), 51
 - testPeriodic() (wpilib.iterativerobot.IterativeRobot method), 51
 - TimedCommand (class in wpilib.command.timedcommand), 120
 - Timer (class in wpilib.timer), 98
 - timeSinceInitialized() (wpilib.command.command.Command method), 112
 - toggleWhenActive() (wpilib.buttons.trigger.Trigger method), 108
 - toggleWhenPressed() (wpilib.buttons.button.Button method), 106
 - transaction() (wpilib.i2c.I2C method), 44
 - transaction() (wpilib.spi.SPI method), 96
 - Trigger (class in wpilib.buttons.trigger), 107
- ## U
- Ultrasonic (class in wpilib.ultrasonic), 100
 - Ultrasonic.PIDSourceType (class in wpilib.ultrasonic), 100
 - Ultrasonic.Unit (class in wpilib.ultrasonic), 100
 - ultrasonicChecker() (wpilib.ultrasonic.Ultrasonic static method), 102
 - updateDutyCycle() (wpilib.digitaloutput.DigitalOutput method), 33
 - updateValues() (wpilib.livewindow.LiveWindow static method), 60
 - usePIDOutput() (wpilib.command.pidcommand.PIDCommand method), 116

usePIDOutput() (wpilib.command.pidsubsystem.PIDSubsystem method), 117

Utility (class in wpilib.utility), 102

V

valueChangedEx() (wpilib.preferences.Preferences method), 68

verifySensor() (wpilib.i2c.I2C method), 45

Victor (class in wpilib.victor), 103

VictorSP (class in wpilib.victorsp), 103

W

WaitCommand (class in wpilib.command.waitcommand), 120

WaitForChildren (class in wpilib.command.waitforchildren), 121

waitForData() (wpilib.driverstation.DriverStation method), 38

waitForInterrupt() (wpilib.interruptablesensorbase.InterruptableSensorBase method), 49

WaitUntilCommand (class in wpilib.command.waituntilcommand), 121

whenActive() (wpilib.buttons.trigger.Trigger method), 108

whenInactive() (wpilib.buttons.trigger.Trigger method), 108

whenPressed() (wpilib.buttons.button.Button method), 106

whenReleased() (wpilib.buttons.button.Button method), 106

whileActive() (wpilib.buttons.trigger.Trigger method), 108

whileHeld() (wpilib.buttons.button.Button method), 106

willRunWhenDisabled() (wpilib.command.command.Command method), 112

wpilib (module), 3

wpilib.adxl345_i2c (module), 5

wpilib.adxl345_spi (module), 7

wpilib.adxl362 (module), 8

wpilib.adxrs450_gyro (module), 10

wpilib.analogaccelerometer (module), 11

wpilib.analoggyro (module), 12

wpilib.analoginput (module), 13

wpilib.analogoutput (module), 16

wpilib.analogpotentiometer (module), 17

wpilib.analogtrigger (module), 18

wpilib.analogtriggeroutput (module), 19

wpilib.builtinaccelerometer (module), 20

wpilib.buttons (module), 106

wpilib.buttons.button (module), 106

wpilib.buttons.internalbutton (module), 107

wpilib.buttons.joystickbutton (module), 107

wpilib.buttons.networkbutton (module), 107

wpilib.buttons.trigger (module), 107

wpilib.cameraserver (module), 21

wpilib.canjaguar (module), 21

wpilib.cantalon (module), 21

wpilib.command (module), 108

wpilib.command.command (module), 109

wpilib.command.commandgroup (module), 112

wpilib.command.conditionalcommand (module), 114

wpilib.command.instantcommand (module), 114

wpilib.command.pidcommand (module), 115

wpilib.command.pidsubsystem (module), 116

wpilib.command.printcommand (module), 118

wpilib.command.scheduler (module), 118

wpilib.command.startcommand (module), 119

wpilib.command.subsystem (module), 119

wpilib.command.timedcommand (module), 120

wpilib.command.waitcommand (module), 120

wpilib.command.waitforchildren (module), 121

wpilib.command.waituntilcommand (module), 121

wpilib.compressor (module), 22

wpilib.controllerpower (module), 23

wpilib.counter (module), 25

wpilib.digitalglitchfilter (module), 30

wpilib.digitalinput (module), 31

wpilib.digitaloutput (module), 31

wpilib.digitalsource (module), 33

wpilib.doublesolenoid (module), 33

wpilib.driverstation (module), 34

wpilib.encoder (module), 38

wpilib.filter (module), 42

wpilib.geartooth (module), 42

wpilib.gyrobase (module), 43

wpilib.i2c (module), 43

wpilib.interfaces (module), 121

wpilib.interfaces.accelerometer (module), 122

wpilib.interfaces.controller (module), 122

wpilib.interfaces.counterbase (module), 123

wpilib.interfaces.gamepadbase (module), 46

wpilib.interfaces.generichid (module), 46, 123

wpilib.interfaces.gyro (module), 126

wpilib.interfaces.namedsendable (module), 126

wpilib.interfaces.pidinterface (module), 126

wpilib.interfaces.pidoutput (module), 127

wpilib.interfaces.pidsource (module), 127

wpilib.interfaces.potentiometer (module), 128

wpilib.interfaces.speedcontroller (module), 128

wpilib.interruptablesensorbase (module), 48

wpilib.iterativerobot (module), 49

wpilib.jaguar (module), 52

wpilib.joystick (module), 52

wpilib.lineardigitalfilter (module), 56

wpilib.livewindow (module), 58

wpilib.livewindowsendable (module), 60

wpilib.motorsafety (module), 60

wpilib.pidcontroller (module), 61

`wplib.powerdistributionpanel` (module), 65
`wplib.preferences` (module), 66
`wplib.pwm` (module), 68
`wplib.pwmspeedcontroller` (module), 71
`wplib.relay` (module), 72
`wplib.resource` (module), 73
`wplib.robotbase` (module), 74
`wplib.robotdrive` (module), 75
`wplib.robotstate` (module), 79
`wplib.safepwm` (module), 80
`wplib.samplerobot` (module), 80
`wplib.sd540` (module), 82
`wplib.sendable` (module), 82
`wplib.sendablechooser` (module), 82
`wplib.sensorbase` (module), 83
`wplib.servo` (module), 85
`wplib.smartdashboard` (module), 86
`wplib.solenoid` (module), 92
`wplib.solenoidbase` (module), 93
`wplib.spark` (module), 94
`wplib.spi` (module), 94
`wplib.talon` (module), 97
`wplib.talonsrx` (module), 98
`wplib.timer` (module), 98
`wplib.ultrasonic` (module), 100
`wplib.utility` (module), 102
`wplib.victor` (module), 103
`wplib.victorsp` (module), 103
`wplib.xboxcontroller` (module), 104
`write()` (`wplib.i2c.I2C` method), 45
`write()` (`wplib.spi.SPI` method), 97
`writeBulk()` (`wplib.i2c.I2C` method), 45

X

`XboxController` (class in `wplib.xboxcontroller`), 104