

---

# **sttp Documentation**

*Release 1.0*

**Adam Warski**

**Oct 14, 2019**



<b>1</b>	<b>Quickstart</b>	<b>3</b>
1.1	Using sbt . . . . .	3
1.2	Using Ammonite . . . . .	3
1.3	Imports . . . . .	4
<b>2</b>	<b>Goals of the project</b>	<b>5</b>
2.1	Non-goals of the project . . . . .	5
2.2	How is sttp different from other libraries? . . . . .	5
<b>3</b>	<b>Community</b>	<b>7</b>
<b>4</b>	<b>Usage examples</b>	<b>9</b>
4.1	POST a form using the synchronous backend . . . . .	9
4.2	GET and parse JSON using the akka-http backend and json4s . . . . .	9
4.3	Test an endpoint requiring multiple parameters . . . . .	10
<b>5</b>	<b>HTTP Constants</b>	<b>13</b>
<b>6</b>	<b>Request definition basics</b>	<b>15</b>
6.1	Sending a request . . . . .	15
6.2	Starting requests . . . . .	16
6.3	Debugging requests . . . . .	16
<b>7</b>	<b>URIs</b>	<b>17</b>
7.1	URI interpolator . . . . .	17
7.2	Optional values . . . . .	18
7.3	Maps and sequences . . . . .	18
7.4	Special cases . . . . .	19
7.5	All features combined . . . . .	19
<b>8</b>	<b>Headers</b>	<b>21</b>
8.1	Common headers . . . . .	21
<b>9</b>	<b>Cookies</b>	<b>23</b>
9.1	Cookies from responses . . . . .	23
<b>10</b>	<b>Authentication</b>	<b>25</b>

<b>11</b>	<b>Setting the request body</b>	<b>27</b>
11.1	Text data . . . . .	27
11.2	Binary data . . . . .	27
11.3	Uploading files . . . . .	28
11.4	Form data . . . . .	28
11.5	Custom body serializers . . . . .	28
<b>12</b>	<b>Multipart requests</b>	<b>29</b>
12.1	Customising part meta-data . . . . .	30
<b>13</b>	<b>Streaming</b>	<b>31</b>
<b>14</b>	<b>The type of request definitions</b>	<b>33</b>
<b>15</b>	<b>Responses</b>	<b>35</b>
15.1	Response code . . . . .	35
15.2	Response headers . . . . .	35
15.3	Obtaining the response body . . . . .	36
<b>16</b>	<b>Response body specification</b>	<b>37</b>
16.1	Basic response specifications . . . . .	37
16.2	Handling non 2xx responses . . . . .	38
16.3	Custom body deserializers . . . . .	38
16.4	Streaming . . . . .	38
<b>17</b>	<b>Supported backends</b>	<b>41</b>
<b>18</b>	<b>Starting &amp; cleaning up</b>	<b>43</b>
<b>19</b>	<b>URLConnection backend</b>	<b>45</b>
<b>20</b>	<b>akka-http backend</b>	<b>47</b>
20.1	Testing . . . . .	48
<b>21</b>	<b>async-http-client backend</b>	<b>49</b>
21.1	Streaming using Monix . . . . .	50
21.2	Streaming using fs2 . . . . .	51
<b>22</b>	<b>OkHttp backend</b>	<b>53</b>
<b>23</b>	<b>Http4s backend</b>	<b>55</b>
<b>24</b>	<b>brave backend</b>	<b>57</b>
<b>25</b>	<b>Prometheus backend</b>	<b>59</b>
<b>26</b>	<b>Fetch backend</b>	<b>61</b>
26.1	Node.js . . . . .	61
26.2	Streaming . . . . .	62
<b>27</b>	<b>Custom backends, logging, metrics</b>	<b>63</b>
27.1	Request tagging . . . . .	63
27.2	Backend wrappers and redirects . . . . .	63
27.3	Example logging backend wrapper . . . . .	64
27.4	Example metrics backend wrapper . . . . .	65
27.5	Example retrying backend wrapper . . . . .	66
27.6	Example new backend . . . . .	66

<b>28</b>	<b>Testing</b>	<b>69</b>
28.1	Creating a stub backend . . . . .	69
28.2	Specifying behavior . . . . .	69
28.3	Simulating exceptions . . . . .	71
28.4	Adjusting the response body type . . . . .	71
28.5	Example: returning JSON . . . . .	72
28.6	Example: returning a file . . . . .	72
28.7	Delegating to another backend . . . . .	72
<b>29</b>	<b>Timeouts</b>	<b>75</b>
<b>30</b>	<b>SSL</b>	<b>77</b>
<b>31</b>	<b>Proxy support</b>	<b>79</b>
<b>32</b>	<b>Redirects</b>	<b>81</b>
32.1	Redirecting POST requests . . . . .	81
<b>33</b>	<b>JSON</b>	<b>83</b>
33.1	Circe . . . . .	83
33.2	Json4s . . . . .	84
33.3	spray-json . . . . .	84
33.4	play-json . . . . .	85
<b>34</b>	<b>Other Scala HTTP clients</b>	<b>87</b>
<b>35</b>	<b>Credits</b>	<b>89</b>



Welcome!

sttp is an open-source library which provides a clean, programmer-friendly API to define HTTP requests and execute them using one of the wrapped backends, such as akka-http, async-http-client, http4s or OkHttp.

Here's a very quick example of sttp in action:

```
import com.softwaremill.sttp._

val sort: Option[String] = None
val query = "http language:scala"

// the `query` parameter is automatically url-encoded
// `sort` is removed, as the value is not defined
val request = sttp.get(uri"https://api.github.com/search/repositories?q=$query&sort=
↳$sort")

implicit val backend = HttpURLConnectionBackend()
val response = request.send()

// response.header(...): Option[String]
println(response.header("Content-Length"))

// response.unsafeBody: by default read into a String
println(response.unsafeBody)
```

For more examples, see the *usage examples* section. Or explore the features in detail:





The main `sttp` API comes in a single jar without transitive dependencies. This also includes a default, synchronous backend, which is based on Java's `URLConnection`. For production usages, you'll often want to use an alternate backend (but what's important is that the API remains the same!). See the section on *backends* for additional instructions.

## 1.1 Using sbt

The basic dependency which provides the API and the default synchronous backend is:

```
"com.softwaremill.sttp" %% "core" % "1.7.2"
```

`sttp` is available for Scala 2.11 and 2.12, and requires Java 8. The core module has no transitive dependencies.

`sttp` is also available for Scala.js 0.6. Note that not all modules are compatible and there are no backends that can be used on both.

## 1.2 Using Ammonite

If you are an `Ammonite` user, you can quickly start experimenting with `sttp` by copy-pasting the following:

```
import $ivy.`com.softwaremill.sttp::core:1.7.2`
import com.softwaremill.sttp.quick._
sttp.get(uri"https://httpbin.org/ip").send()
```

Importing the `quick` object has the same effect as importing `com.softwaremill.sttp._`, plus defining an implicit synchronous backend (`val backend = HttpURLConnectionBackend()`), so that `sttp` can be used right away.

## 1.3 Imports

Working with sttp is most convenient if you import the `sttp` package entirely:

```
import com.softwaremill.sttp._
```

This brings into scope the starting point for defining requests and some helper methods. All examples in this guide assume that this import is in place.

And that's all you need to start using sttp! To create and send your first request, import the above, type `sttp.` and see where your IDE's auto-complete gets you! Or, read on about the *basics of defining requests*.

---

## Goals of the project

---

- provide a simple, discoverable, no-surprises, reasonably type-safe API for making HTTP requests and reading responses
- separate definition of a request from request execution
- provide immutable, easily modifiable data structures for requests and responses
- support multiple execution backends, both synchronous and asynchronous
- provide support for backend-specific request/response streaming
- minimum dependencies

See also the [introduction to sttp](#) and [sttp streaming & URI interpolators](#) blogs.

### 2.1 Non-goals of the project

- implement a full HTTP client. Instead, sttp wraps existing HTTP clients, providing a consistent, programmer-friendly API. All network-related concerns such as sending the requests, connection pooling, receiving responses are delegated to the chosen backend
- provide ultimate flexibility in defining the request. While it's possible to define *most* valid HTTP requests, e.g. some of the less common body chunking approaches aren't available

### 2.2 How is sttp different from other libraries?

- immutable request builder which doesn't impose any order in which request parameters need to be specified. Such an approach allows defining partial requests with common cookies/headers/options, which can later be specialized using a specific URI and HTTP method.
- support for multiple backends, both synchronous and asynchronous, with backend-specific streaming support
- URI interpolator with context-aware escaping, optional parameters support and parameter collections



## CHAPTER 3

---

### Community

---

If you have a question, or hit a problem, feel free to ask on our [gitter channel](#)!

Or, if you encounter a bug, something is unclear in the code or documentation, don't hesitate and [open an issue](#) on GitHub.

We are also always looking for contributions and new ideas, so if you'd like to get into the project, check out the open issues, or post your own suggestions!



## 4.1 POST a form using the synchronous backend

Required dependencies:

```
libraryDependencies += List("com.softwaremill.sttp" %% "core" % "1.7.2")
```

Example code:

```
import com.softwaremill.sttp._

val signup = Some("yes")

val request = sttp
  // send the body as form data (x-www-form-urlencoded)
  .body(Map("name" -> "John", "surname" -> "doe"))
  // use an optional parameter in the URI
  .post(uri"https://httpbin.org/post?signup=$signup")

implicit val backend = HttpURLConnectionBackend()
val response = request.send()

println(response.body)
println(response.headers)
```

## 4.2 GET and parse JSON using the akka-http backend and json4s

Required dependencies:

```
libraryDependencies += List(
  "com.softwaremill.sttp" %% "akka-http-backend" % "1.7.2",
```

(continues on next page)

(continued from previous page)

```
"com.softwaremill.sttp" %% "json4s" % "1.7.2",
"org.json4s" %% "json4s-native" % "3.6.0"
)
```

Example code:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.akkahttp._
import com.softwaremill.sttp.json4s._

import scala.concurrent.ExecutionContext.Implicits.global

case class HttpBinResponse(origin: String, headers: Map[String, String])

implicit val serialization = org.json4s.native.Serialization
val request = sttp
  .get(uri"https://httpbin.org/get")
  .response(asJson[HttpBinResponse])

implicit val backend = AkkaHttpBackend()
val response: Future[Response[HttpBinResponse]] = request.send()

for {
  r <- response
} {
  println(s"Got response code: ${r.code}")
  println(r.body)
  backend.close()
}
```

### 4.3 Test an endpoint requiring multiple parameters

Required dependencies:

```
libraryDependencies += List("com.softwaremill.sttp" %% "core" % "1.7.2")
```

Example code:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.testing._

implicit val backend = SttpBackendStub.synchronous
  .whenRequestMatches(_.uri.paramsMap.contains("filter"))
  .thenRespond("Filtered")
  .whenRequestMatches(_.uri.path.contains("secret"))
  .thenRespond("42")

val parameters1 = Map("filter" -> "name=mary", "sort" -> "asc")
println(
  sttp
    .get(uri"http://example.org?search=true&$parameters1")
    .send()
    .unsafeBody)

```

(continues on next page)



(continued from previous page)

```
val parameters2 = Map("sort" -> "desc")
println(
  sttp
    .get(uri"http://example.org/secret/read?$parameters2")
    .send()
    .unsafeBody)
```



---

## HTTP Constants

---

sttp provides constants for common HTTP header names, media types, and status codes.

Constants for common header names are provided by the `HeaderNames` trait and object.

Constants for common media types are provided by the `MediaTypes` trait and object.

Constants for common status codes are provided by the `StatusCodes` trait and object.

Example with objects:

```
import com.softwaremill.sttp._

object Example {
  val request = sttp.header(HeaderNames.ContentType, MediaTypes.Json).get(uri"https://
↪httpbin.org")
  implicit val backend = HttpURLConnectionBackend()
  val response = request.send()
  if (response.code == StatusCodes.Ok) println("Ok!")
}
```

Example with traits:

```
import com.softwaremill.sttp._

object Example extends HeaderNames with MediaTypes with StatusCodes {
  val request = sttp.header(ContentType, Json).get(uri"https://httpbin.org")

  implicit val backend = HttpURLConnectionBackend()
  val response = request.send()
  if (response.code == Ok) println("Ok!")
}
```

**For more information see**

- [https://en.wikipedia.org/wiki/List\\_of\\_HTTP\\_header\\_fields](https://en.wikipedia.org/wiki/List_of_HTTP_header_fields)
- [https://en.wikipedia.org/wiki/Media\\_type](https://en.wikipedia.org/wiki/Media_type)

- [https://en.wikipedia.org/wiki/List\\_of\\_HTTP\\_status\\_codes](https://en.wikipedia.org/wiki/List_of_HTTP_status_codes)

---

## Request definition basics

---

As mentioned in the *quickstart*, the following import will be needed:

```
import com.softwaremill.sttp._
```

This brings into scope `sttp`, the starting request. This request can be customised, each time yielding a new, immutable request definition (unless a mutable body is set on the request, such as a byte array). As the request definition is immutable, it can be freely stored in values, shared across threads, and customized multiple times in various ways.

For example, we can set a cookie, `String`-body and specify that this should be a `POST` request to a given URI:

```
val request = sttp
  .cookie("login", "me")
  .body("This is a test")
  .post(uri"http://endpoint.com/secret")
```

The request parameters (headers, cookies, body etc.) can be specified **in any order**. It doesn't matter if the request method, the body, the headers or connection options are specified in this sequence or another. This way you can build arbitrary request templates, capturing all that's common among your requests, and customizing as needed. Remember that each time a modifier is applied to a request, you get a new immutable object.

There's a lot of ways in which you can customize a request, which are covered in this guide. Another option is to just explore the API: most of the methods are self-explanatory and carry scaladocs if needed.

Using the modifiers, each time we get a new request definition, but it's just a description: a data object; nothing is sent over the network until the `send()` method is invoked.

### 6.1 Sending a request

A request definition can be created without knowing how it will be sent. But to send a request, a backend is needed. A default, synchronous backend based on Java's `URLConnection` is provided out-of-the box.

To invoke the `send()` method on a request description, an implicit value of type `SttpBackend` needs to be in scope:

```
implicit val backend = HttpURLConnectionBackend()
val response: Response[String] = request.send()
```

The default backend doesn't wrap the response into any container, but other asynchronous backends might do so. See the section on *backends* for more details.

---

**Note:** Only requests with the request method and uri can be sent. If trying to send a request without these components specified, a compile-time error will be reported. On how this is implemented, see the documentation on the *type of request definitions*.

---

## 6.2 Starting requests

sttp provides two starting requests:

- `sttp`, which is an empty request with the `Accept-Encoding: gzip, deflate` header added. That's the one that is most commonly used.
- `empty`, a completely empty request, with no headers at all.

Both of these requests will by default read the response body into a UTF-8 `String`. How the response body is handled is also part of the request definition. See the section on *response body specifications* for more details on how to customize that.

## 6.3 Debugging requests

sttp comes with builtin request to curl converter. To convert request to curl invocation use `toCurl` method.

For example converting given request:

```
sttp.get(uri"http://httpbin.org/ip").toCurl
```

will result in following curl command:

```
curl -L --max-redirs 32 -X GET "http://httpbin.org/ip"
```

Note that the `Accept-Encoding` header, which is added by default to all requests (`Accept-Encoding: gzip, deflate`) is filtered out from the generated command, so that when running a request from the command line, the result has higher chance of being human-readable, and not compressed.

A request can only be sent if the request method & URI are defined. To represent URIs, sttp comes with a `Uri` case class, which captures all of the parts of an address.

To specify the request method and URI, use one of the methods on the request definition corresponding to the name of the desired HTTP method: `.post`, `.get`, `.put` etc. All of them accept a single parameter, the URI to which the request should be sent (these methods only modify the request definition; they don't send the requests).

The `Uri` class is immutable, and can be constructed by hand, but in many cases the URI interpolator will be easier to use.

## 7.1 URI interpolator

Using the URI interpolator it's possible to conveniently create `Uri` instances, for example:

```
import com.softwaremill.sttp._

val user = "Mary Smith"
val filter = "programming languages"

val endpoint: Uri = uri"http://example.com/$user/skills?filter=$filter"

assert(endpoint.toString ==
  "http://example.com/Mary%20Smith/skills?filter=programming+languages")
```

Note the `uri` prefix before the string and the standard Scala string-embedding syntax (`$user`, `$filter`).

Any values embedded in the URI will be URL-encoded, taking into account the context (e.g., the whitespace in `user` will be %-encoded as `%20D`, while the whitespace in `filter` will be query-encoded as `+`). On the other hand, parts of the URI given as literal strings (not embedded values), are assumed to be URL-encoded and thus will be decoded when creating a `Uri` instance.

All components of the URI can be embedded from values: scheme, username/password, host, port, path, query and fragment. The embedded values won't be further parsed, with the exception of the `:` in the host part, which is commonly used to pass in both the host and port:

```
println(uri"http://example.org/${"a/b"}")
// the embedded / is escaped: http://example.org/a%2Fb

println(uri"http://example.org/${"a"}/${"b"}")
// the embedded / is escaped: http://example.org/a/b

println(uri"http://${"example.org:8080"}")
// the embedded : is not escaped: http://example.org:8080
```

Both the `Uri` class and the interpolator can be used stand-alone, without using the rest of sttp. Conversions are available both from and to `java.net.URI`; `Uri.toString` returns the URI as a `String`.

## 7.2 Optional values

The URI interpolator supports optional values for hosts (subdomains), query parameters and the fragment. If the value is `None`, the appropriate URI component will be removed. For example:

```
val v1 = None
val v2 = Some("v2")

val u1 = uri"http://example.com?p1=$v1&p2=v2"
assert(u1.toString == "http://example.com?p2=v2")

val u2 = uri"http://$v1.$v2.example.com"
assert(u2.toString == "http://v2.example.com")

val u3 = uri"http://example.com#$v1"
assert(u3.toString == "http://example.com")
```

## 7.3 Maps and sequences

Maps, sequences of tuples and sequences of values can be embedded in the query part. They will be expanded into query parameters. Maps and sequences of tuples can also contain optional values, for which mappings will be removed if `None`.

For example:

```
val ps = Map("p1" -> "v1", "p2" -> "v2")
val u4 = uri"http://example.com?$ps&p3=p4"
assert(u4.toString == "http://example.com?p1=v1&p2=v2&p3=p4")
```

Sequences in the host part will be expanded to a subdomain sequence, and sequences in the path will be expanded to path components:

```
val ps = List("a", "b", "c")
val u5 = uri"http://example.com/$ps"
assert(u5.toString == "http://example.com/a/b/c")
```



## 7.4 Special cases

If a string containing the protocol is embedded *as the very beginning*, it will not be escaped, allowing to embed entire addresses as prefixes, e.g.: `uri"$endpoint/login"`, where `val endpoint = "http://example.com/api"`.

This is useful when a base URI is stored in a value, and can then be used as a base for constructing more specific URIs.

## 7.5 All features combined

A fully-featured example:

```
import com.softwaremill.sttp._
val secure = true
val scheme = if (secure) "https" else "http"
val subdomains = List("sub1", "sub2")
val vx = Some("y z")
val params = Map("a" -> 1, "b" -> 2)
val jumpTo = Some("section2")
uri"$scheme://$subdomains.example.com?x=$vx&$params#$jumpTo"

// generates:
// https://sub1.sub2.example.com?x=y+z&a=1&b=2#section2
```



Arbitrary headers can be set on the request using the `.header` method:

```
sttp.header("User-Agent", "myapp")
```

As with any other request definition modifier, this method will yield a new request, which has the given header set. The headers can be set at any point when defining the request, arbitrarily interleaved with other modifiers.

While most headers should be set only once on a request, HTTP allows setting a header multiple times. That's why the `header` method has an additional optional boolean parameter, `replaceExisting`, which defaults to `true`. This way, if the same header is specified twice, only the last value will be included in the request. If previous values should be preserved, set this parameter to `false`.

There are also variants of this method accepting a number of headers:

```
def header(k: String, v: String, replaceExisting: Boolean = false)
def headers(hs: Map[String, String])
def headers(hs: (String, String)*)
```

Both of the `headers` append the given headers to the ones currently in the request, without removing duplicates.

## 8.1 Common headers

For some common headers, dedicated methods are provided:

```
def contentType(ct: String)
def contentType(ct: String, encoding: String)
def contentLength(l: Long)
def acceptEncoding(encoding: String)
```

See also documentation on setting *cookies* and *authentication*.



Cookies sent in requests are key-value pairs contained in the `Cookie` header. They can be set on a request in a couple of ways. The first is using the `.cookie(name: String, value: String)` method. This will yield a new request definition which, when sent, will contain the given cookie.

Cookies are currently only available on the JVM.

Cookies can also be set using the following methods:

```
def cookie(nv: (String, String))
def cookie(n: String, v: String)
def cookies(nvs: (String, String)*)
```

## 9.1 Cookies from responses

It is often necessary to copy cookies from a response, e.g. after a login request is sent, and a successful response with the authentication cookie received. Having an object `response: Response[_]`, cookies on a request can be copied:

```
// Method signature
def cookies(r: Response[_])

// Usage
sttp.cookies(response)
```

Or, it's also possible to store only the `com.softwaremill.sttp.Cookie` objects (a sequence of which can be obtained from a response), and set the on the request:

```
def cookies(cs: Seq[Cookie])
```



## CHAPTER 10

---

### Authentication

---

sttp supports basic and bearer-token based authentication. In both cases, an `Authorization` header is added with the appropriate credentials.

Basic authentication, using which the username and password are encoded using Base64, can be added as follows:

```
sttp.auth.basic(username, password)
```

A bearer token can be added using:

```
sttp.auth.bearer(token)
```





---

## Setting the request body

---

### 11.1 Text data

In its simplest form, the request's body can be set as a `String`. By default, this method will:

- use the UTF-8 encoding to convert the string to a byte array
- if not specified before, set `Content-Type: text/plain`
- if not specified before, set `Content-Length` to the number of bytes in the array

A `String` body can be set on a request as follows:

```
sttp.body("Hello, world!")
```

It is also possible to use a different character encoding:

```
def body(b: String)
def body(b: String, encoding: String)
```

### 11.2 Binary data

To set a binary-data body, the following methods are available:

```
def body(b: Array[Byte])
def body(b: ByteBuffer)
def body(b: InputStream)
```

If not specified before, these methods will set the content type to `application/octet-stream`. When using a byte array, additionally the content length will be set to the length of the array (unless specified explicitly).

---

**Note:** While the object defining a request is immutable, setting a mutable request body will make the whole request definition mutable as well. With `InputStream`, the request can be moreover sent only once, as input streams can be

---

consumed once.

---

## 11.3 Uploading files

To upload a file, simply set the request body as a `File` or `Path`:

```
def body(f: File)
def body(b: Path)
```

Note that on JavaScript only a `Web/API/File` is allowed.

As with binary body methods, the content type will default to `application/octet-stream`, and the content length will be set to the length of the file (unless specified explicitly).

See also *multi-part* and *streaming* support.

## 11.4 Form data

If you set the body as a `Map[String, String]` or `Seq[(String, String)]`, it will be encoded as form-data (as if a web form with the given values was submitted). The content type will default to `application/x-www-form-urlencoded`; content length will also be set if not specified.

By default, the UTF-8 encoding is used, but can be also specified explicitly:

```
def body(fs: Map[String, String])
def body(fs: Map[String, String], encoding: String)
def body(fs: (String, String)*)
def body(fs: Seq[(String, String)], encoding: String)
```

## 11.5 Custom body serializers

It is also possible to set custom types as request bodies, as long as there's an implicit `BodySerializer[B]` value in scope, which is simply an alias for a function:

```
type BodySerializer[B] = B => BasicRequestBody
```

A `BasicRequestBody` is a wrapper for one of the supported request body types: a `String`/byte array or an input stream.

For example, here's how to write a custom serializer for a case class, with serializer-specific default content type:

```
case class Person(name: String, surname: String, age: Int)

// for this example, assuming names/surnames can't contain commas
implicit val personSerializer: BodySerializer[Person] = { p: Person =>
  val serialized = s"${p.name}, ${p.surname}, ${p.age}"
  StringBody(serialized, "UTF-8", Some("application/csv"))
}

sttp.body(Person("mary", "smith", 67))
```

See the implementations of the `BasicRequestBody` trait for more options.

---

## Multipart requests

---

To set a multipart body on a request, the `multipartBody` method should be used (instead of `body`). Each body part is represented as an instance of `Multipart`, which can be conveniently constructed using `multipart` methods coming from the `com.softwaremill.sttp` package.

A single part of a multipart request consist of a mandatory name and a payload of type:

- `String`
- `Array[Byte]`
- `ByteBuffer`
- `InputStream`
- `Map[String, String]`
- `Seq[(String, String)]`

To add a file part, the `multipartFile` method (also from the `com.softwaremill.sttp` package) should be used. This method is overloaded and supports `File/Path` objects on the JVM, and `Web/API/File` on JS.

The content type of each part is by default the same as when setting simple bodies: `text/plain` for parts of type `String`, `application/x-www-form-urlencoded` for parts of key-value pairs (form data) and `application/octet-stream` otherwise (for binary data).

The parts can be specified using either a `Seq[Multipart]` or by using multiple arguments:

```
def multipartBody(ps: Seq[Multipart])
def multipartBody(p1: Multipart, ps: Multipart*)
```

For example:

```
sttp.multipartBody(
  multipart("text_part", "data1"),
  multipartFile("file_part", someFile), // someFile: File
  multipart("form_part", Map("x" -> "10", "y" -> "yes"))
)
```

## 12.1 Customising part meta-data

For each part, an optional filename can be specified, as well as a custom content type and additional headers. The following methods are available on `Multipart` instances:

```
case class Multipart {  
  def fileName(v: String): Multipart  
  def contentType(v: String): Multipart  
  def header(k: String, v: String): Multipart  
}
```

For example:

```
sttp.multipartBody(  
  multipartFile("logo", logoFile).fileName("logo.jpg").contentType("image/jpeg"),  
  multipartFile("text", docFile).fileName("text.doc")  
)
```

---

## Streaming

---

Some backends (see *backends summary*) support streaming bodies. If that's the case, you can set a stream of the supported type as a request body using the `streamBody` method, instead of the usual `body` method.

---

**Note:** Here, streaming refers to (usually) non-blocking, asynchronous streams of data. To send data which is available as an `InputStream`, or a file from local storage (which is available as a `File` or `Path`), no special backend support is needed. See the documentation on *setting the request body*.

---

For example, using the *akka-http backend*, a request with a streaming body can be defined as follows:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.akkahttp._

import akka.stream.scaladsl.Source
import akka.util.ByteString

val source: Source[ByteString, Any] = ...

sttp
  .streamBody(source)
  .post(uri"...")
```

---

**Note:** A request with the body set as a stream can only be sent using a backend supporting exactly the given type of streams.

---



---

## The type of request definitions

---

All request definitions have type `RequestT[U, T, S]` (`RequestT` as in `Request Template`). If this looks a bit complex, don't worry, what the three type parameters stand for is the only thing you'll hopefully have to remember when using the API!

Going one-by-one:

- `U[_]` specifies if the request method and URL are specified. Using the API, this can be either type `Empty[X] = None`, meaning that the request has neither a method nor an URI. Or, it can be type `Id[X] = X` (type-level identity), meaning that the request has both a method and an URI specified. Only requests with a specified URI & method can be sent.
- `T` specifies the type to which the response will be read. By default, this is `String`. But it can also be e.g. `Array[Byte]` or `Unit`, if the response should be ignored. Response body handling can be changed by calling the `.response` method. With backends which support streaming, this can also be a supported stream type. See *response body specifications* for more details.
- `S` specifies the stream type that this request uses. Most of the time this will be `Nothing`, meaning that this request does not send a streaming body or receive a streaming response. So most of the time you can just ignore that parameter. But, if you are using a streaming backend and want to send/receive a stream, the `.streamBody` or `response(asStream[S])` will change the type parameter.

There are two type aliases for the request template that are used:

- `type Request[T, S] = RequestT[Id, T, S]`. A sendable request.
- `type PartialRequest[T, S] = RequestT[Empty, T, S]`

As `sttp`, the starting request, by default reads the body into a `String`, its type is:

```
sttp: PartialRequest[String, Nothing]
```





Responses are represented as instances of the case class `Response[T]`, where `T` is the type of the response body. When sending a request, the response will be returned in a wrapper. For example, for asynchronous backends, we can get a `Future[Response[T]]`, while for the default synchronous backend, the wrapper will be a no-op, `Id`, which is the same as no wrapper at all.

If sending the request fails, either due to client or connection errors, an exception will be thrown (synchronous backends), or an error will be represented in the wrapper (e.g. a failed future).

---

**Note:** If the request completes, but results in a non-2xx return code, the request is still considered successful, that is, a `Response[T]` will be returned. See *response body specifications* and/or *handling non 2xx responses* for details on how such cases are handled.

---

## 15.1 Response code

The response code is available through the `.code` property. There are also methods such as `.isSuccess` or `.isServerError` for checking specific response code ranges.

## 15.2 Response headers

Response headers are available through the `.headers` property, which gives all headers as a sequence (not as a map, as there can be multiple headers with the same name).

Individual headers can be obtained using the methods:

```
def header(h: String): Option[String]
def headers(h: String): Seq[String]
```

There are also helper methods available to read some commonly accessed headers:

```
def contentType: Option[String]
def contentLength: Option[Long]
```

Finally, it's possible to parse the response cookies into a sequence of the `Cookie` case class:

```
def cookies: Seq[Cookie]
```

If the cookies from a response should be set without changes on the request, this can be done directly; see the *cookies* section in the request definition documentation.

## 15.3 Obtaining the response body

The response body can be obtained through the `.body: Either[String, T]` lazy value or the `.rawErrorBody: Either[Array[Byte], T]` property. `T` is the body deserialized as specified in the request - see the next section on *response body specifications*.

The response body is an either as the body can only be deserialized if the server responded with one of the expected status codes (by default it's any 2xx code). Otherwise, the response body is most probably an error message.

Hence, `response.body` will be a:

- `Left(errorMessage)` if the request is successful, but response code is not expected (non 2xx by default).
- `Right(deserializedBody)` if the request is successful and the response code is expected (2xx by default).

To learn how to obtain non 2xx response body see *this section*.

You can also forcibly get the deserialized body, regardless of the response code and risking an exception being thrown, using the `response.unsafeBody` method.

---

## Response body specification

---

By default, the received response body will be read as a `String`, using the encoding specified in the `Content-Type` response header (and if none is specified, using UTF-8). This is of course configurable: response bodies can be ignored, deserialized into custom types, received as a stream or saved to a file.

How the response body will be read is part of the request definition, as already when sending the request, the backend needs to know what to do with the response. The type to which the response body should be deserialized is the second type parameter of `RequestT`, and stored in the request definition as the `request.response: ResponseAs[T, S]` property.

### 16.1 Basic response specifications

To conveniently specify how to deserialize the response body, a number of `asXxx` methods are available. They can be used to provide a value for the request definition's response modifier:

```
sttp.response(asByteArray)
```

When the above request is completed and sent, it will result in a `Response[Array[Byte]]`. Other possible response specifications are:

```
def ignore: ResponseAs[Unit, Nothing]
def asString: ResponseAs[String, Nothing]
def asString(encoding: String): ResponseAs[String, Nothing]
def asByteArray: ResponseAs[Array[Byte], Nothing]
def asParams: ResponseAs[Seq[(String, String)], Nothing]
def asParams(encoding: String): ResponseAs[Seq[(String, String)], Nothing] =
def asFile(file: File, overwrite: Boolean = false): ResponseAs[File, Nothing]
def asPath(path: Path, overwrite: Boolean = false): ResponseAs[Path, Nothing]
```

Hence, to discard the response body, simply specify:

```
sttp.response(ignore)
```

And to save the response to a file:

```
sttp.response(asFile(someFile))
```

**Note:** As the handling of response is specified upfront, there's no need to “consume” the response body. It can be safely discarded if not needed.

---

## 16.2 Handling non 2xx responses

By default only a successful (2xx) response body can be obtained. To customize this behaviour use `.parseResponseIf` method:

```
val response =
  sttp
    .post(uri"(...)")
    .body(requestPayload)
    .response(asXxx)
    .parseResponseIf(status => status == 400 || status == 200)
    .send()
```

## 16.3 Custom body deserializers

It's possible to define custom body deserializers by taking any of the built-in response specifications and mapping over them. Each `ResponseAs` instance has `map` and `mapWithMetadata` methods, which can be used to transform it to a specification for another type (optionally using response metadata, such as headers or the status code). Each such value is immutable and can be used multiple times.

As an example, to read the response body as an int, the following response specification can be defined (warning: this ignores the possibility of exceptions!):

```
val asInt: ResponseAs[Int, Nothing] = asString.map(_.toInt)

sttp
  .response(asInt)
  ...
```

To integrate with a third-party JSON library:

```
def parseJson(json: String): Either[JsonError, JsonAST] = ...
val asJson: ResponseAs[Either[JsonError, JsonAST], Nothing] = asString.map(parseJson)

sttp
  .response(asJson)
  ...
```

For some mapped response specifications available out-of-the-box, see *json support*.

## 16.4 Streaming

If the backend used supports streaming (see *backends summary*), it's possible to receive responses as a stream. This can be specified using the following method:

```
def asStream[S]: ResponseAs[S, S] = ResponseAsStream[S, S]()
```

For example, when using the *akka-http* backend:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.akkahttp._

import akka.stream.scaladsl.Source
import akka.util.ByteString

implicit val sttpBackend = AkkaHttpBackend()

val response: Future[Response[Source[ByteString, Any]]] =
  sttp
    .post(uri"...")
    .response(asStream[Source[ByteString, Any]])
    .send()
```

---

**Note:** Unlike with non-streaming response handlers, each streaming response should be entirely consumed by client code.

---



---

## Supported backends

---

sttp supports a number of synchronous and asynchronous backends. It's the backends that take care of managing connections, sending requests and receiving responses: sttp defines only the API to describe the requests to be send and handle the response data. It's the backends where all the heavy-lifting is done.

Choosing the right backend depends on a number of factors: if you are using sttp to explore some data, or is it a production system; are you using a synchronous, blocking architecture or an asynchronous one; do you work mostly with Scala's `Future`, or maybe you use some form of a `Task` abstraction; finally, if you want to stream requests/responses, or not.

Each backend has two type parameters:

- `R[_]`, the type constructor in which responses are wrapped. That is, when you invoke `send()` on a request description, do you get a `Response[_]` directly, or is it wrapped in a `Future` or a `Task`?
- `S`, the type of supported streams. If `Nothing`, streaming is not supported. Otherwise, the given type can be used to send request bodies or receive response bodies.

Below is a summary of all the backends. See the sections on individual backend implementations for more information.

Class	Response wrapper	Supported stream type
HttpURLConnectionBackend	None (Id)	n/a
TryHttpURLConnectionBackend	scala.util.Try	n/a
AkkaHttpBackend	scala.concurrent.Future	akka.stream.scaladsl.Source[ByteString, Any]
AsyncHttpClientFutureBackend	scala.concurrent.Future	n/a
AsyncHttpClientScalazBackend	scalaz.concurrent.Task	n/a
AsyncHttpClientZioBackend	zio.IO	n/a
AsyncHttpClientZioStreamsBackend	zio.IO	zio.stream.Stream[Throwable, ByteBuffer]
AsyncHttpClientMonixBackend	monix.eval.Task	monix.reactive.Observable[ByteBuffer]
AsyncHttpClientCatsBackend	F[_]: cats.effect.Async	n/a
AsyncHttpClientFs2Backend	F[_]: cats.effect.Async	fs2.Stream[F, ByteBuffer]
OkHttpSyncBackend	None (Id)	n/a
OkHttpFutureBackend	scala.concurrent.Future	n/a
OkHttpMonixBackend	monix.eval.Task	monix.reactive.Observable[ByteBuffer]
Http4sBackend	F[_]: cats.effect.Effect	fs2.Stream[F, Byte]

There are also backends which wrap other backends to provide additional functionality. These include:

- TryBackend, which safely wraps any exceptions thrown by a synchronous backend in `scala.util.Try`
- BraveBackend, for Zipkin-compatible distributed tracing. See the *dedicated section*.
- PrometheusBackend, for gathering Prometheus-format metrics. See the *dedicated section*.

In addition there are also backends for JavaScript:

Class	Response wrapper	Supported stream type
FetchBackend	scala.concurrent.Future	n/a
FetchMonixBackend	monix.eval.Task	monix.reactive.Observable[ByteBuffer]

and Scala Native:

Class	Response wrapper	Supported stream type
CurlBackend	None (id)	n/a
CurlTryBackend	scala.util.Try	n/a

Finally, there are third-party backends:

- `sttp-play-ws` for “standard” play-ws (not standalone).
- `akkaMonixSttpBackend`, an Akka-based backend, but using Monix’s Task & Observable.



---

## Starting & cleaning up

---

In case of most backends, you should only instantiate a backend once per application, as a backend typically allocates resources such as thread or connection pools.

When ending the application, make sure to call `backend.close()`, which will free up resources used by the backend (if any). The close process might be asynchronous, that is it can complete after the `close()` method returns.

Note that only resources allocated by the backends are freed. For example, if you use the `AkkaHttpBackend()` the `close()` method will terminate the underlying actor system. However, if you have provided an existing actor system upon backend creation (`AkkaHttpBackend.usingActorSystem()`), the `close()` method will be a no-op.



## CHAPTER 19

---

### HttpURLConnection backend

---

The default **synchronous** backend. Sending a request returns a response wrapped in the identity type constructor, which is equivalent to no wrapper at all.

To use, add an implicit value:

```
implicit val sttpBackend = HttpURLConnectionBackend()
```



## CHAPTER 20

---

### akka-http backend

---

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "akka-http-backend" % "1.7.2"
```

This backend depends on `akka-http`. A fully **asynchronous** backend. Sending a request returns a response wrapped in a `Future`.

Note that you'll also need an explicit dependency on `akka-streams`, as `akka-http` doesn't depend on any specific `akka-streams` version. So you'll also need to add, for example:

```
"com.typesafe.akka" %% "akka-stream" % "2.5.11"
```

Next you'll need to add an implicit value:

```
implicit val sttpBackend = AkkaHttpBackend()

// or, if you'd like to use an existing actor system:
implicit val sttpBackend = AkkaHttpBackend.usingActorSystem(actorSystem)
```

This backend supports sending and receiving `akka-streams` streams of type `akka.stream.scaladsl.Source[ByteString, Any]`.

To set the request body as a stream:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.akkahttp._

import akka.stream.scaladsl.Source
import akka.util.ByteString

val source: Source[ByteString, Any] = ...

sttp
  .streamBody(source)
  .post(uri"...")
```

To receive the response body as a stream:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.akkahttp._

import akka.stream.scaladsl.Source
import akka.util.ByteString

implicit val sttpBackend = AkkaHttpBackend()

val response: Future[Response[Source[ByteString, Any]]] =
  sttp
    .post(uri"...")
    .response(asStream[Source[ByteString, Any]])
    .send()
```

## 20.1 Testing

For testing, you can create a backend using any *HttpRequest => Future[HttpResponse]* function, or an akka-http *Route*.

That way, you can “mock” a server that the backend will talk to, without starting any actual server or making any HTTP calls.

If your application provides a client library for its dependants to use, this is a great way to ensure that the client actually matches the routes exposed by your application:

```
val backend: SttpBackend[Future, Nothing] = {
  AkkaHttpBackend.usingClient(system, http = AkkaHttpClient.stubFromRoute(Routes.
↪ route))
}
```

---

## async-http-client backend

---

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "async-http-client-backend-future" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-scalaz" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-zio" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-zio-streams" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-monix" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-cats" % "1.7.2"
// or
"com.softwaremill.sttp" %% "async-http-client-backend-fs2" % "1.7.2"
```

This backend depends on `async-http-client`. A fully **asynchronous** backend, which uses `Netty` behind the scenes.

The responses are wrapped depending on the dependency chosen in either a:

- standard Scala `Future`
- `Scalaz Task`. There's a transitive dependency on `scalaz-concurrent`.
- `ZIO IO`. There's a transitive dependency on `zio`.
- `Monix Task`. There's a transitive dependency on `monix-eval`.
- Any type implementing the `Cats Effect Async` typeclass, such as `cats.effect.IO`. There's a transitive dependency on `cats-effect`.
- `fs2 Stream`. There are transitive dependencies on `fs2`, `fs2-reactive-streams`, and `cats-effect`.

Next you'll need to add an implicit value:

```
implicit val sttpBackend = AsyncHttpClientFutureBackend()
```

(continues on next page)

(continued from previous page)

```

// or, if you're using the scalaz version:
implicit val sttpBackend = AsyncHttpClientScalazBackend()

// or, if you're using the zio version:
implicit val sttpBackend = AsyncHttpClientZioBackend()

// or, if you're using the zio version with zio-streams for http streaming:
implicit val sttpBackend = AsyncHttpClientZioStreamsBackend()

// or, if you're using the monix version:
implicit val sttpBackend = AsyncHttpClientMonixBackend()

// or, if you're using the cats effect version:
implicit val sttpBackend = AsyncHttpClientCatsBackend[cats.effect.IO]()

// or, if you're using the fs2 version:
implicit val sttpBackend = AsyncHttpClientFs2Backend[cats.effect.IO]()

// or, if you'd like to use custom configuration:
implicit val sttpBackend = AsyncHttpClientFutureBackend.
  ↪usingConfig(asyncHttpClientConfig)

// or, if you'd like to use adjust the configuration sttp creates:
implicit val sttpBackend = AsyncHttpClientFutureBackend.
  ↪usingConfigBuilder(adjustFunction, sttpOptions)

// or, if you'd like to instantiate the AsyncHttpClient yourself:
implicit val sttpBackend = AsyncHttpClientFutureBackend.usingClient(asyncHttpClient)

```

## 21.1 Streaming using Monix

The Monix backend supports streaming (as both Monix and Async Http Client support reactive streams Publishers out of the box). The type of supported streams in this case is `Observable[ByteBuffer]`. That is, you can set such an observable as a request body:

```

import com.softwaremill.sttp._
import com.softwaremill.sttp.asynchttpclient.monix._

import java.nio.ByteBuffer
import monix.reactive.Observable

implicit val sttpBackend = AsyncHttpClientMonixBackend()

val obs: Observable[ByteBuffer] = ...

sttp
  .streamBody(obs)
  .post(uri"...")

```

And receive responses as an observable stream:

```

import com.softwaremill.sttp._
import com.softwaremill.sttp.asynchttpclient.monix._

```

(continues on next page)



(continued from previous page)

```
import java.nio.ByteBuffer
import monix.eval.Task
import monix.reactive.Observable
import scala.concurrent.duration.Duration

implicit val sttpBackend = AsyncHttpClientMonixBackend()

val response: Task[Response[Observable[ByteBuffer]]] =
  sttp
    .post(uri"...")
    .response(asStream[Observable[ByteBuffer]])
    .readTimeout(Duration.Inf)
    .send()
```

## 21.2 Streaming using fs2

The fs2 backend supports streaming in any instance of the `cats.effect.Effect` typeclass, such as `cats.effect.IO`. If `IO` is used then the type of supported streams is `fs2.Stream[IO, ByteBuffer]`.

Requests can be sent with a streaming body like this:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.asyncHttpClient.fs2.AsyncHttpClientFs2Backend

import java.nio.ByteBuffer
import cats.effect.{ContextShift, IO}
import fs2.Stream

implicit val cs: ContextShift[IO] = IO.contextShift(ExecutionContext.Implicits.global)
implicit val sttpBackend = AsyncHttpClientFs2Backend[IO]()

val stream: Stream[IO, ByteBuffer] = ...

sttp
  .streamBody(stream)
  .post(uri"...")
```

Responses can also be streamed:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.asyncHttpClient.fs2.AsyncHttpClientFs2Backend

import java.nio.ByteBuffer
import cats.effect.{ContextShift, IO}
import fs2.Stream
import scala.concurrent.duration.Duration

implicit val cs: ContextShift[IO] = IO.contextShift(ExecutionContext.Implicits.global)
implicit val sttpBackend = AsyncHttpClientFs2Backend[IO]()

val response: IO[Response[Stream[IO, ByteBuffer]]] =
  sttp
    .post(uri"...")
    .response(asStream[Stream[IO, ByteBuffer]])
```

(continues on next page)

(continued from previous page)

```
.readTimeout(Duration.Inf)  
.send()
```

## CHAPTER 22

---

### OkHttp backend

---

To use, add the following dependency to your project:

```
"com.squareup.okhttp3" %% "okhttp-backend" % "1.7.2"
// or, for the monix version:
"com.squareup.okhttp3" %% "okhttp-backend-monix" % "1.7.2"
```

This backend depends on [OkHttp](#), and offers:

- a **synchronous** backend: `OkHttpSyncBackend`
- an **asynchronous**, `Future`-based backend: `OkHttpFutureBackend`
- an **asynchronous**, `Monix-Task`-based backend: `OkHttpMonixBackend`

OkHttp fully supports HTTP/2.



---

### Http4s backend

---

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "http4s-backend" % "1.7.2"
```

This backend depends on [http4s](#) (blaze client), and offers an asynchronous backend, which can wrap results in any type implementing the [cats-effect Effect](#) typeclass.

Please note that: \* the backend does not support `SttpBackendOptions`, that is specifying proxy settings (proxies are not implemented in `http4s`, see [this issue](#)), as well as configuring the connect timeout \* the backend does not support the `RequestT.options.readTimeout` option

Instead, all custom timeout configuration should be done by creating a `org.http4s.client.Client[F]`, using `org.http4s.client.blaze.BlazeClientBuilder[F]` and passing it to the appropriate method of the `Http4sBackend` object.

The backend supports streaming using `fs2`. For usage details, see the documentation on [streaming using fs2 with the async-http-backend](#).



## CHAPTER 24

---

### brave backend

---

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "brave-backend" % "1.7.2"
```

This backend depends on [brave](#), a distributed tracing implementation compatible with Zipkin backend services.

The brave backend wraps any other backend, and needs an instance of brave's `HttpTracing` or `Tracing`, for example:

```
val httpTracing: HttpTracing = ...
implicit val sttpBackend = BraveBackend(AkkaHttpBackend(), httpTracing)
```

The backend obtains the current trace context using default Brave's propagation mechanisms. As it's often challenging to integrate context propagation in an asynchronous setting, there's also a possibility to add the trace context to the request's tags:

```
import com.softwaremill.sttp.brave.BraveBackend._

val parent: TraceContext = ...

sttp
  .get(...)
  .tagWithTraceContext(parent)
```





---

## Prometheus backend

---

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "prometheus-backend" % "1.7.2"
```

This backend depends on [Prometheus JVM Client](#). Keep in mind this backend registers histograms and gathers request times, but you have to expose those metrics to [Prometheus](#) e.g. using [prometheus-akka-http](#).

The Prometheus backend wraps any other backend, for example:

```
implicit val sttpBackend = PrometheusBackend(AkkaHttpBackend())
```

It gathers request execution times in `Histogram`. It uses by default `sttp_request_latency` name, defined in `PrometheusBackend.DefaultHistogramName`. It is possible to define custom histograms name by passing function mapping request to histogram name:

```
implicit val sttpBackend = PrometheusBackend(AkkaHttpBackend(), request => ↵
↳Some(request.uri.host))
```

You can disable request histograms by passing `None` returning function:

```
implicit val sttpBackend = PrometheusBackend(AkkaHttpBackend(), _ => None)
```

This backend also offers `Gauge` with currently in-progress requests number. It uses by default `sttp_requests_in_progress` name, defined in `PrometheusBackend.DefaultRequestsInProgressGaugeName`. It is possible to define custom gauge name by passing function mapping request to gauge name:

```
implicit val sttpBackend = PrometheusBackend(AkkaHttpBackend(), ↵
↳requestToInProgressGaugeNameMapper = request => Some(request.uri.host))
```

You can disable request in-progress gauges by passing `None` returning function:

```
implicit val sttpBackend = PrometheusBackend(AkkaHttpBackend(), ↵
↳requestToInProgressGaugeNameMapper = _ => None)
```



# CHAPTER 26

---

## Fetch backend

---

A JavaScript backend implemented using the [Fetch API](#) and backed via `Future`.

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "core" % "1.7.2"
```

And add an implicit value:

```
implicit val sttpBackend = FetchBackend()
```

Timeouts are handled via the new `AbortController` class. As this class only recently appeared in browsers you may need to add a `polyfill`.

As browsers do not allow access to redirect responses, if a request sets `followRedirects` to `false` then a redirect will cause the response to return an error.

Note that `Fetch` does not pass cookies by default. If your request needs cookies then you will need to pass a `FetchOptions` instance with `credentials` set to either `RequestCredentials.same-origin` or `RequestCredentials.include` depending on your requirements.

## 26.1 Node.js

Running `sttp` in a `node.js` will require downloading modules that implement the various classes and functions used by `sttp`, usually available in browser. At minima, you will need replacement for `fetch`, `AbortController` and `Headers`. To achieve this, you can either use `npm` directly, or the `scalajs-bundler` `sbt` plugin if you use `sbt`

```
npm install --save node-fetch
npm install --save abortcontroller-polyfill
npm install --save fetch-headers
```

You then need to load the modules into your runtime. This can be done in your main method as such

```
val g = scalajs.js.Dynamic.global
g.fetch = g.require("node-fetch")
g.require("abortcontroller-polyfill/dist/polyfill-patch-fetch")
g.Headers = g.require("fetch-headers")
```

## 26.2 Streaming

Streaming support is provided via `FetchMonixBackend`. Note that streaming support on Firefox is hidden behind a flag, see [ReadableStream](#) for more information.

To use, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "monix" % "1.7.2"
```

An example of streaming a response:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.impl.monix._

import java.nio.ByteBuffer
import monix.eval.Task
import monix.reactive.Observable

implicit val sttpBackend = FetchMonixBackend()

val response: Task[Response[Observable[ByteBuffer]]] =
  sttp
    .post(uri"...")
    .response(asStream[Observable[ByteBuffer]])
    .send()
```

---

**Note:** Currently no browsers support passing a stream as the request body. As such, using the `Fetch` backend with a streaming request will result in it being converted into an in-memory array before being sent. Response bodies are returned as a “proper” stream.

---

---

## Custom backends, logging, metrics

---

It is also entirely possible to write custom backends (if doing so, please consider contributing!) or wrap an existing one. One can even write completely generic wrappers for any delegate backend, as each backend comes equipped with a monad for the response type. This brings the possibility to `map` and `flatMap` over responses.

Possible use-cases for wrapper-backend include:

- logging
- capturing metrics
- request signing (transforming the request before sending it to the delegate)

### 27.1 Request tagging

Each request contains a `tags: Map[String, Any]` map. This map can be used to tag the request with any backend-specific information, and isn't used in any way by sttp itself.

Tags can be added to a request using the `def tag(k: String, v: Any)` method, and read using the `def tag(k: String): Option[Any]` method.

Backends, or backend wrappers can use tags e.g. for logging, passing a metric name, using different connection pools, or even different delegate backends.

### 27.2 Backend wrappers and redirects

By default redirects are handled at a low level, using a wrapper around the main, concrete backend: each of the backend factory methods, e.g. `HttpURLConnectionBackend()` returns a backend wrapped in `FollowRedirectsBackend`.

This causes any further backend wrappers to handle a request which involves redirects as one whole, without the intermediate requests. However, wrappers which collect metrics, implement tracing or handle request retries might want to handle every request in the redirect chain. This can be achieved by layering another

FollowRedirectsBackend on top of the wrapper. Only the top-level follow redirects backend will handle redirects, other follow redirect wrappers (at lower levels) will be disabled.

For example:

```
class MyWrapper[R[_], S] private (delegate: SttpBackend[R, S])
  extends SttpBackend[R, S] {
  ...
}

object MyWrapper {
  def apply[R[_], S](delegate: SttpBackend[R, S]): SttpBackend[R, S] = {
    // disables any other FollowRedirectsBackend-s further down the delegate chain
    new FollowRedirectsBackend(new MyWrapper(delegate))
  }
}
```

## 27.3 Example logging backend wrapper

Often it's useful to setup system-wide logging for failed requests. This is possible using a backend wrapper. In this example, we are using `scala-logging` for the logging itself, but of course any logging library can be used:

```
import com.softwaremill.sttp.{MonadError, Request, Response, SttpBackend}
import com.typesafe.scalalogging.StrictLogging

class LoggingSttpBackend[R[_], S](delegate: SttpBackend[R, S]) extends SttpBackend[R, S]
  with StrictLogging {

  override def send[T](request: Request[T, S]): R[Response[T]] = {
    responseMonad.map(responseMonad.handleError(delegate.send(request)) {
      case e: Exception =>
        logger.error(s"Exception when sending request: $request", e)
        responseMonad.error(e)
    }) { response =>
      if (response.isSuccess) {
        logger.debug(s"For request: $request got response: $response")
      } else {
        logger.warn(s"For request: $request got response: $response")
      }
      response
    }
  }

  override def close(): Unit = delegate.close()
  override def responseMonad: MonadError[R] = delegate.responseMonad
}
```

Note that there are three possible outcomes of a request:

- an exception is thrown (handled with `responseMonad.handleError`), e.g. because of a connection error; here, this is logged with level `ERROR`.
- the response completes normally, but the server returns a non-2xx response code. Here, this case is logged with level `WARN`.
- the response completes normally with 2xx response code. Here, this case is logged with level `DEBUG`.

It's quite easy to customize this backend to your particular needs - just copy the code!

## 27.4 Example metrics backend wrapper

Below is an example on how to implement a backend wrapper, which sends metrics for completed requests and wraps any Future-based backend:

```
// the metrics infrastructure
trait MetricsServer {
  def reportDuration(name: String, duration: Long): Unit
}

class CloudMetricsServer extends MetricsServer {
  override def reportDuration(name: String, duration: Long): Unit = ???
}

// the backend wrapper
class MetricWrapper[S](delegate: SttpBackend[Future, S],
                      metrics: MetricsServer)
  extends SttpBackend[Future, S] {

  override def send[T](request: Request[T, S]): Future[Response[T]] = {
    val start = System.currentTimeMillis()

    def report(metricSuffix: String): Unit = {
      val metricPrefix = request.tag("metric").getOrElse("?")
      val end = System.currentTimeMillis()
      metrics.reportDuration(metricPrefix + "-" + metricSuffix, end - start)
    }

    delegate.send(request).andThen {
      case Success(response) if response.is200 => report("ok")
      case Success(response)                  => report("notok")
      case Failure(t)                          => report("exception")
    }
  }

  override def close(): Unit = delegate.close()

  override def responseMonad: MonadError[Future] = delegate.responseMonad
}

// example usage
implicit val backend = new MetricWrapper(
  AkkaHttpBackend(),
  new CloudMetricsServer()
)

sttp
  .get(uri"http://company.com/api/service1")
  .tag("metric", "service1")
  .send()
```

## 27.5 Example retrying backend wrapper

Handling retries is a complex problem when it comes to HTTP requests. When is a request retryable? There are a couple of things to take into account:

- connection exceptions are generally good candidates for retries
- only idempotent HTTP methods (such as GET) could potentially be retried
- some HTTP status codes might also be retryable (e.g. 500 Internal Server Error or 503 Service Unavailable)

In some cases it's possible to implement a generic retry mechanism; such a mechanism should take into account logging, metrics, limiting the number of retries and a backoff mechanism. These mechanisms could be quite simple, or involve e.g. retry budgets (see [Finagle's](#) documentation on retries). In sttp, it's possible to recover from errors using the `responseMonad`. A starting point for a retrying backend could be:

```
import com.softwaremill.sttp.{MonadError, Request, Response, SttpBackend}

class RetryingBackend[R[_], S](
  delegate: SttpBackend[R, S],
  shouldRetry: (Request[_], Either[Throwable, Response[_]]) => Boolean,
  maxRetries: Int)
  extends SttpBackend[R, S] {

  override def send[T](request: Request[T, S]): R[Response[T]] = {
    sendWithRetryCounter(request, 0)
  }

  private def sendWithRetryCounter[T](request: Request[T, S],
    retries: Int): R[Response[T]] = {
    val r = responseMonad.handleError(delegate.send(request)) {
      case t if shouldRetry(request, Left(t)) && retries < maxRetries =>
        sendWithRetryCounter(request, retries + 1)
    }

    responseMonad.flatMap(r) { resp =>
      if (shouldRetry(request, Right(resp)) && retries < maxRetries) {
        sendWithRetryCounter(request, retries + 1)
      } else {
        responseMonad.unit(resp)
      }
    }
  }

  override def close(): Unit = delegate.close()

  override def responseMonad: MonadError[R] = delegate.responseMonad
}
```

Note that some backends also have built-in retry mechanisms, e.g. `akka-http` or `OkHttp` (see the builder's `retryOnConnectionFailure` method).

## 27.6 Example new backend

Implementing a new backend is made easy as the tests are published in the `core` jar file under the `tests` classifier. Simply add the follow dependencies to your `build.sbt`:



```
"com.softwaremill.sttp" %% "core" % "1.7.2" % "test" classifier "tests",
"com.typesafe.akka" %% "akka-http" % "10.1.1" % "test",
"ch.megard" %% "akka-http-cors" % "0.3.0" % "test",
"com.typesafe.akka" %% "akka-stream" % "2.5.12" % "test",
"org.scalatest" %% "scalatest" % "3.0.5" % "test"
```

Implement your backend and extend the `HttpTest` class:

```
import com.softwaremill.sttp.SttpBackend
import com.softwaremill.sttp.testing.{ConvertToFuture, HttpTest}

class MyCustomBackendHttpTest extends HttpTest[Future] {

  override implicit val convertToFuture: ConvertToFuture[Future] = ConvertToFuture.
↪future
  override implicit lazy val backend: SttpBackend[Future, Nothing] = new_
↪MyCustomBackend()

}
```

You can find a more detailed example in the [sttp-vertex](#) repository.



If you need a stub backend for use in tests instead of a “real” backend (you probably don’t want to make HTTP calls during unit tests), you can use the `SttpBackendStub` class. It allows specifying how the backend should respond to requests matching given predicates.

You can also create a stub backend using *akka-http routes*.

## 28.1 Creating a stub backend

An empty backend stub can be created using the following ways:

- by using one of the factory methods `SttpBackendStub.synchronous` or `SttpBackendStub.asynchronousFuture`, which return stubs which use the `Id` or standard Scala’s `Future` response wrappers without streaming support
- by explicitly giving the response wrapper monad and supported streams type, e.g. `SttpBackendStub[Task, Observable[ByteBuffer]](TaskMonad)`
- given an instance of a “real” backend, e.g. `SttpBackendStub(URLConnectionBackend())` or `SttpBackendStub(AsyncHttpClientScalazBackend())`. The stub will then use the same response wrapper and support the same type of streams as the given “real” backend.
- by specifying a fallback/delegate backend, see below

## 28.2 Specifying behavior

Behavior of the stub can be specified using a combination of the `whenRequestMatches` and `thenRespond` methods:

```
implicit val testingBackend = SttpBackendStub.synchronous
  .whenRequestMatches(_.uri.path.startsWith(List("a", "b")))
  .thenRespond("Hello there!")
```

(continues on next page)

(continued from previous page)

```

.whenRequestMatches(_.method == Method.POST)
.thenRespondServerError()

val response1 = sttp.get(uri"http://example.org/a/b/c").send()
// response1.body will be Right("Hello there")

val response2 = sttp.post(uri"http://example.org/d/e").send()
// response2.code will be 500

```

It is also possible to match requests by partial function, returning a response. E.g.:

```

implicit val testingBackend = SttpBackendStub.synchronous
  .whenRequestMatchesPartial({
    case r if r.uri.path.endsWith(List("partial10")) =>
      Response.error("Not found", 404)

    case r if r.uri.path.endsWith(List("partialAda")) =>
      // additional verification of the request is possible
      assert(r.body == StringBody("z"))
      Response.ok("Ada")
  })

val response1 = sttp.get(uri"http://example.org/partial10").send()
// response1.body will be Right(10)

val response2 = sttp.post(uri"http://example.org/partialAda").send()
// response2.body will be Right("Ada")

```

This approach to testing has one caveat: the responses are not type-safe. That is, the stub backend cannot match on or verify that the type of the response body matches the response body type requested.

Another way to specify the behaviour is passing response wrapped in the result monad to the stub. It is useful if you need to test a scenario with a slow server, when the response should be not returned immediately, but after some time. Example with Futures:

```

implicit val testingBackend = SttpBackendStub.asynchronousFuture.whenAnyRequest
  .thenRespondWrapped(Future {
    Thread.sleep(5000)
    Response(Right("OK"), 200, "", Nil, Nil)
  })

val responseFuture = sttp.get(uri"http://example.org").send()
// responseFuture will complete after 5 seconds with "OK" response

```

The returned response may also depend on the request:

```

implicit val testingBackend = SttpBackendStub.synchronous.whenAnyRequest
  .thenRespondWrapped(req =>
    Response(Right("OK, got request sent to ${req.uri.host}"), 200, "", Nil, Nil)
  )

val response = sttp.get(uri"http://example.org").send()
// response.body will be Right("OK, got request sent to example.org")

```

You can define consecutive raw responses that will be served:

```
implicit val testingBackend = SttpBackendStub.synchronous.whenAnyRequest
  .thenRespondCyclic("first", "second", "third")

sttp.get(uri"http://example.org").send() // Right("OK, first")
sttp.get(uri"http://example.org").send() // Right("OK, second")
sttp.get(uri"http://example.org").send() // Right("OK, third")
sttp.get(uri"http://example.org").send() // Right("OK, first")
```

Or multiple *Response* instances:

```
implicit val testingBackend = SttpBackendStub.synchronous.whenAnyRequest
  .thenRespondCyclicResponses(
    Response.ok[String]("first"),
    Response.error[String]("error", 500, "Something went wrong")
  )

sttp.get(uri"http://example.org").send() // code will be 200
sttp.get(uri"http://example.org").send() // code will be 500
sttp.get(uri"http://example.org").send() // code will be 200
```

## 28.3 Simulating exceptions

If you want to simulate an exception being thrown by a backend, e.g. a socket timeout exception, you can do so by throwing the appropriate exception instead of the response, e.g.:

```
implicit val testingBackend = SttpBackendStub.synchronous
  .whenRequestMatches(_ => true)
  .thenRespond(throw new TimeoutException())
```

## 28.4 Adjusting the response body type

If the type of the response body returned by the stub's rules (as specified using the `.whenXxx` methods) doesn't match what was specified in the request, the stub will attempt to convert the body to the desired type. This might be useful when:

- testing code which maps a basic response body to a custom type, e.g. mapping a raw json string using a decoder to a domain type
- reading a classpath resource (which results in an `InputStream`) and requesting a response of e.g. type `String`

The following conversions are supported:

- anything to `()` (unit), when the response is ignored
- `InputStream` and `Array[Byte]` to `String`
- `InputStream` and `String` to `Array[Byte]`
- `InputStream`, `String` and `Array[Byte]` to custom types through mapped response specifications

## 28.5 Example: returning JSON

For example, if you want to return a JSON response, simply use `.withResponse(String)` as below::

```
implicit val testingBackend = SttpBackendStub.synchronous
  .whenRequestMatches(_ => true)
  .thenRespond(""" {"username": "john", "age": 65 } """)

def parseUserJson(a: Array[Byte]): User = ...

val response = sttp.get(uri"http://example.com")
  .response(asByteArray.map(parseUserJson))
  .send()
```

In the example above, the stub's rules specify that a response with a `String`-body should be returned for any request; the request, on the other hand, specifies that response body should be parsed from a byte array to a custom `User` type. These type don't match, so the `SttpBackendStub` will in this case convert the body to the desired type.

Note that no conversions will be attempted for streaming response bodies.

## 28.6 Example: returning a file

If you want to return a file and have a response handler set up like this:

```
val destination = new File("path/to/file.ext")
sttp.get(uri"http://example.com").response(asFile(destination))
```

Then set up the mock like this:

```
val fileResponseHandle = new File("path/to/file.ext")
SttpBackendStub.synchronous
  .whenRequestMatches(_ => true)
  .thenRespond(fileResponseHandle)
```

the `File` set up in the stub will be returned as though it was the `File` set up as destination in the response handler above. This means that the file from `fileResponseHandle` is not written to destination.

If you actually want a file to be written you can set up the stub like this:

```
val sourceFile = new File("path/to/file.ext")
val destinationFile = new File("path/to/file.ext")
SttpBackendStub.synchronous
  .whenRequestMatches(_ => true)
  .thenRespondWrapped { _ =>
    FileUtils.copyFile(sourceFile, destinationFile) // org.apache.commons.io
    IO(Response.Right(destinationFile, 200, ""))
  }
```

## 28.7 Delegating to another backend

It is also possible to create a stub backend which delegates calls to another (possibly “real”) backend if none of the specified predicates match a request. This can be useful during development, to partially stub a yet incomplete API with which we integrate:

```
implicit val testingBackend =
  SttpBackendStub.withFallback(HttpURLConnectionBackend())
    .whenRequestMatches(_.uri.path.startsWith(List("a")))
    .thenRespond("I'm a STUB!")

val response1 = sttp.get(uri"http://api.internal/a").send()
// response1.body will be Right("I'm a STUB")

val response2 = sttp.post(uri"http://api.internal/b").send()
// response2 will be whatever a "real" network call to api.internal/b returns
```





sttp supports read and connection timeouts:

- Connection timeout - can be set globally (30 seconds by default)
- Read timeout - can be set per request (1 minute by default)

How to use:

```
import com.softwaremill.sttp._
import scala.concurrent.duration._

// all backends provide a constructor that allows to specify backend options
implicit val backend = HttpURLConnectionBackend(
  options = SttpBackendOptions.connectionTimeout(1.minute))

sttp
  .get(uri"...")
  .readTimeout(5.minutes) // or Duration.Inf to turn read timeout off
  .send()
```



SSL handling can be customized (or disabled) when creating a backend and is backend-specific.

Depending on the underlying backend's client, you can customize SSL settings as follows:

- `HttpURLConnectionBackend`: when creating the backend, specify the `customizeConnection: HttpURLConnection => Unit` parameter, and set the hostname verifier & SSL socket factory as required
- `akka-http`: when creating the backend, specify the `customHttpsContext: Option[HttpsConnectionContext]` parameter. See [akka-http docs](#)
- `async-http-client`: create a custom client and use the `setSSLContext` method
- `OkHttp`: create a custom client modifying the SSL settings as described [on the wiki](#)



sttp library by default checks for your System proxy properties ([docs](#)):

Following settings are checked:

1. socksProxyHost and socksProxyPort (*default: 1080*)
2. http.proxyHost and http.proxyPort (*default: 80*) 2. https.proxyHost and https.proxyPort (*default: 443*)

Settings are loaded **in given order** and the **first existing value** is being used.

Otherwise, proxy values can be specified manually when creating a backend:

```
import com.softwaremill.sttp._

implicit val backend = HttpURLConnectionBackend(
  options = SttpBackendOptions.httpProxy("some.host", 8080))

sttp
  .get(uri"...")
  .send() // uses the proxy
```

Or in case your proxy requires authentication (supported by the JVM backends):

```
SttpBackendOptions.httpProxy("some.host", 8080, "username", "password")
```



By default, `sttp` follows redirects.

If you'd like to disable following redirects, use the `followRedirects` method:

```
sttp.followRedirects(false)
```

If a request has been redirected, the history of all followed redirects is accessible through the `response.history` list. The first response (oldest) comes first. The body of each response will be a `Left(message)` (as the status code is non-2xx), where the message is whatever the server returned as the response body.

## 32.1 Redirecting POST requests

If a POST or PUT request is redirected, by default it will be sent unchanged to the new address, that is using the original body and method. However, most browsers and some clients issue a GET request in such case, without the body.

To enable this behavior, use the `redirectToGet` method:

```
sttp.redirectToGet(true)
```

Note that this only affects 301 Moved Permanently and 302 Found redirects. 303 See Other redirects are always converted, while 307 Temporary Redirect and 308 Permanent Redirect never.





Adding support for JSON (or other format) bodies in requests/responses is a matter of providing a *body serializer* and/or a *response body specification*. Both are quite straightforward to implement, so integrating with your favorite JSON library shouldn't be a problem. However, there are some integrations available out-of-the-box.

Also read about *handling non 2xx responses* if you need to unmarshal error responses.

## 33.1 Circe

JSON encoding of bodies and decoding of responses can be handled using [Circe](#) by the `circe` module. To use add the following dependency to your project:

```
"com.softwaremill.sttp" %% "circe" % "1.7.2"
```

This module adds a method to the request and a function that can be given to a request to decode the response to a specific object:

```
import com.softwaremill.sttp._
import com.softwaremill.sttp.circe._

implicit val backend = HttpURLConnectionBackend()

// Assume that there is an implicit circe encoder in scope
// for the request Payload, and a decoder for the MyResponse
val requestPayload: Payload = ???

val response: Response[Either[DeserializationError[io.circe.Error], MyResponse]] =
  sttp
    .post(uri"...")
    .body(requestPayload)
    .response(asJson[MyResponse])
    .send()
```

## 33.2 Json4s

To encode and decode json using json4s, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "json4s" % "1.7.2"  
"org.json4s" %% "json4s-native" % "3.6.0"
```

Note that in this example we are using the json4s-native backend, but you can use any other json4s backend.

Using this module it is possible to set request bodies and read response bodies as case classes, using the implicitly available `org.json4s.Formats` (which defaults to `org.json4s.DefaultFormats`), and by bringing an implicit `org.json4s.Serialization` into scope.

Usage example:

```
import com.softwaremill.sttp._  
import com.softwaremill.sttp.json4s._  
  
implicit val backend = HttpURLConnectionBackend()  
  
case class Payload(...)  
case class MyResponse(...)  
  
val requestPayload: Payload = Payload(...)  
  
implicit val serialization = org.json4s.native.Serialization  
  
val response: Response[MyResponse] =  
  sttp  
    .post(uri "...")  
    .body(requestPayload)  
    .response(asJson[MyResponse])  
    .send()
```

## 33.3 spray-json

To encode and decode JSON using spray-json, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "spray-json" % "1.7.2"
```

Using this module it is possible to set request bodies and read response bodies as your custom types, using the implicitly available instances of `spray.json.JsonWriter` / `spray.json.JsonReader` or `spray.json.JsonFormat`.

Usage example:

```
import com.softwaremill.sttp._  
import com.softwaremill.sttp.sprayJson._  
import spray.json._  
  
implicit val backend = HttpURLConnectionBackend()  
  
case class Payload(...)  
object Payload {  
  implicit val jsonFormat: RootJsonFormat[Payload] = ...  
}
```

(continues on next page)

(continued from previous page)

```
}  
  
case class MyResponse(...)  
object MyResponse {  
  implicit val jsonFormat: RootJsonFormat[MyResponse] = ...  
}  
  
val requestPayload: Payload = Payload(...)  
  
val response: Response[MyResponse] =  
  sttp  
    .post(uri"...")  
    .body(requestPayload)  
    .response(asJson[MyResponse])  
    .send()
```

## 33.4 play-json

To encode and decode JSON using `play-json`, add the following dependency to your project:

```
"com.softwaremill.sttp" %% "play-json" % "1.7.2"
```

To use, add an import: `import com.softwaremill.sttp.playJson._`.



---

## Other Scala HTTP clients

---

- scalaj
- akka-http client
- dispatch
- play ws
- fs2-http
- http4s
- Gigahorse
- RösHTTP
- Requests-Scala

Also, check the [comparison](#) by Marco Firrincieli on how to implement a simple request using a number of Scala HTTP libraries.



## CHAPTER 35

---

### Credits

---

- Adam Warski
- Tomasz Szymański
- Omar Alejandro Mainegra Sarduy
- Bjørn Madsen
- Piotr Buda
- Piotr Gabara
- Gabriele Petronella
- Paweł Stawicki
- Michał Siatkowski
- Marcin Kubala