
web3.js Documentation

Release 1.0.0

Fabian Vogelsteller, Marek Kotewicz, Jeffrey Wilcke, Marian Oancea

Mar 03, 2019

1	Getting Started	3
1.1	Adding web3.js	3
2	Callbacks Promises Events	5
3	Glossary	7
3.1	json interface	7
4	Web3	11
4.1	Web3.modules	11
4.2	options	12
4.3	defaultBlock	13
4.4	defaultAccount	13
4.5	defaultGasPrice	13
4.6	defaultGas	14
4.7	transactionBlockTimeout	14
4.8	transactionConfirmationBlocks	14
4.9	transactionPollingTimeout	15
4.10	transactionSigner	15
4.11	setProvider	16
4.12	providers	17
4.13	givenProvider	17
4.14	currentProvider	18
4.15	BatchRequest	18
4.16	version	19
5	web3.eth	21
5.1	Note on checksum addresses	21
5.2	subscribe	22
5.3	Contract	22
5.4	Iban	22
5.5	personal	22
5.6	accounts	22
5.7	ens	22
5.8	abi	22
5.9	net	23
5.10	options	23

5.11	defaultBlock	23
5.12	defaultAccount	24
5.13	defaultGasPrice	24
5.14	defaultGas	24
5.15	transactionBlockTimeout	25
5.16	transactionConfirmationBlocks	25
5.17	transactionPollingTimeout	25
5.18	transactionSigner	26
5.19	setProvider	26
5.20	providers	27
5.21	givenProvider	28
5.22	currentProvider	28
5.23	BatchRequest	29
5.24	defaultAccount	29
5.25	defaultBlock	30
5.26	getProtocolVersion	31
5.27	isSyncing	31
5.28	getCoinbase	32
5.29	isMining	32
5.30	getHashrate	33
5.31	getGasPrice	33
5.32	getAccounts	34
5.33	getBlockNumber	34
5.34	getBalance	34
5.35	getStorageAt	35
5.36	getCode	36
5.37	getBlock	36
5.38	getBlockTransactionCount	38
5.39	getUncle	38
5.40	getTransaction	39
5.41	getTransactionFromBlock	40
5.42	getTransactionReceipt	41
5.43	getTransactionCount	42
5.44	sendTransaction	43
5.45	sendSignedTransaction	44
5.46	sign	45
5.47	signTransaction	46
5.48	call	47
5.49	estimateGas	48
5.50	getPastLogs	48
5.51	getWork	50
5.52	submitWork	50
5.53	requestAccounts	51
6	web3.eth.subscribe	53
6.1	subscribe	53
6.2	clearSubscriptions	54
6.3	subscribe(“pendingTransactions”)	55
6.4	subscribe(“newBlockHeaders”)	55
6.5	subscribe(“syncing”)	57
6.6	subscribe(“logs”)	58
7	web3.eth.Contract	61
7.1	new contract	61

7.2	= Properties =	62
7.3	options	62
7.4	options.address	63
7.5	options.jsonInterface	63
7.6	= Methods =	64
7.7	clone	64
7.8	deploy	65
7.9	methods	66
7.10	methods.myMethod.call	67
7.11	methods.myMethod.send	69
7.12	methods.myMethod.estimateGas	71
7.13	methods.myMethod.encodeABI	72
7.14	= Events =	73
7.15	once	73
7.16	events	74
7.17	events.allEvents	76
7.18	getPastEvents	76
8	web3.eth.accounts	79
8.1	create	79
8.2	privateKeyToAccount	80
8.3	signTransaction	81
8.4	recoverTransaction	82
8.5	hashMessage	83
8.6	sign	83
8.7	recover	84
8.8	encrypt	85
8.9	decrypt	86
8.10	wallet	87
8.11	wallet.create	88
8.12	wallet.add	88
8.13	wallet.remove	89
8.14	wallet.clear	90
8.15	wallet.encrypt	90
8.16	wallet.decrypt	91
8.17	wallet.save	92
8.18	wallet.load	93
9	web3.eth.personal	95
9.1	options	95
9.2	defaultBlock	96
9.3	defaultAccount	96
9.4	defaultGasPrice	97
9.5	defaultGas	97
9.6	transactionBlockTimeout	97
9.7	transactionConfirmationBlocks	98
9.8	transactionPollingTimeout	98
9.9	transactionSigner	98
9.10	setProvider	99
9.11	providers	100
9.12	givenProvider	101
9.13	currentProvider	101
9.14	BatchRequest	102
9.15	newAccount	102

9.16	sign	103
9.17	ecRecover	104
9.18	signTransaction	104
9.19	sendTransaction	106
9.20	unlockAccount	106
9.21	lockAccount	107
9.22	getAccounts	107
9.23	importRawKey	108
10	web3.eth.ens	111
10.1	registry	111
10.2	resolver	112
10.3	supportsInterface	112
10.4	getAddress	113
10.5	setAddress	113
10.6	getPubkey	115
10.7	setPubkey	115
10.8	getText	117
10.9	setText	117
10.10	getContent	119
10.11	setContent	119
10.12	getMultihash	121
10.13	setMultihash	121
10.14	getContenthash	122
10.15	setContenthash	123
10.16	Ens events	124
11	web3.eth.Iban	127
11.1	Iban instance	127
11.2	toAddress	127
11.3	toIban	128
11.4	fromAddress	129
11.5	fromBban	129
11.6	createIndirect	130
11.7	isValid	130
11.8	prototype.isValid	131
11.9	prototype.isDirect	131
11.10	prototype.isIndirect	132
11.11	prototype.checksum	132
11.12	prototype.institution	133
11.13	prototype.client	133
11.14	prototype.toAddress	133
11.15	prototype.toString	134
12	web3.eth.net	135
12.1	getId	135
12.2	isListening	136
12.3	getPeerCount	136
12.4	getNetworkType	137
13	web3.eth.abi	139
13.1	encodeFunctionSignature	139
13.2	encodeEventSignature	140
13.3	encodeParameter	141
13.4	encodeParameters	142

13.5	encodeFunctionCall	142
13.6	decodeParameter	143
13.7	decodeParameters	144
13.8	decodeLog	144
14	web3.*.net	147
14.1	getId	147
14.2	isListening	148
14.3	getPeerCount	148
15	web3.bzz	151
15.1	setProvider	151
15.2	givenProvider	152
15.3	currentProvider	152
15.4	upload	153
15.5	download	154
15.6	pick	155
16	web3.shh	157
16.1	options	157
16.2	defaultBlock	158
16.3	defaultAccount	158
16.4	defaultGasPrice	159
16.5	defaultGas	159
16.6	transactionBlockTimeout	159
16.7	transactionConfirmationBlocks	160
16.8	transactionPollingTimeout	160
16.9	transactionSigner	160
16.10	setProvider	161
16.11	providers	162
16.12	givenProvider	163
16.13	currentProvider	163
16.14	BatchRequest	164
16.15	getId	164
16.16	isListening	165
16.17	getPeerCount	165
16.18	getVersion	166
16.19	getInfo	166
16.20	setMaxMessageSize	167
16.21	setMinPoW	168
16.22	markTrustedPeer	168
16.23	newKeyPair	169
16.24	addPrivateKey	169
16.25	deleteKeyPair	170
16.26	hasKeyPair	171
16.27	getPublicKey	171
16.28	getPrivateKey	172
16.29	newSymKey	172
16.30	addSymKey	173
16.31	generateSymKeyFromPassword	173
16.32	hasSymKey	174
16.33	getSymKey	174
16.34	deleteSymKey	175
16.35	post	176

16.36	subscribe	177
16.37	clearSubscriptions	178
16.38	newMessageFilter	179
16.39	deleteMessageFilter	179
16.40	getFilterMessages	180
17	web3.utils	181
17.1	randomHex	181
17.2	BN	182
17.3	isBN	182
17.4	isBigNumber	183
17.5	sha3	183
17.6	soliditySha3	184
17.7	isHex	186
17.8	isHexStrict	186
17.9	isAddress	187
17.10	toChecksumAddress	188
17.11	checkAddressChecksum	188
17.12	toHex	189
17.13	toBN	190
17.14	hexToNumberString	190
17.15	hexToNumber	191
17.16	numberToHex	191
17.17	hexToUtf8	192
17.18	hexToAscii	192
17.19	utf8ToHex	193
17.20	asciiToHex	193
17.21	hexToBytes	194
17.22	bytesToHex	194
17.23	toWei	195
17.24	fromWei	196
17.25	unitMap	198
17.26	padLeft	199
17.27	padRight	200
17.28	toTwosComplement	201
17.29	getSignatureParameters	201

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

web3.js is a collection of libraries which allow you to interact with a local or remote ethereum node, using a HTTP or IPC connection.

The following documentation will guide you through *installing and running web3.js*, as well as providing a API reference documentation with examples.

Contents:

[Keyword Index](#), [Search Page](#)

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

The web3.js library is a collection of modules which contain specific functionality for the ethereum ecosystem.

- The `web3-eth` is for the ethereum blockchain and smart contracts
- The `web3-shh` is for the whisper protocol to communicate p2p and broadcast
- The `web3-bzz` is for the swarm protocol, the decentralized file storage
- The `web3-utils` contains useful helper functions for Dapp developers.

1.1 Adding web3.js

First you need to get web3.js into your project. This can be done using the following methods:

- `npm`: `npm install web3`
- `meteor`: `meteor add ethereum:web3`
- `pure js`: link the `dist/web3.min.js`

After that you need to create a web3 instance and set a provider. Ethereum supported Browsers like Mist or MetaMask will have a `ethereumProvider` or `web3.currentProvider` available. For web3.js, check `Web3.givenProvider`. If this property is null you should connect to a remote/local node.

```
// in node.js use: const Web3 = require('web3');  
  
const web3 = new Web3(Web3.givenProvider || "ws://localhost:8546");
```

That's it! now you can use the `web3` object.

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

Callbacks Promises Events

To help web3 integrate into all kind of projects with different standards we provide multiple ways to act on asynchronous functions.

Most web3.js objects allow a callback as the last parameter, as well as returning promises to chain functions.

Ethereum as a blockchain has different levels of finality and therefore needs to return multiple “stages” of an action. To cope with requirement we return a “promiEvent” for functions like `web3.eth.sendTransaction` or contract methods. This “promiEvent” is a promise combined with an event emitter to allow acting on different stages of action on the blockchain, like a transaction.

PromiEvents work like a normal promises with added `on`, `once` and `off` functions. This way developers can watch for additional events like on “receipt” or “transactionHash”.

```
web3.eth.sendTransaction({from: '0x123...', data: '0x432...'})
  .once('transactionHash', function(hash){ ... })
  .once('receipt', function(receipt){ ... })
  .on('confirmation', function(confNumber, receipt){ ... })
  .on('error', function(error){ ... })
  .then(function(receipt){
    // will be fired once the receipt is mined
  });
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

3.1 json interface

The json interface is a json object describing the [Application Binary Interface \(ABI\)](#) for an Ethereum smart contract.

Using this json interface web3.js is able to create JavaScript object representing the smart contract and its methods and events using the *web3.eth.Contract object*.

3.1.1 Specification

Functions:

- `type`: "function", "constructor" (can be omitted, defaulting to "function"; "fallback" also possible but not relevant in web3.js);
- `name`: the name of the function (only present for function types);
- `constant`: true if function is specified to not modify the blockchain state;
- `payable`: true if function accepts ether, defaults to false;
- `stateMutability`: a string with one of the following values: `pure` (specified to not read blockchain state), `view` (same as `constant` above), `nonpayable` and `payable` (same as `payable` above);
- `inputs`: an array of objects, each of which contains:
 - `name`: the name of the parameter;
 - `type`: the canonical type of the parameter.
- `outputs`: an array of objects same as `inputs`, can be omitted if no outputs exist.

Events:

- `type`: always "event"

- name: the name of the event;
- inputs: an array of objects, each of which contains:
 - name: the name of the parameter;
 - type: the canonical type of the parameter.
 - indexed: true if the field is part of the log's topics, false if it one of the log's data segment.
- anonymous: true if the event was declared as anonymous.

3.1.2 Example

```
contract Test {
  uint a;
  address d = 0x12345678901234567890123456789012;

  function Test(uint testInt) { a = testInt;}

  event Event(uint indexed b, bytes32 c);

  event Event2(uint indexed b, bytes32 c);

  function foo(uint b, bytes32 c) returns(address) {
    Event(b, c);
    return d;
  }
}

// would result in the JSON:
[
  {
    "type": "constructor",
    "payable": false,
    "stateMutability": "nonpayable"
    "inputs": [{"name": "testInt", "type": "uint256"}],
  },
  {
    "type": "function",
    "name": "foo",
    "constant": false,
    "payable": false,
    "stateMutability": "nonpayable",
    "inputs": [{"name": "b", "type": "uint256"}, {"name": "c", "type": "bytes32"}],
    "outputs": [{"name": "", "type": "address"}]
  },
  {
    "type": "event",
    "name": "Event",
    "inputs": [{"indexed": true, "name": "b", "type": "uint256"}, {"indexed": false, "name": "c
↔", "type": "bytes32"}],
    "anonymous": false
  },
  {
    "type": "event",
    "name": "Event2",
    "inputs": [{"indexed": true, "name": "b", "type": "uint256"}, {"indexed": false, "name": "c
↔", "type": "bytes32"}],
    "anonymous": false
  }
]
```


Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

The Web3 class is a wrapper to house all Ethereum related modules.

```
import {Web3} from 'web3';

// "Web3.providers.givenProvider" will be set if in an Ethereum supported browser.
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

> web3.eth
> web3.shh
> web3.bzz
> web3.utils
> web3.version
```

4.1 Web3.modules

Static property of the Web3 class

```
Web3.modules
```

```
Will return an object with the classes of all major sub modules, to be able to ↳  
↳ instantiate them manually.
```

4.1.1 Returns

Object: A list of modules:

- Eth - Function: the Eth module for interacting with the Ethereum network see [web3.eth](#) for more.
- Net - Function: the Net module for interacting with network properties see [web3.eth.net](#) for more.

- Personal - Function: the Personal module for interacting with the Ethereum accounts see [web3.eth.personal](#) for more.
- Shh - Function: the Shh module for interacting with the whisper protocol see [web3.shh](#) for more.
- Bzz - Function: the Bzz module for interacting with the swarm network see [web3.bzz](#) for more.

4.1.2 Example

```
Web3.modules
> {
  Eth: Eth function(provider, options?, net?),
  Net: Net function(provider, options?, net?),
  Personal: Personal function(provider, options?, net?),
  Shh: Shh function(provider, options?, net?),
  Bzz: Bzz function(provider, options?, net?),
}
```

4.2 options

An Web3 module does provide several options for configuring the transaction confirmation workflow or for defining default values. These are the currently available option properties on a Web3 module:

4.2.1 Module Options

defaultAccount

defaultBlock

defaultGas

defaultGasPrice

transactionBlockTimeout

transactionConfirmationBlocks

transactionPollingTimeout

transactionSigner

4.2.2 Example

```
import Web3 from 'web3';

const options = {
  defaultAccount: '0x0',
  defaultBlock: 'latest',
  defaultGas: 1,
  defaultGasPrice: 0,
  transactionBlockTimeout: 50,
  transactionConfirmationBlocks: 24,
```

(continues on next page)

(continued from previous page)

```
transactionPollingTimeout: 480,  
transactionSigner: new CustomTransactionSigner()  
}  
  
const web3 = new Web3('http://localhost:8545', options);
```

4.3 defaultBlock

```
web3.defaultBlock  
web3.eth.defaultBlock  
web3.shh.defaultBlock  
...
```

The default block which will be used for a requests.

4.3.1 Returns

string|number: The current value of the defaultBlock property.

4.4 defaultAccount

```
web3.defaultAccount  
web3.eth.defaultAccount  
web3.shh.defaultAccount  
...
```

The default account which will be used for a requests.

4.4.1 Returns

null|string: The current value of the defaultAccount property.

4.5 defaultGasPrice

```
web3.defaultGasPrice  
web3.eth.defaultGasPrice  
web3.shh.defaultGasPrice  
...
```

The default gas price which will be used for a request.

4.5.1 Returns

string|number: The current value of the defaultGasPrice property.

4.6 defaultGas

```
web3.defaultGas
web3.eth.defaultGas
web3.shh.defaultGas
...
```

The default gas which will be used for a request.

4.6.1 Returns

string|number: The current value of the defaultGas property.

4.7 transactionBlockTimeout

```
web3.transactionBlockTimeout
web3.eth.transactionBlockTimeout
web3.shh.transactionBlockTimeout
...
```

This can be used with a socket provider and defines the number of blocks until the PromiEvent rejects with a timeout error.

4.7.1 Returns

number: The current value of transactionBlockTimeout

4.8 transactionConfirmationBlocks

```
web3.transactionConfirmationBlocks
web3.eth.transactionConfirmationBlocks
web3.shh.transactionConfirmationBlocks
...
```

This defines the number of blocks it requires until a transaction will be handled as confirmed. The PromiEvent will resolve with the desired receipt when enough confirmations happened.

4.8.1 Returns

number: The current value of transactionConfirmationBlocks

4.9 transactionPollingTimeout

```
web3.transactionPollingTimeout
web3.eth.transactionPollingTimeout
web3.shh.transactionPollingTimeout
...
```

This defines the polling cycles amount when you send a transaction with the HttpProvider. The PromiEvent rejects with a timeout error when the timeout got exceeded. (1 cycle == 1sec).

4.9.1 Returns

number: The current value of transactionPollingTimeout

4.10 transactionSigner

```
web3.eth.transactionSigner
...
```

The transactionSigner property does provide us the possibility to customize the signing process of the Eth module and the related sub-modules.

The interface of a TransactionSigner:

```
interface TransactionSigner {
  sign(txObject: Transaction): Promise<SignedTransaction>
}

interface SignedTransaction {
  messageHash: string,
  v: string,
  r: string,
  s: string,
  rawTransaction: string
}
```

4.10.1 Returns

TransactionSigner: A JavaScript class of type TransactionSigner.

4.11 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package `web3` it will also set the provider for all sub modules `web3.eth`, `web3.shh`, etc EXCEPT `web3.bzz` which needs a separate provider at all times.

4.11.1 Parameters

1. Object|String - provider: a valid provider
2. Net - net: (optional) the node.js Net package. This is only required for the IPC provider.

4.11.2 Returns

Boolean

4.11.3 Example

```
import Web3 from 'web3';

const web3 = new Web3('http://localhost:8545');

// or
const web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');
const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path

// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```


4.12 providers

```
Web3.providers
Eth.providers
...
```

Contains the current available providers.

4.12.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

4.12.2 Example

```
const Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
const web3 = new Web3(Web3.givenProvider || 'ws://localhost:8546');
// or
const web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');

const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

4.13 givenProvider

```
Web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

4.13.1 Returns

Object: The given provider set or null;

4.13.2 Example

```
web3.setProvider(Web3.givenProvider || 'ws://localhost:8546');
```

4.14 currentProvider

```
web3.currentProvider  
web3.eth.currentProvider  
web3.shh.currentProvider  
web3.bzz.currentProvider  
...
```

Will return the current provider, otherwise null.

4.14.1 Returns

Object: The current provider set or null;

4.14.2 Example

```
if(!web3.currentProvider) {  
  web3.setProvider('http://localhost:8545');  
}
```

4.15 BatchRequest

```
new web3.BatchRequest()  
new web3.eth.BatchRequest()  
new web3.shh.BatchRequest()  
...
```

Class to create and execute batch requests.

4.15.1 Parameters

none

4.15.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

4.15.3 Example

```
const contract = new web3.eth.Contract(abi, address);

const batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↪ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↪ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

4.16 version

Property of the Web3 class.

```
Web3.version
web3.version
```

Contains the version of the web3 wrapper class.

4.16.1 Returns

String: The current version.

4.16.2 Example

```
web3.version;
> "1.0.0"
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

The `web3-eth` package allows you to interact with an Ethereum blockchain and Ethereum smart contracts.

```
import Web3 from 'web3';
import {Eth} from 'web3-eth';

// "Web3.givenProvider" will be set if in an Ethereum supported browser.
const eth = new Eth(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
  ↪options);

// or using the web3 umbrella package

const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
  ↪options);

// -> web3.eth
```

5.1 Note on checksum addresses

All Ethereum addresses returned by functions of this package are returned as checksum addresses. This means some letters are uppercase and some are lowercase. Based on that it will calculate a checksum for the address and prove its correctness. Incorrect checksum addresses will throw an error when passed into functions. If you want to circumvent the checksum check you can make an address all lower- or uppercase.

5.1.1 Example

```
web3.eth.getAccounts(console.log);
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe" ,
  ↪"0x85F43D8a49eeB85d32Cf465507DD71d507100C1d"]
```

5.2 subscribe

For `web3.eth.subscribe` see the *Subscribe reference documentation*

5.3 Contract

For `web3.eth.Contract` see the *Contract reference documentation*

5.4 Iban

For `web3.eth.Iban` see the *Iban reference documentation*

5.5 personal

For `web3.eth.personal` see the *personal reference documentation*

5.6 accounts

For `web3.eth.accounts` see the *accounts reference documentation*

5.7 ens

For `web3.eth.ens` see the *Ens reference documentation*

5.8 abi

For `web3.eth.abi` see the *ABI reference documentation*

5.9 net

For `web3.eth.net` see the *net reference documentation*

5.10 options

An Web3 module does provide several options for configuring the transaction confirmation workflow or for defining default values. These are the currently available option properties on a Web3 module:

5.10.1 Module Options

defaultAccount

defaultBlock

defaultGas

defaultGasPrice

transactionBlockTimeout

transactionConfirmationBlocks

transactionPollingTimeout

transactionSigner

5.10.2 Example

```
import Web3 from 'web3';

const options = {
  defaultAccount: '0x0',
  defaultBlock: 'latest',
  defaultGas: 1,
  defaultGasPrice: 0,
  transactionBlockTimeout: 50,
  transactionConfirmationBlocks: 24,
  transactionPollingTimeout: 480,
  transactionSigner: new CustomTransactionSigner()
}

const web3 = new Web3('http://localhost:8545', options);
```

5.11 defaultBlock

```
web3.defaultBlock
web3.eth.defaultBlock
web3.shh.defaultBlock
...
```

The default block which will be used for a requests.

5.11.1 Returns

string|number: The current value of the defaultBlock property.

5.12 defaultAccount

```
web3.defaultAccount
web3.eth.defaultAccount
web3.shh.defaultAccount
...
```

The default account which will be used for a requests.

5.12.1 Returns

null|string: The current value of the defaultAccount property.

5.13 defaultGasPrice

```
web3.defaultGasPrice
web3.eth.defaultGasPrice
web3.shh.defaultGasPrice
...
```

The default gas price which will be used for a request.

5.13.1 Returns

string|number: The current value of the defaultGasPrice property.

5.14 defaultGas

```
web3.defaultGas
web3.eth.defaultGas
web3.shh.defaultGas
...
```

The default gas which will be used for a request.

5.14.1 Returns

string|number: The current value of the defaultGas property.

5.15 transactionBlockTimeout

```
web3.transactionBlockTimeout
web3.eth.transactionBlockTimeout
web3.shh.transactionBlockTimeout
...
```

This can be used with a socket provider and defines the number of blocks until the PromiEvent rejects with a timeout error.

5.15.1 Returns

number: The current value of transactionBlockTimeout

5.16 transactionConfirmationBlocks

```
web3.transactionConfirmationBlocks
web3.eth.transactionConfirmationBlocks
web3.shh.transactionConfirmationBlocks
...
```

This defines the number of blocks it requires until a transaction will be handled as confirmed. The PromiEvent will resolve with the desired receipt when enough confirmations happened.

5.16.1 Returns

number: The current value of transactionConfirmationBlocks

5.17 transactionPollingTimeout

```
web3.transactionPollingTimeout
web3.eth.transactionPollingTimeout
web3.shh.transactionPollingTimeout
...
```

This defines the polling cycles amount when you send a transaction with the HttpProvider. The PromiEvent rejects with a timeout error when the timeout got exceeded. (1 cycle == 1sec.).

5.17.1 Returns

number: The current value of transactionPollingTimeout

5.18 transactionSigner

```
web3.eth.transactionSigner
...
```

The transactionSigner property does provide us the possibility to customize the signing process of the Eth module and the related sub-modules.

The interface of a TransactionSigner:

```
interface TransactionSigner {
  sign(txObject: Transaction): Promise<SignedTransaction>
}

interface SignedTransaction {
  messageHash: string,
  v: string,
  r: string,
  s: string,
  rawTransaction: string
}
```

5.18.1 Returns

TransactionSigner: A JavaScript class of type TransactionSigner.

5.19 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc EXCEPT web3.bzz which needs a separate provider at all times.

5.19.1 Parameters

1. Object|String - provider: a valid provider
2. Net - net: (optional) the node.js Net package. This is only required for the IPC provider.

5.19.2 Returns

Boolean

5.19.3 Example

```
import Web3 from 'web3';

const web3 = new Web3('http://localhost:8545');

// or
const web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');
const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path

// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↪geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

5.20 providers

```
Web3.providers
Eth.providers
...
```

Contains the current available providers.

5.20.1 Value

Object with the following providers:

- Object - HttpProvider: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - WebsocketProvider: The Websocket provider is the standard for usage in legacy browsers.
- Object - IpcProvider: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

5.20.2 Example

```
const Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
const web3 = new Web3(Web3.givenProvider || 'ws://localhost:8546');
// or
const web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');

const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/geth.ipc', net)); // mac os path
// on windows the path is: '\\\\.\\pipe\\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

5.21 givenProvider

```
Web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

5.21.1 Returns

Object: The given provider set or null;

5.21.2 Example

```
web3.setProvider(Web3.givenProvider || 'ws://localhost:8546');
```

5.22 currentProvider

```
web3.currentProvider
web3.eth.currentProvider
web3.shh.currentProvider
web3.bzz.currentProvider
...
```

Will return the current provider, otherwise null.

5.22.1 Returns

Object: The current provider set or null;

5.22.2 Example

```
if(!web3.currentProvider) {
  web3.setProvider('http://localhost:8545');
}
```

5.23 BatchRequest

```
new web3.BatchRequest ()
new web3.eth.BatchRequest ()
new web3.shh.BatchRequest ()
...
```

Class to create and execute batch requests.

5.23.1 Parameters

none

5.23.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

5.23.3 Example

```
const contract = new web3.eth.Contract(abi, address);

const batch = new web3.BatchRequest();
batch.add(web3.eth.getBalance.request('0x0000000000000000000000000000000000000000',
  ↪ 'latest', callback));
batch.add(contract.methods.balance(address).call.request({from:
  ↪ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute();
```

5.24 defaultAccount

```
web3.eth.defaultAccount
```

This default address is used as the default "from" property, if no "from" property is specified in for the following methods:

- *web3.eth.sendTransaction()*
- *web3.eth.call()*
- *new web3.eth.Contract() -> myContract.methods.myMethod().call()*
- *new web3.eth.Contract() -> myContract.methods.myMethod().send()*

5.24.1 Property

String - 20 Bytes: Any ethereum address. You should have the private key for that address in your node or keystore. (Default is undefined)

5.24.2 Example

```
web3.eth.defaultAccount;  
> undefined  
  
// set the default account  
web3.eth.defaultAccount = '0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe';
```

5.25 defaultBlock

```
web3.eth.defaultBlock
```

The default block is used for certain methods. You can override it by passing in the defaultBlock as last parameter. The default value is "latest".

- *web3.eth.getBalance()*
- *web3.eth.getCode()*
- *web3.eth.getTransactionCount()*
- *web3.eth.getStorageAt()*
- *web3.eth.call()*
- *new web3.eth.Contract() -> myContract.methods.myMethod().call()*

5.25.1 Property

Default block parameters can be one of the following:

- Number: A block number
- "genesis" - String: The genesis block
- "latest" - String: The latest block (current head of the blockchain)

- "pending" - String: The currently mined block (including pending transactions)

Default is "latest"

5.25.2 Example

```
web3.eth.defaultBlock;  
> "latest"  
  
// set the default block  
web3.eth.defaultBlock = 231;
```

5.26 getProtocolVersion

```
web3.eth.getProtocolVersion([callback])
```

Returns the ethereum protocol version of the node.

5.26.1 Returns

Promise<string> - The protocol version.

5.26.2 Example

```
web3.eth.getProtocolVersion()  
.then(console.log);  
> "63"
```

5.27 isSyncing

```
web3.eth.isSyncing([callback])
```

Checks if the node is currently syncing and returns either a syncing object, or false.

5.27.1 Returns

Promise<object|boolean> - A sync object when the node is currently syncing or false:

- startingBlock - Number: The block number where the sync started.
- currentBlock - Number: The block number where at which block the node currently synced to already.
- highestBlock - Number: The estimated block number to sync to.
- knownStates - Number: The estimated states to download
- pulledStates - Number: The already downloaded states

5.27.2 Example

```
web3.eth.isSyncing()  
.then(console.log);  
  
> {  
  startingBlock: 100,  
  currentBlock: 312,  
  highestBlock: 512,  
  knownStates: 234566,  
  pulledStates: 123455  
}
```

5.28 getCoinbase

```
getCoinbase([callback])
```

Returns the coinbase address to which mining rewards will go.

5.28.1 Returns

Promise<string> - The coinbase address set in the node for mining rewards.

5.28.2 Example

```
web3.eth.getCoinbase()  
.then(console.log);  
> "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe"
```

5.29 isMining

```
web3.eth.isMining([callback])
```

Checks whether the node is mining or not.

5.29.1 Returns

Promise<boolean> - Returns true if the node is mining, otherwise false.

5.29.2 Example

```
web3.eth.isMining()  
.then(console.log);  
> true
```

5.30 getHashrate

```
web3.eth.getHashrate([callback])
```

Returns the number of hashes per second that the node is mining with.

5.30.1 Returns

Promise<number> - The Number of hashes per second.

5.30.2 Example

```
web3.eth.getHashrate()  
.then(console.log);  
> 493736
```

5.31 getGasPrice

```
web3.eth.getGasPrice([callback])
```

Returns the current gas price oracle. The gas price is determined by the last few blocks median gas price. GasPrice is the wei per unit of gas,.

5.31.1 Returns

Promise<string> - Number string of the current gas price in wei.

See the *A note on dealing with big numbers in JavaScript*.

5.31.2 Example

```
web3.eth.getGasPrice()  
.then(console.log);  
> "200000000000"
```

5.32 getAccounts

```
web3.eth.getAccounts([callback])
```

Returns a list of accounts the node controls by using the provider and calling the RPC method `eth_accounts`. Using `web3.eth.accounts.create()` will not add accounts into this list. For that use `web3.eth.personal.newAccount()`.

The results are the same as `web3.eth.personal.getAccounts()` except that calls the RPC method `personal_listAccounts`.

5.32.1 Returns

Promise<Array> - An array of addresses controlled by node.

5.32.2 Example

```
web3.eth.getAccounts()
  .then(console.log);
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  ↪ "0xDCc6960376d6C6dEa93647383FfB245CfCed97Cf"]
```

5.33 getBlockNumber

```
web3.eth.getBlockNumber([callback])
```

Returns the current block number.

5.33.1 Returns

Promise<number> - The number of the most recent block.

5.33.2 Example

```
web3.eth.getBlockNumber()
  .then(console.log);
> 2744
```

5.34 getBalance

```
web3.eth.getBalance(address [, defaultBlock] [, callback])
```

Get the balance of an address at a given block.

5.34.1 Parameters

1. `String` - The address to get the balance of.
2. `Number|String` - (optional) If you pass this parameter it will not use the default block set with `web3.eth.defaultBlock`.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.34.2 Returns

`Promise<string>` - The current balance for the given address in wei.

See the A note on dealing with big numbers in JavaScript.

5.34.3 Example

```
web3.eth.getBalance("0x407d73d8a49eeb85d32cf465507dd71d507100c1")
.then(console.log);
> "100000000000000"
```

5.35 getStorageAt

```
web3.eth.getStorageAt(address, position [, defaultBlock] [, callback])
```

Get the storage at a specific position of an address.

5.35.1 Parameters

1. `String` - The address to get the storage from.
2. `Number` - The index position of the storage.
3. `Number|String` - (optional) If you pass this parameter it will not use the default block set with `web3.eth.defaultBlock`.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.35.2 Returns

`Promise<string>` - The value in storage at the given position.

5.35.3 Example

```
web3.eth.getStorageAt("0x407d73d8a49eeb85d32cf465507dd71d507100c1", 0)
.then(console.log);
> "0x033456732123ffff2342342dd12342434324234234fd234fd23fd4f23d4234"
```

5.36 getCode

```
web3.eth.getCode(address [, defaultBlock] [, callback])
```

Get the code at a specific address.

5.36.1 Parameters

1. `String` - The address to get the code from.
2. `Number|String` - (optional) If you pass this parameter it will not use the default block set with `web3.eth.defaultBlock`.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.36.2 Returns

`Promise<string>` - The data at given address address.

5.36.3 Example

```
web3.eth.getCode("0xd5677cf67b5aa051bb40496e68ad359eb97cfbf8")
.then(console.log);
>
↪ "0x600160008035811a818181146012578301005b601b6001356025565b8060005260206000f25b60006007820290509190"
↪ "
```

5.37 getBlock

```
web3.eth.getBlock(blockHashOrBlockNumber [, returnTransactionObjects] [, callback])
```

Returns a block matching the block number or block hash.

5.37.1 Parameters

1. `String|Number` - The block number or block hash. Or the string "genesis", "latest" or "pending" as in the *default block parameter*.
2. `Boolean` - (optional, default `false`) If `true`, the returned block will contain all transactions as objects, if `false` it will only contains the transaction hashes.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

(continued from previous page)

```
    "stateRoot": "0xf1133199d44695dfa8fd1bcfe424d82854b5cebef75bddd7e40ea94cda515bcb",
    "receiptsRoot": '0x56e81f171bcc55a6ff8345e692c0f86e5b48e01b996cad001622fb5e363b421
    ↪',
    "miner": "0x8888f1f195afa192cfee860698584c030f4c9db1",
    "difficulty": '21345678965432',
    "totalDifficulty": '324567845321',
    "size": 616,
    "extraData": "0x",
    "gasLimit": 3141592,
    "gasUsed": 21662,
    "timestamp": 1429287689,
    "transactions": [
      "0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b"
    ],
    "uncles": []
  }
}
```

5.38getBlockTransactionCount

```
web3.eth.getBlockTransactionCount(blockHashOrBlockNumber [, callback])
```

Returns the number of transaction in a given block.

5.38.1 Parameters

1. String|Number - The block number or hash. Or the string "genesis", "latest" or "pending" as in the *default block parameter*.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.38.2 Returns

Promise<number> - The number of transactions in the given block.

5.38.3 Example

```
web3.eth.getBlockTransactionCount("0x407d73d8a49eeb85d32cf465507dd71d507100c1")
  .then(console.log);
> 1
```

5.39 getUncle

```
web3.eth.getUncle(blockHashOrBlockNumber, uncleIndex [, callback])
```

Returns a blocks uncle by a given uncle index position.

5.39.1 Parameters

1. `String|Number` - The block number or hash. Or the string "genesis", "latest" or "pending" as in the *default block parameter*.
2. `Number` - The index position of the uncle.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.39.2 Returns

`Promise<object>` - The returned uncle. For a return value see [web3.eth.getBlock\(\)](#).

Note: An uncle doesn't contain individual transactions.

5.39.3 Example

```
web3.eth.getUncle(500, 0)
  .then(console.log);
> // see web3.eth.getBlock
```

5.40 getTransaction

```
web3.eth.getTransaction(transactionHash [, callback])
```

Returns a transaction matching the given transaction hash.

5.40.1 Parameters

1. `String` - The transaction hash.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.40.2 Returns

`Promise<object>` - A transaction object its hash `transactionHash`:

- `hash` 32 Bytes - `String`: Hash of the transaction.
- `nonce` - `Number`: The number of transactions made by the sender prior to this one.
- `blockHash` 32 Bytes - `String`: Hash of the block where this transaction was in. `null` when its pending.
- `blockNumber` - `Number`: Block number where this transaction was in. `null` when its pending.
- `transactionIndex` - `Number`: Integer of the transactions index position in the block. `null` when its pending.
- `from` - `String`: Address of the sender.

- `to` - String: Address of the receiver. `null` when its a contract creation transaction.
- `value` - String: Value transferred in wei.
- `gasPrice` - String: The wei per unit of gas provided by the sender in wei.
- `gas` - Number: Gas provided by the sender.
- `input` - String: The data sent along with the transaction.

5.40.3 Example

```
web3.eth.getTransaction(
  ↪ '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b$234')
.then(console.log);

> {
  "hash": "0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b",
  "nonce": 2,
  "blockHash": "0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
  "blockNumber": 3,
  "transactionIndex": 0,
  "from": "0xa94f5374f5e5edbc8e2a8697c15331677e6ebf0b",
  "to": "0x6295ee1b4f6dd65047762f924ecd367c17eabf8f",
  "value": '123450000000000000',
  "gas": 314159,
  "gasPrice": '2000000000000',
  "input": "0x57cb2fc4"
}
```

5.41 getTransactionFromBlock

```
getTransactionFromBlock(hashStringOrNumber, indexNumber [, callback])
```

Returns a transaction based on a block hash or number and the transactions index position.

5.41.1 Parameters

1. String - A block number or hash. Or the string "genesis", "latest" or "pending" as in the *default block parameter*.
2. Number - The transactions index position.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.41.2 Returns

Promise<object> - A transaction object, see *web3.eth.getTransaction*:

5.41.3 Example

```
const transaction = web3.eth.getTransactionFromBlock('0x4534534534', 2)
.then(console.log);
> // see web3.eth.getTransaction
```

5.42 getTransactionReceipt

```
web3.eth.getTransactionReceipt(hash [, callback])
```

Returns the receipt of a transaction by transaction hash.

Note: The receipt is not available for pending transactions and returns `null`.

5.42.1 Parameters

1. `String` - The transaction hash.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.42.2 Returns

Promise returns `Object` - A transaction receipt object, or `null` when no receipt was found:

- `status` - `Boolean`: `TRUE` if the transaction was successful, `FALSE`, if the EVM reverted the transaction.
- `blockHash` 32 Bytes - `String`: Hash of the block where this transaction was in.
- `blockNumber` - `Number`: Block number where this transaction was in.
- `transactionHash` 32 Bytes - `String`: Hash of the transaction.
- `transactionIndex` - `Number`: Integer of the transactions index position in the block.
- `from` - `String`: Address of the sender.
- `to` - `String`: Address of the receiver. `null` when its a contract creation transaction.
- `contractAddress` - `String`: The contract address created, if the transaction was a contract creation, otherwise `null`.
- `cumulativeGasUsed` - `Number`: The total amount of gas used when this transaction was executed in the block.
- `gasUsed` - `Number`: The amount of gas used by this specific transaction alone.
- `logs` - `Array`: Array of log objects, which this transaction generated.

5.42.3 Example

```
const receipt = web3.eth.getTransactionReceipt(
  ↪ '0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b')
  .then(console.log);

> {
  "status": true,
  "transactionHash":
  ↪ "0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b",
  "transactionIndex": 0,
  "blockHash": "0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
  "blockNumber": 3,
  "contractAddress": "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  "cumulativeGasUsed": 314159,
  "gasUsed": 30234,
  "logs": [{
    // logs as returned by getPastLogs, etc.
  }, ...]
}
```

5.43 getTransactionCount

```
web3.eth.getTransactionCount(address [, defaultBlock] [, callback])
```

Get the numbers of transactions sent from this address.

5.43.1 Parameters

1. String - The address to get the numbers of transactions from.
2. Number|String - (optional) If you pass this parameter it will not use the default block set with *web3.eth.defaultBlock*.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.43.2 Returns

Promise<number> - The number of transactions sent from the given address.

5.43.3 Example

```
web3.eth.getTransactionCount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
  .then(console.log);
> 1
```

5.44 sendTransaction

```
web3.eth.sendTransaction(transactionObject [, callback])
```

Sends a transaction to the network.

5.44.1 Parameters

1. `Object` - The transaction object to send:

- `from` - `String|Number`: The address for the sending account. Uses the `web3.eth.defaultAccount` property, if not specified. Or an address or index of a local wallet in `web3.eth.accounts.wallet`.
- `to` - `String`: (optional) The destination address of the message, left undefined for a contract-creation transaction.
- `value` - `Number|String|BN|BigNumber`: (optional) The value transferred for the transaction in wei, also the endowment if it's a contract-creation transaction.
- `gas` - `Number`: (optional, default: To-Be-Determined) The amount of gas to use for the transaction (unused gas is refunded).
- `gasPrice` - `Number|String|BN|BigNumber`: (optional) The price of gas for this transaction in wei, defaults to `web3.eth.gasPrice`.
- `data` - `String`: (optional) Either a [ABI byte string](#) containing the data of the function call on a contract, or in the case of a contract-creation transaction the initialisation code.
- `nonce` - `Number`: (optional) Integer of a nonce. This allows to overwrite your own pending transactions that use the same nonce.

2. `callback` - `Function`: (optional) Optional callback, returns an error object as first parameter and the result as second.

Note: The `from` property can also be an address or index from the `web3.eth.accounts.wallet`. It will then sign locally using the private key of that account, and send the transaction via `web3.eth.sendSignedTransaction()`.

5.44.2 Returns

The **callback** will return the 32 bytes transaction hash.

`PromiEvent`: A *promise combined event emitter*. Will be resolved when the transaction *receipt* is available. Additionally the following events are available:

- `"transactionHash"` returns `String`: Is fired right after the transaction is sent and a transaction hash is available.
- `"receipt"` returns `Object`: Is fired when the transaction receipt is available.
- `"confirmation"` returns `Number, Object`: Is fired for every confirmation up to the 12th confirmation. Receives the confirmation number as the first and the *receipt* as the second argument. Fired from confirmation 0 on, which is the block where its mined.
- `"error"` returns `Error`: Is fired if an error occurs during sending. If a out of gas error, the second parameter is the receipt.

- Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.45.2 Returns

PromiseEvent: A *promise combined event emitter*. Will be resolved when the transaction *receipt* is available.

Please see the return values for *web3.eth.sendTransaction* for details.

5.45.3 Example

```
const Tx = require('ethereumjs-tx');
const privateKey = new Buffer(
  ↪ 'e331b6d69882b4cb4ea581d88e0b604039a3de5967688d3dcffd2270c0fd109', 'hex')

const rawTx = {
  nonce: '0x00',
  gasPrice: '0x09184e72a000',
  gasLimit: '0x2710',
  to: '0x00000000000000000000000000000000',
  value: '0x00',
  data: '0x7f74657374320000000000000000000000000000000000000000000000000600057'
}

const tx = new Tx(rawTx);
tx.sign(privateKey);

const serializedTx = tx.serialize();

// console.log(serializedTx.toString('hex'));
// ↪
↪ 0xf889808609184e72a0008227109400000000000000000000000000000000080a47f7465737432000000000000

web3.eth.sendSignedTransaction('0x' + serializedTx.toString('hex'))
.on('receipt', console.log);

> // see eth.getTransactionReceipt() for details
```

5.46 sign

```
web3.eth.sign(dataToSign, address [, callback])
```

Signs data using a specific account. This account needs to be unlocked.

5.46.1 Parameters

- String - Data to sign. If String it will be converted using *web3.utils.utf8ToHex*.
- String|Number - Address to sign data with. Or an address or index of a local wallet in *web3.eth.accounts.wallet*.
- Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

Note: The 2. address parameter can also be an address or index from the `web3.eth.accounts.wallet`. It will then sign locally using the private key of this account.

5.46.2 Returns

Promise<string> - The signature.

5.46.3 Example

```
web3.eth.sign("Hello world", "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log);
>
↪ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d..."
↪ ""

// the below is the same
web3.eth.sign(web3.utils.utf8ToHex("Hello world"),
↪ "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log);
>
↪ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d..."
↪ ""
```

5.47 signTransaction

```
web3.eth.signTransaction(transactionObject [, address] [, callback])
```

The method `signTransaction` signs a transaction with the private key of the given address. This method does only work if you're connected to a Parity node.

5.47.1 Parameters

1. Object - The transaction data to sign `web3.eth.sendTransaction()` for more.
2. String - (optional) Address to sign transaction with.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.47.2 Returns

Promise<object> - The RLP encoded transaction. The `raw` property can be used to send the transaction using `web3.eth.sendSignedTransaction`.

5.50.1 Parameters

1. Object - The filter options as follows:

- `fromBlock` - `Number|String`: The number of the earliest block ("latest" may be given to mean the most recent and "pending" currently mining, block). By default "latest".
- `toBlock` - `Number|String`: The number of the latest block ("latest" may be given to mean the most recent and "pending" currently mining, block). By default "latest".
- `address` - `String|Array`: An address or a list of addresses to only get logs from particular account(s).
- `topics` - `Array`: An array of values which must each appear in the log entries. The order is important, if you want to leave topics out use null, e.g. `[null, '0x12...']`. You can also pass an array for each topic with options for that topic e.g. `[null, ['option1', 'option2']]`

5.50.2 Returns

`Promise<Array>` - Array of log objects.

The structure of the returned event Object in the Array looks as follows:

- `address` - `String`: From which this event originated from.
- `data` - `String`: The data containing non-indexed log parameter.
- `topics` - `Array`: An array with max 4 32 Byte topics, topic 1-3 contains indexed parameters of the log.
- `logIndex` - `Number`: Integer of the event index position in the block.
- `transactionIndex` - `Number`: Integer of the transaction's index position, the event was created in.
- `transactionHash` 32 Bytes - `String`: Hash of the transaction this event was created in.
- `blockHash` 32 Bytes - `String`: Hash of the block where this event was created in. null when its still pending.
- `blockNumber` - `Number`: The block number where this log was created in. null when still pending.

5.50.3 Example

```
web3.eth.getPastLogs({
  address: "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  topics: ["0x033456732123ffff2342342dd12342434324234234fd234fd23fd4f23d4234"]
})
.then(console.log);

> [{
  data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}, {...}]
```

5.51 getWork

```
web3.eth.getWork([callback])
```

Gets work for miners to mine on. Returns the hash of the current block, the seedHash, and the boundary condition to be met (“target”).

5.51.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.51.2 Returns

`Promise<Array>` - The mining work with the following structure:

- `String` 32 Bytes - at **index 0**: current block header pow-hash
- `String` 32 Bytes - at **index 1**: the seed hash used for the DAG.
- `String` 32 Bytes - at **index 2**: the boundary condition (“target”), 2^{256} / difficulty.

5.51.3 Example

```
web3.eth.getWork()
  .then(console.log);
> [
  "0x1234567890abcdef1234567890abcdef1234567890abcdef1234567890abcdef",
  "0x5EED000000000000000000000000000000000000000000000000000000000000",
  "0xd1ff1c0171000000000000000000000000000000000000000000000000000000"
]
```

5.52 submitWork

```
web3.eth.submitWork(nonce, powHash, digest, [callback])
```

Used for submitting a proof-of-work solution.

5.52.1 Parameters

1. `String` 8 Bytes: The nonce found (64 bits)
2. `String` 32 Bytes: The header’s pow-hash (256 bits)
3. `String` 32 Bytes: The mix digest (256 bits)
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.52.2 Returns

Promise<boolean> - Returns `true` if the provided solution is valid, otherwise false.

5.52.3 Example

```
web3.eth.submitWork([
  "0x0000000000000001",
  "0x1234567890abcdef1234567890abcdef1234567890abcdef1234567890abcdef",
  "0xD1FE570000000000000000000000000000D1FE570000000000000000000000"
])
.then(console.log);
> true
```

5.53 requestAccounts

```
web3.eth.requestAccounts([callback])
```

This method will request/enable the accounts from the current environment it is running (Metamask, Status or Mist). It doesn't work if you're connected to a node with a default Web3.js provider. (WebsocketProvider, HttpProvider and IpcProvider) This method will only work if you're using the injected provider from an application like Status, Mist or Metamask.

For further information about the behavior of this method please read the EIP of it: [EIP-1102](#)

5.53.1 Parameters

1. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

5.53.2 Returns

Promise<Array> - Returns an array of enabled accounts.

5.53.3 Example

```
web3.eth.requestAccounts().then(console.log);
> ['0aae0B295369a9FD31d5F28D9Ec85E40f4cb692BAf',
↪ 0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe]
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

web3.eth.subscribe

The `web3.eth.subscribe` function lets you subscribe to specific events in the blockchain.

6.1 subscribe

```
web3.eth.subscribe(type [, options] [, callback]);
```

6.1.1 Parameters

1. `String` - The subscription, you want to subscribe to.
2. `Mixed` - (optional) Optional additional parameters, depending on the subscription type.
3. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription, and the subscription itself as 3 parameter.

6.1.2 Returns

`EventEmitter` - A Subscription instance

- `subscription.id`: The subscription id, used to identify and unsubscribing the subscription.
- `subscription.subscribe([callback])`: Can be used to re-subscribe with the same parameters.
- `subscription.unsubscribe([callback])`: Unsubscribes the subscription and returns `TRUE` in the callback if successful.
- `subscription.arguments`: The subscription arguments, used when re-subscribing.
- `on("data")` returns `Object`: Fires on each incoming log with the log object as argument.
- `on("changed")` returns `Object`: Fires on each log which was removed from the blockchain. The log will have the additional property `"removed: true"`.

- `on("error")` returns `Object`: Fires when an error in the subscription occurs.

6.1.3 Notification returns

- `any` - depends on the subscription, see the different subscriptions for more.

6.1.4 Example

```
const subscription = web3.eth.subscribe('logs', {
  address: '0x123456..',
  topics: ['0x12345...']
}, function(error, result){
  if (!error)
    console.log(result);
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if(success)
    console.log('Successfully unsubscribed!');
});
```

6.2 clearSubscriptions

```
web3.eth.clearSubscriptions()
```

Resets subscriptions.

Note: This will not reset subscriptions from other packages like `web3-shh`.

6.2.1 Returns

Promise<boolean>

6.2.2 Example

```
web3.eth.subscribe('logs', {}, function(){ ... });

...

web3.eth.clearSubscriptions();
```

6.3 subscribe("pendingTransactions")

```
web3.eth.subscribe('pendingTransactions' [, callback]);
```

Subscribes to incoming pending transactions.

6.3.1 Parameters

1. `String` - "pendingTransactions", the type of the subscription.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.3.2 Returns

EventEmitter: An *subscription instance* as an event emitter with the following events:

- "data" returns `String`: Fires on each incoming pending transaction and returns the transaction hash.
- "error" returns `Object`: Fires when an error in the subscription occurs.

6.3.3 Notification returns

1. `Object|Null` - First parameter is an error object if the subscription failed.
2. `String` - Second parameter is the transaction hash.

6.3.4 Example

```
const subscription = web3.eth.subscribe('pendingTransactions', function(error, result)
  → {
    if (!error)
      console.log(result);
  })
.on("data", function(transaction) {
  console.log(transaction);
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success) {
  if (success)
    console.log('Successfully unsubscribed!');
});
```

6.4 subscribe("newBlockHeaders")

```
web3.eth.subscribe('newBlockHeaders' [, callback]);
```

Subscribes to incoming block headers. This can be used as timer to check for changes on the blockchain.

6.4.1 Parameters

1. `String` - "newBlockHeaders", the type of the subscription.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.4.2 Returns

`EventEmitter`: An *subscription instance* as an event emitter with the following events:

- "data" returns `Object`: Fires on each incoming block header.
- "error" returns `Object`: Fires when an error in the subscription occurs.

The structure of a returned block header is as follows:

- `number` - `Number`: The block number. `null` when its pending block.
- `hash` 32 Bytes - `String`: Hash of the block. `null` when its pending block.
- `parentHash` 32 Bytes - `String`: Hash of the parent block.
- `nonce` 8 Bytes - `String`: Hash of the generated proof-of-work. `null` when its pending block.
- `sha3Uncles` 32 Bytes - `String`: SHA3 of the uncles data in the block.
- `logsBloom` 256 Bytes - `String`: The bloom filter for the logs of the block. `null` when its pending block.
- `transactionsRoot` 32 Bytes - `String`: The root of the transaction trie of the block
- `stateRoot` 32 Bytes - `String`: The root of the final state trie of the block.
- `receiptsRoot` 32 Bytes - `String`: Transaction receipts are used to store the state after a transaction has been executed and are kept in an index-keyed trie. The hash of its root is placed in the block header as the receipts root.
- `miner` - `String`: The address of the beneficiary to whom the mining rewards were given.
- `extraData` - `String`: The "extra data" field of this block.
- `gasLimit` - `Number`: The maximum gas allowed in this block.
- `gasUsed` - `Number`: The total used gas by all transactions in this block. It can be multiplied to *gasPrice* to obtain total amount in wei.
- `timestamp` - `Number`: The unix timestamp for when the block was collated.

6.4.3 Notification returns

1. `Object|Null` - First parameter is an error object if the subscription failed.
2. `Object` - The block header object like above.

6.4.4 Example

```
const subscription = web3.eth.subscribe('newBlockHeaders', function(error, result){
  if (!error) {
    console.log(result);
  }
});
```

(continues on next page)

(continued from previous page)

```
        return;
    }

    console.error(error);
})
.on("data", function(blockHeader) {
    console.log(blockHeader);
})
.on("error", console.error);

// unsubscribes the subscription
subscription.unsubscribe(function(error, success) {
    if (success) {
        console.log('Successfully unsubscribed!');
    }
});
```

6.5 subscribe(“syncing”)

```
web3.eth.subscribe('syncing' [, callback]);
```

Subscribe to syncing events. This will return an object when the node is syncing and when its finished syncing will return `FALSE`.

6.5.1 Parameters

1. `String` - "syncing", the type of the subscription.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.5.2 Returns

`EventEmitter`: An *subscription instance* as an event emitter with the following events:

- "data" returns `Object`: Fires on each incoming sync object as argument.
- "changed" returns `Object`: Fires when the synchronisation is started with `true` and when finished with `false`.
- "error" returns `Object`: Fires when an error in the subscription occurs.

For the structure of a returned event `Object` see [web3.eth.isSyncing return values](#).

6.5.3 Notification returns

1. `Object|Null` - First parameter is an error object if the subscription failed.
2. `Object|Boolean` - The syncing object, when started it will return `true` once or when finished it will return *false* once.

6.5.4 Example

```
const subscription = web3.eth.subscribe('syncing', function(error, sync){
  if (!error)
    console.log(sync);
})
.on("data", function(sync){
  // show some syncing stats
})
.on("changed", function(isSyncing){
  if(isSyncing) {
    // stop app operation
  } else {
    // regain app operation
  }
});

// unsubscribes the subscription
subscription.unsubscribe(function(error, success){
  if(success)
    console.log('Successfully unsubscribed!');
});
```

6.6 subscribe("logs")

```
web3.eth.subscribe('logs', options [, callback]);
```

Subscribes to incoming logs, filtered by the given options.

6.6.1 Parameters

1. "logs" - String, the type of the subscription.
2. Object - The subscription options
 - fromBlock - Number: The number of the earliest block. By default null.
 - address - String|Array: An address or a list of addresses to only get logs from particular account(s).
 - topics - Array: An array of values which must each appear in the log entries. The order is important, if you want to leave topics out use null, e.g. [null, '0x00...']. You can also pass another array for each topic with options for that topic e.g. [null, ['option1', 'option2']]
3. callback - Function: (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription.

6.6.2 Returns

EventEmitter: An *subscription instance* as an event emitter with the following events:

- "data" returns Object: Fires on each incoming log with the log object as argument.
- "changed" returns Object: Fires on each log which was removed from the blockchain. The log will have the additional property "removed: true".

- "error" returns Object: Fires when an error in the subscription occurs.

For the structure of a returned event Object see *web3.eth.getPastEvents return values*.

6.6.3 Notification returns

1. Object | Null - First parameter is an error object if the subscription failed.
2. Object - The log object like in *web3.eth.getPastEvents return values*.

6.6.4 Example

```
const subscription = web3.eth.subscribe('logs', {
  address: '0x123456..',
  topics: ['0x12345...']
}, (error, result) => {
  if (!error) {
    console.log(result);
  }

  console.error(error);
})
.on("data", (log) => {
  console.log(log);
})
.on("changed", (log) => {
  console.log(log);
});

// unsubscribes the subscription
subscription.unsubscribe((error, success) => {
  if (success) {
    console.log('Successfully unsubscribed!');
  }
});
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

web3.eth.Contract

The `web3.eth.Contract` object makes it easy to interact with smart contracts on the ethereum blockchain. When you create a new contract object you give it the `json` interface of the respective smart contract and web3 will auto convert all calls into low level ABI calls over RPC for you.

This allows you to interact with smart contracts as if they were JavaScript objects.

To use it standalone:

7.1 new contract

```
new web3.eth.Contract(jsonInterface, address, options)
```

Creates a new contract instance with all its methods and events defined in its *json interface* object.

7.1.1 Parameters

1. `jsonInterface` - `Array`: The `json` interface for the contract to instantiate
2. `address` - `String` (optional): This address is necessary for transactions and call requests and can also be added later using `myContract.options.address = '0x1234..'`.
3. **options - Object (optional): The options of the contract. Some are used as fallbacks for calls and transactions:**
 - `from` - `String`: The address transactions should be made from.
 - `gasPrice` - `String`: The gas price in wei to use for transactions. It is the wei per unit of gas.
 - `gas` - `Number`: The maximum gas provided for a transaction (gas limit).
 - `data` - `String`: The byte code of the contract. Used when the contract gets *deployed*.

7.1.2 Returns

Object: The contract instance with all its methods and events.

7.1.3 Example

```
const myContract = new web3.eth.Contract([...],
  ↪ '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe', {
    from: '0x1234567890123456789012345678901234567891', // default from address
    gasPrice: '20000000000' // default gas price in wei, 20 gwei in this case
  });
```

7.2 = Properties =

7.3 options

```
myContract.options
```

The options object for the contract instance. `from`, `gas` and `gasPrice` are used as fallback values when sending transactions.

7.3.1 Properties

Object - options:

- `address` - String: The address where the contract is deployed. See *options.address*.
- `jsonInterface` - Array: The json interface of the contract. See *options.jsonInterface*.
- `data` - String: The byte code of the contract. Used when the contract gets *deployed*.
- `from` - String: The address transactions should be made from.
- `gasPrice` - String: The gas price in wei to use for transactions. It is the wei per unit of gas.
- `gas` - Number: The maximum gas provided for a transaction (gas limit).

7.3.2 Example

```
myContract.options;
> {
  address: '0x1234567890123456789012345678901234567891',
  jsonInterface: [...],
  from: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe',
  gasPrice: '100000000000000',
  gas: 1000000
}
```

(continues on next page)

(continued from previous page)

```
myContract.options.from = '0x1234567890123456789012345678901234567891'; // default ↵  
↵from address  
myContract.options.gasPrice = '2000000000000'; // default gas price in wei  
myContract.options.gas = 5000000; // provide as fallback always 5M gas
```

7.4 options.address

```
myContract.options.address
```

The address used for this contract instance. All transactions generated by web3.js from this contract will contain this address as the “to”.

The address will be stored in lowercase.

7.4.1 Property

address - String|null: The address for this contract, or null if it's not yet set.

7.4.2 Example

```
myContract.options.address;  
> '0xde0b295669a9fd93d5f28d9ec85e40f4cb697bae'  
  
// set a new address  
myContract.options.address = '0x1234FFDD...';
```

7.5 options.jsonInterface

```
myContract.options.jsonInterface
```

The *json interface* object derived from the [ABI](#) of this contract.

7.5.1 Property

jsonInterface - Array: The *json interface* for this contract. Re-setting this will regenerate the methods and events of the contract instance.

7.5.2 Example

```
myContract.options.jsonInterface;
> [{
  "type": "function",
  "name": "foo",
  "inputs": [{"name": "a", "type": "uint256"}],
  "outputs": [{"name": "b", "type": "address"}]
}, {
  "type": "event",
  "name": "Event",
  "inputs": [{"name": "a", "type": "uint256", "indexed": true}, {"name": "b", "type":
  ↪ "bytes32", "indexed": false}],
}]

// set a new interface
myContract.options.jsonInterface = [...];
```

7.6 = Methods =

7.7 clone

```
myContract.clone()
```

Clones the current contract instance.

7.7.1 Parameters

none

7.7.2 Returns

Object: The new contract instance.

7.7.3 Example

```
const contract1 = new eth.Contract(abi, address, {gasPrice: '12345678', from:
  ↪fromAddress});

const contract2 = contract1.clone();
contract2.options.address = address2;

(contract1.options.address !== contract2.options.address);
> true
```


7.8 deploy

```
myContract.deploy(options)
```

Call this function to deploy the contract to the blockchain. After successful deployment the promise will resolve with a new contract instance.

7.8.1 Parameters

1. **options - Object: The options used for deployment.**

- `data` - String: The byte code of the contract.
- `arguments` - Array (optional): The arguments which get passed to the constructor on deployment.

7.8.2 Returns

Object: The transaction object:

- `Array` - arguments: The arguments passed to the method before. They can be changed.
- `Function` - `send`: Will deploy the contract. The promise will resolve with the new contract instance, instead of the receipt!
- `Function` - `estimateGas`: Will estimate the gas used for deploying.
- `Function` - `encodeABI`: Encodes the ABI of the deployment, which is contract data + constructor parameters

For details to the methods see the documentation below.

7.8.3 Example

```
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.send({
  from: '0x1234567890123456789012345678901234567891',
  gas: 1500000,
  gasPrice: '3000000000000'
}, (error, transactionHash) => { ... })
.on('error', (error) => { ... })
.on('transactionHash', (transactionHash) => { ... })
.on('receipt', (receipt) => {
  console.log(receipt.contractAddress) // contains the new contract address
})
.on('confirmation', (confirmationNumber, receipt) => { ... })
.then((newContractInstance) => {
  console.log(newContractInstance.options.address) // instance with the new
  ↪contract address
});

// When the data is already set as an option to the contract itself
myContract.options.data = '0x12345...';
```

(continues on next page)

```

myContract.deploy({
  arguments: [123, 'My String']
})
.send({
  from: '0x1234567890123456789012345678901234567891',
  gas: 1500000,
  gasPrice: '30000000000000'
})
.then((newContractInstance) => {
  console.log(newContractInstance.options.address) // instance with the new
  ↪ contract address
});

// Simply encoding
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.encodeABI();
> '0x12345...0000012345678765432'

// Gas estimation
myContract.deploy({
  data: '0x12345...',
  arguments: [123, 'My String']
})
.estimateGas((err, gas) => {
  console.log(gas);
});

```

7.9 methods

```
myContract.methods.myMethod([param1[, param2[, ...]])
```

Creates a transaction object for that method, which then can be *called*, *send*, estimated.

The methods of this smart contract are available through:

- The name: `myContract.methods.myMethod(123)`
- The name with parameters: `myContract.methods['myMethod(uint256)'](123)`
- The signature: `myContract.methods['0x58cf5f10'](123)`

This allows calling functions with same name but different parameters from the JavaScript contract object.

7.9.1 Parameters

Parameters of any method depend on the smart contracts methods, defined in the *JSON interface*.

7.9.2 Returns

Object: The Transaction Object:

- **Array - arguments:** The arguments passed to the method before. They can be changed.
- **Function - *call*:** Will call the “constant” method and execute its smart contract method in the EVM without sending a transaction (Can’t alter the smart contract state).
- **Function - *send*:** Will send a transaction to the smart contract and execute its method (Can alter the smart contract state).
- **Function - *estimateGas*:** Will estimate the gas used when the method would be executed on chain.
- **Function - *encodeABI*:** Encodes the ABI for this method. This can be send using a transaction, call the method or passing into another smart contracts method as argument.

For details to the methods see the documentation below.

7.9.3 Example

```
// calling a method
myContract.methods.myMethod(123).call({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'}, (error, result) => {
  ...
});

// or sending and using a promise
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then((receipt) => {
  // receipt can also be a new contract instance, when coming from a "contract.
  ↪deploy({...}).send() "
});

// or sending and using the events

myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.on('transactionHash', (hash) => {
  ...
})
.on('receipt', (receipt) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('error', console.error);
```

7.10 methods.myMethod.call

```
myContract.methods.myMethod([param1[, param2[, ...]]) .call(transactionObject, ↵  
↵blockNumber, callback)
```

Will call a “constant” method and execute its smart contract method in the EVM without sending any transaction. Note calling can not alter the smart contract state.

7.10.1 Parameters

options - Object (optional): The options used for calling. 1.* transactionObject

- from - String (optional): The address the call “transaction” should be made from.
- gasPrice - String (optional): The gas price in wei to use for this call “transaction”. It is the wei per unit of gas.
- gas - Number (optional): The maximum gas provided for this call “transaction” (gas limit).

2.* “blockNumber” - Number: The block number this log was created in. null when still pending. 3.* “callback” - Function (optional): This callback will be fired with the result of the smart contract method execution as the second argument, or with an error object as the first argument.

7.10.2 Returns

Promise<any> - The return value(s) of the smart contract method. If it returns a single value, it’s returned as is. If it has multiple return values they are returned as an object with properties and indices:

7.10.3 Example

```
// using the callback  
myContract.methods.myMethod(123) .call({from:  
↵'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'}, (error, result) => {  
  ...  
});  
  
// using the promise  
myContract.methods.myMethod(123) .call({from:  
↵'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})  
 .then((result) => {  
  ...  
});  
  
// MULTI-ARGUMENT RETURN:  
  
// Solidity  
contract MyContract {  
  function myFunction() returns(uint256 myNumber, string myString) {  
    return (23456, "Hello!");  
  }  
}  
  
// web3.js  
const MyContract = new web3.eth.Contract(abi, address);  
MyContract.methods.myFunction().call()
```

(continues on next page)

(continued from previous page)

```

.then(console.log);
> Result {
  myNumber: '23456',
  myString: 'Hello!%',
  0: '23456', // these are here as fallbacks if the name is not know or given
  1: 'Hello!%'
}

// SINGLE-ARGUMENT RETURN:

// Solidity
contract MyContract {
  function myFunction() returns(string myString) {
    return "Hello!%";
  }
}

// web3.js
const MyContract = new web3.eth.Contract(abi, address);
MyContract.methods.myFunction().call()
.then(console.log);
> "Hello!%"

```

7.11 methods.myMethod.send

```
myContract.methods.myMethod([param1[, param2[, ...]]]).send(options[, callback])
```

Will send a transaction to the smart contract and execute its method. Note this can alter the smart contract state.

7.11.1 Parameters

1. options - Object: The options used for sending.

- `from` - String: The address the transaction should be sent from.
- `gasPrice` - String (optional): The gas price in wei to use for this transaction. It is the wei per unit of gas.
- `gas` - Number (optional): The maximum gas provided for this transaction (gas limit).
- `value` - "Number|String|BN|BigNumber" (optional): The value transferred for the transaction in wei.

2. `callback` - Function (optional): This callback will be fired first with the "transactionHash", or with an error object as the first argument.

7.11.2 Returns

The `callback` will return the 32 bytes transaction hash.

PromiEvent: A *promise combined event emitter*. Will be resolved when the transaction *receipt* is available, OR if this `send()` is called from a `someContract.deploy()`, then the promise will resolve with the *new contract instance*. Additionally the following events are available:

- "transactionHash" returns String: is fired right after the transaction is sent and a transaction hash is available.
- "receipt" returns Object: is fired when the transaction *receipt* is available. Receipts from contracts will have no `logs` property, but instead an `events` property with event names as keys and events as properties. See *getPastEvents return values* for details about the returned event object.
- "confirmation" returns Number, Object: is fired for every confirmation up to the 24th confirmation. Receives the confirmation number as the first and the receipt as the second argument. Fired from confirmation 1 on, which is the block where it's mined.
- "error" returns Error: is fired if an error occurs during sending. If an out of gas error, the second parameter is the receipt.

7.11.3 Example

```
// using the callback
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'}, (error, transactionHash) => {
  ...
});

// using the promise
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then((receipt) => {
  // receipt can also be a new contract instance, when coming from a "contract.
  ↪deploy({...}).send()"
});

// using the event emitter
myContract.methods.myMethod(123).send({from:
  ↪'0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.on('transactionHash', (hash) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('receipt', (receipt) => {
  // receipt example
  console.log(receipt);
  > {
    "transactionHash":
  ↪"0x9fc76417374aa880d4449a1f7f31ec597f00b1f6f3dd2d66f4c9c6c445836d8b",
    "transactionIndex": 0,
    "blockHash":
  ↪"0xef95f2f1ed3ca60b048b4bf67cde2195961e0bba6f70bcbea9a2c4e133e34b46",
    "blockNumber": 3,
    "contractAddress": "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
    "cumulativeGasUsed": 314159,
    "gasUsed": 30234,
```

(continues on next page)

(continued from previous page)

```

    "events": {
      "MyEvent": {
        returnValues: {
          myIndexedParam: 20,
          myOtherIndexedParam: '0x123456789...',
          myNonIndexParam: 'My String'
        },
        raw: {
          data:
↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
          topics: [
↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
          },
          event: 'MyEvent',
          signature:
↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
          logIndex: 0,
          transactionIndex: 0,
          transactionHash:
↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
          blockHash:
↪ '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
          blockNumber: 1234,
          address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
        },
      "MyOtherEvent": {
        ...
      },
      "MyMultipleEvent":[ {...}, {...}] // If there are multiple of the same_
↪ event, they will be in an array
    }
  }
})
.on('error', console.error); // If there's an out of gas error the second parameter_
↪ is the receipt.

```

7.12 methods.myMethod.estimateGas

```

myContract.methods.myMethod([param1[, param2[, ...]])
.estimateGas(options[, _
↪ callback])

```

Will call estimate the gas a method execution will take when executed in the EVM without. The estimation can differ from the actual gas used when later sending a transaction, as the state of the smart contract can be different at that time.

7.12.1 Parameters

1. **options - Object (optional):** The options used for calling.

- **from - String (optional):** The address the call “transaction” should be made from.

- `gas` - Number (optional): The maximum gas provided for this call “transaction” (gas limit). Setting a specific value helps to detect out of gas errors. If all gas is used it will return the same number.
 - `value` - “Number|String|BN|BigNumber” (optional): The value transferred for the call “transaction” in wei.
2. `callback` - Function (optional): This callback will be fired with the result of the gas estimation as the second argument, or with an error object as the first argument.

7.12.2 Returns

Promise<number> - The gas amount estimated.

7.12.3 Example

```
// using the callback
myContract.methods.myMethod(123).estimateGas({gas: 5000000}, function(error, ↵
↵ gasAmount) {
  if(gasAmount == 5000000)
    console.log('Method ran out of gas');
});

// using the promise
myContract.methods.myMethod(123).estimateGas({from:
↵ '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'})
.then(function(gasAmount) {
  ...
})
.catch(function(error) {
  ...
});
```

7.13 methods.myMethod.encodeABI

```
myContract.methods.myMethod([param1[, param2[, ...]]) .encodeABI()
```

Encodes the ABI for this method. This can be used to send a transaction, call a method, or pass it into another smart contracts method as arguments.

7.13.1 Parameters

none

7.13.2 Returns

String: The encoded ABI byte code to send via a transaction or call.

(continued from previous page)

```

raw: {
  data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffd57a7af66ab4ead7
↪', '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
},
event: 'MyEvent',
signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffd57a7af66ab4ead7',
logIndex: 0,
transactionIndex: 0,
transactionHash:
↪'0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffd57a7af66ab4ead7',
blockNumber: 1234,
address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}

```

7.16 events

```
myContract.events.MyEvent([options][, callback])
```

Subscribe to an event

7.16.1 Parameters

1. **options - Object (optional):** The options used for deployment.

- **filter - Object (optional):** Let you filter events by indexed parameters, e.g. `{filter: {myNumber: [12, 13]}}` means all events where “myNumber” is 12 or 13.
- **fromBlock - Number (optional):** The block number from which to get events on.
- **topics - Array (optional):** This allows to manually set the topics for the event filter. If given the filter property and event signature, `(topic[0])` will not be set automatically.

2. **callback - Function (optional):** This callback will be fired for each *event* as the second argument, or an error as the first argument.

7.16.2 Returns

`EventEmitter`: The event emitter has the following events:

- **"data" returns Object:** Fires on each incoming event with the event object as argument.
- **"changed" returns Object:** Fires on each event which was removed from the blockchain. The event will have the additional property `"removed: true"`.
- **"error" returns Object:** Fires when an error in the subscription occurs.

The structure of the returned event `Object` looks as follows:

- **event - String:** The event name.
- **signature - String|Null:** The event signature, null if it's an anonymous event.

- `address` - String: Address this event originated from.
- `returnValues` - Object: The return values coming from the event, e.g. `{myVar: 1, myVar2: '0x234...'}`.
- `logIndex` - Number: Integer of the event index position in the block.
- `transactionIndex` - Number: Integer of the transaction's index position the event was created in.
- `transactionHash 32 Bytes` - String: Hash of the transaction this event was created in.
- `blockHash 32 Bytes` - String: Hash of the block this event was created in. `null` when it's still pending.
- `blockNumber` - Number: The block number this log was created in. `null` when still pending.
- `raw.data` - String: The data containing non-indexed log parameter.
- `raw.topics` - Array: An array with max 4 32 Byte topics, topic 1-3 contains indexed parameters of the event.

7.16.3 Example

```

myContract.events.MyEvent({
  filter: {myIndexedParam: [20,23], myOtherIndexedParam: '0x123456789...'}, //
  ↳Using an array means OR: e.g. 20 or 23
  fromBlock: 0
}, (error, event) => { console.log(event); })
.on('data', (event) => {
  console.log(event); // same results as the optional callback above
})
.on('changed', (event) => {
  // remove event from local database
})
.on('error', console.error);

// event output example
> {
  returnValues: {
    myIndexedParam: 20,
    myOtherIndexedParam: '0x123456789...',
    myNonIndexParam: 'My String'
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7
  ↳', '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
  },
  event: 'MyEvent',
  signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  ↳'0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,
  address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}

```

7.17 events.allEvents

```
myContract.events.allEvents([options][, callback])
```

Same as *events* but receives all events from this smart contract. Optionally the filter property can filter those events.

7.18 getPastEvents

```
myContract.getPastEvents(event[, options][, callback])
```

Gets past events for this contract.

7.18.1 Parameters

1. *event* - String: The name of the event in the contract, or "allEvents" to get all events.
2. **options - Object (optional): The options used for deployment.**
 - *filter* - Object (optional): Lets you filter events by indexed parameters, e.g. {filter: {myNumber: [12,13]}} means all events where "myNumber" is 12 or 13.
 - *fromBlock* - Number (optional): The block number from which to get events on.
 - *toBlock* - Number (optional): The block number to get events up to (Defaults to "latest").
 - *topics* - Array (optional): This allows manually setting the topics for the event filter. If given the filter property and event signature, (topic[0]) will not be set automatically.
3. *callback* - Function (optional): This callback will be fired with an array of event logs as the second argument, or an error as the first argument.

7.18.2 Returns

Promise returns Array: An array with the past event Objects, matching the given event name and filter.

For the structure of a returned event Object see *getPastEvents return values*.

7.18.3 Example

```
myContract.getPastEvents('MyEvent', {
  filter: {myIndexedParam: [20,23], myOtherIndexedParam: '0x123456789...'}, // 
  ↪ Using an array means OR: e.g. 20 or 23
  fromBlock: 0,
  toBlock: 'latest'
}, (error, events) => { console.log(events); })
.then((events) => {
  console.log(events) // same results as the optional callback above
});
> [{
```

(continues on next page)

(continued from previous page)

```
returnValues: {
  myIndexedParam: 20,
  myOtherIndexedParam: '0x123456789...',
  myNonIndexParam: 'My String'
},
raw: {
  data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  topics: ['0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7
↪', '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385']
},
event: 'MyEvent',
signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
logIndex: 0,
transactionIndex: 0,
transactionHash:
↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
blockNumber: 1234,
address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
}, {
  ...
}]
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

web3.eth.accounts

The `web3.eth.accounts` contains functions to generate Ethereum accounts and sign transactions and data.

Note: This package has NOT been audited and might potentially be unsafe. Take precautions to clear memory properly, store the private keys safely, and test transaction receiving and sending functionality properly before using in production!

To use this package standalone use:

```
import {Accounts} from 'web3-eth-accounts';

// Passing in the eth or web3 package is necessary to allow retrieving chainId, ↵
↳ gasPrice and nonce automatically
// for accounts.signTransaction().
const accounts = new Accounts('ws://localhost:8546', options);
```

8.1 create

```
web3.eth.accounts.create([entropy]);
```

Generates an account object with private key and public key. It's different from `web3.eth.personal.newAccount()` which creates an account over the network on the node via an RPC call.

8.1.1 Parameters

1. `entropy - String` (optional): A random string to increase entropy. If given it should be at least 32 characters. If none is given a random string will be generated using `randomhex`.

8.1.2 Returns

Object - The account object with the following structure:

- `address` - string: The account address.
- `privateKey` - string: The accounts private key. This should never be shared or stored unencrypted in localStorage! Also make sure to null the memory after usage.
- `signTransaction(tx [, callback])` - Function: The function to sign transactions. See [web3.eth.accounts.signTransaction\(\)](#) for more.
- `sign(data)` - Function: The function to sign transactions. See [web3.eth.accounts.sign\(\)](#) for more.

8.1.3 Example

```
web3.eth.accounts.create();
> {
  address: "0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01",
  privateKey: "0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.create('2435@#@#@±±±±!!!!
↪678543213456764321$34567543213456785432134567');
> {
  address: "0xF2CD2AA0c7926743B1D4310b2BC984a0a453c3d4",
  privateKey: "0xd7325de5c2c1cf0009fac77d3d04a9c004b038883446b065871bc3e831dcd098",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.create(web3.utils.randomHex(32));
> {
  address: "0xe78150FaCD36E8EB00291e251424a0515AA1FF05",
  privateKey: "0xcc505ee6067fba3f6fc2050643379e190e087aef5d958ab9f2f3ed3800fa4e",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.2 privateKeyToAccount

```
web3.eth.accounts.privateKeyToAccount(privateKey);
```

Creates an account object from a private key.

8.2.1 Parameters

1. `privateKey` - String: The private key hex string beginning with 0x.

8.2.2 Returns

Object - The account object with the *structure seen here*.

8.2.3 Example

```
web3.eth.accounts.privateKeyToAccount (
  ↪ '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709');
> {
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01',
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.3 signTransaction

```
web3.eth.accounts.signTransaction(tx, privateKey [, callback]);
```

Signs an Ethereum transaction with a given private key.

8.3.1 Parameters

1. **tx - Object:** The transaction's properties object as follows:

- **nonce - String:** (optional) The nonce to use when signing this transaction. Default will use `web3.eth.getTransactionCount()`.
- **chainId - String:** (optional) The chain id to use when signing this transaction. Default will use `web3.eth.net.getId()`.
- **to - String:** (optional) The receiver of the transaction, can be empty when deploying a contract.
- **data - String:** (optional) The call data of the transaction, can be empty for simple value transfers.
- **value - String:** (optional) The value of the transaction in wei.
- **gasPrice - String:** (optional) The gas price set by this transaction, if empty, it will use `web3.eth.gasPrice()`
- **gas - String:** The gas provided by the transaction.

2. **privateKey - String:** The private key to sign with.

3. **callback - Function:** (optional) Optional callback, returns an error object as first parameter and the result as second.

8.3.2 Returns

Promise returning Object: The signed data RLP encoded transaction, or if `returnSignature` is `true` the signature value

- `messageHash` - String: The hash of the given message.
- `r` - String: First 32 bytes of the signature
- `s` - String: Next 32 bytes of the signature
- `v` - String: Recovery value + 27
- `rawTransaction` - String: The RLP encoded transaction, ready to be send using *web3.eth.sendSignedTransaction*.

8.3.3 Example

```
web3.eth.accounts.signTransaction({
  to: '0xF0109fC8DF283027b6285cc889F5aA624EaC1F55',
  value: '1000000000',
  gas: 2000000
}, '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318')
.then(console.log);
> {
  messageHash: '0x88cfbd7e51c7a40540b233cf68b62ad1df3e92462f1c6018d6d67eae0f3b08f5',
  v: '0x25',
  r: '0xc9cf86333bcb065d140032ecaab5d9281bde80f21b9687b3e94161de42d51895',
  s: '0x727a108a0b8d101465414033c3f705a9c7b826e596766046ee1183dbc8aeaa68',
  rawTransaction:
  ↪ '0xf869808504e3b29200831e848094f0109fc8df283027b6285cc889f5aa624eac1f55843b9aca008025a0c9cf86333bcb065d140032ecaab5d9281bde80f21b9687b3e94161de42d51895'
  ↪
}

web3.eth.accounts.signTransaction({
  to: '0xF0109fC8DF283027b6285cc889F5aA624EaC1F55',
  value: '1000000000',
  gas: 2000000,
  gasPrice: '234567897654321',
  nonce: 0,
  chainId: 1
}, '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318')
.then(console.log);
> {
  messageHash: '0x6893a6ee8df79b0f5d64a180cd1ef35d030f3e296a5361cf04d02ce720d32ec5',
  r: '0x9ebb6ca057a0535d6186462bc0b465b561c94a295bdb0621fc19208ab149a9c',
  s: '0x440ffd775ce91a833ab41077204d5341a6f9fa91216a6f3ee2c051fea6a0428',
  v: '0x25',
  rawTransaction:
  ↪ '0xf86a8086d55698372431831e848094f0109fc8df283027b6285cc889f5aa624eac1f55843b9aca008025a009ebb6ca057a0535d6186462bc0b465b561c94a295bdb0621fc19208ab149a9c'
  ↪
}
```

8.4 recoverTransaction

```
web3.eth.accounts.recoverTransaction(rawTransaction);
```

Recovers the Ethereum address which was used to sign the given RLP encoded transaction.

8.4.1 Parameters

1. `signature` - `String`: The RLP encoded transaction.

8.4.2 Returns

`String`: The Ethereum address used to sign this transaction.

8.4.3 Example

```
web3.eth.accounts.recoverTransaction(
  ↪ '0xf86180808401ef364594f0109fc8df283027b6285cc889f5aa624eac1f5580801ca031573280d608f75137e33fc1465'
  ↪ ');
> "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55"
```

8.5 hashMessage

```
web3.eth.accounts.hashMessage(message);
```

Hashes the given message to be passed `web3.eth.accounts.recover()` function. The data will be UTF-8 HEX decoded and enveloped as follows: `"\x19Ethereum Signed Message:\n" + message.length + message` and hashed using keccak256.

8.5.1 Parameters

1. `message` - `String`: A message to hash, if its HEX it will be UTF8 decoded before.

8.5.2 Returns

`String`: The hashed message

8.5.3 Example

```
web3.eth.accounts.hashMessage("Hello World")
> "0xa1de988600a42c4b4ab089b619297c17d53cffae5d5120d82d8a92d0bb3b78f2"

// the below results in the same hash
web3.eth.accounts.hashMessage(web3.utils.utf8ToHex("Hello World"))
> "0xa1de988600a42c4b4ab089b619297c17d53cffae5d5120d82d8a92d0bb3b78f2"
```

8.6 sign

```
web3.eth.accounts.sign(data, privateKey);
```

Signs arbitrary data. This data is before UTF-8 HEX decoded and enveloped as follows: "\x19Ethereum Signed Message:\n" + message.length + message.

8.6.1 Parameters

1. data - String: The data to sign. If its a string it will be
2. privateKey - String: The private key to sign with.

8.6.2 Returns

String|Object: The signed data RLP encoded signature, or if `returnSignature` is `true` the signature values as follows:

- message - String: The the given message.
- messageHash - String: The hash of the given message.
- r - String: First 32 bytes of the signature
- s - String: Next 32 bytes of the signature
- v - String: Recovery value + 27

8.6.3 Example

```
web3.eth.accounts.sign('Some data',
↳ '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318');
> {
  message: 'Some data',
  messageHash: '0x1da44b586eb0729ff70a73c326926f6ed5a25f5b056e7f47fbc6e58d86871655',
  v: '0x1c',
  r: '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  s: '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029',
  signature:
↳ '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd6007e74cd82e037b800186422fc2da1
↳ '
}
```

8.7 recover

```
web3.eth.accounts.recover(signatureObject);
web3.eth.accounts.recover(message, signature [, preFixed]);
web3.eth.accounts.recover(message, v, r, s [, preFixed]);
```

Recovers the Ethereum address which was used to sign the given data.

8.7.1 Parameters

1. `message|signatureObject - String|Object`: Either signed message or hash, or the signature object as following

- `messageHash - String`: The hash of the given message already prefixed with `"\x19Ethereum Signed Message:\n" + message.length + message`.
- `r - String`: First 32 bytes of the signature
- `s - String`: Next 32 bytes of the signature
- `v - String`: Recovery value + 27

2. `signature - String`: The raw RLP encoded signature, OR parameter 2-4 as v, r, s values.

3. `preFixed - Boolean` (optional, default: `false`): If the last parameter is true, the given message will NOT automatically be prefixed with `"\x19Ethereum Signed Message:\n" + message.length + message`, and assumed to be already prefixed.

8.7.2 Returns

String: The Ethereum address used to sign this data.

8.7.3 Example

```
web3.eth.accounts.recover({
  messageHash: '0x1da44b586eb0729ff70a73c326926f6ed5a25f5b056e7f47fbc6e58d86871655',
  v: '0x1c',
  r: '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  s: '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029'
})
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"

// message, signature
web3.eth.accounts.recover('Some data',
  ↪ '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029',
  ↪ ');
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"

// message, v, r, s
web3.eth.accounts.recover('Some data', '0x1c',
  ↪ '0xb91467e570a6466aa9e9876cbcd013baba02900b8979d43fe208a4a4f339f5fd',
  ↪ '0x6007e74cd82e037b800186422fc2da167c747ef045e5d18a5f5d4300f8e1a029');
> "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23"
```

8.8 encrypt

```
web3.eth.accounts.encrypt(privateKey, password);
```

Encrypts a private key to the web3 keystore v3 standard.

8.8.1 Parameters

1. `privateKey` - String: The private key to encrypt.
2. `password` - String: The password used for encryption.

8.8.2 Returns

Object: The encrypted keystore v3 JSON.

8.8.3 Example

```
web3.eth.accounts.encrypt (
  ↪ '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318', 'test!')
> {
  version: 3,
  id: '04e9bcbb-96fa-497b-94d1-14df4cd20af6',
  address: '2c7536e3605d9c16a7a3d7b1898e529396a65c23',
  crypto: {
    ciphertext: 'alc25da3ecde4e6a24f3697251dd15d6208520efc84ad97397e906e6df24d251
  ↪',
    cipherparams: { iv: '2885df2b63f7ef247d753c82fa20038a' },
    cipher: 'aes-128-ctr',
    kdf: 'scrypt',
    kdfparams: {
      dklen: 32,
      salt: '4531b3c174cc3ff32a6a7a85d6761b410db674807b2d216d022318ceee50be10',
      n: 262144,
      r: 8,
      p: 1
    },
    mac: 'b8b010fff37f9ae5559a352a185e86f9b9c1d7f7a9f1bd4e82a5dd35468fc7f6'
  }
}
```

8.9 decrypt

```
web3.eth.accounts.decrypt(keystoreJsonV3, password);
```

Decrypts a keystore v3 JSON, and creates the account.

8.9.1 Parameters

1. `keystoreJsonV3` - String: The encrypted keystore v3 JSON.
2. `password` - String: The password used for encryption.

8.9.2 Returns

Object: The decrypted account.

8.9.3 Example

```

web3.eth.accounts.decrypt({
  version: 3,
  id: '04e9bcbb-96fa-497b-94d1-14df4cd20af6',
  address: '2c7536e3605d9c16a7a3d7b1898e529396a65c23',
  crypto: {
    ciphertext: 'alc25da3ecde4e6a24f3697251dd15d6208520efc84ad97397e906e6df24d251
↪',
    cipherparams: { iv: '2885df2b63f7ef247d753c82fa20038a' },
    cipher: 'aes-128-ctr',
    kdf: 'scrypt',
    kdfparams: {
      dklen: 32,
      salt: '4531b3c174cc3ff32a6a7a85d6761b410db674807b2d216d022318ceee50be10',
      n: 262144,
      r: 8,
      p: 1
    },
    mac: 'b8b010fff37f9ae5559a352a185e86f9b9c1d7f7a9f1bd4e82a5dd35468fc7f6'
  }
}, 'test!');
> {
  address: "0x2c7536E3605D9C16a7a3D7b1898e529396a65c23",
  privateKey: "0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318",
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

```

8.10 wallet

```
web3.eth.accounts.wallet;
```

Contains an in memory wallet with multiple accounts. These accounts can be used when using `web3.eth.sendTransaction()`.

8.10.1 Example

```

web3.eth.accounts.wallet;
> Wallet {
  0: {...}, // account by index
  "0xF0109fc8DF283027b6285cc889F5aA624EaC1F55": {...}, // same account by address
  "0xf0109fc8df283027b6285cc889f5aa624eac1f55": {...}, // same account by address
↪ lowercase
  1: {...},
  "0xD0122fc8DF283027b6285cc889F5aA624EaC1d23": {...},
  "0xd0122fc8df283027b6285cc889f5aa624eac1d23": {...},

  add: function(){},
  remove: function(){},
  save: function(){},
  load: function(){},
}

```

(continues on next page)

(continued from previous page)

```
clear: function() {},
length: 2,
}
```

8.11 wallet.create

```
web3.eth.accounts.wallet.create(numberOfAccounts [, entropy]);
```

Generates one or more accounts in the wallet. If wallets already exist they will not be overridden.

8.11.1 Parameters

1. `numberOfAccounts` - `Number`: Number of accounts to create. Leave empty to create an empty wallet.
2. `entropy` - `String` (optional): A string with random characters as additional entropy when generating accounts. If given it should be at least 32 characters.

8.11.2 Returns

Object: The wallet object.

8.11.3 Example

```
web3.eth.accounts.wallet.create(2, '54674321$3456764321$345674321$3453647544±±±$±±±!
↪!!43534534534534');
> Wallet {
  0: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xf0109fc8df283027b6285cc889f5aa624eac1f55": {...},
  ...
}
```

8.12 wallet.add

```
web3.eth.accounts.wallet.add(account);
```

Adds an account using a private key or account object to the wallet.

8.12.1 Parameters

1. `account` - `String|Object`: A private key or account object created with `web3.eth.accounts.create()`.

8.12.2 Returns

Object: The added account.

8.12.3 Example

```
web3.eth.accounts.wallet.add(
  ↪ '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318');
> {
  index: 0,
  address: '0x2c7536E3605D9C16a7a3D7b1898e529396a65c23',
  privateKey: '0x4c0883a69102937d6231471b5dbb6204fe5129617082792ae468d01a3f362318',
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}

web3.eth.accounts.wallet.add({
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01'
});
> {
  index: 0,
  address: '0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01',
  privateKey: '0x348ce564d427a3311b6536bbcff9390d69395b06ed6c486954e971d960fe8709',
  signTransaction: function(tx){...},
  sign: function(data){...},
  encrypt: function(password){...}
}
```

8.13 wallet.remove

```
web3.eth.accounts.wallet.remove(account);
```

Removes an account from the wallet.

8.13.1 Parameters

1. `account` - `String|Number`: The account address, or index in the wallet.

8.13.2 Returns

Boolean: `true` if the wallet was removed. `false` if it couldn't be found.

8.13.3 Example

```
web3.eth.accounts.wallet;
> Wallet {
  0: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...}
  1: {...},
  "0xb8CE9ab6943e0eCED004cDe8e3bBed6568B2Fa01": {...}
  ...
}

web3.eth.accounts.wallet.remove('0xF0109fC8DF283027b6285cc889F5aA624EaC1F55');
> true

web3.eth.accounts.wallet.remove(3);
> false
```

8.14 wallet.clear

```
web3.eth.accounts.wallet.clear();
```

Securely empties the wallet and removes all its accounts.

8.14.1 Parameters

none

8.14.2 Returns

Object: The wallet object.

8.14.3 Example

```
web3.eth.accounts.wallet.clear();
> Wallet {
  add: function() {},
  remove: function() {},
  save: function() {},
  load: function() {},
  clear: function() {},

  length: 0
}
```

8.15 wallet.encrypt

```
web3.eth.accounts.wallet.encrypt(password);
```

Encrypts all wallet accounts to an array of encrypted keystore v3 objects.

8.15.1 Parameters

1. password - String: The password which will be used for encryption.

8.15.2 Returns

Array: The encrypted keystore v3.

8.15.3 Example

```
web3.eth.accounts.wallet.encrypt('test');
> [ { version: 3,
  id: 'dcf8ab05-a314-4e37-b972-bf9b86f91372',
  address: '06f702337909c06c82b09b7a22f0a2f0855d1f68',
  crypto:
    { ciphertext: '0de804dc63940820f6b3334e5a4bfc8214e27fb30bb7e9b7b74b25cd7eb5c604',
      cipherparams: [Object],
      cipher: 'aes-128-ctr',
      kdf: 'scrypt',
      kdfparams: [Object],
      mac: 'b2aac1485bd6ee1928665642bf8eae9ddfbc039c3a673658933d320bac6952e3' } },
  { version: 3,
  id: '9e1c7d24-b919-4428-b10e-0f3ef79f7cf0',
  address: 'b5d89661b59a9af0b34f58d19138baa2de48baaf',
  crypto:
    { ciphertext: 'd705ebed2a136d9e4db7e5ae70ed1f69d6a57370d5fbe06281eb07615f404410',
      cipherparams: [Object],
      cipher: 'aes-128-ctr',
      kdf: 'scrypt',
      kdfparams: [Object],
      mac: 'af9eca5eb01b0f70e909f824f0e7cdb90c350a802f04a9f6afe056602b92272b' } }
]
```

8.16 wallet.decrypt

```
web3.eth.accounts.wallet.decrypt(keystoreArray, password);
```

Decrypts keystore v3 objects.

8.16.1 Parameters

1. keystoreArray - Array: The encrypted keystore v3 objects to decrypt.
2. password - String: The password which will be used for encryption.

8.16.2 Returns

Object: The wallet object.

8.16.3 Example

```
web3.eth.accounts.wallet.decrypt([
  { version: 3,
    id: '83191a81-aaca-451f-b63d-0c5f3b849289',
    address: '06f702337909c06c82b09b7a22f0a2f0855d1f68',
    crypto:
      { ciphertext: '7d34deae112841fba86e3e6cf08f5398dda323a8e4d29332621534e2c4069e8d',
        cipherparams: { iv: '497f4d26997a84d570778eae874b2333' },
        cipher: 'aes-128-ctr',
        kdf: 'scrypt',
        kdfparams:
          { dklen: 32,
            salt: '208dd732a27aa4803bb760228dff18515d5313fd085bbce60594a3919ae2d88d',
            n: 262144,
            r: 8,
            p: 1 },
          mac: '0062a853de302513c57bfe3108ab493733034bf3cb313326f42cf26ea2619cf9' } },
    { version: 3,
      id: '7d6b91fa-3611-407b-b16b-396efb28f97e',
      address: 'b5d89661b59a9af0b34f58d19138baa2de48baaf',
      crypto:
        { ciphertext: 'cb9712d1982ff89f571fa5dbef447f14b7e5f142232bd2a913aac833730eeb43',
          cipherparams: { iv: '8cccb91cb84e435437f7282ec2ffd2db' },
          cipher: 'aes-128-ctr',
          kdf: 'scrypt',
          kdfparams:
            { dklen: 32,
              salt: '08ba6736363c5586434cd5b895e6fe41ea7db4785bd9b901dedce77a1514e8b8',
              n: 262144,
              r: 8,
              p: 1 },
            mac: 'd2eb068b37e2df55f56fa97a2bf4f55e072bef0dd703bfd917717d9dc54510f0' } }
  ], 'test');
> Wallet {
  0: {...},
  1: {...},
  "0xf0109fc8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xD0122fc8DF283027b6285cc889F5aA624EaC1d23": {...}
  ...
}
```

8.17 wallet.save

```
web3.eth.accounts.wallet.save(password [, keyName]);
```

Stores the wallet encrypted and as string in local storage.

Note: Browser only.

8.17.1 Parameters

1. `password` - `String`: The password to encrypt the wallet.
2. `keyName` - `String`: (optional) The key used for the local storage position, defaults to "web3js_wallet".

8.17.2 Returns

Boolean

8.17.3 Example

```
web3.eth.accounts.wallet.save('test#!$');  
> true
```

8.18 wallet.load

```
web3.eth.accounts.wallet.load(password [, keyName]);
```

Loads a wallet from local storage and decrypts it.

Note: Browser only.

8.18.1 Parameters

1. `password` - `String`: The password to decrypt the wallet.
2. `keyName` - `String`: (optional) The key used for the localstorage position, defaults to "web3js_wallet".

8.18.2 Returns

Object: The wallet object.

8.18.3 Example

```
web3.eth.accounts.wallet.load('test#!$', 'myWalletKey');
> Wallet {
  0: {...},
  1: {...},
  "0xF0109fC8DF283027b6285cc889F5aA624EaC1F55": {...},
  "0xD0122fC8DF283027b6285cc889F5aA624EaC1d23": {...}
  ...
}
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

web3.eth.personal

The `web3-eth-personal` package allows you to interact with the Ethereum node's accounts.

Note: Many of these functions send sensitive information, like password. Never call these functions over a unsecured Websocket or HTTP provider, as your password will be sent in plain text!

```
import Web3 from 'web3';
import {Personal} from 'web3-eth-personal';

// "Web3.givenProvider" will be set if in an Ethereum supported browser.
const personal = new Personal(Web3.givenProvider || 'ws://some.local-or-remote.
↳node:8546', options);

// or using the web3 umbrella package
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
↳options);

// -> web3.eth.personal
```

9.1 options

An Web3 module does provide several options for configuring the transaction confirmation workflow or for defining default values. These are the currently available option properties on a Web3 module:

9.1.1 Module Options

defaultAccount

defaultBlock

defaultGas

defaultGasPrice

transactionBlockTimeout

transactionConfirmationBlocks

transactionPollingTimeout

transactionSigner

9.1.2 Example

```
import Web3 from 'web3';

const options = {
  defaultAccount: '0x0',
  defaultBlock: 'latest',
  defaultGas: 1,
  defaultGasPrice: 0,
  transactionBlockTimeout: 50,
  transactionConfirmationBlocks: 24,
  transactionPollingTimeout: 480,
  transactionSigner: new CustomTransactionSigner()
}

const web3 = new Web3('http://localhost:8545', options);
```

9.2 defaultBlock

```
web3.defaultBlock
web3.eth.defaultBlock
web3.shh.defaultBlock
...
```

The default block which will be used for a requests.

9.2.1 Returns

string|number: The current value of the defaultBlock property.

9.3 defaultAccount

```
web3.defaultAccount
web3.eth.defaultAccount
web3.shh.defaultAccount
...
```


The default account which will be used for a requests.

9.3.1 Returns

`null|string`: The current value of the `defaultAccount` property.

9.4 defaultGasPrice

```
web3.defaultGasPrice
web3.eth.defaultGasPrice
web3.shh.defaultGasPrice
...
```

The default gas price which will be used for a request.

9.4.1 Returns

`string|number`: The current value of the `defaultGasPrice` property.

9.5 defaultGas

```
web3.defaultGas
web3.eth.defaultGas
web3.shh.defaultGas
...
```

The default gas which will be used for a request.

9.5.1 Returns

`string|number`: The current value of the `defaultGas` property.

9.6 transactionBlockTimeout

```
web3.transactionBlockTimeout
web3.eth.transactionBlockTimeout
web3.shh.transactionBlockTimeout
...
```

This can be used with a socket provider and defines the number of blocks until the `PromiEvent` rejects with a timeout error.

9.6.1 Returns

number: The current value of `transactionBlockTimeout`

9.7 transactionConfirmationBlocks

```
web3.transactionConfirmationBlocks
web3.eth.transactionConfirmationBlocks
web3.shh.transactionConfirmationBlocks
...
```

This defines the number of blocks it requires until a transaction will be handled as confirmed. The `PromiEvent` will resolve with the desired receipt when enough confirmations happened.

9.7.1 Returns

number: The current value of `transactionConfirmationBlocks`

9.8 transactionPollingTimeout

```
web3.transactionPollingTimeout
web3.eth.transactionPollingTimeout
web3.shh.transactionPollingTimeout
...
```

This defines the polling cycles amount when you send a transaction with the `HttpProvider`. The `PromiEvent` rejects with a timeout error when the timeout got exceeded. (1 cycle == 1sec).

9.8.1 Returns

number: The current value of `transactionPollingTimeout`

9.9 transactionSigner

```
web3.eth.transactionSigner
...
```

The `transactionSigner` property does provide us the possibility to customize the signing process of the `Eth` module and the related sub-modules.

The interface of a `TransactionSigner`:

```
interface TransactionSigner {
  sign(txObject: Transaction): Promise<SignedTransaction>
}

interface SignedTransaction {
  messageHash: string,
  v: string,
  r: string,
  s: string,
  rawTransaction: string
}
```

9.9.1 Returns

TransactionSigner: A JavaScript class of type TransactionSigner.

9.10 setProvider

```
web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...
```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc EXCEPT web3.bzz which needs a separate provider at all times.

9.10.1 Parameters

1. Object|String - provider: a valid provider
2. Net - net: (optional) the node.js Net package. This is only required for the IPC provider.

9.10.2 Returns

Boolean

9.10.3 Example

```
import Web3 from 'web3';

const web3 = new Web3('http://localhost:8545');
```

(continues on next page)

(continued from previous page)

```
// or
const web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');
const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path

// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

9.11 providers

```
Web3.providers
Eth.providers
...
```

Contains the current available providers.

9.11.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

9.11.2 Example

```
const Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
const web3 = new Web3(Web3.givenProvider || 'ws://localhost:8546');
// or
const web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://
↳localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');

const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
```

(continues on next page)

(continued from previous page)

```
// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

9.12 givenProvider

```
Web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

9.12.1 Returns

Object: The given provider set or null;

9.12.2 Example

```
web3.setProvider(Web3.givenProvider || 'ws://localhost:8546');
```

9.13 currentProvider

```
web3.currentProvider
web3.eth.currentProvider
web3.shh.currentProvider
web3.bzz.currentProvider
...
```

Will return the current provider, otherwise null.

9.13.1 Returns

Object: The current provider set or null;

9.13.2 Example

```
if(!web3.currentProvider) {
  web3.setProvider('http://localhost:8545');
}
```

9.14 BatchRequest

```
new web3.BatchRequest ()
new web3.eth.BatchRequest ()
new web3.shh.BatchRequest ()
...
```

Class to create and execute batch requests.

9.14.1 Parameters

none

9.14.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

9.14.3 Example

```
const contract = new web3.eth.Contract(abi, address);

const batch = new web3.BatchRequest ();
batch.add(web3.eth.getBalance.request ('0x0000000000000000000000000000000000000000',
  ↪ 'latest', callback));
batch.add(contract.methods.balance(address).call.request ({from:
  ↪ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute ();
```

9.15 newAccount

```
web3.eth.personal.newAccount (password, [callback])
```

Create a new account on the node that Web3 is connected to with its provider. The RPC method used is `personal_newAccount`. It differs from `web3.eth.accounts.create()` where the key pair is created only on client and it's up to the developer to manage it.

Note: Never call this function over a unsecured Websocket or HTTP provider, as your password will be send in plain text!

9.15.1 Parameters

1. `password` - `String`: The password to encrypt this account with.

9.15.2 Returns

`Promise<string>` - The address of the newly created account.

9.15.3 Example

```
web3.eth.personal.newAccount('!@superpassword')
.then(console.log);
> '0x1234567891011121314151617181920212223456'
```

9.16 sign

```
web3.eth.personal.sign(dataToSign, address, password [, callback])
```

Signs data using a specific account. This data is before UTF-8 HEX decoded and enveloped as follows: `"\x19Ethereum Signed Message:\n" + message.length + message`.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.16.1 Parameters

1. `String` - Data to sign. If `String` it will be converted using `web3.utils.utf8ToHex`.
2. `String` - Address to sign data with.
3. `String` - The password of the account to sign data with.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.16.2 Returns

`Promise<string>` - The signature.

9.16.3 Example

```
web3.eth.personal.sign("Hello world", "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
↳ "test password!")
.then(console.log);
>
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ "

// the below is the same
web3.eth.personal.sign(web3.utils.utf8ToHex("Hello world"),
↳ "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe", "test password!")
.then(console.log);
>
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ "
```

9.17 ecRecover

```
web3.eth.personal.ecRecover(dataThatWasSigned, signature [, callback])
```

Recovers the account that signed the data.

9.17.1 Parameters

1. String - Data that was signed. If String it will be converted using *web3.utils.utf8ToHex*.
2. String - The signature.
3. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.17.2 Returns

Promise<string> - The account.

9.17.3 Example

```
web3.eth.personal.ecRecover("Hello world",
↳ "0x30755ed65396facf86c53e6217c52b4daebe72aa4941d89635409de4c9c7f9466d4e9aaec7977f05e923889b33c0d0d
↳ ").then(console.log);
> "0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe"
```

9.18 signTransaction

3. `unlockDuration` - `Number` - The duration for the account to remain unlocked.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.20.2 Returns

`Promise<boolean>` - True if the account got unlocked successful otherwise false.

9.20.3 Example

```
web3.eth.personal.unlockAccount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe", "test_
↳password!", 600)
.then(console.log('Account unlocked!'));
> "Account unlocked!"
```

9.21 lockAccount

```
web3.eth.personal.lockAccount(address [, callback])
```

Locks the given account.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.21.1 Parameters

1. `address` - `String`: The account address.
4. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

9.21.2 Returns

`Promise<boolean>`

9.21.3 Example

```
web3.eth.personal.lockAccount("0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe")
.then(console.log('Account locked!'));
> "Account locked!"
```

9.22 getAccounts

```
web3.eth.personal.getAccounts([callback])
```

Returns a list of accounts the node controls by using the provider and calling the RPC method `personal_listAccounts`. Using `web3.eth.accounts.create()` will not add accounts into this list. For that use `web3.eth.personal.newAccount()`.

The results are the same as `web3.eth.getAccounts()` except that calls the RPC method `eth_accounts`.

9.22.1 Returns

Promise<Array> - An array of addresses controlled by node.

9.22.2 Example

```
web3.eth.personal.getAccounts()
.then(console.log);
> ["0x11f4d0A3c12e86B4b5F39B213F7E19D048276DAe",
  ↪ "0xDCc6960376d6C6dEa93647383FfB245CfCed97Cf"]
```

9.23 importRawKey

```
web3.eth.personal.importRawKey(privateKey, password)
```

Imports the given private key into the key store, encrypting it with the passphrase.

Returns the address of the new account.

Note: Sending your account password over an unsecured HTTP RPC connection is highly unsecure.

9.23.1 Parameters

1. `privateKey` - String - An unencrypted private key (hex string).
2. `password` - String - The password of the account.

9.23.2 Returns

Promise<string> - The address of the account.

9.23.3 Example

```
web3.eth.personal.importRawKey(
  ↪ "cd3376bb711cb332ee3fb2ca04c6a8b9f70c316fcdf7a1f44ef4c7999483295e", "password1234")
.then(console.log);
> "0x8f337bf484b2fc75e4b0436645dcc226ee2ac531"
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

CHAPTER 10

web3.eth.ens

The `web3.eth.ens` functions let you interacting with Ens.

```
import Web3 from 'web3';
import {Ens} from 'web3-eth-ens';
import {Accounts} from 'web3-eth-accounts';

// "Web3.givenProvider" will be set if in an Ethereum supported browser.
const eth = new Ens(
  Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
  new Accounts(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
    ↪options),
  options
);

// or using the web3 umbrella package

const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
  ↪options);

// -> web3.eth.ens
```

10.1 registry

```
web3.eth.ens.registry;
```

Returns the network specific Ens registry.

10.1.1 Returns

Registry - The current Ens registry.

10.1.2 Example

```
web3.eth.ens.registry;
> {
  ens: Ens,
  contract: Contract,
  owner: Function(name),
  resolve: Function(name)
}
```

10.2 resolver

```
web3.eth.ens.resolver(name);
```

Returns the resolver contract to an Ethereum address.

10.2.1 Returns

Resolver - The Ens resolver for this name.

10.2.2 Example

```
web3.eth.ens.resolver('ethereum.eth').then((contract) => {
  console.log(contract);
});
> Contract<Resolver>
```

10.3 supportsInterface

```
web3.eth.ens.supportsInterface(ENSName, interfaceId);
```

Checks if the current resolver does support the desired interface.

10.3.1 Parameters

1. ENSName - String: The Ens name to resolve.
2. interfaceId - String: A defined ENS interfaceId.

10.3.2 Returns

Boolean - Returns true if the given interfaceId is supported by the resolver.

10.3.3 Example

```
web3.eth.ens.supportsInterface('ethereum.eth', '0xbc1c58d1').then((supportsInterface) => {
  console.log(supportsInterface);
})
> true
```

10.4 getAddress

```
web3.eth.ens.getAddress(ENSName);
```

Resolves an Ens name to an Ethereum address.

10.4.1 Parameters

1. ENSName - String: The Ens name to resolve.

10.4.2 Returns

String - The Ethereum address of the given name.

10.4.3 Example

```
web3.eth.ens.getAddress('ethereum.eth').then((address) => {
  console.log(address);
})
> 0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359
```

10.5 setAddress

```
web3.eth.ens.setAddress(ENSName, address, options);
```

Sets the address of an Ens name in his resolver.

10.5.1 Parameters

1. ENSName - String: The Ens name.
2. address - String: The address to set.
3. **options - Object: The options used for sending.**
 - from - String: The address the transaction should be sent from.
 - gasPrice - String (optional): The gas price in wei to use for this transaction.
 - gas - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an AddrChanged event.

10.5.2 Example

```
web3.eth.ens.setAddress (
  'ethereum.eth',
  '0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then((result) => {
  console.log(result.events);
});
> AddrChanged(...)

// Or using the event emitter

web3.eth.ens.setAddress (
  'ethereum.eth',
  '0xfB6916095ca1df60bB79Ce92cE3Ea74c37c5d359',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', (hash) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('receipt', (receipt) => {
  ...
})
.on('error', console.error);

// Or listen to the AddrChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then((resolver) => {
  resolver.events.AddrChanged({fromBlock: 0}, (error, event) => {
    console.log(event);
  })
  .on('data', (event) => {
    console.log(event);
  })
})
```

(continues on next page)

(continued from previous page)

```
.on('changed', (event) => {  
  // remove event from local database  
})  
.on('error', console.error);  
});
```

For further information on the handling of contract events please see here [contract-events_](#).

10.6 getPubkey

```
web3.eth.ens.getPubkey(ENSName);
```

Returns the X and Y coordinates of the curve point for the public key.

10.6.1 Parameters

1. ENSName - String: The Ens name.

10.6.2 Returns

Object<String, String> - The X and Y coordinates.

10.6.3 Example

```
web3.eth.ens.getPubkey('ethereum.eth').then((result) => {  
  console.log(result)  
});  
> {  
  "0": "0x0000000000000000000000000000000000000000000000000000000000000000",  
  "1": "0x0000000000000000000000000000000000000000000000000000000000000000",  
  "x": "0x0000000000000000000000000000000000000000000000000000000000000000",  
  "y": "0x0000000000000000000000000000000000000000000000000000000000000000"  
}
```

10.7 setPubkey

```
web3.eth.ens.setPubkey(ENSName, x, y, options);
```

Sets the SECP256k1 public key associated with an Ens node

10.7.1 Parameters

1. ENSName - String: The Ens name.
2. x - String: The X coordinate of the public key.
3. y - String: The Y coordinate of the public key.
4. **options - Object: The options used for sending.**
 - from - String: The address the transaction should be sent from.
 - gasPrice - String (optional): The gas price in wei to use for this transaction.
 - gas - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an PubkeyChanged event.

10.7.2 Example

```
web3.eth.ens.setPubkey(
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then((result) => {
  console.log(result.events);
});
> PubkeyChanged(...)

// Or using the event emitter

web3.eth.ens.setPubkey(
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', (hash) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('receipt', (receipt) => {
  ...
})
.on('error', console.error);

// Or listen to the PubkeyChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then((resolver) => {
  resolver.events.PubkeyChanged({fromBlock: 0}, function(error, event) {
    console.log(event);
  })
})
```

(continues on next page)

10.9.1 Parameters

1. ENSName - String: The Ens name.
2. key - String: The key. 3. value - String: The value. 3. options - Object: The options used for sending.
 - from - String: The address the transaction should be sent from.
 - gasPrice - String (optional): The gas price in wei to use for this transaction.
 - gas - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an TextChanged event.

10.9.2 Example

```
web3.eth.ens.setText(  
  'ethereum.eth',  
  'key',  
  'value',  
  {  
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'  
  }  
)  
.then((result) => {  
  console.log(result.events);  
});  
> ContentChanged(...)  
  
// Or using the event emitter  
  
web3.eth.ens.setText(  
  'ethereum.eth',  
  'key',  
  'value',  
  {  
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'  
  }  
)  
.on('transactionHash', (hash) => {  
  ...  
})  
.on('confirmation', (confirmationNumber, receipt) => {  
  ...  
})  
.on('receipt', (receipt) => {  
  ...  
})  
.on('error', console.error);  
  
// And listen to the TextChanged event on the resolver  
  
web3.eth.ens.resolver('ethereum.eth').then((resolver) => {  
  resolver.events.TextChanged({fromBlock: 0}, (error, event) => {  
    console.log(event);  
  })  
  .on('data', (event) => {  
    console.log(event);  
  })  
})
```

(continues on next page)

(continued from previous page)

```
.on('changed', (event) => {  
  // remove event from local database  
})  
.on('error', console.error);  
});
```

For further information on the handling of contract events please see here [contract-events_](#).

10.10 getContent

```
web3.eth.ens.getContent(ENSName);
```

Returns the content hash associated with an Ens node.

10.10.1 Parameters

1. ENSName - String: The Ens name.

10.10.2 Returns

String - The content hash associated with an Ens node.

10.10.3 Example

```
web3.eth.ens.getContent('ethereum.eth').then((result) => {  
  console.log(result);  
});  
> "0x0000000000000000000000000000000000000000000000000000000000000000"
```

10.11 setContent

```
web3.eth.ens.setContent(ENSName, hash, options);
```

Sets the content hash associated with an Ens node.

10.11.1 Parameters

1. ENSName - String: The Ens name.
2. hash - String: The content hash to set.
3. **options - Object: The options used for sending.**
 - from - String: The address the transaction should be sent from.

- `gasPrice` - String (optional): The gas price in wei to use for this transaction.
- `gas` - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an `ContentChanged` event.

10.11.2 Example

```
web3.eth.ens.setContent (
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then((result) => {
  console.log(result.events);
});
> ContentChanged(...)

// Or using the event emitter

web3.eth.ens.setContent (
  'ethereum.eth',
  '0x0000000000000000000000000000000000000000000000000000000000000000',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', (hash) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('receipt', (receipt) => {
  ...
})
.on('error', console.error);

// Or listen to the ContentChanged event on the resolver

web3.eth.ens.resolver('ethereum.eth').then((resolver) => {
  resolver.events.ContentChanged({fromBlock: 0}, (error, event) => {
    console.log(event);
  })
  .on('data', (event) => {
    console.log(event);
  })
  .on('changed', (event) => {
    // remove event from local database
  })
  .on('error', console.error);
});
```

For further information on the handling of contract events please see here [contract-events](#).

10.12 getMultihash

```
web3.eth.ens.getMultihash(ENSName);
```

Returns the multihash associated with an Ens node.

10.12.1 Parameters

1. ENSName - String: The Ens name.

10.12.2 Returns

String - The associated multihash.

10.12.3 Example

```
web3.eth.ens.getMultihash('ethereum.eth').then((result) => {
  console.log(result);
});
> 'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK'
```

10.13 setMultihash

```
web3.eth.ens.setMultihash(ENSName, hash, options);
```

Sets the multihash associated with an Ens node.

10.13.1 Parameters

1. ENSName - String: The Ens name.
2. hash - String: The multihash to set.
3. **options - Object: The options used for sending.**
 - from - String: The address the transaction should be sent from.
 - gasPrice - String (optional): The gas price in wei to use for this transaction.
 - gas - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an “MultihashChanged” event.

10.13.2 Example

```
web3.eth.ens.setMultihash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then((result) => {
  console.log(result.events);
});
> MultihashChanged(...)

// Or using the event emitter

web3.eth.ens.setMultihash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', (hash) => {
  ...
})
.on('confirmation', (confirmationNumber, receipt) => {
  ...
})
.on('receipt', (receipt) => {
  ...
})
.on('error', console.error);
```

For further information on the handling of contract events please see here [contract-events_](#).

10.14 getContenthash

```
web3.eth.ens.getContenthash(ENSName);
```

Returns the contenthash associated with an Ens node.

10.14.1 Parameters

1. ENSName - String: The Ens name.

10.14.2 Returns

String - The associated contenthash.

10.14.3 Example

```
web3.eth.ens.getContenthash('ethereum.eth').then((result) => {
  console.log(result);
});
> 'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK'
```

10.15 setContenthash

```
web3.eth.ens.setContenthash(ENSName, hash, options);
```

Sets the contenthash associated with an Ens node.

10.15.1 Parameters

1. ENSName - String: The Ens name.
2. hash - String: The contenthash to set.
3. **options - Object: The options used for sending.**
 - from - String: The address the transaction should be sent from.
 - gasPrice - String (optional): The gas price in wei to use for this transaction.
 - gas - Number (optional): The maximum gas provided for this transaction (gas limit).

Emits an “ContenthashChanged” event.

10.15.2 Example

```
web3.eth.ens.setContenthash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
).then((result) => {
  console.log(result.events);
});
> ContenthashChanged(...)

// Or using the event emitter

web3.eth.ens.setContenthash(
  'ethereum.eth',
  'QmXpSwxdmgWaYrgMUzuDWCnjsZo5RxphE3oW7VhTMSCoKK',
  {
    from: '0x9CC9a2c777605Af16872E0997b3Aeb91d96D5D8c'
  }
)
.on('transactionHash', (hash) => {
```

(continues on next page)

(continued from previous page)

```

    ...
  })
  .on('confirmation', (confirmationNumber, receipt) => {
    ...
  })
  .on('receipt', (receipt) => {
    ...
  })
  .on('error', console.error);

```

For further information on the handling of contract events please see here [contract-events_](#).

10.16 Ens events

The Ens API provides the possibility for listening to all Ens related events.

10.16.1 Known resolver events

1. AddrChanged - AddrChanged(node bytes32, a address)
2. ContentChanged - ContentChanged(node bytes32, hash bytes32)
4. NameChanged - NameChanged(node bytes32, name string)
5. ABIChanged - ABIChanged(node bytes32, contentType uint256)
6. PubkeyChanged - PubkeyChanged(node bytes32, x bytes32, y bytes32)
6. TextChanged - TextChanged(bytes32 indexed node, string indexedKey, string key)
6. ContenthashChanged - ContenthashChanged(bytes32 indexed node, bytes hash)

10.16.2 Example

```

web3.eth.ens.resolver('ethereum.eth').then((resolver) => {
  resolver.events.AddrChanged({fromBlock: 0}, (error, event) => {
    console.log(event);
  })
  .on('data', (event) => {
    console.log(event);
  })
  .on('changed', (event) => {
    // remove event from local database
  })
  .on('error', console.error);
});
> {
  returnValues: {
    node: '0x123456789...',
    a: '0x123456789...',
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: [
      '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
      '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'
    ]
  }
}

```

(continues on next page)

(continued from previous page)

```

    },
    event: 'AddrChanged',
    signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
    logIndex: 0,
    transactionIndex: 0,
    transactionHash:
    ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
    blockNumber: 1234,
    address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'
  }

```

10.16.3 Known registry events

1. Transfer - Transfer(node bytes32, owner address)
2. NewOwner - NewOwner(node bytes32, label bytes32, owner address)
4. NewResolver - NewResolver(node bytes32, resolver address)
5. NewTTL - NewTTL(node bytes32, ttl uint64)

10.16.4 Example

```

web3.eth.ens.resistry.then((registry) => {
  registry.events.Transfer({fromBlock: 0}, (error, event) => {
    console.log(event);
  })
  .on('data', (event) => {
    console.log(event);
  })
  .on('changed', (event) => {
    // remove event from local database
  })
  .on('error', console.error);
});
> {
  returnValues: {
    node: '0x123456789...',
    owner: '0x123456789...',
  },
  raw: {
    data: '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
    topics: [
      '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
      '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385'
    ]
  },
  event: 'Transfer',
  signature: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  logIndex: 0,
  transactionIndex: 0,
  transactionHash:
  ↪ '0x7f9fade1c0d57a7af66ab4ead79fade1c0d57a7af66ab4ead7c2c2eb7b11a91385',
  blockHash: '0xfd43ade1c09fade1c0d57a7af66ab4ead7c2c2eb7b11a91ffdd57a7af66ab4ead7',
  blockNumber: 1234,

```

(continues on next page)

(continued from previous page)

```
address: '0xde0B295669a9FD93d5F28D9Ec85E40f4cb697BAe'  
}
```

For further information on the handling of contract events please see here [contract-events_](#).

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

CHAPTER 11

web3.eth.Iban

The `web3.eth.Iban` function lets convert Ethereum addresses from and to IBAN and BBAN.

```
import {Iban} from 'web3-eth-iban';

const iban = new Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS');

// or using the web3 umbrella package

import {Web3 } from 'web3';
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546', {
  ↪options});

// -> new web3.eth.Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS')
```

11.1 Iban instance

This's instance of Iban

```
> Iban { _iban: 'XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS' }
```

11.2 toAddress

static function

```
web3.eth.Iban.toAddress(ibanAddress)
```

Singleton: Converts a direct IBAN address into an Ethereum address.

Note: This method also exists on the IBAN instance.

11.2.1 Parameters

1. String: the IBAN address to convert.

11.2.2 Returns

String - The Ethereum address.

11.2.3 Example

```
web3.eth.Iban.toAddress("XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS");  
> "0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8"
```

11.3 tolban

static function

```
web3.eth.Iban.toIban(address)
```

Singleton: Converts an Ethereum address to a direct IBAN address.

11.3.1 Parameters

1. String: the Ethereum address to convert.

11.3.2 Returns

String - The IBAN address.

11.3.3 Example

```
web3.eth.Iban.toIban("0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8");  
> "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"
```

static function, return IBAN instance

11.4 fromAddress

```
web3.eth.Iban.fromAddress(address)
```

Singleton: Converts an Ethereum address to a direct IBAN instance.

11.4.1 Parameters

1. `String`: the Ethereum address to convert.

11.4.2 Returns

`Object` - The IBAN instance.

11.4.3 Example

```
web3.eth.Iban.fromAddress("0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8");  
> Iban {__iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

static function, return IBAN instance

11.5 fromBban

```
web3.eth.Iban.fromBban(bbanAddress)
```

Singleton: Converts an BBAN address to a direct IBAN instance.

11.5.1 Parameters

1. `String`: the BBAN address to convert.

11.5.2 Returns

`Object` - The IBAN instance.

11.5.3 Example

```
web3.eth.Iban.fromBban('ETHXREGGAVOFYORK');  
> Iban {__iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

static function, return IBAN instance

11.6 createIndirect

```
web3.eth.Iban.createIndirect(options)
```

Singleton: Creates an indirect IBAN address from a institution and identifier.

11.6.1 Parameters

1. **Object:** the options object as follows:

- `institution` - `String`: the institution to be assigned
- `identifier` - `String`: the identifier to be assigned

11.6.2 Returns

Object - The IBAN instance.

11.6.3 Example

```
web3.eth.Iban.createIndirect({
  institution: "XREG",
  identifier: "GAVOFYORK"
});
> Iban {_iban: "XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS"}
```

static function, return boolean

11.7 isValid

```
web3.eth.Iban.isValid(ibanAddress)
```

Singleton: Checks if an IBAN address is valid.

Note: This method also exists on the IBAN instance.

11.7.1 Parameters

1. `String`: the IBAN address to check.

11.7.2 Returns

Boolean

11.7.3 Example

```
web3.eth.Iban.isValid("XE81ETHXREGGAVOFYORK");  
> true  
  
web3.eth.Iban.isValid("XE82ETHXREGGAVOFYORK");  
> false // because the checksum is incorrect
```

11.8 prototype.isValid

method of Iban instance

```
web3.eth.Iban.prototype.isValid()
```

Singleton: Checks if an IBAN address is valid.

Note: This method also exists on the IBAN instance.

11.8.1 Parameters

1. String: the IBAN address to check.

11.8.2 Returns

Boolean

11.8.3 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");  
iban.isValid();  
> true
```

11.9 prototype.isDirect

method of Iban instance

```
web3.eth.Iban.prototype.isDirect()
```

Checks if the IBAN instance is direct.

11.9.1 Returns

Boolean

11.9.2 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.isDirect();
> false
```

11.10 prototype.isIndirect

method of Iban instance

```
web3.eth.Iban.prototype.isIndirect()
```

Checks if the IBAN instance is indirect.

11.10.1 Returns

Boolean

11.10.2 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.isIndirect();
> true
```

11.11 prototype.checksum

method of Iban instance

```
web3.eth.Iban.prototype.checksum()
```

Returns the checksum of the IBAN instance.

11.11.1 Returns

String: The checksum of the IBAN

11.11.2 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.checksum();
> "81"
```

11.12 prototype.institution

method of Iban instance

```
web3.eth.Iban.prototype.institution()
```

Returns the institution of the IBAN instance.

11.12.1 Returns

String: The institution of the IBAN

11.12.2 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.institution();
> 'XREG'
```

11.13 prototype.client

method of Iban instance

```
web3.eth.Iban.prototype.client()
```

Returns the client of the IBAN instance.

11.13.1 Returns

String: The client of the IBAN

11.13.2 Example

```
const iban = new web3.eth.Iban("XE81ETHXREGGAVOFYORK");
iban.client();
> 'GAVOFYORK'
```

11.14 prototype.toAddress

method of Iban instance

```
web3.eth.Iban.prototype.toString()
```

Returns the Ethereum address of the IBAN instance.

11.14.1 Returns

String: The Ethereum address of the IBAN

11.14.2 Example

```
const iban = new web3.eth.Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS');
iban.toAddress();
> '0x00c5496aEe77C1bA1f0854206A26DdA82a81D6D8'
```

11.15 prototype.toString

method of Iban instance

```
web3.eth.Iban.prototype.toString()
```

Returns the IBAN address of the IBAN instance.

11.15.1 Returns

String: The IBAN address.

11.15.2 Example

```
const iban = new web3.eth.Iban('XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS');
iban.toString();
> 'XE73380073KYGTWWZN0F2WZ0R8PX5ZPPZS'
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

Contains functions to receive information about the current network.

12.1 getId

```
web3.eth.net.getId([callback])
web3.bzz.net.getId([callback])
web3.shh.net.getId([callback])
```

Gets the current network ID.

12.1.1 Parameters

none

12.1.2 Returns

Promise returns Number: The network ID.

12.1.3 Example

```
web3.eth.net.getId()
  .then(console.log);
> 1
```

12.2 isListening

```
web3.eth.net.isListening([callback])
web3.bzz.net.isListening([callback])
web3.shh.net.isListening([callback])
```

Checks if the node is listening for peers.

12.2.1 Parameters

none

12.2.2 Returns

Promise returns Boolean

12.2.3 Example

```
web3.eth.isListening()
  .then(console.log);
> true
```

12.3 getPeerCount

```
web3.eth.net.getPeerCount([callback])
web3.bzz.net.getPeerCount([callback])
web3.shh.net.getPeerCount([callback])
```

Get the number of peers connected to.

12.3.1 Parameters

none

12.3.2 Returns

Promise returns Number

12.3.3 Example

```
web3.eth.getPeerCount()
  .then(console.log);
> 25
```


12.4 getNetworkType

```
web3.eth.net.getNetworkType([callback])
```

Guesses the chain the node is connected by comparing the genesis hashes.

Note: This is not a 100% accurate guess as any private network could use testnet and mainnet genesis blocks and network IDs.

12.4.1 Returns

Promise returns String:

- "main" for main network
- "morden" for the morden test network
- "ropsten" for the morden test network
- "private" for undetectable networks.

12.4.2 Example

```
web3.eth.net.getNetworkType()  
.then(console.log);  
> "main"
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

The `web3-eth-abi` package allows you to de- and encode parameters from a ABI (Application Binary Interface). This will be used for function calls to the EVM (Ethereum Virtual Machine).

```
import {AbiCoder} from 'web3-eth-abi';

const abiCoder = new AbiCoder();

// or using the web3 umbrella package

import {Web3} from 'web3';

const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
  ↳options);
// -> web3.eth.abi
```

13.1 encodeFunctionSignature

```
web3.eth.abi.encodeFunctionSignature(functionName);
```

Encodes the function name to its ABI signature, which are the first 4 bytes of the sha3 hash of the function name including types.

13.1.1 Parameters

1. `functionName` - `String|Object`: The function name to encode. or the *JSON interface* object of the function. If string it has to be in the form `function(type,type,...)`, e.g: `myFunction(uint256,uint32[],bytes10,bytes)`

13.1.2 Returns

String - The ABI signature of the function.

13.1.3 Example

```
// From a JSON interface object
web3.eth.abi.encodeFunctionSignature({
  name: 'myMethod',
  type: 'function',
  inputs: [{
    type: 'uint256',
    name: 'myNumber'
  }, {
    type: 'string',
    name: 'myString'
  }]
})
> 0x24ee0097

// Or string
web3.eth.abi.encodeFunctionSignature('myMethod(uint256,string)')
> '0x24ee0097'
```

13.2 encodeEventSignature

```
web3.eth.abi.encodeEventSignature(eventName);
```

Encodes the event name to its ABI signature, which are the sha3 hash of the event name including input types.

13.2.1 Parameters

1. eventName - String|Object: The event name to encode. or the *JSON interface* object of the event. If string it has to be in the form event (type, type, ...), e.g: myEvent (uint256, uint32 [], bytes10, bytes)

13.2.2 Returns

String - The ABI signature of the event.

13.2.3 Example

```
web3.eth.abi.encodeEventSignature('myEvent(uint256,bytes32)')
> 0xf2eeb729e636a8cb783be044acf6b7b1e2c5863735b60d6daae84c366ee87d97

// or from a json interface object
web3.eth.abi.encodeEventSignature({
  name: 'myEvent',
```

(continues on next page)

The `web3-net` package allows you to interact with the Ethereum nodes network properties.

```
import Web3 from 'web3';
import {Net} from 'web3-net';

// "Personal.providers.givenProvider" will be set if in an Ethereum supported browser.
const net = new Net(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
↳options);

// or using the web3 umbrella package
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
↳options);

// -> web3.eth.net
// -> web3.bzz.net
// -> web3.shh.net
```

14.1 getId

```
web3.eth.net.getId([callback])
web3.bzz.net.getId([callback])
web3.shh.net.getId([callback])
```

Gets the current network ID.

14.1.1 Parameters

none

14.1.2 Returns

Promise returns Number: The network ID.

14.1.3 Example

```
web3.eth.net.getId()  
.then(console.log);  
> 1
```

14.2 isListening

```
web3.eth.net.isListening([callback])  
web3.bzz.net.isListening([callback])  
web3.shh.net.isListening([callback])
```

Checks if the node is listening for peers.

14.2.1 Parameters

none

14.2.2 Returns

Promise returns Boolean

14.2.3 Example

```
web3.eth.isListening()  
.then(console.log);  
> true
```

14.3 getPeerCount

```
web3.eth.net.getPeerCount([callback])  
web3.bzz.net.getPeerCount([callback])  
web3.shh.net.getPeerCount([callback])
```

Get the number of peers connected to.

14.3.1 Parameters

none

14.3.2 Returns

Promise returns Number

14.3.3 Example

```
web3.eth.getPeerCount ()  
.then (console.log);  
> 25
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

CHAPTER 15

web3.bzz

Note: This API might change over time.

The web3-bzz package allows you to interact with the decentralized file store. For more see the [Swarm Docs](#).

```
import Web3 from 'web3';
import {Bzz} from 'web3-bzz';

// will autodetect if the "ethereum" object is present and will either connect to the
↳ local swarm node, or the swarm-gateways.net.
// Optional you can give your own provider URL; If no provider URL is given it will
↳ use "http://swarm-gateways.net"
const bzz = new Bzz(Web3.givenProvider || 'http://swarm-gateways.net');

// or using the web3 umbrella package
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546');

// -> web3.bzz.currentProvider // if Web3.givenProvider was an ethereum provider it
↳ will set: "http://localhost:8500" otherwise it will set: "http://swarm-gateways.net"
```

15.1 setProvider

```
web3.bzz.setProvider(myProvider)
```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc EXCEPT web3.bzz which needs a separate provider at all times.

15.1.1 Parameters

1. Object - myProvider: a valid provider.

15.1.2 Returns

Boolean

15.1.3 Example

```
import {Bzz} from 'web3-bzz';

const bzz = new Bzz('http://localhost:8500');

// change provider
bzz.setProvider('http://swarm-gateways.net');
```

15.2 givenProvider

```
web3.bzz.givenProvider
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

15.2.1 Returns

Object: The given provider set or null;

15.2.2 Example

```
bzz.givenProvider;
> {
  send: function(),
  on: function(),
  bzz: "http://localhost:8500",
  shh: true,
  ...
}

bzz.setProvider(bzz.givenProvider || "http://swarm-gateways.net");
```

15.3 currentProvider


```
web3.bzz.currentProvider
```

Will return the current provider URL, otherwise null.

15.3.1 Returns

Object: The current provider URL or null;

15.3.2 Example

```
bzz.currentProvider;
> "http://localhost:8500"

if(!bzz.currentProvider) {
  bzz.setProvider("http://swarm-gateways.net");
}
```

15.4 upload

```
web3.bzz.upload(mixed)
```

Uploads files folders or raw data to swarm.

15.4.1 Parameters

1. **mixed - String|Buffer|Uint8Array|Object:** The data to upload, can be a file content, file Buffer/Uint8Array, or

- **String|Buffer|Uint8Array:** A file content, file Uint8Array or Buffer to upload, or:

- **Object:**

(a) **Multiple key values for files and directories. The paths will be kept the same:**

- **key must be the files path, or name, e.g. "/foo.txt" and its value is an object with:**

- * **type:** The mime-type of the file, e.g. "text/html".

- * **data:** A file content, file Uint8Array or Buffer to upload.

(b) **Upload a file or a directory from disk in Node.js. Requires and object with the following properties:**

- **path:** The path to the file or directory.

- **kind:** The type of the source "directory", "file" or "data".

- **defaultFile (optional):** Path of the "defaultFile" when "kind": "directory", e.g. "/index.html".

(c) **Upload file or folder in the browser. Requires and object with the following properties:**

- pick: The file picker to launch. Can be "file", "directory" or "data".

15.4.2 Returns

Promise<String> - Returns the content hash of the manifest.

15.4.3 Example

```
// raw data
bzz.upload("test file").then((hash) => {
  console.log("Uploaded file. Address:", hash);
})

// raw directory
const dir = {
  "/foo.txt": {type: "text/plain", data: "sample file"},
  "/bar.txt": {type: "text/plain", data: "another file"}
};

bzz.upload(dir).then((hash) => {
  console.log("Uploaded directory. Address:", hash);
});

// upload from disk in node.js
bzz.upload({
  path: "/path/to/thing",      // path to data / file / directory
  kind: "directory",          // could also be "file" or "data"
  defaultFile: "/index.html"  // optional, and only for kind === "directory"
})
.then(console.log)
.catch(console.log);

// upload from disk in the browser
bzz.upload({pick: "file"}) // could also be "directory" or "data"
.then(console.log);
```

15.5 download

```
web3.bzz.download(bzzHash [, localpath])
```

Downloads files and folders from swarm, as buffer or to disk (only node.js).

15.5.1 Parameters

1. bzzHash - String: The file or directory to download. If the hash is a raw file it will return a Buffer, if a manifest file, it will return the directory structure. If the localpath is given, it will return that path where it downloaded the files to.
2. localpath - String: The local folder to download the content into. (only node.js)

15.5.2 Returns

Promise<Buffer|Object|String> - The Buffer of the file downloaded, an object with the directory structure, or the path where it was downloaded to.

15.5.3 Example

```
// download raw file
const fileHash = "a5c10851ef054c268a2438f10a21f6efe3dc3dcdcc2ea0e6a1a7a38bf8c91e23";
bzz.download(fileHash).then((buffer) => {
  console.log("Downloaded file:", buffer.toString());
});

// download directory, if the hash is manifest file.
const dirHash = "7e980476df218c05ecfcb0a2ca73597193a34c5a9d6da84d54e295ecd8e0c641";
bzz.download(dirHash).then((dir) => {
  console.log("Downloaded directory:");
  > {
    'bar.txt': { type: 'text/plain', data: <Buffer 61 6e 6f 74 68 65 72 20 66 69
↪6c 65> },
    'foo.txt': { type: 'text/plain', data: <Buffer 73 61 6d 70 6c 65 20 66 69 6c
↪65> }
  }
});

// download file/directory to disk (only node.js)
const dirHash = "a5c10851ef054c268a2438f10a21f6efe3dc3dcdcc2ea0e6a1a7a38bf8c91e23";
bzz.download(dirHash, "/target/dir")
.then((path) => console.log(`Downloaded directory to ${path}.`))
.catch(console.log);
```

15.6 pick

```
web3.bzz.pick.file()
web3.bzz.pick.directory()
web3.bzz.pick.data()
```

Opens a file picker in the browser to select file(s), directory or data.

15.6.1 Parameters

none

15.6.2 Returns

Promise<Object> - Returns the file or multiple files.

15.6.3 Example

```
web3.bzz.pick.file()  
.then(console.log);  
> {  
  ...  
}
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

The `web3-shh` package allows you to interact with the whisper protocol for broadcasting. For more see [Whisper Overview](#).

```
import Web3 from 'web3';
import {Shh} import 'web3-shh';

// "Web3.givenProvider" will be set if in an Ethereum supported browser.
const shh = new Shh(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
↳options);

// or using the web3 umbrella package
const web3 = new Web3(Web3.givenProvider || 'ws://some.local-or-remote.node:8546',
↳options);

// -> web3.shh
```

16.1 options

An Web3 module does provide several options for configuring the transaction confirmation workflow or for defining default values. These are the currently available option properties on a Web3 module:

16.1.1 Module Options

defaultAccount

defaultBlock

defaultGas

defaultGasPrice

transactionBlockTimeout

transactionConfirmationBlocks

transactionPollingTimeout

transactionSigner

16.1.2 Example

```
import Web3 from 'web3';

const options = {
  defaultAccount: '0x0',
  defaultBlock: 'latest',
  defaultGas: 1,
  defaultGasPrice: 0,
  transactionBlockTimeout: 50,
  transactionConfirmationBlocks: 24,
  transactionPollingTimeout: 480,
  transactionSigner: new CustomTransactionSigner()
}

const web3 = new Web3('http://localhost:8545', options);
```

16.2 defaultBlock

```
web3.defaultBlock
web3.eth.defaultBlock
web3.shh.defaultBlock
...
```

The default block which will be used for a requests.

16.2.1 Returns

string|number: The current value of the defaultBlock property.

16.3 defaultAccount

```
web3.defaultAccount
web3.eth.defaultAccount
web3.shh.defaultAccount
...
```

The default account which will be used for a requests.

16.3.1 Returns

`null|string`: The current value of the `defaultAccount` property.

16.4 defaultGasPrice

```
web3.defaultGasPrice
web3.eth.defaultGasPrice
web3.shh.defaultGasPrice
...
```

The default gas price which will be used for a request.

16.4.1 Returns

`string|number`: The current value of the `defaultGasPrice` property.

16.5 defaultGas

```
web3.defaultGas
web3.eth.defaultGas
web3.shh.defaultGas
...
```

The default gas which will be used for a request.

16.5.1 Returns

`string|number`: The current value of the `defaultGas` property.

16.6 transactionBlockTimeout

```
web3.transactionBlockTimeout
web3.eth.transactionBlockTimeout
web3.shh.transactionBlockTimeout
...
```

This can be used with a socket provider and defines the number of blocks until the `PromiEvent` rejects with a timeout error.

16.6.1 Returns

number: The current value of transactionBlockTimeout

16.7 transactionConfirmationBlocks

```
web3.transactionConfirmationBlocks
web3.eth.transactionConfirmationBlocks
web3.shh.transactionConfirmationBlocks
...
```

This defines the number of blocks it requires until a transaction will be handled as confirmed. The PromiEvent will resolve with the desired receipt when enough confirmations happened.

16.7.1 Returns

number: The current value of transactionConfirmationBlocks

16.8 transactionPollingTimeout

```
web3.transactionPollingTimeout
web3.eth.transactionPollingTimeout
web3.shh.transactionPollingTimeout
...
```

This defines the polling cycles amount when you send a transaction with the HttpProvider. The PromiEvent rejects with a timeout error when the timeout got exceeded. (1 cycle == 1sec).

16.8.1 Returns

number: The current value of transactionPollingTimeout

16.9 transactionSigner

```
web3.eth.transactionSigner
...
```

The `transactionSigner` property does provide us the possibility to customize the signing process of the Eth module and the related sub-modules.

The interface of a `TransactionSigner`:


```

interface TransactionSigner {
  sign(txObject: Transaction): Promise<SignedTransaction>
}

interface SignedTransaction {
  messageHash: string,
  v: string,
  r: string,
  s: string,
  rawTransaction: string
}

```

16.9.1 Returns

TransactionSigner: A JavaScript class of type TransactionSigner.

16.10 setProvider

```

web3.setProvider(myProvider)
web3.eth.setProvider(myProvider)
web3.shh.setProvider(myProvider)
web3.bzz.setProvider(myProvider)
...

```

Will change the provider for its module.

Note: When called on the umbrella package web3 it will also set the provider for all sub modules web3.eth, web3.shh, etc EXCEPT web3.bzz which needs a separate provider at all times.

16.10.1 Parameters

1. Object|String - provider: a valid provider
2. Net - net: (optional) the node.js Net package. This is only required for the IPC provider.

16.10.2 Returns

Boolean

16.10.3 Example

```

import Web3 from 'web3';

const web3 = new Web3('http://localhost:8545');

```

(continues on next page)

(continued from previous page)

```
// or
const web3 = new Web3(new Web3.providers.HttpProvider('http://localhost:8545'));

// change provider
web3.setProvider('ws://localhost:8546');
// or
web3.setProvider(new Web3.providers.WebsocketProvider('ws://localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');
const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path

// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

16.11 providers

```
Web3.providers
Eth.providers
...
```

Contains the current available providers.

16.11.1 Value

Object with the following providers:

- Object - `HttpProvider`: The HTTP provider is **deprecated**, as it won't work for subscriptions.
- Object - `WebsocketProvider`: The Websocket provider is the standard for usage in legacy browsers.
- Object - `IpcProvider`: The IPC provider is used node.js dapps when running a local node. Gives the most secure connection.

16.11.2 Example

```
const Web3 = require('web3');
// use the given Provider, e.g in Mist, or instantiate a new websocket provider
const web3 = new Web3(Web3.givenProvider || 'ws://localhost:8546');
// or
const web3 = new Web3(Web3.givenProvider || new Web3.providers.WebsocketProvider('ws://
↳localhost:8546'));

// Using the IPC provider in node.js
const net = require('net');

const web3 = new Web3('/Users/myuser/Library/Ethereum/geth.ipc', net); // mac os path
```

(continues on next page)

(continued from previous page)

```
// or
const web3 = new Web3(new Web3.providers.IpcProvider('/Users/myuser/Library/Ethereum/
↳geth.ipc', net)); // mac os path
// on windows the path is: '\\.\pipe\geth.ipc'
// on linux the path is: '/users/myuser/.ethereum/geth.ipc'
```

16.12 givenProvider

```
Web3.givenProvider
web3.eth.givenProvider
web3.shh.givenProvider
web3.bzz.givenProvider
...
```

When using web3.js in an Ethereum compatible browser, it will set with the current native provider by that browser. Will return the given provider by the (browser) environment, otherwise null.

16.12.1 Returns

Object: The given provider set or null;

16.12.2 Example

```
web3.setProvider(Web3.givenProvider || 'ws://localhost:8546');
```

16.13 currentProvider

```
web3.currentProvider
web3.eth.currentProvider
web3.shh.currentProvider
web3.bzz.currentProvider
...
```

Will return the current provider, otherwise null.

16.13.1 Returns

Object: The current provider set or null;

16.13.2 Example

```
if(!web3.currentProvider) {
  web3.setProvider('http://localhost:8545');
}
```

16.14 BatchRequest

```
new web3.BatchRequest ()
new web3.eth.BatchRequest ()
new web3.shh.BatchRequest ()
...
```

Class to create and execute batch requests.

16.14.1 Parameters

none

16.14.2 Returns

Object: With the following methods:

- `add(request)`: To add a request object to the batch call.
- `execute()`: Will execute the batch request.

16.14.3 Example

```
const contract = new web3.eth.Contract(abi, address);

const batch = new web3.BatchRequest ();
batch.add(web3.eth.getBalance.request ('0x0000000000000000000000000000000000000000',
  ↳ 'latest', callback));
batch.add(contract.methods.balance(address).call.request ({from:
  ↳ '0x0000000000000000000000000000000000000000'}, callback2));
batch.execute ();
```

16.15 getId

```
web3.eth.net.getId([callback])
web3.bzz.net.getId([callback])
web3.shh.net.getId([callback])
```

Gets the current network ID.

16.15.1 Parameters

none

16.15.2 Returns

Promise returns Number: The network ID.

16.15.3 Example

```
web3.eth.net.getId()  
.then(console.log);  
> 1
```

16.16 isListening

```
web3.eth.net.isListening([callback])  
web3.bzz.net.isListening([callback])  
web3.shh.net.isListening([callback])
```

Checks if the node is listening for peers.

16.16.1 Parameters

none

16.16.2 Returns

Promise returns Boolean

16.16.3 Example

```
web3.eth.isListening()  
.then(console.log);  
> true
```

16.17 getPeerCount

```
web3.eth.net.getPeerCount([callback])  
web3.bzz.net.getPeerCount([callback])  
web3.shh.net.getPeerCount([callback])
```

Get the number of peers connected to.

16.17.1 Parameters

none

16.17.2 Returns

Promise returns Number

16.17.3 Example

```
web3.eth.getPeerCount ()  
.then(console.log);  
> 25
```

16.18 getVersion

```
web3.shh.getVersion([callback])
```

Returns the version of the running whisper.

16.18.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.18.2 Returns

Promise<string> - The version of the current whisper running.

16.18.3 Example

```
web3.shh.getVersion()  
.then(console.log);  
> "5.0"
```

16.19 getInfo

```
web3.shh.getInfo([callback])
```

Gets information about the current whisper node.

16.19.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.19.2 Returns

`Promise<Object>` - The information of the node with the following properties:

- `messages` - `Number`: Number of currently floating messages.
- `maxMessageSize` - `Number`: The current message size limit in bytes.
- `memory` - `Number`: The memory size of the floating messages in bytes.
- `minPow` - `Number`: The current minimum PoW requirement.

16.19.3 Example

```
web3.shh.getInfo()
  .then(console.log);
> {
  "minPow": 0.8,
  "maxMessageSize": 12345,
  "memory": 1234335,
  "messages": 20
}
```

16.20 setMaxMessageSize

```
web3.shh.setMaxMessageSize(size, [callback])
```

Sets the maximal message size allowed by this node. Incoming and outgoing messages with a larger size will be rejected. Whisper message size can never exceed the limit imposed by the underlying P2P protocol (10 Mb).

16.20.1 Parameters

1. `Number` - Message size in bytes.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.20.2 Returns

`Promise<boolean>` - Returns `true` on success, error on failure.

16.20.3 Example

```
web3.shh.setMaxMessageSize(1234565)
.then(console.log);
> true
```

16.21 setMinPoW

```
web3.shh.setMinPoW(pow, [callback])
```

Sets the minimal PoW required by this node.

This experimental function was introduced for the future dynamic adjustment of PoW requirement. If the node is overwhelmed with messages, it should raise the PoW requirement and notify the peers. The new value should be set relative to the old value (e.g. double). The old value can be obtained via [web3.shh.getInfo\(\)](#).

16.21.1 Parameters

1. Number - The new PoW requirement.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.21.2 Returns

Promise<boolean> - Returns true on success, error on failure.

16.21.3 Example

```
web3.shh.setMinPoW(0.9)
.then(console.log);
> true
```

16.22 markTrustedPeer

```
web3.shh.markTrustedPeer(enode, [callback])
```

Marks specific peer trusted, which will allow it to send historic (expired) messages.

Note: This function is not adding new nodes, the node needs to be an existing peer.

16.22.1 Parameters

1. `String` - Enode of the trusted peer.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.22.2 Returns

`Promise<boolean>` - Returns `true` on success, error on failure.

16.22.3 Example

```
web3.shh.markTrustedPeer()  
.then(console.log);  
> true
```

16.23 newKeyPair

```
web3.shh.newKeyPair([callback])
```

Generates a new public and private key pair for message decryption and encryption.

16.23.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.23.2 Returns

`Promise<string>` - Returns the Key ID on success and an error on failure.

16.23.3 Example

```
web3.shh.newKeyPair()  
.then(console.log);  
> "5e57b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

16.24 addPrivateKey

```
web3.shh.addPrivateKey(privateKey, [callback])
```

Stores a key pair derived from a private key, and returns its ID.

16.24.1 Parameters

1. `String` - The private key as HEX bytes to import.
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.24.2 Returns

`Promise<string>` - The Key ID on success and an error on failure.

16.24.3 Example

```
web3.shh.addPrivateKey(  
  ↪ '0x8bda3abeb454847b515fa9b404cede50b1cc63cfdeddd4999d074284b4c21e15')  
  .then(console.log);  
> "3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

16.25 deleteKeyPair

```
web3.shh.deleteKeyPair(id, [callback])
```

Deletes the specifies key if it exists.

16.25.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.25.2 Returns

`Promise<boolean>` - Returns `true` on success, error on failure.

16.25.3 Example

```
web3.shh.deleteKeyPair(  
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')  
  .then(console.log);  
> true
```

16.26 hasKeyPair

```
web3.shh.hasKeyPair(id, [callback])
```

Checks if the whisper node has a private key of a key pair matching the given ID.

16.26.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.26.2 Returns

`Promise<boolean>` - Returns `true` on if the key pair exist in the node, `false` if not. Error on failure.

16.26.3 Example

```
web3.shh.hasKeyPair('fe22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f  
→')  
.then(console.log);  
> true
```

16.27 getPublicKey

```
web3.shh.getPublicKey(id, [callback])
```

Returns the public key for a key pair ID.

16.27.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.27.2 Returns

`Promise<string>` - Returns the Public key on success and an error on failure.

16.27.3 Example

```
web3.shh.getPublicKey(  
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')  
  .then(console.log);  
>  
↪ "0x04d1574d4eab8f3dde4d2dc7ed2c4d699d77cbbdd09167b8fffa099652ce4df00c4c6e0263eafe05007a46fdf0c8d321"  
↪ "
```

16.28 getPrivateKey

```
web3.shh.getPrivateKey(id, [callback])
```

Returns the private key for a key pair ID.

16.28.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.28.2 Returns

`Promise<string>` - Returns the private key on success and an error on failure.

16.28.3 Example

```
web3.shh.getPrivateKey(  
  ↪ '3e22b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')  
  .then(console.log);  
> "0x234234e22b9ffc2387e18636e0534534a3d0c56b0243567432453264c16e78a2adc"
```

16.29 newSymKey

```
web3.shh.newSymKey([callback])
```

Generates a random symmetric key and stores it under an ID, which is then returned. Will be used for encrypting and decrypting of messages where the sym key is known to both parties.

16.29.1 Parameters

1. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.29.2 Returns

Promise<string> - Returns the Key ID on success and an error on failure.

16.29.3 Example

```
web3.shh.newSymKey()  
.then(console.log);  
> "cec94d139ff51d7df1d228812b90c23ec1f909afa0840ed80f1e04030bb681e4"
```

16.30 addSymKey

```
web3.shh.addSymKey(symKey, [callback])
```

Stores the key, and returns its ID.

16.30.1 Parameters

1. String - The raw key for symmetric encryption as HEX bytes.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.30.2 Returns

Promise<string> - Returns the key ID on success and an error on failure.

16.30.3 Example

```
web3.shh.addSymKey('0x5e11b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f  
↪')  
.then(console.log);  
> "fea94d139ff51d7df1d228812b90c23ec1f909afa0840ed80f1e04030bb681e4"
```

16.31 generateSymKeyFromPassword

```
web3.shh.generateSymKeyFromPassword(password, [callback])
```

Generates the key from password, stores it, and returns its ID.

16.31.1 Parameters

1. String - A password to generate the sym key from.
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.31.2 Returns

Promise<String|Error> - Returns the Key ID on success and an error on failure.

16.31.3 Example

```
web3.shh.generateSymKeyFromPassword('Never use this password - password!')
.then(console.log);
> "2e57b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f"
```

16.32 hasSymKey

```
web3.shh.hasSymKey(id, [callback])
```

Checks if there is a symmetric key stored with the given ID.

16.32.1 Parameters

1. String - The key pair ID, returned by the creation functions (shh.newSymKey, shh.addSymKey or shh.generateSymKeyFromPassword).
2. Function - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.32.2 Returns

Promise<boolean> - Returns true on if the symmetric key exist in the node, false if not. Error on failure.

16.32.3 Example

```
web3.shh.hasSymKey('f6dcf21ed6a17bd78d8c4c63195ab997b3b65ea683705501eae82d32667adc92')
.then(console.log);
> true
```

16.33 getSymKey

```
web3.shh.getSymKey(id, [callback])
```

Returns the symmetric key associated with the given ID.

16.33.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.33.2 Returns

`Promise<string>` - Returns the raw symmetric key on success and an error on failure.

16.33.3 Example

```
web3.shh.getSymKey('af33b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
  .then(console.log);
> "0xa82a520aff70f7a989098376e48ec128f25f767085e84d7fb995a9815eebff0a"
```

16.34 deleteSymKey

```
web3.shh.deleteSymKey(id, [callback])
```

Deletes the symmetric key associated with the given ID.

16.34.1 Parameters

1. `String` - The key pair ID, returned by the creation functions (`shh.newKeyPair` and `shh.addPrivateKey`).
2. `Function` - (optional) Optional callback, returns an error object as first parameter and the result as second.

16.34.2 Returns

`Promise<boolean>` - Returns `true` on if the symmetric key was deleted, error on failure.

16.34.3 Example

```
web3.shh.deleteSymKey(
  → 'bf31b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f')
  .then(console.log);
> true
```

16.35 post

```
web3.shh.post(object [, callback])
```

This method should be called, when we want to post whisper a message to the network.

16.35.1 Parameters

1. Object - The post object:

- `symKeyID` - *String* (optional): ID of symmetric key for message encryption (Either `symKeyID` or `pubKey` must be present. Can not be both.).
- `pubKey` - *String* (optional): The public key for message encryption (Either `symKeyID` or `pubKey` must be present. Can not be both.).
- `sig` - *String* (optional): The ID of the signing key.
- `ttl` - *Number*: Time-to-live in seconds.
- `topic` - *String*: 4 Bytes (mandatory when key is symmetric): Message topic.
- `payload` - *String*: The payload of the message to be encrypted.
- `padding` - *Number* (optional): Padding (byte array of arbitrary length).
- `powTime` - *Number* (optional)?: Maximal time in seconds to be spent on proof of work.
- `powTarget` - *Number* (optional)?: Minimal PoW target required for this message.
- `targetPeer` - *Number* (optional): Peer ID (for peer-to-peer message only).

2. `callback` - *Function*: (optional) Optional callback, returns an error object as first parameter and the result as second.

16.35.2 Returns

Promise returns *Promise* - returns a promise. Upon success, the `then` function will be passed a string representing the hash of the sent message. On error, the `catch` function will be passed a string containing the reason for the error.

16.35.3 Example

```
const identities = [];  
  
Promise.all([  
  web3.shh.newSymKey().then((id) => {identities.push(id);}),  
  web3.shh.newKeyPair().then((id) => {identities.push(id);})  
]).then(() => {  
  
  // will receive also its own message send, below  
  const subscription = shh.subscribe("messages", {  
    symKeyID: identities[0],  
    topics: ['0xffaadd11']  
  }).on('data', console.log);  
});
```

(continues on next page)

(continued from previous page)

```

}).then(() => {
  web3.shh.post({
    symKeyID: identities[0], // encrypts using the sym key ID
    sig: identities[1], // signs the message using the keyPair ID
    ttl: 10,
    topic: '0xffaadd11',
    payload: '0xffffffffdddd1122',
    powTime: 3,
    powTarget: 0.5
  }).then(hash => console.log(`Message with hash ${hash} was successfully sent`))
  .catch(err => console.log("Error: ", err));
});

```

16.36 subscribe

```
web3.shh.subscribe('messages', options [, callback])
```

Subscribe for incoming whisper messages.

16.36.1 Parameters

1. "messages" - String: Type of the subscription.
2. **Object - The subscription options:**
 - symKeyID - String: ID of symmetric key for message decryption.
 - privateKeyID - String: ID of private (asymmetric) key for message decryption.
 - sig - String (optional): Public key of the signature, to verify.
 - topics - Array (optional when "privateKeyID" key is given): Filters messages by this topic(s). Each topic must be a 4 bytes HEX string.
 - minPow - Number (optional): Minimal PoW requirement for incoming messages.
 - allowP2P - Boolean (optional): Indicates if this filter allows processing of direct peer-to-peer messages (which are not to be forwarded any further, because they might be expired). This might be the case in some very rare cases, e.g. if you intend to communicate to MailServers, etc.
3. callback - Function: (optional) Optional callback, returns an error object as first parameter and the result as second. Will be called for each incoming subscription, and the subscription itself as 3 parameter.

16.36.2 Notification Returns

Object - The incoming message:

- hash - String: Hash of the enveloped message.
- sig - String: Public key which signed this message.
- recipientPublicKey - String: The recipients public key.
- timestamp - String: Unix timestamp of the message generation.

- `ttl` - Number: Time-to-live in seconds.
- `topic` - String: 4 Bytes HEX string message topic.
- `payload` - String: Decrypted payload.
- `padding` - Number: Optional padding (byte array of arbitrary length).
- `pow` - Number: Proof of work value.

16.36.3 Example

```
web3.shh.subscribe('messages', {
  symKeyID: 'bf31b9ffc2387e18636e0a3d0c56b023264c16e78a2adcba1303cefc685e610f',
  sig:
  ↪ '0x04d1574d4eab8f3dde4d2dc7ed2c4d699d77cbbdd09167b8fffa099652ce4df00c4c6e0263eafe05007a46fdf0c8d321
  ↪ ',
  ttl: 20,
  topics: ['0xffddaa11'],
  minPow: 0.8,
}, (error, message, subscription) => {

  console.log(message);
  > {
    "hash": "0x4158eb81ad8e30cfcee67f20b1372983d388f1243a96e39f94fd2797b1e9c78e",
    "padding":
  ↪ "0xc15f786f34e5cef0fef6ce7c1185d799ecdb5ebca72b3310648c5588db2e99a0d73301c7a8d90115a91213f0bc9c722
  ↪ ",
    "payload": "0xdeadbeaf",
    "pow": 0.5371803278688525,
    "recipientPublicKey": null,
    "sig": null,
    "timestamp": 1496991876,
    "topic": "0x01020304",
    "ttl": 50
  }
})
// or
.on('data', (message) => { ... });
```

16.37 clearSubscriptions

```
web3.shh.clearSubscriptions()
```

Resets subscriptions.

Note: This will not reset subscriptions from other packages like `web3-eth`, as they use their own `requestManager`.

16.37.1 Parameters

1. Boolean: If `true` it keeps the "syncing" subscription.

16.37.2 Returns

Boolean

16.37.3 Example

```
web3.shh.subscribe('messages', {...}, () => { ... });  
...  
web3.shh.clearSubscriptions();
```

16.38 newMessageFilter

```
web3.shh.newMessageFilter(options)
```

Create a new filter within the node. This filter can be used to poll for new messages that match the set of criteria.

16.38.1 Parameters

1. Object: See *web3.shh.subscribe() options* for details.

16.38.2 Returns

Promise<string> - Returns the filter ID.

16.38.3 Example

```
web3.shh.newMessageFilter()  
.then(console.log);  
> "2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326"
```

16.39 deleteMessageFilter

```
web3.shh.deleteMessageFilter(id)
```

Deletes a message filter in the node.

16.39.1 Parameters

1. String: The filter ID created with *shh.newMessageFilter()*.

16.39.2 Returns

Promise<boolean> - Returns `true` on success, error on failure.

16.39.3 Example

```
web3.shh.deleteMessageFilter (
  ↪ '2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326')
  .then(console.log);
> true
```

16.40 getFilterMessages

```
web3.shh.getFilterMessages(id)
```

Retrieve messages that match the filter criteria and are received between the last time this function was called and now.

16.40.1 Parameters

1. String: The filter ID created with `shh.newMessageFilter()`.

16.40.2 Returns

Promise<Array> - Returns an array of message objects like *web3.shh.subscribe()* notification returns

16.40.3 Example

```
web3.shh.getFilterMessages (
  ↪ '2b47fbafb3cce24570812a82e6e93cd9e2551bbc4823f6548ff0d82d2206b326')
  .then(console.log);
> [{
  "hash": "0x4158eb81ad8e30cfcee67f20b1372983d388f1243a96e39f94fd2797b1e9c78e",
  "padding":
  ↪ "0xc15f786f34e5cef0fef6ce7c1185d799ecd5ebca72b3310648c5588db2e99a0d73301c7a8d90115a91213f0bc9c722",
  ↪ ",
  "payload": "0xdeadbeaf",
  "pow": 0.5371803278688525,
  "recipientPublicKey": null,
  "sig": null,
  "timestamp": 1496991876,
  "topic": "0x01020304",
  "ttl": 50
}, {...}]
```

Note: This documentation is work in progress and web3.js 1.0 stable is not yet released! You can find the current documentation for web3 0.x.x at github.com/ethereum/wiki/wiki/JavaScript-API.

This package provides utility functions for Ethereum dapps and other web3.js packages.

17.1 randomHex

```
web3.utils.randomHex(size)
```

The `randomHex` library to generate cryptographically strong pseudo-random HEX strings from a given byte size.

17.1.1 Parameters

1. `size` - Number: The byte size for the HEX string, e.g. 32 will result in a 32 bytes HEX string with 64 characters prefixed with "0x".

17.1.2 Returns

String: The generated random HEX string.

17.1.3 Example

```
web3.utils.randomHex(32)
> "0xa5b9d60f32436310afebcfda832817a68921beb782fabf7915cc0460b443116a"

web3.utils.randomHex(4)
> "0x6892ffc6"

web3.utils.randomHex(2)
```

(continues on next page)

(continued from previous page)

```
> "0x99d6"  
  
web3.utils.randomHex(1)  
> "0x9a"  
  
web3.utils.randomHex(0)  
> "0x"
```

17.2 BN

```
web3.utils.BN(mixed)
```

The [BN.js](#) library for calculating with big numbers in JavaScript. See the [BN.js documentation](#) for details.

Note: For safe conversion of many types, incl [BigNumber.js](#) use [utils.toBN](#)

17.2.1 Parameters

1. value - String|Number: A number, number string or HEX string to convert to a BN object.

17.2.2 Returns

Object: The [BN.js](#) instance.

17.2.3 Example

```
const BN = web3.utils.BN;  
  
new BN(1234).toString();  
> "1234"  
  
new BN('1234').add(new BN('1')).toString();  
> "1235"  
  
new BN('0xea').toString();  
> "234"
```

17.3 isBN

```
web3.utils.isBN(bn)
```

Checks if a given value is a [BN.js](#) instance.

17.3.1 Parameters

1. bn - Object: An `BN.js` instance.

17.3.2 Returns

Boolean

17.3.3 Example

```
const number = new BN(10);  
web3.utils.isBN(number);  
> true
```

17.4 isBigNumber

```
web3.utils.isBigNumber(bignumber)
```

Checks if a given value is a `BigNumber.js` instance.

17.4.1 Parameters

1. BigNumber - Object: A `BigNumber.js` instance.

17.4.2 Returns

Boolean

17.4.3 Example

```
const number = new BigNumber(10);  
web3.utils.isBigNumber(number);  
> true
```

17.5 sha3

```
web3.utils.sha3(string)  
web3.utils.keccak256(string) // ALIAS
```

Will calculate the sha3 of the input.

Note: To mimic the sha3 behaviour of solidity use *soliditySha3*

17.5.1 Parameters

1. string - String: A string to hash.

17.5.2 Returns

String: the result hash.

17.5.3 Example

```
web3.utils.sha3('234'); // taken as string
> "0xc1912fee45d61c87cc5ea59dae311904cd86b84fee17cc96966216f811ce6a79"

web3.utils.sha3(new BN('234'));
> "0xbc36789e7a1e281436464229828f817d6612f7b477d66591ff96a9e064bcc98a"

web3.utils.sha3(234);
> null // can't calculate the has of a number

web3.utils.sha3(0xea); // same as above, just the HEX representation of the number
> null

web3.utils.sha3('0xea'); // will be converted to a byte array first, and then hashed
> "0x2f20677459120677484f7104c76deb6846a2c071f9b3152c103bb12cd54d1a4a"
```

17.6 soliditySha3

```
web3.utils.soliditySha3(param1 [, param2, ...])
```

Will calculate the sha3 of given input parameters in the same way solidity would. This means arguments will be ABI converted and tightly packed before being hashed.

17.6.1 Parameters

1. paramX - Mixed: Any type, or an object with {type: 'uint', value: '123456'} or {t: 'bytes', v: '0xffff456'}. Basic types are autodetected as follows:
 - String non numerical UTF-8 string is interpreted as string.
 - String|Number|BN|HEX positive number is interpreted as uint256.
 - String|Number|BN negative number is interpreted as int256.
 - Boolean as bool.

- String HEX string with leading 0x is interpreted as bytes.
- HEX HEX number representation is interpreted as uint256.

17.6.2 Returns

String: the result hash.

17.6.3 Example

```
web3.utils.soliditySha3('234564535', '0xfff23243', true, -10);
// auto detects:      uint256,      bytes,      bool,      int256
> "0x3e27a893dc40ef8a7f0841d96639de2f58a132be5ae466d40087a2cfa83b7179"

web3.utils.soliditySha3('Hello!%'); // auto detects: string
> "0x661136a4267dba9ccdf6bfddb7c00e714de936674c4bdb065a531cf1cb15c7fc"

web3.utils.soliditySha3('234'); // auto detects: uint256
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3(0xea); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3(new BN('234')); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3({type: 'uint256', value: '234'}); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3({t: 'uint', v: new BN('234')}); // same as above
> "0x61c831beab28d67d1bb40b5ae1a11e2757fa842f031a2d0bc94a7867bc5d26c2"

web3.utils.soliditySha3('0x407D73d8a49eeb85D32Cf465507dd71d507100c1');
> "0x4e8ebbef452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b"

web3.utils.soliditySha3({t: 'bytes', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1'}
↳);
> "0x4e8ebbef452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b" // same result
↳as above

web3.utils.soliditySha3({t: 'address', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1
↳'});
> "0x4e8ebbef452077428f93c9520d3edd60594ff452a29ac7d2ccc11d47f3ab95b" // same as
↳above, but will do a checksum check, if its multi case

web3.utils.soliditySha3({t: 'bytes32', v: '0x407D73d8a49eeb85D32Cf465507dd71d507100c1
↳'});
> "0x3c69a194aaf415ba5d6afca734660d0a3d45acdc05d54cd1ca89a8988e7625b4" // different
↳result as above
```

(continues on next page)

(continued from previous page)

```
web3.utils.soliditySha3({t: 'string', v: 'Hello!%'}, {t: 'int8', v:-23}, {t: 'address
↪', v: '0x85F43D8a49eeB85d32Cf465507DD71d507100C1d'});
> "0xa13b31627c1ed7aaded5aecec71baf02fe123797fffd45e662eac8e06fbe4955"
```

17.7 isHex

```
web3.utils.isHex(hex)
```

Checks if a given string is a HEX string.

17.7.1 Parameters

1. hex - String|HEX: The given HEX string.

17.7.2 Returns

Boolean

17.7.3 Example

```
web3.utils.isHex('0xc1912');
> true

web3.utils.isHex(0xc1912);
> true

web3.utils.isHex('c1912');
> true

web3.utils.isHex(345);
> true // this is tricky, as 345 can be a a HEX representation or a number, be_
↪ careful when not having a 0x in front!

web3.utils.isHex('0xZ1912');
> false

web3.utils.isHex('Hello');
> false
```

17.8 isHexStrict

```
web3.utils.isHexStrict(hex)
```

Checks if a given string is a HEX string. Difference to `web3.utils.isHex()` is that it expects HEX to be prefixed with `0x`.

17.8.1 Parameters

1. `hex - String|HEX`: The given HEX string.

17.8.2 Returns

Boolean

17.8.3 Example

```
web3.utils.isHexStrict('0xc1912');
> true

web3.utils.isHexStrict(0xc1912);
> false

web3.utils.isHexStrict('c1912');
> false

web3.utils.isHexStrict(345);
> false // this is tricky, as 345 can be a a HEX representation or a number, be_
↪ careful when not having a 0x in front!

web3.utils.isHexStrict('0xZ1912');
> false

web3.utils.isHex('Hello');
> false
```

17.9 isAddress

```
web3.utils.isAddress(address)
```

Checks if a given string is a valid Ethereum address. It will also check the checksum, if the address has upper and lowercase letters.

17.9.1 Parameters

1. `address - String`: An address string.

17.9.2 Returns

Boolean

17.9.3 Example

```
web3.utils.isAddress('0xc1912fee45d61c87cc5ea59dae31190fffff232d');
> true

web3.utils.isAddress('c1912fee45d61c87cc5ea59dae31190fffff232d');
> true

web3.utils.isAddress('0XC1912FEE45D61C87CC5EA59DAE31190FFFFFF232D');
> true // as all is uppercase, no checksum will be checked

web3.utils.isAddress('0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');
> true

web3.utils.isAddress('0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');
> false // wrong checksum
```

17.10 toChecksumAddress

```
web3.utils.toChecksumAddress(address)
```

Will convert an upper or lowercase Ethereum address to a checksum address.

17.10.1 Parameters

1. address - String: An address string.

17.10.2 Returns

String: The checksum address.

17.10.3 Example

```
web3.utils.toChecksumAddress('0xc1912fee45d61c87cc5ea59dae31190fffff2323');
> "0xc1912fEE45d61C87Cc5EA59DaE31190FFFFFF232d"

web3.utils.toChecksumAddress('0XC1912FEE45D61C87CC5EA59DAE31190FFFFFF232D');
> "0xc1912fEE45d61C87Cc5EA59DaE31190FFFFFF232d" // same as above
```

17.11 checkAddressChecksum

```
web3.utils.checkAddressChecksum(address)
```

Checks the checksum of a given address. Will also return false on non-checksum addresses.

17.11.1 Parameters

1. `address` - `String`: An address string.

17.11.2 Returns

`Boolean`: `true` when the checksum of the address is valid, `false` if its not a checksum address, or the checksum is invalid.

17.11.3 Example

```
web3.utils.checkAddressChecksum('0xc1912fEE45d61C87Cc5EA59DaE31190FFFFf232d');  
> true
```

17.12 toHex

```
web3.utils.toHex(mixed)
```

Will auto convert any given value to HEX. Number strings will interpreted as numbers. Text strings will be interpreted as UTF-8 strings.

17.12.1 Parameters

1. `value` - `String|Number|BN|BigNumber`: The input to convert to HEX.

17.12.2 Returns

`String`: The resulting HEX string.

17.12.3 Example

```
web3.utils.toHex('234');  
> "0xea"  
  
web3.utils.toHex(234);  
> "0xea"  
  
web3.utils.toHex(new BN('234'));  
> "0xea"  
  
web3.utils.toHex(new BigNumber('234'));  
> "0xea"  
  
web3.utils.toHex('I have 100€');  
> "0x49206861766520313030e282ac"
```

17.13 toBN

```
web3.utils.toBN(number)
```

Will safely convert any given value (including `BigNumber.js` instances) into a `BN.js` instance, for handling big numbers in JavaScript.

Note: For just the `BN.js` class use `utils.BN`

17.13.1 Parameters

1. `number` - `String` | `Number` | `HEX`: Number to convert to a big number.

17.13.2 Returns

Object: The `BN.js` instance.

17.13.3 Example

```
web3.utils.toBN(1234).toString();
> "1234"

web3.utils.toBN('1234').add(web3.utils.toBN('1')).toString();
> "1235"

web3.utils.toBN('0xea').toString();
> "234"
```

17.14 hexToNumberString

```
web3.utils.hexToNumberString(hex)
```

Returns the number representation of a given HEX value as a string.

17.14.1 Parameters

1. `hexString` - `String` | `HEX`: A string to hash.

17.14.2 Returns

String: The number as a string.

17.14.3 Example

```
web3.utils.hexToNumberString('0xea');  
> "234"
```

17.15 hexToNumber

```
web3.utils.hexToNumber(hex)  
web3.utils.toDecimal(hex) // ALIAS, deprecated
```

Returns the number representation of a given HEX value.

Note: This is not useful for big numbers, rather use *utils.toBN* instead.

17.15.1 Parameters

1. `hexString` - `String`|`HEX`: A string to hash.

17.15.2 Returns

`Number`

17.15.3 Example

```
web3.utils.hexToNumber('0xea');  
> 234
```

17.16 numberToHex

```
web3.utils.numberToHex(number)  
web3.utils.fromDecimal(number) // ALIAS, deprecated
```

Returns the HEX representation of a given number value.

17.16.1 Parameters

1. `number` - `String`|`Number`|`BN`|`BigNumber`: A number as string or number.

17.16.2 Returns

`String`: The HEX value of the given number.

17.16.3 Example

```
web3.utils.numberToHex('234');  
> '0xea'
```

17.17 hexToUtf8

```
web3.utils.hexToUtf8(hex)  
web3.utils.hexToString(hex) // ALIAS  
web3.utils.toUtf8(hex) // ALIAS, deprecated
```

Returns the UTF-8 string representation of a given HEX value.

17.17.1 Parameters

1. `hex - String`: A HEX string to convert to a UTF-8 string.

17.17.2 Returns

`String`: The UTF-8 string.

17.17.3 Example

```
web3.utils.hexToUtf8('0x49206861766520313030e282ac');  
> "I have 100€"
```

17.18 hexToAscii

```
web3.utils.hexToAscii(hex)  
web3.utils.toAscii(hex) // ALIAS, deprecated
```

Returns the ASCII string representation of a given HEX value.

17.18.1 Parameters

1. `hex - String`: A HEX string to convert to a ASCII string.

17.18.2 Returns

`String`: The ASCII string.

17.18.3 Example

```
web3.utils.hexToAscii('0x4920686176652031303021');  
> "I have 100!"
```

17.19 utf8ToHex

```
web3.utils.utf8ToHex(string)  
web3.utils.stringToHex(string) // ALIAS  
web3.utils.fromUtf8(string) // ALIAS, deprecated
```

Returns the HEX representation of a given UTF-8 string.

17.19.1 Parameters

1. `string` - String: A UTF-8 string to convert to a HEX string.

17.19.2 Returns

String: The HEX string.

17.19.3 Example

```
web3.utils.utf8ToHex('I have 100€');  
> "0x49206861766520313030e282ac"
```

17.20 asciiToHex

```
web3.utils.asciiToHex(string)  
web3.utils.fromAscii(string) // ALIAS, deprecated
```

Returns the HEX representation of a given ASCII string. If you would like to transform an ASCII string into a valid `bytes4`, `bytes8` etc. value then please pass the correct length as the second parameter.

17.20.1 Parameters

1. `string` - String: A ASCII string to convert to a HEX string.
2. `length` - Number: The length of the returned hex string. The default size is 32 e.g.: `bytes32`.

17.20.2 Returns

String: The HEX string.

17.22.2 Returns

String: The HEX string.

17.22.3 Example

```
web3.utils.bytesToHex([ 72, 101, 108, 108, 111, 33, 36 ]);  
> "0x48656c6c66f2125"
```

17.23 toWei

```
web3.utils.toWei(number [, unit])
```

Converts any [ether value](#) value into [wei](#).

Note: “wei” are the smallest ether unit, and you should always make calculations in wei and convert only for display reasons.

17.23.1 Parameters

1. `number` - `String|BN`: The value.
2. `unit` - `String` (optional, defaults to "ether"): The ether to convert from. Possible units are:
 - `noether`: '0'
 - `wei`: '1'
 - `kwei`: '1000'
 - `Kwei`: '1000'
 - `babbage`: '1000'
 - `femtoether`: '1000'
 - `mwei`: '1000000'
 - `Mwei`: '1000000'
 - `lovelace`: '1000000'
 - `picoether`: '1000000'
 - `gwei`: '1000000000'
 - `Gwei`: '1000000000'
 - `shannon`: '1000000000'
 - `nanoether`: '1000000000'
 - `nano`: '1000000000'
 - `szabo`: '1000000000000'

- microether: '1000000000000'
- micro: '1000000000000'
- finney: '1000000000000000'
- milliether: '1000000000000000'
- milli: '1000000000000000'
- ether: '1000000000000000000'
- kether: '1000000000000000000000'
- grand: '1000000000000000000000'
- mether: '1000000000000000000000000'
- gether: '1000000000000000000000000000'
- tether: '1000000000000000000000000000000'

17.23.2 Returns

String|BN: If a string is given it returns a number string, otherwise a BN.js instance.

17.23.3 Example

```
web3.utils.toWei('1', 'ether');
> "1000000000000000000"

web3.utils.toWei('1', 'finney');
> "1000000000000000"

web3.utils.toWei('1', 'szabo');
> "1000000000000"

web3.utils.toWei('1', 'shannon');
> "1000000000"
```

17.24 fromWei

```
web3.utils.fromWei(number [, unit])
```

Converts any **wei** value into a **ether** value.

Note: “wei” are the smallest ether unit, and you should always make calculations in wei and convert only for display reasons.

17.24.1 Parameters

1. `number - String|BN`: The value in wei.
2. **`unit - String` (optional, defaults to "ether")**: The ether to convert to. Possible units are:
 - `noether`: '0'
 - `wei`: '1'
 - `kwei`: '1000'
 - `Kwei`: '1000'
 - `babbage`: '1000'
 - `femtoether`: '1000'
 - `mwei`: '1000000'
 - `Mwei`: '1000000'
 - `lovelace`: '1000000'
 - `picoether`: '1000000'
 - `gwei`: '1000000000'
 - `Gwei`: '1000000000'
 - `shannon`: '1000000000'
 - `nanoether`: '1000000000'
 - `nano`: '1000000000'
 - `szabo`: '1000000000000'
 - `microether`: '1000000000000'
 - `micro`: '1000000000000'
 - `finney`: '1000000000000000'
 - `milliether`: '1000000000000000'
 - `milli`: '1000000000000000'
 - `ether`: '1000000000000000000'
 - `kether`: '1000000000000000000000'
 - `grand`: '1000000000000000000000'
 - `meth`: '1000000000000000000000000'
 - `gether`: '1000000000000000000000000000'
 - `tether`: '10000000000000000000000000000000'

17.24.2 Returns

`String`: It always returns a string number.

17.24.3 Example

```
web3.utils.fromWei('1', 'ether');
> "0.00000000000000000001"

web3.utils.fromWei('1', 'finney');
> "0.0000000000000001"

web3.utils.fromWei('1', 'szabo');
> "0.00000000000001"

web3.utils.fromWei('1', 'shannon');
> "0.000000001"
```

17.25 unitMap

```
web3.utils.unitMap
```

Shows all possible ether value and their amount in wei.

17.25.1 Return value

- **Object with the following properties:**
 - noether: '0'
 - wei: '1'
 - kwei: '1000'
 - Kwei: '1000'
 - babbage: '1000'
 - femtoether: '1000'
 - mwei: '1000000'
 - Mwei: '1000000'
 - lovelace: '1000000'
 - picoether: '1000000'
 - gwei: '1000000000'
 - Gwei: '1000000000'
 - shannon: '1000000000'
 - nanoether: '1000000000'
 - nano: '1000000000'
 - szabo: '1000000000000'
 - microether: '1000000000000'
 - micro: '1000000000000'

```

- finney: '1000000000000000'
- milliether: '1000000000000000'
- milli: '1000000000000000'
- ether: '1000000000000000000'
- kether: '10000000000000000000'
- grand: '100000000000000000000'
- mether: '1000000000000000000000'
- gether: '10000000000000000000000'
- tether: '100000000000000000000000'

```

17.25.2 Example

```

web3.utils.unitMap
> {
  noether: '0',
  wei: '1',
  kwei: '1000',
  Kwei: '1000',
  babbage: '1000',
  femtoether: '1000',
  mwei: '1000000',
  Mwei: '1000000',
  lovelace: '1000000',
  picoether: '1000000',
  gwei: '1000000000',
  Gwei: '1000000000',
  shannon: '1000000000',
  nanoether: '1000000000',
  nano: '1000000000',
  szabo: '1000000000000',
  microether: '1000000000000',
  micro: '1000000000000',
  finney: '1000000000000000',
  milliether: '1000000000000000',
  milli: '1000000000000000',
  ether: '1000000000000000000',
  kether: '10000000000000000000',
  grand: '100000000000000000000',
  mether: '1000000000000000000000',
  gether: '10000000000000000000000',
  tether: '100000000000000000000000'
}

```

17.26 padLeft

```

web3.utils.padLeft(string, characterAmount [, sign])
web3.utils.leftPad(string, characterAmount [, sign]) // ALIAS

```

Adds a padding on the left of a string, Useful for adding paddings to HEX strings.

17.26.1 Parameters

1. `string - String`: The string to add padding on the left.
2. `characterAmount - Number`: The number of characters the total string should have.
3. `sign - String (optional)`: The character sign to use, defaults to "0".

17.26.2 Returns

`String`: The padded string.

17.26.3 Example

```
web3.utils.padLeft('0x3456ff', 20);  
> "0x0000000000000000003456ff"  
  
web3.utils.padLeft(0x3456ff, 20);  
> "0x0000000000000000003456ff"  
  
web3.utils.padLeft('Hello', 20, 'x');  
> "xxxxxxxxxxxxxxxxHello"
```

17.27 padRight

```
web3.utils.padRight(string, characterAmount [, sign])  
web3.utils.rightPad(string, characterAmount [, sign]) // ALIAS
```

Adds a padding on the right of a string, Useful for adding paddings to HEX strings.

17.27.1 Parameters

1. `string - String`: The string to add padding on the right.
2. `characterAmount - Number`: The number of characters the total string should have.
3. `sign - String (optional)`: The character sign to use, defaults to "0".

17.27.2 Returns

`String`: The padded string.

17.27.3 Example


```
web3.utils.padRight('0x3456ff', 20);
> "0x3456ff0000000000000000"

web3.utils.padRight(0x3456ff, 20);
> "0x3456ff0000000000000000"

web3.utils.padRight('Hello', 20, 'x');
> "Helloxxxxxxxxxxxxxxxxxx"
```

17.28 toTwosComplement

```
web3.utils.toTwosComplement(number)
```

Converts a negative number into a two's complement.

17.28.1 Parameters

1. `number` - `Number|String|BigNumber`: The number to convert.

17.28.2 Returns

`String`: The converted hex string.

17.28.3 Example

```
web3.utils.toTwosComplement('-1');
> "0xffffffffffffffffffffffffffffffffffffffffffffffffffffffffffff"

web3.utils.toTwosComplement(-1);
> "0xffffffffffffffffffffffffffffffffffffffffffffffffffffffffffff"

web3.utils.toTwosComplement('0x1');
> "0x00000000000000000000000000000000000000000000000000000000000001"

web3.utils.toTwosComplement(-15);
> "0xffffffffffffffffffffffffffffffffffffffffffffffffffffffffffff1"

web3.utils.toTwosComplement('-0x1');
> "0xffffffffffffffffffffffffffffffffffffffffffffffffffffffffffff"
```

17.29 getSignatureParameters

```
web3.utils.getSignatureParameters(string)
```

Gets the `r`, `s` and `v` values of an ECDSA signature

17.29.1 Parameters

1. `string - String`: An ECDSA signature.

17.29.2 Returns

Object: Object containing r,s,v values.

17.29.3 Example

```
web3.utils.getSignatureParameters(  
  ↪ '0x5763ab346198e3e6cc4d53996ccdeca0c941cb6cb70d671d97711c421d3bf7922c77ef244ad40e5262d1721bf9638fb'  
  ↪ );  
> "{ r: '0x5763ab346198e3e6cc4d53996ccdeca0c941cb6cb70d671d97711c421d3bf792', s:  
  ↪ '0x2c77ef244ad40e5262d1721bf9638fb06bab8ed3c43bfaa80d6da0be9bbd33dc', v: 27 }"
```

B

bower, 3

C

contract deploy, 64

J

JSON interface, 61

M

meteor, 3

N

npm, 3